

RF Exposure Evaluation Report

Product	: ENC DUAL MIC NOISE-CANCELING TWS BLUETOOTH EARPHONES
Trade mark	: MINISO
Model/Type reference	: MINISO-P66
Serial Number	: N/A
Report Number	: EED32O80105503
FCC ID	: 2ART4-P06A
Date of Issue	: Aug. 23, 2022
Test Standards	: 47 CFR Part 1.1307 47 CFR Part 2.1093 KDB447498D01 General RF Exposure Guidance v06
Test result	: PASS

Prepared for:

Miniso Corporation

**Room 2501, No. 486 Heye Square Kangwang Middle Road,
Liwan District, GuangZhou, Guangdong, China**

Prepared by:

**Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China**

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Compiled by:

mark.chen

Mark Chen

Reviewed by:

Tom Chen

Tom Chen

Approved by:

Aaron Ma

Aaron Ma

Date:

Aug. 23, 2022

Check No.:3850210122



1 Version

Version No.	Date	Description
00	Aug. 23, 2022	Original

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BLE	4
3.4 GENERAL DESCRIPTION OF BT CLASSIC	4
3.5 TEST LOCATION	5
3.6 DEVIATION FROM STANDARDS	5
3.7 ABNORMALITIES FROM STANDARD CONDITIONS	5
3.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
4 SAR EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 Standard Requirement	6
4.1.2 EUT RF Exposure	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	9

3 General Information

3.1 Client Information

Applicant:	Miniso Corporation
Address of Applicant:	Room 2501, No. 486 Heye Square Kangwang Middle Road, Liwan District, GuangZhou, Guangdong, China
Manufacturer:	CNCE
Address of Manufacturer:	37F, Headquarters Building, No. 2, HBC Huilong Center, Mintang Road, Longhua District, Shenzhen City, Guangdong Province, China
Factory:	CNCE
Address of Factory:	37F, Headquarters Building, No. 2, HBC Huilong Center, Mintang Road, Longhua District, Shenzhen City, Guangdong Province, China

3.2 General Description of EUT

Product Name:	ENC DUAL MIC NOISE-CANCELING TWS BLUETOOTH EARPHONES
Model No.(EUT):	MINISO-P66
Trade mark:	MINISO
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Power Supply:	DC 3.7V
Test Voltage:	DC 3.7V
Sample Received Date:	Jan. 24, 2022
Sample tested Date:	Jan. 24, 2022 to Apr. 07, 2022
Remark:	<p>Company Name and Address shown on Report, the sample(s) and sample Information were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.</p> <p>During the test, the data was showed in all modes, only the worst case left ear was recorded in the report.</p> <p>The left and right headphone are same electrical circuit design and color.</p>

3.3 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Modulation Type:	GFSK
Transfer Rate:	<input checked="" type="checkbox"/> 1Mbps <input checked="" type="checkbox"/> 2Mbps
Number of Channel:	40
Antenna Type:	Chip Antenna
Antenna Gain:	2.5dBi

3.4 General Description of BT Classic

Operation Frequency:	2402MHz~2480MHz
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Antenna Type:	Chip Antenna
Antenna Gain:	2.5dBi

3.5 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

3.6 Deviation from Standards

None.

3.7 Abnormalities from Standard Conditions

None.

3.8 Other Information Requested by the Customer

None.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06
Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.2 EUT RF Exposure

1) For BLE

Measurement Data:

The Ear L for 1M of data is worst, only the worst case is recorded in the report.

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	1.75	2.0±1	3	1.995
Middle(2440MHz)	1.8	2.0±1	3	1.995
Highest(2480MHz)	1.88	2.0±1	3	1.995

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	1.75	2.0±1	3	1.995	0.62	3.0
Middle (2440MHz)	1.8	2.0±1	3	1.995	0.62	
Highest (2480MHz)	1.88	2.0±1	3	1.995	0.62	
Conclusion: the calculated value ≤ 3.0 , SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: EED32O80105501.

2) For BT Classic

Measurement Data

The Ear L of data is worst, only the worst case is recorded in the report.

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	2.01	2.5±1	3.5	2.239
Middle(2441MHz)	2.03	2.5±1	3.5	2.239
Highest(2480MHz)	2.37	2.5±1	3.5	2.239
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	2.8	3.0±1	4.0	2.512
Middle(2441MHz)	2.95	3.0±1	4.0	2.512
Highest(2480MHz)	3.04	3.0±1	4.0	2.512

Worst case: π/4DQPSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	2.8	3.0±1	4.0	2.512	0.8	3.0
Middle (2441MHz)	2.95	3.0±1	4.0	2.512	0.8	
Highest (2480MHz)	3.04	3.0±1	4.0	2.512	0.8	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: EED32O80105502.

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32O80105501 for EUT external and internal photos.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***