
TEST REPORT FOR BLE TESTING

Report No.: SRTC2021-9004(F)-21030304(E)

Product Name: BACnet IP/MSTP VAV Controller

Product Model: WEB-VA75IBWA24NM, CPO-VA75IBWA24NM

Applicant: Honeywell (Beijing) Technology Solutions Lab Co., Ltd.

Manufacturer: Honeywell (Beijing) Technology Solutions Lab Co., Ltd.

Specification: FCC Part 15 Subpart C (2020)

FCC ID: 2ARTN-00006

The State Radio_monitoring_center Testing Center (SRTC)

15th Building, No.30 Shixing Street, Shijingshan District,

Beijing, P.R.China

Tel: 86-10-57996183 Fax: 86-10-57996388

CONTENTS

1. GENERAL INFORMATION	2
1.1 NOTES OF THE TEST REPORT	2
1.2 INFORMATION ABOUT THE TESTING LABORATORY	2
1.3 APPLICANT’S DETAILS	2
1.4 MANUFACTURER’S DETAILS	2
1.5 TEST ENVIRONMENT	3
2 DESCRIPTION OF THE DEVICE UNDER TEST	4
2.1 FINAL EQUIPMENT BUILD STATUS	4
2.2 DESCRIPTION OF TEST MODES	5
2.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	6
2.3 DUTY CYCLE OF TEST SIGNAL	7
2.4 EUT OPERATING CONDITIONS	7
3 REFERENCE SPECIFICATION.....	8
4 KEY TO NOTES AND RESULT CODES.....	8
5 RESULT SUMMARY	9
6 TEST RESULT	10
6.1 6dB BANDWIDTH	10
6.2 TRANSMITTER OUTPUT POWER	11
6.3 TRANSMITTER POWER SPECTRAL DENSITY	12
6.4 CONDUCTED OUT OF BAND EMISSION MEASUREMENT.....	13
6.5 BAND-EDGE MEASUREMENT	14
6.6 SPURIOUS RADIATED EMISSIONS	15
6.7 AC POWER LINE CONDUCTED EMISSION	20
7 MEASUREMENT UNCERTAINTIES.....	22
8 TEST EQUIPMENTS	23
APPENDIX A – TEST DATA OF RADIATED EMISSION.....	24

1. GENERAL INFORMATION

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC). The test results relate only to individual items of the samples which have been tested. The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

1.2 Information about the testing laboratory

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	15th Building, No.30 Shixing Street, Shijingshan District, P.R.China
City:	Beijing
Country or Region:	P.R.China
Contacted person:	Liu Jia
Tel:	+86 10 57996183
Fax:	+86 10 57996388
Email:	liujiaf@srtc.org.cn

1.3 Applicant's details

Company:	Honeywell (Beijing) Technology Solutions Lab Co., Ltd.
Address:	A1 Building, C&W Industry Zone, No.14 Jiuxianqiao Road, Chaoyang District, Beijing, 100015, P.R. China
City:	Beijing
Country or Region:	China
Contacted person:	Zhang John
Tel:	010 56696736
Fax:	---
Email:	John.Zhang@Honeywell.com

1.4 Manufacturer's details

Company:	Honeywell (Beijing) Technology Solutions Lab Co., Ltd.
Address:	A1 Building, C&W Industry Zone, No.14 Jiuxianqiao Road, Chaoyang District, Beijing, 100015, P.R. China
City:	Beijing
Country or Region:	China
Contacted person:	Zhang John
Tel:	010 56696736
Fax:	---
Email:	John.Zhang@Honeywell.com

1.5 Test Environment

Date of Receipt of test sample at SRTC:	2021-03-03
Testing Start Date:	2021-03-03
Testing End Date:	2021-04-10

Environmental Data:	Temperature (°C)	Humidity (%)
Ambient	25	40

Normal Supply Voltage (V d.c.):	24.0
---------------------------------	------

2 DESCRIPTION OF THE DEVICE UNDER TEST

2.1 Final Equipment Build Status

Frequency Range	2.402GHz~2.480GHz
Number of Channel	40
Modulation Type	GFSK
Equipment Class	DTS
Channel Spacing	2MHz
Data Rate	1Mbps
Power Supply	AC Power Supply
Hardware Version	301001
Software Version	N/A
IMEI or Sample	#1
Antenna type	Refer to Note2
Antenna connector	Refer to Note2

Note1: There are two product models provided by manufacturers, but their RF parameters have not changed, and we choose WEB-VA75IBWA24NM as the test model.

Antenna requirement (FCC part 15.203)

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

- The antenna(s) of the EUT are permanently attached.
- There are no provisions for connection to an external antenna.

Note2: The antenna provide to the EUT, please refer to the following table:

SN	Brand	Model	Antenna gain(dBi)	Frequency range(GHz)	Antenna type	Connecter Type
Ant1	N/A	ANT-DB1-LCD-SMA	2.80	2.402GHz~2.480GHz	Fixed External Antenna	SMA
Ant2	N/A	MPN ARY113-0012-006-00	-0.31	2.402GHz~2.480GHz	Fixed External Antenna	SMA

Manufacturers ensure that their designs will not be modified by the user or third parties arbitrary antenna parameters and performance. The EUT complies with the requirement of §15.203.

This report tested for all types of antenna which mentioned in page 5 of this report, just the worst data is showing in this report.

This device uses an antenna with SMA connector, only professional installation will be permitted. The installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Note3: We only test RSE, the other test result reference test report No.: SRTC2018-9004(F)-18102401(E).

2.2 Description of Test Modes

40 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

2.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE ≥ 1G	RE<1G	PLC	APCM	
GFSK	√	√	√	√	-

Where

RE ≥ 1G: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Radiated Emission Test (Above 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	19	GFSK	1

Radiated Emission Test (Below 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	19	GFSK	1

Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	19	GFSK	1

Antenna Port Conducted Measurement:

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	0, 19, 39	GFSK	1

2.3 Duty Cycle of Test Signal

Duty cycle of test signal is < 98 %, duty factor shall be considered.

Duty cycle = 59.4%

Correction factor = $10 * \log (1/\text{duty cycle}) = 10 * \log (1/0.594) = 2.26\text{dB}$

2.4 EUT Operating conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

2.5 Support Equipment

The following support equipment was used to exercise the DUT during testing:
NA.

3 REFERENCE SPECIFICATION

Specification	Version	Title
FCC part15 Subpart C	2020	Intentional radiators
ANSI C63.10	2013	Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB 558074D01 V05R02r02	April 2, 2019	Guidance for compliance measurements on Digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules




4 KEY TO NOTES AND RESULT CODES

Code	Meaning
PASS	Test result shows that the requirements of the relevant specification have been met.
FAIL	Test result shows that the requirements of the relevant specification have not been met.
N/T	Test case is not tested.

5 RESULT SUMMARY

No.	Test case	Reference	Verdict
1	6dB Bandwidth	15.247(a)(2)	Pass*
2	Transmitter Output Power	15.247(b)(3))	Pass*
3	Transmitter Power Spectral Density	15.247(e))	Pass*
4	Conducted Out of band emission measurement	15.247(d)	Pass*
5	Band-edge	15.247(d)	Pass
6	Spurious Radiated Emissions	15.205/15.209/15.247(d)	Pass
7	AC Power line Conducted Emission	15.207	Pass
8	Antenna requirement	15.203	Pass(refer to section 2.1)

Note: Pass* (refer to original report SRTC2018-9004(F)-18102401(E)).

This Test Report Is Issued by: Mr. Peng Zhen 	Checked by: Mr. Li Bin 
Tested by: Mr. Tong Daocheng 	Issued date: 20210615

6 TEST RESULT

6.1 6dB Bandwidth

6.1.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	40%	101.5kPa

6.1.2 Test limit

Part15.247 (a) (2)

The minimum permissible 6dB bandwidth is 500 kHz

6.1.3 Test Procedure Used

ANSI C63.10-2013 – Section 11.8.2 Option 2

KDB 558074 D01 v05r02 – Section 8.2

6.1.4 Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.

2. RBW = 100 kHz

3. VBW $\geq 3 \times$ RBW

4. Detector = Peak


5. Trace mode = max hold

6. Sweep = auto couple

7. The trace was allowed to stabilize

6.1.5 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.1.6 Test result

The test results refer to original report SRTC2018-9004(F)-18102401(E).

6.2 Transmitter Output Power

6.2.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	40%	101.5kPa

6.2.2 Test limit

Part15.247 (b) (3)

The maximum permissible conducted output power is 1 Watt.

6.2.3 Test Procedure Used

ANSI C63.10-2013 – Section 11.9.1.3

ANSI C63.10-2013 – Section 11.9.2.3.2

KDB 558074 D01 v05r02 – Section 8.3.1.3

6.2.4 Test Settings

Peak Power Measurement


The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

6.2.5 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.2.6 Test result

The test results refer to original report SRTC2018-9004(F)-18102401(E).

6.3 Transmitter Power Spectral Density

6.3.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	40%	101.5kPa

6.3.2 Test limit

Part15.247 (e)

The maximum permissible power spectral density is 8.0dBm in any 3 kHz band.

6.3.3 Test Procedure Used

ANSI C63.10-2013 – Section 11.10.2 Method PKPSD


KDB 558074 D01 v05r02 – Section 8.4

6.3.4 Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3 kHz
4. VBW = 10 kHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

6.3.5 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.3.7 Test result

The test results refer to original report SRTC2018-9004(F)-18102401(E).

6.4 Conducted Out of band emission measurement

6.4.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	40%	101.5kPa

6.4.2 Test limit

Part 15.247(d): The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.

6.4.3 Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3

KDB 558074 D01 v05r02 – Section 8.5

6.4.4 Reference level measurement Settings

Establish a reference level by using the following procedure:


- Set instrument center frequency to DTS channel center frequency.
- Set the span to ≥ 1.5 MHz
- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

6.4.5 Test Settings

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Set span to encompass the spectrum to be examined
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

6.4.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.4.7 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement. The test results refer to original report SRTC2018-9004(F)-18102401(E).

6.5 Band-edge measurement

6.5.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	40%	101.5kPa

6.5.2 Test limit

Part 15.247(d): The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.

6.5.3 Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3

KDB 558074 D01 v05r02 – Section 8.7.2

6.5.4 Reference level measurement Settings

Establish a reference level by using the following procedure:


- Set instrument center frequency to DTS channel center frequency.
- Set the span to ≥ 1.5 MHz
- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

6.5.5 Test Settings

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Set span to encompass the spectrum to be examined
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

6.5.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.5.7 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement. The test results refer to original report SRTC2018-9004(F)-18102401(E).

6.6 Spurious Radiated Emissions

6.6.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	40%	101.5kPa

6.6.2 Test Description

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

6.6.3 Test limit

Part15.205, 15.209, 15.247(d)

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in below Table per Section 15.209. The spectrum shall be investigated from the lowest radio frequency signal generated in the device

Frequency [MHz]	Field strength [$\mu\text{V}/\text{m}$]	Measured Distance [meters]
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Radiated Limits

Part15.35(b):

There is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit

Used conversion factor: Limit (dB $\mu\text{V}/\text{m}$) = 20 log (Limit ($\mu\text{V}/\text{m}$)/1 $\mu\text{V}/\text{m}$)

Frequency [MHz]	Detector	Unit (dB $\mu\text{V}/\text{m}$)
30~88	Quasi-peak	40.0
88~216	Quasi-peak	43.5
216~960	Quasi-peak	46.0
960~1000	Quasi-peak	54.0
1000~5th harmonic of the highest frequency or 40GHz, whichever is lower	Average	54.0
	Peak	74.0

Conversion Radiated limits

6.6.4 Test Procedure Used

KDB 558074 D01 DTS Meas Guidance v05r02r02 – Section 12.2.7

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and recorded the reading with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer complied the following setting:

Frequency	RBW
9-150kHz	200-300Hz
0.15-30MHz	9-10kHz

2. Signals below 30MHz are not recorded in the report because they are lower than the limits by more than 20dB.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground in chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and recorded the reading with Maximum Hold Mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detector and recorded the reading with Maximum Hold Mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Average detection (AV) at frequency above 1GHz. If duty cycle of test signal is < 98%, the duty factor need added to measured value.
4. All modes of operation were investigated and the worst-case emissions are reported.

6.6.5 Test Settings

Average Field Strength Measurements per Section 12.2.7 of KDB 558074 (Part 15.35)

Frequency	Detector
<1000MHz	Quasi-peak
>1000MHz	Peak and average

Peak Field Strength Measurements per Section 12.2.7of KDB 558074 (Part 15.35)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in following table

Frequency	RBW
9-150kHz	200-300Hz
0.15-30MHz	9-10kHz
30-1000MHz	100-120kHz
>1000MHz	1MHz


3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

6.6.6 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



6.6.7 Test result

The test results are shown in Appendix A.

6.7 AC Power line Conducted Emission

6.7.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	40%	101.5kPa

6.7.2 Test limit

FCC Part15.207

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

The measurement is made according to ANSI C63.10-2013

6.7.3 Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.


b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

The EUT shall test under the power AC120V/60Hz.

6.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.5 Test result

The test results are shown in Appendix A.

7 MEASUREMENT UNCERTAINTIES

Items	Uncertainty	
Occupied Bandwidth	3kHz	
Peak power output	0.67dB	
Band edge compliance	1.20dB	
Spurious emissions	30MHz~1GHz	2.83dB
	1GHz~12.75GHz	2.50dB
	12.75GHz~25GHz	2.75dB

8 TEST EQUIPMENTS

No	Name/ Model	Manufacturer	S/N	Cal date	Cal Due date
1.	Spectrum Analyzer FSV	ROHDE& SCHWARZ	101065	2020.08.20	2021.08.19
2.	Power Meter E4416A	Agilent	MY52370013	2020.04.13	2021.04.12
3.	Power Sensor E9327A	Agilent	MY52420006	2020.04.13	2021.04.12
4.	23.18m×16.88m×9.60 m Semi-Anechoic Chamber	FRANKONIA	---	-----	-----
5.	Turn table Diameter:5m	FRANKONIA	-----	-----	-----
6.	Antenna master SAC(MA4.0)	MATURO	-----	-----	-----
7.	9.080m×5.255m×3.525 m Shielding room	FRANKONIA	-----	-----	-----
8.	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	2020.08.20	2021.08.19
9.	3160-09 Receive antenna	SCHWARZ- BECK	002058-002	2020.08.20	2021.08.19
10.	ESI 40 EMI test receiver	R&S	100015	2020.08.20	2021.08.19
11.	ESCS30 EMI test receiver	R&S	100029	2020.08.20	2021.08.19
12.	HL562 Receive antenna	R&S	100167	2020.08.20	2021.08.19
13.	ENV216 AMN	R&S	3560.6550.12	2020.08.20	2021.08.19

APPENDIX A – TEST DATA OF RADIATED EMISSION

Band-Edge Radiated Emissions

LE (1Mbps)

The worst case attitude: The EUT lay down.

Carrier frequency (MHz): 2402

Channel No.:0

Test Mode: GFSK (LE)

Polarity: Vertical

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2402	103.66	69.66	N/A	N/A	8.90	25.10
2	2390	51.86	17.86	-22.14	74.00	8.90	25.10

Carrier frequency (MHz): 2402

Channel No.:0

Test Mode: GFSK (LE)

Polarity: Horizontal

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2402	98.61	64.61	N/A	N/A	8.90	25.10
2	2390	46.17	12.17	-27.83	74.00	8.90	25.10

Carrier frequency (MHz): 2402

Channel No.:0

Test Mode: GFSK (LE)

Polarity: Vertical

Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2402	91.24	57.24	N/A	N/A	8.90	25.10
2	2390	40.29	6.29	-13.71	54.00	8.90	25.10

Carrier frequency (MHz): 2402
Channel No.:0
Test Mode: GFSK (LE)
Polarity: Horizontal
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2402	89.73	55.73	N/A	N/A	8.90	25.10
2	2390	38.00	4.00	-16.00	54.00	8.90	25.10

Carrier frequency (MHz): 2480
Channel No.:39
Test Mode: GFSK (LE)
Polarity: Vertical
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2480	104.78	70.78	N/A	N/A	8.90	25.10
2	2483.5	49.46	15.46	-24.54	74.00	8.90	25.10

Carrier frequency (MHz): 2480
Channel No.:39
Test Mode: GFSK (LE)
Polarity: Horizontal
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2480	98.49	64.49	N/A	N/A	8.90	25.10
2	2483.5	47.92	13.92	-26.08	74.00	8.90	25.10

Carrier frequency (MHz): 2480
Channel No.:39
Test Mode: GFSK (LE)
Polarity: Vertical
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2480	91.21	57.21	N/A	N/A	8.90	25.10
2	2483.5	38.96	4.96	-15.04	54.00	8.90	25.10

Carrier frequency (MHz): 2480

Channel No.:39
Test Mode: GFSK (LE)
Polarity: Horizontal
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2480	85.74	51.74	N/A	N/A	8.90	25.10
2	2483.5	37.33	3.33	-16.67	54.00	8.90	25.10

Spurious Radiated Emissions

Sample Calculations

Determining Spurious Emissions Levels

A “reference path loss” is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{mea}} + A_{Rpl}$$

Sample calculation: $(30.54\text{dB}\mu\text{V/m}) = (-20.4\text{dB/m}) + (50.94\text{dBuV})$, the corresponding frequency is 32.533500MHz.

The worst case: BLE 1Mbps.

For GFSK

Channel No.:0

Frequency (MHz)	Result (dBuV/m)	ARpl (dB/m)	Pmea (dBuV)	Polarity	Limit (dBuV/m)
44.598500	23.42	-20.2	40.50	Vertical	40.00
349.954500	34.08	-16.4	41.18	Vertical	46.00
441.813500	27.96	-13.5	48.30	Vertical	46.00
491.574500	40.79	-11.9	45.68	Vertical	46.00
549.968500	26.71	-10.6	26.09	Vertical	46.00
799.986000	28.16	-5.8	19.90	Vertical	46.00

For $\pi/4$ DQPSK

Channel No.:0

Frequency (MHz)	Result (dBuV/m)	ARpl (dB/m)	Pmea (dBuV)	Polarity	Limit (dBuV/m)
44.986500	22.28	-20.5	42.78	Vertical	40.00
349.954500	34.10	-16.4	50.50	Vertical	46.00
491.574500	40.76	-11.9	52.66	Vertical	46.00
549.968500	26.71	-10.6	37.31	Vertical	46.00
799.986000	28.13	-5.8	33.93	Vertical	46.00
849.989500	28.42	-5.0	33.42	Vertical	46.00

For 8DPSK
Channel No.:0

Frequency (MHz)	Result (dBuV/m)	ARpl (dB/m)	Pmea (dBuV)	Polarity	Limit (dBuV/m)
44.986500	21.80	-20.5	42.30	Vertical	40.00
349.954500	34.01	-16.4	50.41	Vertical	46.00
441.813500	27.88	-13.5	41.38	Vertical	46.00
491.574500	40.64	-11.9	52.54	Vertical	46.00
849.989500	28.37	-5.0	33.37	Vertical	46.00
899.993000	27.90	-4.3	32.20	Vertical	46.00

For GFSK
Channel No.:39

Frequency (MHz)	Result (dBuV/m)	ARpl (dB/m)	Pmea (dBuV)	Polarity	Limit (dBuV/m)
44.986500	20.95	-20.5	41.45	Vertical	40.00
349.954500	34.01	-16.4	50.41	Vertical	46.00
491.574500	40.61	-11.9	52.51	Vertical	46.00
799.986000	28.01	-5.8	33.81	Vertical	46.00
849.989500	28.34	-5.0	33.34	Vertical	46.00
899.993000	27.84	-4.3	32.14	Vertical	46.00

For $\pi/4$ DQPSK
Channel No.:39

Frequency (MHz)	Result (dBuV/m)	ARpl (dB/m)	Pmea (dBuV)	Polarity	Limit (dBuV/m)
44.210500	22.31	-20.0	42.31	Vertical	40.00
349.954500	33.94	-16.4	50.34	Vertical	46.00
491.574500	40.51	-11.9	52.41	Vertical	46.00
539.977500	29.93	-10.8	40.73	Vertical	46.00
799.986000	27.90	-5.8	33.70	Vertical	46.00
849.989500	28.28	-5.0	33.28	Vertical	46.00

For 8DPSK
Channel No.:39

Frequency (MHz)	Result (dBuV/m)	ARpl (dB/m)	Pmea (dBuV)	Polarity	Limit (dBuV/m)
42.222000	23.37	-18.7	42.07	Vertical	40.00
349.954500	34.05	-16.4	50.45	Vertical	46.00
491.574500	40.60	-11.9	52.50	Vertical	46.00
549.968500	26.67	-10.6	37.27	Vertical	46.00
799.986000	28.00	-5.8	33.80	Vertical	46.00
849.989500	28.39	-5.0	33.39	Vertical	46.00

For GFSK
Channel No.:78

Frequency (MHz)	Result (dBuV/m)	ARpl (dB/m)	Pmea (dBuV)	Polarity	Limit (dBuV/m)
43.822500	1.11	-19.7	20.81	Vertical	40.00
349.954500	27.40	-16.4	43.80	Vertical	46.00
491.574500	36.44	-11.9	48.34	Vertical	46.00
549.968500	23.76	-10.6	34.36	Vertical	46.00
799.986000	25.55	-5.8	31.35	Vertical	46.00
849.989500	26.53	-5.0	31.53	Vertical	46.00


For $\pi/4$ DQPSK
Channel No.:78

Frequency (MHz)	Result (dBuV/m)	ARpl (dB/m)	Pmea (dBuV)	Polarity	Limit (dBuV/m)
43.386000	19.76	-19.4	39.16	Vertical	40.00
349.954500	34.04	-16.4	50.44	Vertical	46.00
491.574500	40.55	-11.9	52.45	Vertical	46.00
549.968500	26.66	-10.6	37.26	Vertical	46.00
799.986000	27.94	-5.8	33.74	Vertical	46.00
849.989500	28.38	-5.0	33.38	Vertical	46.00

For 8DPSK
Channel No.:78


Frequency (MHz)	Result (dBuV/m)	ARpl (dB/m)	Pmea (dBuV)	Polarity	Limit (dBuV/m)
45.423000	23.26	-20.8	44.06	Vertical	40.00
49.060500	24.39	-23.2	47.59	Vertical	40.00
349.954500	33.94	-16.4	50.34	Vertical	46.00
491.574500	40.44	-11.9	52.34	Vertical	46.00
799.986000	27.85	-5.8	33.65	Vertical	46.00
849.989500	28.27	-5.0	33.27	Vertical	46.00

Carrier frequency (MHz): 2402
Channel No.:0




Comment

Frequency Range: 30MHz-1000MHz
Detector: QP mode
Modulation type: GFSK




Frequency Range: 1GHz-3GHz
Detector: Av mode and PK mode
Modulation type: GFSK

Full Spectrum




Frequency Range: 3GHz- 6GHz
 Detector: Av mode and PK mode
 Modulation type: GFSK

Full Spectrum




Frequency Range: 6GHz- 18GHz
 Detector: Av mode and PK mode
 Modulation type: GFSK

Full Spectrum



Frequency Range: 18GHz-25GHz
Detector: Av mode and PK mode
Modulation type: GFSK


Full Spectrum



Comment

Frequency Range: 30MHz-1000 MHz
Detector: QP mode
Modulation type: $\pi/4$ DQPSK


Full Spectrum



Comment


Frequency Range: 1GHz-3GHz
Detector: Av mode and PK mode
Modulation type: $\pi/4$ DQPSK

Full Spectrum




Frequency Range: 3GHz- 6GHz
Detector: Av mode and PK mode
Modulation type: $\pi/4$ DQPSK

Full Spectrum



Frequency Range: 6GHz-18GHz
Detector: Av mode and PK mode
Modulation type: $\pi/4$ DQPSK


Full Spectrum



- Preview Result 2-AVG
- Preview Result 1-PK+
- * Critical_Freqs PK+
- PK.74
- Critical_Freqs AVG
- ◆ Final_Result PK+
- ◆ Final_Result AVG
- AV54

Frequency Range: 18GHz-25GHz
Detector: Av mode and PK mode
Modulation type: $\pi/4$ DQPSK


Full Spectrum



Comment

Frequency Range: 30MHz-1000 MHz
Detector: QP mode
Modulation type: 8DPSK


Full Spectrum



Comment


Frequency Range: 1GHz-3GHz
Detector: Av mode and PK mode
Modulation type: 8DPSK

Full Spectrum




Frequency Range: 3GHz- 6GHz
 Detector: Av mode and PK mode
 Modulation type: 8DPSK

Full Spectrum



Frequency Range: 6GHz-18GHz
 Detector: Av mode and PK mode
 Modulation type: 8DPSK


Full Spectrum



Frequency Range: 18GHz-25GHz
Detector: Av mode and PK mode
Modulation type: 8DPSK

Carrier frequency (MHz): 2441
Channel No.:39


Full Spectrum



Comment

Frequency Range: 30MHz-1000MHz
Detector: QP mode
Modulation type: GFSK


Full Spectrum



Comment


Frequency Range: 1GHz-3GHz
 Detector: Av mode and PK mode
 Modulation type: GFSK

Full Spectrum




Frequency Range: 3GHz- 6GHz
 Detector: Av mode and PK mode
 Modulation type: GFSK

Full Spectrum



Frequency Range: 3GHz- 18GHz
Detector: Av mode and PK mode
Modulation type: GFSK


Full Spectrum



— Preview Result 2-AVG — Preview Result 1-PK+ * Critical_Freqs AVG
* Critical_Freqs PK+ — PK.74 — AV54
◆ Final_Result PK+ ◆ Final_Result AVG

Frequency Range: 18GHz-25GHz
Detector: Av mode and PK mode
Modulation type: GFSK


Full Spectrum



Comment

Frequency Range: 30MHz-1000 MHz
Detector: QP mode
Modulation type: $\pi/4$ DQPSK


Full Spectrum



Comment


Frequency Range: 1GHz-3GHz
Detector: Av mode and PK mode
Modulation type: $\pi/4$ DQPSK

Full Spectrum



Frequency Range: 3GHz- 6GHz
 Detector: Av mode and PK mode
 Modulation type: $\pi/4$ DQPSK

Full Spectrum




Frequency Range: 6GHz-18GHz
 Detector: Av mode and PK mode
 Modulation type: $\pi/4$ DQPSK

Full Spectrum



Frequency Range: 18GHz-25GHz
Detector: Av mode and PK mode
Modulation type: $\pi/4$ DQPSK


Full Spectrum



Comment

Frequency Range: 30MHz-1000 MHz
Detector: QP mode
Modulation type: 8DPSK


Full Spectrum



Comment


Frequency Range: 1GHz-3GHz
Detector: Av mode and PK mode
Modulation type: 8DPSK

Full Spectrum




Frequency Range: 3GHz- 6GHz
Detector: Av mode and PK mode
Modulation type: 8DPSK

Full Spectrum



Frequency Range: 6GHz-18GHz
Detector: Av mode and PK mode
Modulation type: 8DPSK

Full Spectrum




— Preview Result 2-AVG — Preview Result 1-PK+ * Critical_Freqs AVG
* Critical_Freqs PK+ — PK.74 — AV54
◆ Final_Result PK+ ◆ Final_Result AVG

Frequency Range: 18GHz-25GHz
Detector: Av mode and PK mode
Modulation type: 8DPSK

Carrier frequency (MHz): 2480
Channel No.:78


Full Spectrum



Comment

Frequency Range: 30MHz-1000MHz
Detector: QP mode
Modulation type: GFSK


Full Spectrum



Comment


Frequency Range: 1GHz-3GHz
Detector: Av mode and PK mode
Modulation type: GFSK

Full Spectrum




Frequency Range: 3GHz- 6GHz
 Detector: Av mode and PK mode
 Modulation type: GFSK

Full Spectrum




Frequency Range: 3GHz- 18GHz
 Detector: Av mode and PK mode
 Modulation type: GFSK

Full Spectrum



Frequency Range: 18GHz-25GHz
Detector: Av mode and PK mode
Modulation type: GFSK


Full Spectrum



Comment

Frequency Range: 30MHz-1000 MHz
Detector: QP mode
Modulation type: $\pi/4$ DQPSK


Full Spectrum



Comment


Frequency Range: 1GHz-3GHz
Detector: Av mode and PK mode
Modulation type: $\pi/4$ DQPSK

Full Spectrum




Frequency Range: 3GHz- 6GHz
Detector: Av mode and PK mode
Modulation type: $\pi/4$ DQPSK

Full Spectrum



Frequency Range: 6GHz-18GHz
Detector: Av mode and PK mode
Modulation type: $\pi/4$ DQPSK


Full Spectrum



	Preview Result 2-AVG		Preview Result 1-PK +		Critical_Freqs AVG
	Critical_Freqs PK +		PK.74		AV54
	Final_Result PK +		Final_Result AVG		

Frequency Range: 18GHz-25GHz
Detector: Av mode and PK mode
Modulation type: $\pi/4$ DQPSK


Full Spectrum



Comment

Frequency Range: 30MHz-1000 MHz
 Detector: QP mode
 Modulation type: 8DPSK


Full Spectrum



Comment


Frequency Range: 1GHz-3GHz
 Detector: Av mode and PK mode
 Modulation type: 8DPSK

Full Spectrum




Frequency Range: 3GHz- 6GHz
 Detector: Av mode and PK mode
 Modulation type: 8DPSK

Full Spectrum



Frequency Range: 6GHz-18GHz
 Detector: Av mode and PK mode
 Modulation type: 8DPSK

Full Spectrum




- Preview Result 2-AVG
- Preview Result 1-PK+
- * Critical_Freqs PK+
- ◆ Final_Result PK+
- ◆ Final_Result AVG
- ◆ Critical_Freqs AVG
- AV54
- PK.74

Frequency Range: 18GHz-25GHz
 Detector: Av mode and PK mode
 Modulation type: 8DPSK

AC Power line Conducted Emission

Full Spectrum



L+N Line

MEASUREMENT RESULT:

Frequency (MHz)	MaxPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.193897	55.31	---	63.87	8.56	L1	30.0
0.193897	---	33.42	53.87	20.45	L1	30.0
0.250963	46.15	---	61.73	15.58	L1	30.0
0.250963	---	26.18	51.73	25.55	L1	30.0
0.312419	37.14	---	59.91	22.76	N	30.1
0.369485	32.27	---	58.51	26.24	N	30.1
0.997213	---	20.99	46.00	25.02	L1	29.9
1.458132	---	20.87	46.00	25.13	L1	29.9
2.761875	---	21.70	46.00	24.30	N	29.9
3.543243	29.87	---	56.00	26.14	N	29.8
4.166581	---	22.25	46.00	23.75	L1	29.8
4.381676	30.87	---	56.00	25.13	L1	29.8

---End of Test Report---