



■ Report No.: DDT-R21042026-2E05

■ Issued Date: Sep. 20, 2021

## RF EXPOSURE REPORT

### FOR

<b>Applicant</b>	:	Pokit Innovations PTY. LTD.
<b>Address</b>	:	Unit 2.01, 56 Delhi Road, Macquarie Park 2113, NSW, Australia
<b>Equipment under Test</b>	:	Pokit PRO
<b>Model No.</b>	:	POK-PRO
<b>Trade Mark</b>	:	N/A
<b>FCC ID</b>	:	2ARUE-POKPRO
<b>Manufacturer</b>	:	Dongguan MediDiagno Biotech Co., Ltd.
<b>Address</b>	:	Rm 801, Rongyi Building, No.5 Xinxu Road, High-tech Industrial Development Zone, Songshan Lake, Dongguan, Guang Dong, China, 523808

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

**Tel:** +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

# REPORT

## Table of Contents

Test report declares.....	3
1. General information.....	5
1.1. Description of Equipment.....	5
1.2. Assess laboratory.....	5
2. RF Exposure evaluation for FCC.....	6

**TEST REPORT DECLARE**

<b>Applicant</b>	:	Pokit Innovations PTY. LTD.
<b>Address</b>	:	Unit 2.01, 56 Delhi Road, Macquarie Park 2113, NSW, Australia
<b>Equipment under Test</b>	:	Pokit PRO
<b>Model No.</b>	:	POK-PRO
<b>Trade mark</b>	:	N/A
<b>Manufacturer</b>	:	Dongguan MediDiagno Biotech Co., Ltd.
<b>Address</b>	:	Rm 801, Rongyi Building, No.5 Xinxi Road, High-tech Industrial Development Zone, SongShan Lake, Dongguan, Guang Dong, China, 523808

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above.

The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No:</b>	DDT-R21042026-2E05		
<b>Date of Receipt:</b>	Apr. 21, 2021	<b>Date of Test:</b>	Aug. 21, 2021 ~ Sep. 15, 2021

**Prepared By:**

*Jacky Huang*

**Jacky Huang/Engineer**

**Approved By:**



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

### Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Sep. 20, 2021	

## 1. General information

### 1.1. Description of Equipment

EUT* Name	: Pokit PRO
Model Number	: POK-PRO
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 5V by external AC Adapter or 3.7V built-in lithium battery
Radio Specification	: Bluetooth V5.0
Operation Frequency	: 2402 MHz - 2480 MHz
Modulation	: GFSK
Data Rate	: 1 Mbps
Antenna Gain	: Max:0.5dBi
Sample Type	: Series production
Series Number	: N/A

### 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,  
Guangdong Province, China, 523808

Tel: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com)

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

## 2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Worse case is as below: [2480MHz, -1.40 dBm 0.724mW) output power]

$(0.724/5) \cdot [\sqrt{2.480(\text{GHz})}] = 0.23 < 3.0$  for 1-g SAR

Then SAR evaluation is not required.

**END OF REPORT**