




시험 성적서 TEST REPORT

페이지(page) : (1) / (총 31)

성적서 번호 Report No.		ICRT-TR-E181663-0A	
신청자 Client	기관명 Name	Sentech Korea Corp	
	주소 Address	21-6, Jimokro75-gil, Paju-Si, Gyeonggi-Do, 10880, Republic of Korea	
시험대상품목 Sample description		Breathanalyzer	
모델명 Type designation		iSober S	
정격 Ratings		DC 3 V	
시험기간 Date of test		Nov. 27, 2018 ~ Nov. 28, 2018	
시험방법/항목 Test Method/Item		FCC Part 15 Subpart C §15.247	
시험결과 Test Results		Refer to 3. Test Summary	
확인 Affirmation	작성자 Tested by	기술책임자 Technical Manager	
	성명 Name Hong-Kyu, Lee (Signature)	성명 Name Jun-Hui, Lee (Signature)	
<input type="checkbox"/> 위 성적서는 고객이 제공한 시료에 대한 시험결과 이며, 용도 이외의 사용은 금합니다. This is certified that the above mentioned products have been tested for the sample provided by customer and forbid the use except for original purpose.			
<input type="checkbox"/> 위 성적서는 한국인정기구(KOLAS)인정과 관련이 없습니다. The above test report is not related to accreditation by Korea Laboratory Accreditation scheme.			
<input type="checkbox"/> 위 성적서는 주식회사 아이씨알의 승인 없이는 복제 및 재발급이 금지됩니다. No part of this document may be duplicated or reproduced by any means without the express written permission of the ICR.			
2018. 12. 12			
주식회사 아이씨알 대표이사			
The head of INTERNATIONAL CERTIFICATION REGISTRAR			

본 성적서의 진위 확인은 G4B 혹은 ICR 홈페이지에서 가능합니다.

경기도 김포시 양촌읍 황금3로7번길 112

112, Hwanggeum3-ro 7beon-gil, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea



Contents

1. Applicant & Manufacturer & Test Laboratory Information.....	4
1.1 Applicant information.....	4
1.2 Manufacturer Information	4
1.3 Test Laboratory Information	4
2. Equipment under Test(EUT) Information	5
2.1 General Information.....	5
2.2 Additional Information	5
2.3 Mode of operation during the test	5
2.4 Modifications of EUT	5
3. Test Summary	6
3.1 Test standards and results	6
3.2 Purpose of the test	6
3.3 Antenna requirement.....	6
4. Used equipment on test	7
5. 6 dB Bandwidth	8
5.1 Operating environment	8
5.2 Measurement method	8
5.3 Test setup	8
5.4 Test data	9
6. Maximum Conducted Output Power	11
6.1 Operating environment	11
6.2 Measurement method	11
6.3 Test setup	11
6.4 Test data	12
7. Power Spectral Density.....	14
7.1 Operating environment	14
7.2 Measurement method	14
7.3 Test setup	14
7.4 Test data	15
8. Conducted Spurious Emission.....	17
8.1 Operating environment	17
8.2 Measurement method	17
8.3 Test setup	17
8.4 Test data	18
9. Radiated Spurious Emission	23
9.1 Operating environment	23
9.2 Measurement method	23
9.3 Test setup	23
9.4 Test data	25
10. Test Setup Photo	30



Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
ICRT-TR-E181663-0A	12-Dec-2018	Initial Issue	All



1. Applicant & Manufacturer & Test Laboratory Information

1.1 Applicant information

Applicant	Sentech Korea Corp
Address	21-6, Jimokro75-gil, Paju-Si, Gyeonggi-Do, 10880, Republic of Korea
Contact Person	JunNo Lee
Telephone No.	+82-10-5028-0706
Fax No.	+82-31-8071-4411
E-mail	jnlee@sentechkorea.com

1.2 Manufacturer Information

Manufacturer	Sentech Korea Corp
Address	21-6, Jimokro75-gil, Paju-Si, Gyeonggi-Do, 10880, Republic of Korea

1.3 Test Laboratory Information

Conducted tests were performed at	
Laboratory	ICR Co., Ltd.
Address	112, Hwanggeum 3-ro 7beon-gil, Hagun-ri, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea
Telephone No.	+82-2-6351-9002
Fax No.	+82-2-6351-9007
RRA No.	KR0165
KOLAS No.	KT652



2. Equipment under Test(EUT) Information

2.1 General Information

Product Name	Breathanalyzer
Brand Name	-
Model Name	iSober S
Additional Model Name	Dingo E-030, iScreen, Promiler, AC-018, ISOBER 70 PRO
Hardware Version	-
Software Version	-
Power Supply	DC 3 V

2.2 Additional Information

Equipment Class	DTS-Digital Transmission System
Device Type	Stand-alone
Operating Frequency	2 402 MHz ~ 2 480 MHz
RF Output Power	-0.03 dBm
Number of Channel	40
Modulation Type	GFSK
Antenna Type	Integral Antenna (Chip Antenna)
Antenna Gain	0.5 dBi
Antenna Operating Mode	Single Antenna Equipment with only one antenna
List of Each Oscillator or Crystal Frequency	8 MHz

2.3 Mode of operation during the test

- The EUT is continuous transmission mode during the test

2.4 Modifications of EUT

- None



3. Test Summary

3.1 Test standards and results

FCC Part 15 Subpart C			
Clause	Test items	Applied	Results
§15.247 (a) (1)	6 dB Bandwidth	<input checked="" type="checkbox"/>	PASS
§15.247 (b) (3)	Maximum Conducted Output Power	<input checked="" type="checkbox"/>	PASS
§15.247 (e)	Power Spectral Density	<input checked="" type="checkbox"/>	PASS
§15.247 (d)	Conducted Spurious Emission	<input checked="" type="checkbox"/>	PASS
§15.247 (d) & §15.209 & §15.205	Radiated Spurious Emission	<input checked="" type="checkbox"/>	PASS
§15.207	Power Line Conducted Emission	<input type="checkbox"/>	N/A (See Note)
§15.203	Antenna Requirement	<input checked="" type="checkbox"/>	PASS

※ Note: This test is not performed because the EUT is operated by DC battery.

3.2 Purpose of the test

- To determine whether the equipment under test fulfills the requirements of the standards stated in FCC Part 15 Subpart C Section 15.247

3.3 Antenna requirement

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.

Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.1 Result: Pass

The transmitter has an *integral Chip antenna*. The directional gain of the antenna is *0.5* dBi.



4. Used equipment on test

	Description	Model Name	Serial Number	Manufacturer	Last Cal. (cycle)
<input type="checkbox"/>	Spectrum Analyzer	FSW85	100864	Rohde & Schwarz	2018. 03. 22 (1Y)
<input checked="" type="checkbox"/>	Spectrum Analyzer	FSV40	101455	Rohde & Schwarz	2018 .07. 10 (1Y)
<input checked="" type="checkbox"/>	Signal Generator	SMB100A	180607	Rohde & Schwarz	2018. 03. 05 (1Y)
<input type="checkbox"/>	Power Sensor	NRP-Z81	103673	Rohde & Schwarz	2018. 03. 05 (1Y)
<input type="checkbox"/>	Open Switch and Control Platform	OSP150	101000	Rohde & Schwarz	2018. 03. 22 (1Y)
<input type="checkbox"/>	Environmental Test Chamber	MHK-408NKDA	1060908	TERCHY	2018. 03. 14 (1Y)
<input checked="" type="checkbox"/>	DC Power Supply	XDL 35-5P	J00385373	Sorensen	2018. 03. 05 (1Y)
<input type="checkbox"/>	DC Power Supply	6603D	672483	Topward	2018. 03. 05 (1Y)
<input checked="" type="checkbox"/>	Loop Antenna	HFH2-Z2	100506	Rohde & Schwarz	2017. 06. 19 (2Y)
<input checked="" type="checkbox"/>	TRILOG BROADBAND ANTENNA	VULB9162	120	SCHWARZBECK	2018. 11. 23 (2Y)
<input checked="" type="checkbox"/>	RF Pre Amplifier	SCU08	100747	Rohde & Schwarz	2018. 04. 17 (1Y)
<input checked="" type="checkbox"/>	DOUBLE-RIDGE WAVEGUIDE HORN ANTENNA	HF907	102556	Rohde & Schwarz	2017. 07. 05 (2Y)
<input checked="" type="checkbox"/>	RF Pre Amplifier	SCU18	102342	Rohde & Schwarz	2018. 04. 17 (1Y)
<input checked="" type="checkbox"/>	Horn Antenna	LB-42-10-C-KF	J202024625	AINFO Inc.	2018. 04. 20 (2Y)
<input checked="" type="checkbox"/>	RF Pre Amplifier	AMF-4F-18265-35-8P-1	771846	MITEQ	2018. 03. 06(1Y)
<input type="checkbox"/>	Horn Antenna	LB-28-10-C-KF	J202024627	AINFO Inc.	2018. 04. 20 (2Y)
<input type="checkbox"/>	RF Pre Amplifier	AMF-4D-260400-45-6P	779919	MITEQ	2018. 03. 22 (1Y)
<input checked="" type="checkbox"/>	EMI Test Receiver	ESR26	101461	Rohde & Schwarz	2018. 04. 17 (1Y)
<input type="checkbox"/>	EMI Test Receiver	ESR3	102119	Rohde & Schwarz	2018. 04. 17 (1Y)
<input type="checkbox"/>	LISN	ENV216	102193	Rohde & Schwarz	2018. 04. 16 (1Y)

※ All test equipment used is calibration on a regular basis.



5. 6 dB Bandwidth

5.1 Operating environment


Temperature : 25 °C
Relative humidity : 48 %

5.2 Measurement method

Standard : §15.247 (a) (2)

5.3 Test setup

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz, and peak detection was used. The 6 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 6 dB.






5.4 Test data


Test date : 27. Nov. 2018
 Operating mode : Transmit mode
 Test Result : Pass

5.4.1 Measured Results


Modulation Type	Channel (Frequency)	Measured Value (kHz)	Limit (kHz)
Bluetooth LE	0 (2 402 MHz)	690.3	at least 500
	19 (2 440 MHz)	699.0	
	39 (2 480 MHz)	699.0	

5.4.2 Measured Graph





Mid CH



High CH



6. Maximum Conducted Output Power

6.1 Operating environment


Temperature : 25 °C
Relative humidity : 48 %

6.2 Measurement method

Standard : §15.247 (b) (3)

6.3 Test setup

The maximum peak output power was measured with the spectrum analyzer connected to the antenna output of the EUT. The spectrum analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99 % bandwidth. The EUT was operating in transmit mode at the appropriate center frequency.






6.4 Test data


Test date : 27. Nov. 2018
 Operating mode : Transmit mode
 Test Result : Pass

6.4.1 Measured Results


Modulation Type	Channel (Frequency)	Highest signal level (dBm)	Limit (dBm)
Bluetooth LE	0 (2 402 MHz)	-0.78	30 (1 Watt)
	19 (2 440 MHz)	-0.56	
	39 (2 480 MHz)	-0.03	

6.4.2 Measured Graph





Mid CH



High CH



7. Power Spectral Density

7.1 Operating environment


Temperature : 25 °C
Relative humidity : 48 %

7.2 Measurement method

Standard : §15.247 (e)

7.3 Test setup

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 3 kHz, the video bandwidth is set to 3 times the resolution bandwidth.






7.4 Test data


Test date : 27. Nov. 2018
 Operating mode : Transmit mode
 Test Result : Pass

7.4.1 Measured Results


Modulation Type	Channel (Frequency)	Highest signal level (dBm)	Limit (dBm/3 kHz)
Bluetooth LE	0 (2 402 MHz)	-11.27	8
	19 (2 440 MHz)	-11.34	
	39 (2 480 MHz)	-10.65	

7.4.2 Measured Graph





Mid CH



High CH



8. Conducted Spurious Emission

8.1 Operating environment


Temperature : 25 °C
Relative humidity : 48 %

8.2 Measurement method

Standard : §15.247 (d)

8.3 Test setup

The antenna output of the EUT was connected to the spectrum analyzer. The resolution and video bandwidth is set to 100 kHz, and peak detection was used.







8.4 Test data

Test date : 27. Nov. 2018
Operating mode : Transmit mode
Test Result : Pass


8.4.1 Measured Results

8.4.1.1 Signal level (dB m)






Mid CH




High CH




8.4.1.2 Unwanted Emissions In Non-Restricted Frequency Bands



Low CH




Mid CH





8.4.1.3 Band Edge



9. Radiated Spurious Emission

9.1 Operating environment

Temperature : 25 °C
Relative humidity : 53 %

9.2 Measurement method


Standard : §15.247 (d), §15.209, §15.205

9.3 Test setup


The radiated emissions measurements were performed on the 3 m, open-field test site. The EUT was placed on a non-conductive turntable above the ground plane.

The frequency spectrum from 9 kHz to 26.5 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.


9.3.1 Below 30 MHz



9.3.2 30 MHz to 1 GHz



9.3.3 Above 1 GHz





9.4 Test data

Test date : 28. Nov. 2018
 Operating mode : Transmit mode
 Test Result : Pass

9.4.1 Test data for Restricted band

Frequency (MHz)	Reading (dB μ V)	Detector	Ant. Pol. (H/V)	Corr. Factor (dB)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Low CH							
2 387.19	62.90	Peak	H	-11.30	51.60	73.98	-22.38
	46.01	Average	H		34.71	53.98	-19.27
High CH							
2 483.56	63.52	Peak	V	-10.50	53.02	73.98	-20.96
	45.34	Average	V		34.84	53.98	-19.14

- ※ Ant. Pol. : Antenna Polarization
- ※ Corr. Factor. : Antenna Factor + Cable Loss - Amplifier Gain
- ※ Result = Reading + Corr. Factor
- ※ Margin = Result - Limit

9.4.2 Test data for Spurious & Harmonic


9.4.2.1 Measurement Results for below 30 MHz

Frequency (MHz)	Reading (dB μ V)	Detector	Ant. Pol. (H/V)	Corr. Factor (dB)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Low CH							
It was not found any emissions peaks found from the EUT.							
Mid CH							
It was not found any emissions peaks found from the EUT.							
High CH							
It was not found any emissions peaks found from the EUT.							

- ※ Ant. Pol. : Antenna Polarization
- ※ Corr. Factor. : Antenna Factor + Cable Loss - Amplifier Gain
- ※ Result = Reading + Corr. Factor
- ※ Margin = Result - Limit




9.4.2.2 Measurement Results for below 1 GHz



Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
192.838750	26.98	43.50	16.52	1000.0	120.000	150.2	H	257.0	-21.6
241.096250	28.51	46.00	17.49	1000.0	120.000	99.7	H	137.0	-19.9
289.475000	27.32	46.00	18.68	1000.0	120.000	99.7	H	164.0	-18.8
399.994375	22.69	46.00	23.31	1000.0	120.000	99.7	V	346.0	-16.0
599.996250	22.78	46.00	23.22	1000.0	120.000	99.7	V	50.0	-12.4


Low CH



Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
55.280625	20.62	40.00	19.38	1000.0	120.000	99.7	V	244.0	-19.0
192.960000	28.14	43.50	15.36	1000.0	120.000	99.7	H	259.0	-21.6
241.217500	27.09	46.00	18.91	1000.0	120.000	99.7	H	289.0	-19.9
289.414375	26.90	46.00	19.10	1000.0	120.000	99.7	H	172.0	-18.8
399.994375	22.89	46.00	23.11	1000.0	120.000	99.7	V	333.0	-16.0

Mid CH



Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
55.280625	20.84	40.00	19.16	1000.0	120.000	100.0	V	344.0	-19.0
192.838750	28.23	43.50	15.27	1000.0	120.000	100.0	H	289.0	-21.6
241.096250	28.28	46.00	17.72	1000.0	120.000	100.0	H	289.0	-19.9
289.293125	28.62	46.00	17.38	1000.0	120.000	100.0	H	147.0	-18.8
399.994375	23.11	46.00	22.89	1000.0	120.000	100.0	H	127.0	-16.0
599.996250	23.52	46.00	22.48	1000.0	120.000	100.0	V	63.0	-12.4

High CH






9.4.2.3 Measurement Results for Above 1 GHz

Frequency (MHz)	Reading (dB μ V)	Detector	Ant. Pol. (H/V)	Corr. Factor (dB)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Low CH							
1 595.00	59.92	Peak	V	-15.10	44.82	73.98	-29.16
	36.62	Average	V		21.52	53.98	-32.46
4 804.00	48.02	Peak	H	-2.70	45.32	73.98	-28.66
	35.51	Average	H		32.81	53.98	-21.17
9 608.00	48.01	Peak	H	3.00	51.01	73.98	-22.97
	36.37	Average	H		39.37	53.98	-14.61
Mid CH							
1 595.00	63.41	Peak	V	-15.10	48.31	73.98	-25.67
	37.84	Average	V		22.74	53.98	-31.24
4 880.00	48.39	Peak	V	-2.50	45.89	73.98	-28.09
	39.13	Average	V		36.63	53.98	-17.35
12 429.10	47.33	Peak	H	6.10	53.43	73.98	-20.55
	32.39	Average	H		38.49	53.98	-15.49
High CH							
1 595.00	64.09	Peak	V	-15.10	48.99	73.98	-24.99
	35.02	Average	V		19.92	53.98	-34.06
1 695.30	53.67	Peak	V	-14.80	38.87	73.98	-35.11
	43.59	Average	V		28.79	53.98	-25.19
4 960.00	50.54	Peak	H	-2.40	48.14	73.98	-25.84
	42.07	Average	H		39.67	53.98	-14.31

- ※ Ant. Pol. : Antenna Polarization
- ※ Corr. Factor. : Antenna Factor + Cable Loss - Amplifier Gain
- ※ Result = Reading + Corr. Factor
- ※ Margin = Result - Limit

10. Test Setup Photo

Test Setup	Radiated measurement for below 1 GHz (Front side) 
Test Setup	Radiated measurement for below 1 GHz (Rear side) 

Test Setup	Radiated measurement for Above 1 GHz (Front side)
	
Test Setup	Radiated measurement for Above 1 GHz (Rear side)
