




TEST PLOT OF OUT OF BAND EMISSIONS THE WORST CASE OF 802.11n40 FOR MODULATION IN HIGH CHANNEL






Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





Note: Two transmit chains had been tested, the chain 0 was the worst case and record in the test report.



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,

Xixiang, Bao'an District, Shenzhen, Guangdong, China Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com



Report No.: AGC05925190404FE05

Page 43 of 96

#### 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

#### **10.1 MEASUREMENT PROCEDURE**

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set SPA Trace 1 Max hold, then View.

Note: The method of AVGPSD-1 in the ANSI C63.10 (2013) item 10.3 was used in this testing.

# 10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer To Section 8.2.

# **10.3 MEASUREMENT EQUIPMENT USED**

Refer To Section 6.

#### **10.4 LIMITS AND MEASUREMENT RESULT**

TEST ITEM	POWER SPECTRAL DENSITY
TEST MODE	802.11b with data rate 1

Channel No.	Power density Chain 0 (dBm/20kHz)	Power density Chain 1 (dBm/20kHz)	Power density Total (dBm/20kHz)	Limit (dBm/3kHz)	Result
Low Channel	7.271	7.355	N/A	8	Pass
Middle Channel	6.684	7.689	N/A	8	Pass
High Channel	6.932	7.815	N/A	8	Pass


TEST ITEM	POWER SPECTRAL DENSITY		10	(G)
TEST MODE	802.11g with data rate 6	r.C	0	

Channel No.	Power density Chain 0	Power density Chain 1	Power density Total	Limit	Result
	(dBm/20kHz)	(dBm/20kHz)	(dBm/20kHz)	(dBm/3kHz)	
Low Channel	0.518	0.584	N/A	8	Pass
Middle Channel	0.397	1.096	N/A	8	Pass
High Channel	0.514	2.281	N/A	8	Pass



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





TEST ITEM	POWER SPECTRAL DENSITY	0		10	
TEST MODE	802.11n 20 with data rate 6.5	CO	<b>c.</b> C	· ·	

Channel No.	Power density Chain 0 (dBm/20kHz)	Power density Chain 1 (dBm/20kHz)	Power density Total (dBm/20kHz)	Limit (dBm/3kHz)	Result
Low Channel	0.583	1.277	3.954	8	Pass
Middle Channel	1.178	1.014	4.107	8	Pass
High Channel	1.154	1.404	4.291	8	Pass


TEST ITEM	POWER SPECTRAL DENSITY	
TEST MODE	802.11n 40 with data rate 13.5	

Channel No.	Power density Chain 0 (dBm/20kHz)	Power density Chain 1 (dBm/20kHz)	Power density Total (dBm/20kHz)	Limit (dBm/3kHz)	Result
Low Channel	-3.193	-4.048	-0.589	8	Pass
Middle Channel	-2.735	-3.064	0.114	8	Pass
High Channel	-2.538	-2.384	0.550	8	Pass





# 802.11b TEST RESULT AT CHAIN 0 TEST PLOT OF SPECTRAL DENSITY FOR LOW CHANNEL



#### TEST PLOT OF SPECTRAL DENSITY FOR MIDDLE CHANNEL





Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,

Xixiang, Bao'an District, Shenzhen, Guangdong, China Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com



#### TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL



802.11b TEST RESULT AT CHAIN 1 TEST PLOT OF SPECTRAL DENSITY FOR LOW CHANNEL






Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,

Xixiang, Bao'an District, Shenzhen, Guangdong, China Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com



#### TEST PLOT OF SPECTRAL DENSITY FOR MIDDLE CHANNEL



#### TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL






Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,


Xixiang, Bao'an District, Shenzhen, Guangdong, China Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com



# 802.11g TEST RESULT AT CHAIN 0



#### TEST PLOT OF SPECTRAL DENSITY FOR MIDDLE CHANNEL






Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,


Xixiang, Bao'an District, Shenzhen, Guangdong, China



#### TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL



802.11g TEST RESULT AT CHAIN 1 TEST PLOT OF SPECTRAL DENSITY FOR LOW CHANNEL






Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,


Xixiang, Bao'an District, Shenzhen, Guangdong, China Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com



#### TEST PLOT OF SPECTRAL DENSITY FOR MIDDLE CHANNEL



#### TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL






Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,


Xixiang, Bao'an District, Shenzhen, Guangdong, China



# 802.11n 20 TEST RESULT AT CHAIN 0 TEST PLOT OF SPECTRAL DENSITY FOR LOW CHANNEL



#### TEST PLOT OF SPECTRAL DENSITY FOR MIDDLE CHANNEL






Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,


Xixiang, Bao'an District, Shenzhen, Guangdong, China



#### TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL



802.11n 20 TEST RESULT AT CHAIN 1 TEST PLOT OF SPECTRAL DENSITY FOR LOW CHANNEL






Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,


Xixiang, Bao'an District, Shenzhen, Guangdong, China Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com



#### TEST PLOT OF SPECTRAL DENSITY FOR MIDDLE CHANNEL



#### TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL






Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,


Xixiang, Bao'an District, Shenzhen, Guangdong, China



# 802.11n 40 TEST RESULT AT CHAIN 0 TEST PLOT OF SPECTRAL DENSITY FOR LOW CHANNEL



#### TEST PLOT OF SPECTRAL DENSITY FOR MIDDLE CHANNEL






Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,


Xixiang, Bao'an District, Shenzhen, Guangdong, China Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com



#### TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL



802.11n 40 TEST RESULT AT CHAIN 1 TEST PLOT OF SPECTRAL DENSITY FOR LOW CHANNEL






Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,


Xixiang, Bao'an District, Shenzhen, Guangdong, China Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com



#### TEST PLOT OF SPECTRAL DENSITY FOR MIDDLE CHANNEL



#### TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL





Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,

Xixiang, Bao'an District, Shenzhen, Guangdong, China Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com



Report No.: AGC05925190404FE05

Page 57 of 96

#### 11. RADIATED EMISSION

#### 11.1. MEASUREMENT PROCEDURE


- The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.






#### 11.2. TEST SETUP


# Radiated Emission Test-Setup Frequency Below 30MHz



#### RADIATED EMISSION TEST SETUP 30MHz-1000MHz



#### RADIATED EMISSION TEST SETUP ABOVE 1000MHz





Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,



Report No.: AGC05925190404FE05

Page 59 of 96

# 11.3. LIMITS AND MEASUREMENT RESULT

15.209(a) Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested For restricted band radiated emission, the test records reported below are the worst result compared to other modes.

# 11.4. TEST RESULT

#### **RADIATED EMISSION BELOW 30MHZ**

No emission found between lowest internal used/generated frequencies to 30MHz.




Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,



# **RADIATED EMISSION BELOW 1GHZ**

EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHZ	Antenna	Horizontal




Suspe	Suspected Data List							
NO.	Freq.	Level	Factor	Limit	Margin	Height	Angle	Delevito
NO.	[MHz]	[dBµV/m]	[dB]	[dBµV/m]	[dB]	[cm]	[°]	Polarity
1	89.1700	27.06	10.26	43.50	16.44	200	187	Horizontal
2	190.050	34.74	12.53	43.50	8.76	200	294	Horizontal
3	237.580	29.52	14.65	46.00	16.48	150	91	Horizontal
4	300.630	30.49	15.92	46.00	15.51	100	133	Horizontal
5	377.260	35.28	18.91	46.00	10.72	100	272	Horizontal
6	637.220	31.14	24.92	46.00	14.86	150	12	Horizontal

**RESULT: PASS** 




 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 





EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHZ	Antenna	Vertical



Suspe	Suspected Data List								
NO	Freq.	Level	Factor	Limit	Margin	Height	Angle	Delevite	
NO.	[MHz]	[dBµV/m]	[dB]	[dBµV/m]	[dB]	[cm]	[°]	Polarity	
1	49.4000	29.24	14.69	40.00	10.76	100	178	Vertical	
2	88.2000	28.36	10.24	43.50	15.14	200	148	Vertical	
3	117.300	24.67	13.19	43.50	18.83	100	23	Vertical	
4	187.140	37.58	12.65	43.50	5.92	100	23	Vertical	
5	280.260	29.36	16.29	46.00	16.64	200	299	Vertical	
6	377.260	33.07	18.91	46.00	12.93	200	148	Vertical	

#### **RESULT: PASS**

#### Note:


- 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.
- 2. The "Factor" value can be calculated automatically by software of measurement system.
- 3. All test modes had been pre-tested. The 802.11b at low channel is the worst case and recorded in the report.



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,

Xixiang, Bao'an District, Shenzhen, Guangdong, China Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com





**RADIATED EMISSION ABOVE 1GHZ** 

EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHZ	Antenna	Horizontal


Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4824.062	44.23	7.12	51.35	74.00	-22.65	peak
4824.062	41.02	7.12	48.14	54.00	-5.86	AVG
7236.093	35.67	9.84	45.51	74.00	-28.49	peak
7236.093	31.49	9.84	41.33	54.00	-12.67	AVG
			8		- 60	
			8			
Remark:						
actor = Ante	enna Factor + C	able Loss –	Pre-amplifier.	- G	(8)	

EUT	JT Teton Router 750 Model Name		TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHZ	Antenna	Vertical

Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
46.35	7.12	53.47	74.00	-20.53	peak
40.82	7.12	47.94	54.00	-6.06	AVG
36.74	9.84	46.58	74.00	-27.42	peak
34.18	9.84	44.02	54.00	-9.98	AVG
	0				
	- C-	®		<u> </u>	
		Ci -			< O
enna Factor + Ca	ble Loss – l	Pre-amplifier.	1		
	(dBµV) 46.35 40.82 36.74 34.18	(dBµV) (dB) 46.35 7.12 40.82 7.12 36.74 9.84 34.18 9.84	(dBμV)     (dB)     (dBμV/m)       46.35     7.12     53.47       40.82     7.12     47.94       36.74     9.84     46.58	(dBμV)     (dB)     (dBμV/m)     (dBμV/m)       46.35     7.12     53.47     74.00       40.82     7.12     47.94     54.00       36.74     9.84     46.58     74.00       34.18     9.84     44.02     54.00	(dBμV)     (dB)     (dBμV/m)     (dBμV/m)     (dBμV/m)       46.35     7.12     53.47     74.00     -20.53       40.82     7.12     47.94     54.00     -6.06       36.74     9.84     46.58     74.00     -27.42       34.18     9.84     44.02     54.00     -9.98



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 






EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2437MHZ	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4874.062	43.35	7.12	50.47	74.00	-23.53	peak
4874.062	38.96	7.12	46.08	54.00	-7.92	AVG
7311.093	39.26	9.84	49.10	74.00	-24.90	peak
7311.093	37.67	9.84	47.51	54.00	-6.49	AVG
- G	8				8	
0	-0	0			- C	9
Remark:		1			10	
actor = Ante	enna Factor + C	able Loss – I	Pre-amplifier.	(6)		

EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2437MHZ	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4874.062	44.29	7.12	51.41	74.00	-22.59	peak
4874.062	41.52	7.12	48.64	54.00	-5.36	AVG
7311.093	39.74	9.84	49.58	74.00	-24.42	peak
7311.093	36.87	9.84	46.71	54.00	-7.29	AVG
Remark:						
actor = Ante	enna Factor + Ca	ble Loss – I	Pre-amplifier.		0	







EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2462MHZ	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4924.062	43.58	7.12	50.70	74.00	-23.30	peak
4924.062	41.57	7.12	48.69	54.00	-5.31	AVG
7386.093	37.77	9.84	47.61	74.00	-26.39	peak
7386.093	35.82	9.84	45.66	54.00	-8.34	AVG
- Cı				-6	8	
0	- C	<b>®</b>			- C	0
Remark:		1				
actor = Ante	enna Factor + C	able Loss – l	Pre-amplifier.	0		
				337		

EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2462MHZ	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4924.062	43.35	7.12	50.47	74.00	-23.53	peak
4924.062	41.52	7.12	48.64	54.00	-5.36	AVG
7386.093	37.80	9.84	47.64	74.00	-26.36	peak
7386.093	35.68	9.84	45.52	54.00	-8.48	AVG
a.C						0
	-C	<b>©</b>		C		
Remark:		- 6	®		< C	
actor = Ante	enna Factor + Ca	ble Loss –	Pre-amplifier.	0		<b>\</b> (0)

# **RESULT: PASS**

#### Note:

Other emissions from 1G to 25 GHz are considered as ambient noise. No recording in the test report. Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

All test modes had been pre-tested. The 802.11b mode is the worst case and recorded in the report.



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,



Report No.: AGC05925190404FE05

Page 65 of 96

#### 12. BAND EDGE EMISSION

#### 12.1. MEASUREMENT PROCEDURE

Radiated restricted band edge measurements

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting

#### 12.2. TEST SET-UP

same as 11.2

#### Note:

- 1. Factor=Antenna Factor + Cable loss Amplifier gain. Field Strength=Factor + Reading level
- 2. The factor had been edited in the "Input Correction" of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB( $\mu$ V) to represent the Amplitude. Use the F dB( $\mu$ V/m) to represent the Field Strength. So A=F.



Xixiang, Bao'an District, Shenzhen, Guangdong, China



#### 12.3. Test Result

EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHZ	Antenna	Horizontal

#### PK



#### AV




# **RESULT: PASS**



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHZ	Antenna	Vertical



#### ΑV




# **RESULT: PASS**



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHZ	Antenna	Horizontal



#### ΑV




# **RESULT: PASS**



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHZ	Antenna	Vertical



#### ΑV




# **RESULT: PASS**



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2412MHZ	Antenna	Horizontal



#### ΑV




# **RESULT: PASS**



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2412MHZ	Antenna	Vertical



#### ΑV




# **RESULT: PASS**



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2462MHZ	Antenna	Horizontal



#### ΑV




# **RESULT: PASS**



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2462MHZ	Antenna	Vertical



#### ΑV




# **RESULT: PASS**



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2412MHZ	Antenna	Horizontal



#### ΑV




# **RESULT: PASS**



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2412MHZ	Antenna	Vertical



#### ΑV




# **RESULT: PASS**



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2462MHZ	Antenna	Horizontal



#### ΑV




# **RESULT: PASS**



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2462MHZ	Antenna	Vertical



#### ΑV




# **RESULT: PASS**



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 40 with data rate 13.5 2422MHZ	Antenna	Horizontal



#### ΑV




# **RESULT: PASS**



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 40 with data rate 13.5 2422MHZ	Antenna	Vertical



#### ΑV




# **RESULT: PASS**



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,





EUT	Teton Router 750	Model Name	TR750
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 40with data rate 13.5 2452MHZ	Antenna	Horizontal



#### ΑV



# **RESULT: PASS**



 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,