## **Cover Letter-Wireless Charger Approval**

FCC ID: 2ARVRWC067CLK Date: 2020-05-31

## Gentlemen:

There's a Qi Wireless charging Pad that would like to have your authorization as an Inductive wireless power transfer applications approval.

The specific product as below, Qi Wireless charging Pad, with its designed features and specified description, meets special requirements for KDB 680106 D01 section 5.2 requirements.

| Company:      | SHENZHEN DBK ELECTRONICS CO., LTD |
|---------------|-----------------------------------|
| Product Name: | Qi Wireless charging Pad          |
| Model Number: | WC067BLK                          |
| FCC ID:       | 2ARVRWC067BLK                     |

| KDB 680106 D01 Section 5.2 Requirements:                             | Product Technical Specification:   | Result:  |
|--|------------------------------------|----------|
| a) Power transfer frequency is less than 1 MHz                       | 120.19kHz to 149.84kHz             | Complied |
| b) Output power from each primary coil is less than or equal to      | 5watts                             | Complied |
| 15 watts.  |                                    |          |
| c) The transfer system includes only single primary and secondary    |                                    | Complied |
| coils. This includes charging systems that may have multiple         |                                    |          |
| primary coils and clients that are able to detect and allow          |                                    |          |
| coupling only between individual pairs of coils                      |                                    |          |
| d) Client device is placed directly in contact with the transmitter. |                                    | Complied |
| e) Mobile exposure conditions only (portable exposure conditions     |                                    | Complied |
| are not covered by this exclusion)                                   |                                    |          |
| f) The aggregate H-field strengths at 15 cm surrounding the          | Please refer to RF exposure report | Complied |
| device and 20 cm above the top surface from all simultaneous         |                                    |          |
| transmitting coils are demonstrated to be less than 50% of the       |                                    |          |
| MPE limit.   |                                    |          |

Sincerely,

Print Name: Daniel Kang

Signature:

Title: Sales Director

On behalf of Company: SHENZHEN DBK ELECTRONICS CO., LTD.

Telephone: 86-755-61861886

Fax: 86-755-61886160

E-mail: Daniel.Kang@dbk.com.cn