

RF Exposure Evaluation Report

Product : Bluetooth Controller
Trade mark : JULY
Model/Type reference : BLU-SEN-C, BLU-SEN-CXX('XX' can be 0-9 or A-Z)
Serial Number : N/A
Report Number : EED32K00316702
FCC ID : 2ARWE01BLUSE01
Date of Issue : Dec. 24, 2018
47 CFR Part 1.1307
Test Standards : 47 CFR Part 1.1310
KDB447498D01v06
Test result : PASS

Prepared for:

Shanghai July Electronic Co., Ltd.
Room 310, building C, 255 MEG Road, Minhang District, Shanghai

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Tested by:

Tom-chen

Compiled by:

Peter

Reviewed by:

Ware Xin

Approved by:

Kevin Yang

Date:

Dec. 24, 2018

Check No.:3319502743



2 Version

Version No.	Date	Description
00	Dec. 24, 2018	Original

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 RF EXPOSURE EVALUATION	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.1.1 Limits.....	6
5.1.2 Test Procedure.....	6
5.1.3 EUT RF Exposure Evaluation.....	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	8

4 General Information

4.1 Client Information

Applicant:	Shanghai July Electronic Co., Ltd.
Address of Applicant:	Room 310, building C, 255 MEG Road, Minhang District, Shanghai
Manufacturer:	Shanghai July Electronic Co., Ltd.
Address of Manufacturer:	Room 310, building C, 255 MEG Road, Minhang District, Shanghai
Factory:	Wuxi Toyo Electric Co., Ltd
Address of Factory:	No. 18 Xianguang Road, Mashan, Binhu District, Wuxi City, Jiangsu Province, P. R. China

4.2 General Description of EUT

Product Name:	Bluetooth Controller
Model No.:	BLU-SEN-C, BLU-SEN-CXX('XX' can be 0-9 or A-Z)
Test Model No.:	BLU-SEN-C
Trade Mark:	JULY
EUT Supports Radios application	BT: 4.2 BT Dual mode: 2402MHz to 2480MHz

4.3 Product Specification subjective to this standard

Frequency Range:	2402MHz to 2480MHz
Sample Type:	Fixed production
Test Power Grade:	N/A
Test Software of EUT:	N/A
Antenna Type:	Monopole Antenna
Antenna Gain:	2dBi
Power Supply:	DC 3.3V
Test Voltage:	AC 120V
Conducted Peak Output Power:	5.226dBm The Conducted Peak Output Power data refer to the report EED32K00316701
Firmware version:	v317(manufacturer declare)
Hardware version:	V1.0(manufacturer declare)
Sample Received Date:	Nov. 23, 2018
Sample tested Date:	Nov. 29, 2018 to Dec. 24, 2018
<p>The tested sample(s) and the sample information are provided by the client. Model No.: BLU-SEN-C, BLU-SEN-CXX('XX' can be 0-9 or A-Z) Only the model BLU-SEN-C was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference outer decoration.</p>	

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R= distance to the centre of radiation of the antenna

EIRP = P*G

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user.

Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limit S, then we can conclude the device complies with the rules.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.

5.1.3 EUT RF Exposure Evaluation

Antenna Gain: 2dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency (MHz)	Max Conducted Peak Output Power(dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R (cm)	S (mW/cm ²)	Limit (mW/cm ²)	Result
Highest	2480	5.226	2	7.226	5.280	20	0.001	1.0	Pass

Note: Refer to report No.EED32K00316701for EUT test Max Conducted Peak Output Power value.

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32K00316701 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.