

# FCC RF Exposure

EUT Description: **Earmuff**  
 Model No.: **Vanquish Pro Elite**  
 FCC ID: **2ARWF-VANQUISH**

## 1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤50 mm are determined by:

$[(\text{max power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,

Where:

Result =  $P / D \cdot \sqrt{F}$

F = the RF channel transmit frequency in GHz

P = Maximum turn-up power in mw

D = Min. test separation distance in mm

## 2. Test Result of RF Exposure Evaluation

### 2.4G

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	frequency (GHz)	Min test separation distance mm	Result	Limit (mW/cm <sup>2</sup> )	SAR Test Exclusion
EDR	3.45	3±1	4/ 2.51	2.480	5	0.790	3.0	Pass

Note:  
 PK Output power = conducted power.  
 Conducted power see the test report HK1909252465-E,  
 antenna gain = 0dBi

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.790 which is ≤ 3, SAR testing is not required.

Note: Exclusion Thresholds Results =  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz

Distance = 5mm