

RF Exposure Report

Report No.: SABHDI-WTW-P21120081

FCC ID: 2ARXKVHE09-4GL

Test Model: VHE09-4GL, VHH09-4GL

Series Model: VHE09XXXXX (X=A-Z, 0-9, blank or "-")

Received Date: Dec. 24, 2021

Date of Evaluation: Apr. 07, 2022

Issued Date: Apr. 22, 2022

Applicant: Veea Inc

Address: 164 E 83rd Street, New York NY, 10028, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SABHDI-WTW-P21120081	Original Release	Apr. 22, 2022

1 Certificate of Conformity

Product: veeaHub

Brand: 

Test Model: VHE09-4GL, VHH09-4GL

Series Model: VHE09XXXXX (X=A-Z, 0-9, blank or "-")

Sample Status: Engineering Sample


Applicant: Veea Inc


Date of Evaluation: Apr. 07, 2022

Standards: FCC Part 2 (Section 2.1091)

References Test Guidance : KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :  _____, **Date:** Apr. 22, 2022
Lena Wang / Specialist

Approved by :  _____, **Date:** Apr. 22, 2022
Jeremy Lin / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 33 cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max AV Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2412~2462	27.13	6.21	33	0.158	1
WLAN 5180~5240	28.94	8.12	33	0.371	1
WLAN 5260~5320	23.36	8.12	33	0.103	1
WLAN 5500~5720	23.63	8.12	33	0.109	1
WLAN 5745~5825	29.65	8.12	33	0.437	1
Zigbee 2405~2475	16.76	3.2	33	0.007	1
BT LE 2402~2480	-5.33	6.0	33	0.0001	1
BT EDR 2402~2480	0.03	6.0	33	0.0003	1
LoRa 923.3 MHz – 927.5 MHz	24.71	5.0	33	0.068	0.616

For WLAN 2.4GHz Band: Directional gain = 3.2dBi + 10log(2) = 6.21dBi

For WLAN 5.0GHz Band: Directional gain = 2.1dBi + 10log(4) = 8.12dBi

For Zigbee: antenna gain = 3.2dBi

For BT: max. antenna gain = 6.0dBi

For LoRa: antenna gain = 5.0dBi

WWAN (module model: EG25G MINPCIE)

Band	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
GSM850	824-849	32.60	0.3	33	0.142	0.55
PCS1900	1850-1910	28.54	1.7	33	0.077	1.00
WCDMA II	1850-1910	23.49	1.7	33	0.024	1.00
WCDMA IV	1710-1755	23.60	1.7	33	0.025	1.00
WCDMA V	824-849	23.68	0.3	33	0.018	0.55
LTE 2	1850-1910	22.72	1.7	33	0.020	1.00
LTE 4	1710-1755	22.96	1.7	33	0.021	1.00
LTE 5	824-849	23.41	0.3	33	0.017	0.55
LTE 7	2500-2570	22.50	2.3	33	0.022	1.00
LTE 12	699-716	22.96	0.3	33	0.015	0.47
LTE 13	777-787	23.56	0.3	33	0.018	0.52
LTE 25	1850-1915	22.88	1.7	33	0.021	1.00
LTE 26	814-849	23.48	0.3	33	0.017	0.54
LTE 38	2575-2610	22.52	2.3	33	0.022	1.00
LTE 41	2496-2690	22.51	2.3	33	0.022	1.00

Note:

1. This report is issued as a supplementary report to BV CPS report no. SA200424C06. The difference compared with original report is adding model name (VHH09-4GL), updating mainboard and changing WWAN Module (EG25-G MINIPCIE). Therefore, MPE value was re-calculated in this report.

2. Model difference as below

Model	Type	LoRa Module	LTE Module	LED for LTE Status	Power Button	USB 3.0	Console	SD Slot	Power	PCB Design
VHE09-4GL	Indoor	RG-1008M (915MHz)	EC25A	Y	Y	Y	Y(RS-232)	Y	65W DC-48V desktop power adapter	Same design (VHE09/VHE10/VHH10)
VHH09-4GL	Outdoor	RG-1008M (915MHz)	EG25G	N	N	N	Y(M.12)	N	Power adapter or PoE	

3. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
4. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible
5. Contains module FCC ID: 2ATM8EG25G

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4G + WLAN 5G + Zigbee + Bluetooth + LoRa + WWAN (module model: EG25G MINPCIE) =
 $0.158/1+0.437/1+0.007/1+0.0003/1+0.068/0.616+0.142/0.55=0.971$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---