

TEST REPORT FOR BLUETOOTH TESTING

Report No: SRTC2019-9004(F)-19080201(E)

Product Name: Fi Smart Collar

Product Model: FC1

Applicant: Barking Labs Corp.

Manufacturer: Barking Labs Corp.

Specification: FCC Part 15, Subpart C (2019)

FCC ID: 2ARXN-FC1

The State Radio_monitoring_center Testing Center (SRTC)

15th Building, No.30 Shixing Street, Shijingshan District,

Beijing, P.R.China

Tel: 86-10-57996183 Fax: 86-10-57996388

CONTENTS

1. GENERAL INFORMATION	2
1.1 NOTES OF THE TEST REPORT	2
1.2 INFORMATION ABOUT THE TESTING LABORATORY	2
1.3 APPLICANT’S DETAILS	2
1.4 MANUFACTURER’S DETAILS	2
1.5 TEST ENVIRONMENT	3
2 DESCRIPTION OF THE DEVICE UNDER TEST	4
2.1 FINAL EQUIPMENT BUILD STATUS	4
2.2 DESCRIPTION OF TEST MODES	5
2.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	5
2.3 DUTY CYCLE OF TEST SIGNAL	6
2.4 EUT OPERATING CONDITIONS	7
2.5 SUPPORT EQUIPMENT	7
3 REFERENCE SPECIFICATION	8
4 KEY TO NOTES AND RESULT CODES	8
5 RESULT SUMMARY	9
6 TEST RESULT	10
6.1 OCCUPIED BANDWIDTH	10
6.2 PEAK POWER OUTPUT	11
6.3 TRANSMITTER POWER SPECTRAL DENSITY	12
6.4 CONDUCTED OUT OF BAND EMISSION MEASUREMENT	13
6.5 BAND-EDGE MEASUREMENT	14
6.6 SPURIOUS RADIATED EMISSIONS	16
6.7 AC POWER LINE CONDUCTED EMISSION	21
7 MEASUREMENT UNCERTAINTIES	23
8 TEST EQUIPMENTS	24
APPENDIX A – TEST DATA OF CONDUCTED EMISSION	25
APPENDIX B – TEST DATA OF RADIATED EMISSION	32

1. GENERAL INFORMATION

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

1.2 Information about the testing laboratory

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	15th Building, No.30 Shixing Street, Shijingshan District, P.R.China
City:	Beijing
Country or Region:	P.R.China
Contacted person:	Liu Jia
Tel:	+86 10 57996183
Fax:	+86 10 57996388
Email:	liujiaf@srtc.org.cn

1.3 Applicant's details

Company:	Barking Labs Corp.
Address:	53 Bridge St., Suite 103
City:	Brooklyn, NY
Country or Region:	USA
Contacted person:	Bob Blake
Tel:	+1-914-249-9347
Fax:	---
Email:	bob@tryfi.com

1.4 Manufacturer's details

Company:	Barking Labs Corp.
Address:	53 Bridge St., Suite 103
City:	Brooklyn, NY
Country or Region:	USA
Contacted person:	Bob Blake
Tel:	+1-914-249-9347
Fax:	---
Email:	bob@tryfi.com

1.5 Test Environment

Date of Receipt of test sample at SRTC:	2019-01-29
Testing Start Date:	2019-01-29
Testing End Date:	2019-08-19

Environmental Data:	Temperature (°C)	Humidity (%)
Ambient	25	30

Normal Supply Voltage (V d.c.):	3.85
---------------------------------	------

2 DESCRIPTION OF THE DEVICE UNDER TEST

2.1 Final Equipment Build Status

Frequency Range	2.402GHz~2.480GHz
Number of Channel	40
Modulation Type	GFSK
Equipment Class	DTS
Channel Spacing	2MHz
Data Rate	1Mbps
Power Supply	Battery/Charge
HW Version	Rev.B
SW Version	1.0
SN	Sample 1#
Antenna type	Refer to Note
Antenna connector	Refer to Note

Note:

The antenna provide to the EUT, please refer to the following table:

Brand	Model	Antenna gain	Frequency range(GHz)	Antenna type	Connector Type
N/A	N/A	2.26dBi	2.402GHz~2.480GHz	IFA Antenna	N/A

Manufacturers ensure that their designs will not be modified by the user or third parties arbitrary antenna parameters and performance.

Note: The conducted test results of variant product derive from original product Report No.: SRTC2019-9004(F)-19012902(E).

2.2 Description of Test Modes

40 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

2.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE ≥ 1G	RE<1G	PLC	APCM	
GFSK	√	√	√	√	-

Where RE ≥ 1G: Radiated Emission above 1GHz RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Radiated Emission Test (Above 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	19	GFSK	1

Radiated Emission Test (Below 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	19	GFSK	1

Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	19	GFSK	1

Antenna Port Conducted Measurement:

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	0, 19, 39	GFSK	1

2.3 Duty Cycle of Test Signal

Duty cycle of test signal is < 98 %, duty factor shall be considered.

Duty cycle = 59.5%

Correction factor = $10 * \log (1/\text{duty cycle}) = 10 * \log (1/0.595) = 2.26 \text{ dB}$

2.4 EUT Operating conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

2.5 Support Equipment

The following support equipment was used to exercise the DUT during testing:

Equipment	Notebook
Manufacturer	LENOVO
Model Number	E420
SN	---

Equipment	Charger
Manufacturer	DEE VAN ENTERPRISE CO., LTD.
Model Number	DSA-5PF03-05 FUS 050100
SN	---

Equipment	USB cable
Manufacturer	SuZhou KELI TECHNOLOGY DEVELOPMENT CO., LTD.
Model Number	KLC-3103
SN	---

3 REFERENCE SPECIFICATION




Specification	Version	Title
15.35	2019	Measurement detector functions and bandwidths.
15.209	2019	Radiated emission limits; general requirements.
15.247	2019	Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.
15.203	2019	Antenna requirement
ANSI C63.10	2013	Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB 558074 D01	v05, August 24,2018	GUIDANCE FOR PERFORMING COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEMS (DTS) OPERATING UNDER SECTION 15.247

4 KEY TO NOTES AND RESULT CODES

Code	Meaning
PASS	Test result shows that the requirements of the relevant specification have been met.
FAIL	Test result shows that the requirements of the relevant specification have not been met.
N/T	Test case is not tested.
NTC	Nominal voltage, Normal Temperature
HV	High voltage, Normal Temperature
LV	Low voltage, Normal Temperature
HTHV	high voltage, High Temperature
LTHV	High voltage, Low Temperature
HTLV	Low voltage, High Temperature
LTLV	Low voltage, Low Temperature

5 RESULT SUMMARY

No.	Test case	Reference	Verdict
1	Occupied Bandwidth	15.247(a)(2)	Pass
2	Peak Power Output	15.247(b)(3))	Pass
3	Transmitter Power Spectral Density	15.247(e))	Pass
4	Conducted Out of band emission measurement	15.247(d)	Pass
5	Band-edge	15.247(d)	Pass
6	Spurious Radiated Emissions	15.247(d)/15.35(b)/15.209	Pass
7	AC Power line Conducted Emission	15.207	Pass
8	Antenna requirement	15.203	Pass (refer to section 2.1)

This Test Report Is Issued by: Mr. Peng Zhen 	Checked by: Mr. Li Bin 
Tested by: Mr. He Dengshun 	Issued date: 20190820

6 TEST RESULT

6.1 Occupied Bandwidth

6.1.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

6.1.2 Test Description

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer and Bluetooth test set via a power splitter with a known loss. Which connected to the transmitter antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies. All modes of operation were investigated and the worst case configuration results are reported in this section.

6.1.3 Test limit

Part15.247 (a)(2)

The minimum permissible 6dB bandwidth is 500 kHz

6.1.4 Test Procedure Used


KDB 558074 D01 DTS Meas Guidance v05 – Section 8.1 Option 1

6.1.5 Test Settings

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.1.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.1.7 Test result

The test results are shown in Appendix A .

6.2 Peak Power Output

6.2.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

6.2.2 Test Description

The transmitter antenna terminal of the EUT is connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss. Measurements are made while the EUT is operating at maximum power and at the appropriate frequencies.

6.2.3 Test limit

Part15.247(b)(3)

The maximum permissible conducted output power is 1 Watt.

Used conversion factor: Limit (dBm) = 10 log (Limit (W)/1mW)

==> Maximum Output Power: 30.0 dBm

6.2.4 Test Procedure Used


KDB 558074 D01 DTS Meas Guidance v05 - Section 9.1.3

6.2.5 Test Settings

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

6.2.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.2.7 Test result

The test results are shown in Appendix A .

6.3 Transmitter Power Spectral Density

6.3.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

6.3.2 Test Description

The peak power density is measured with a spectrum analyzer and Bluetooth test set via a power splitter with a known loss connected to the antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies.

6.3.3 Test limit

Part15.247(e)

The maximum permissible power spectral density is 8.0 dBm in any 3 kHz band.

6.3.4 Test Procedure Used


KDB 558074 D01 DTS Meas Guidance v05 Section 10.2.

6.3.5 Test Settings

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.3.7 Test result

The test results are shown in Appendix A.

6.4 Conducted Out of band emission measurement

6.4.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

6.4.2 Test Description

For the following out of band conducted spurious emissions plots, the EUT was set to transmit at maximum power with the largest packet size available. The worst case spurious emissions were found in this configuration.

6.4.3 Test limit

Part 15.247(d) The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.

6.4.4 Test Procedure Used

KDB 558074 D01 DTS Meas Guidance v05 Section 11.3,11.2

6.4.5 Reference level measurement Settings

Establish a reference level by using the following procedure:


- Set instrument center frequency to DTS channel center frequency.
- Set the span to ≥ 1.5 MHz
- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

6.4.6 Test Settings

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Set span to encompass the spectrum to be examined
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

6.4.8 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.4.9 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

The test results are shown in Appendix A .

6.5 Band-edge measurement

6.5.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

6.5.2 Test Description

For the following out of band conducted spurious emissions plots, the EUT was set to transmit at maximum power with the largest packet size available. The worst case spurious emissions were found in this configuration.

6.5.3 Test limit

Part 15.247(d)

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.

6.5.4 Test Procedure Used

KDB 558074 D01 DTS Meas Guidance v05 Section 11.2

6.5.5 Reference level measurement Settings

Establish a reference level by using the following procedure:

- Set instrument center frequency to DTS channel center frequency.
- Set the span to ≥ 1.5 MHz
- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.


6.5.6 Test Settings

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.

- e) Set span to encompass the spectrum to be examined
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level.

6.5.8 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.5.9 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement. The test results are shown in Appendix A .

6.6 Spurious Radiated Emissions

6.6.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

6.6.2 Test Description

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section. The measurements shall be repeated with orthogonal polarization of the test antenna. The results shall be showed the worst case of the three orthogonal axes of EUT.

6.6.3 Test limit

Part15.205, 15.209, 15.247(d)

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in below Table per Section 15.209.

Frequency [MHz]	Field strength [μV/m]	Measured Distance [meters]
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Radiated Limits

Part15.35(b):

there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit

Used conversion factor: Limit (dBμV/m) = 20 log (Limit (μV/m)/1μV/m)

Frequency [MHz]	Detector	Unit (dBμV/m)
30~88	Quasi-peak	40.0
88~216	Quasi-peak	43.5
216~960	Quasi-peak	46.0
960~1000	Quasi-peak	54.0
1000~5th harmonic of the highest frequency or 40GHz, whichever is lower	Average	54.0
	Peak	74.0

Conversion Radiated limits

6.6.4 Test Procedure Used

KDB 558074 D01 DTS Meas Guidance v05 - Section 12.2.7

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement

antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Average detection (AV) at frequency above 1GHz. If duty cycle of test signal is < 98%, the duty factor need added to measured value.
4. All modes of operation were investigated and the worst-case emissions are reported.

6.6.5 Test Settings

Average Field Strength Measurements per Section 12.2.7 of KDB 558074 (Part 15.35)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz > 1/T
4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
5. Detector = peak
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to run for at least 50 times (1/duty cycle) traces

Peak Field Strength Measurements per Section 12.2.7of KDB 558074 (Part 15.35)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in following table

Frequency	RBW
9-150kHz	200-300Hz
0.15-30MHz	9-10kHz
30-1000MHz	100-120kHz
>1000MHz	1MHz


3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

6.6.6 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



6.6.7 Test result

The test results are shown in Appendix B.

6.7 AC Power line Conducted Emission

6.7.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

6.7.2 Test limit

FCC Part15.207

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

The measurement is made according to ANSI C63.10-2013

6.7.3 Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.


b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

The EUT shall test under the power AC120V/60Hz.

6.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.5 Test result

The test results are shown in AppendixB .

7 MEASUREMENT UNCERTAINTIES

Items	Uncertainty	
Occupied Bandwidth	3kHz	
Peak power output	0.67dB	
Band edge compliance	1.20dB	
Spurious emissions	30MHz~1GHz	2.83dB
	1GHz~12.75GHz	2.50dB
	12.75GHz~25GHz	2.75dB

8 TEST EQUIPMENTS

No.	Name/ Model	Manufacturer	S/N	Cal date	Cal Due date
1.	Spectrum Analyzer FSV	ROHDE&SCHWARZ	101065	2018.08.20	2019.08.19
2.	Power Meter E4416A	Agilent	MY52370013	2019.03.01	2020.02.28
3.	Power Sensor E9327A	Agilent	MY52420006	2019.03.01	2020.02.28
4.	23.18m×16.88m×9.60m Semi-Anechoic Chamber	FRANKONIA	---	----	----
5.	Turn table Diameter:5m	FRANKONIA	----	----	----
6.	Antenna master SAC(MA4.0)	MATURO	----	----	----
7.	9.080m×5.255m×3.525m Shielding room	FRANKONIA	----	----	----
8.	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	2018.08.20	2019.08.19
9.	3160-09 Receive antenna	SCHWARZ-BECK	002058-002	2018.08.20	2019.08.19
10.	ESI 40 EMI test receiver	R&S	100015	2018.08.20	2019.08.19
11.	ESCS30 EMI test receiver	R&S	100029	2018.08.20	2019.08.19
12.	HL562 Receive antenna	R&S	100167	2018.08.20	2019.08.19
13.	ENV216 AMN	R&S	3560.6550.12	2018.08.20	2019.08.19


APPENDIX A – TEST DATA OF CONDUCTED EMISSION

6dB Bandwidth

Offset 1.0dB = Temporary antenna connector loss 0.2dB+ Cable loss 0.8dB


Modulation type: GFSK (LE 1Mbps)

Carrier frequency (MHz)	Channel No.	6 dB bandwidth(kHz)
2402	0	723.53
2440	19	720.13
2480	39	715.53




Date: 12.FEB.2019 18:11:32

Carrier frequency (MHz): 2402
Channel No.:0
Modulation type: GFSK (LE 1Mbps)



Date: 12.FEB.2019 18:13:37

Carrier frequency (MHz): 2440
Channel No.:19
Modulation type: GFSK (LE 1Mbps)



Date: 12.FEB.2019 18:14:12

Carrier frequency (MHz): 2480
Channel No.:39
Modulation type: GFSK (LE 1Mbps)

Peak Power Output

Modulation type	Peak Power Output (dBm)		
	2402MHz (Ch0)	2440MHz (Ch19)	2480MHz (Ch39)
GFSK (LE 1Mbps)	-1.34	-1.19	-1.78

Modulation type	Average Power Output (dBm)		
	2402MHz (Ch0)	2440MHz (Ch19)	2480MHz (Ch39)
GFSK (LE 1Mbps)	-3.44	-3.27	-3.15

Peak Power Output (Variant Test Result)

Modulation type	Peak Power Output (dBm)		
	2402MHz (Ch0)	2440MHz (Ch19)	2480MHz (Ch39)
GFSK (LE 1Mbps)	-2.04	-2.03	-1.38


Modulation type	Average Power Output (dBm)		
	2402MHz (Ch0)	2440MHz (Ch19)	2480MHz (Ch39)
GFSK (LE 1Mbps)	-3.52	-3.39	-2.73

Transmitter Power Spectral Density

Offset 1.0dB = Temporary antenna connector loss 0.2dB+ Cable loss 0.8dB


Modulation type: GFSK (LE 1Mbps)

Carrier frequency (MHz)	Channel No	Power Density(dBm/10kHz)
2402	0	-10.20
2440	19	-10.26
2480	39	-10.03




Date: 12.FEB.2019 18:16:36

Carrier frequency (MHz): 2402
Channel No.:0
Modulation type: GFSK (LE 1Mbps)



Date: 12.FEB.2019 18:17:12

Carrier frequency (MHz): 2440
Channel No.:19
Modulation type: GFSK (LE 1Mbps)



Date: 12.FEB.2019 18:17:38


Carrier frequency (MHz): 2480
Channel No.:39
Modulation type: GFSK (LE 1Mbps)

Conducted Out of band emission measurement


Offset 1.0dB = Temporary antenna connector loss 0.2dB+ Cable loss 0.8dB

Modulation type: GFSK (LE 1Mbps)


CH0



CH19





CH39





Band edge measurement (RF Conducted measurement)

Offset 1.0dB = Temporary antenna connector loss 0.2dB+ Cable loss 0.8dB

CH0 GFSK (LE 1Mbps)



CH39 GFSK (LE 1Mbps)



APPENDIX B – TEST DATA OF RADIATED EMISSION

Spurious Radiated Emissions

The worst case attitude: The EUT lay down.

The measurement results are obtained as described below:

Measure Level = Reading Level + cable loss + antenna factor

Sample calculation: (90.60 dBuV/m) = (56.60 dBμV) + (8.90 dB) + (25.10 dB/m), the corresponding frequency is 2402MHz.

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB/m)
1	2402	90.60	56.60	N/A	N/A	8.90	25.10

Carrier frequency (MHz): 2402

Channel No.:0

Test Mode: GFSK (LE)

Polarity: Vertical

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB/m)
1	2402	90.60	56.60	N/A	N/A	8.90	25.10
2	2390	40.27	6.27	-33.73	74.0	8.90	25.10

Carrier frequency (MHz): 2402

Channel No.:0

Test Mode: GFSK (LE)

Polarity: Horizontal

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB/m)
1	2402	86.28	52.28	N/A	N/A	8.90	25.10
2	2390	34.64	0.64	-39.36	74.0	8.90	25.10

Carrier frequency (MHz): 2402

Channel No.:0

Test Mode: GFSK (LE)

Polarity: Vertical

Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB/m)
1	2402	80.04	46.04	N/A	N/A	8.90	25.10
2	2390	27.21	-6.79	-26.79	54.0	8.90	25.10

Carrier frequency (MHz): 2402
Channel No.:0
Test Mode: GFSK (LE)
Polarity: Horizontal
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB/m)
1	2402	76.54	42.54	N/A	N/A	8.90	25.10
2	2390	26.54	-7.46	-27.46	54.0	8.90	25.10

Carrier frequency (MHz): 2480
Channel No.:39
Test Mode: GFSK (LE)
Polarity: Vertical
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB/m)
1	2480	89.83	55.83	N/A	N/A	8.90	25.10
2	2483.5	37.27	3.27	-36.73	74.0	8.90	25.10

Carrier frequency (MHz): 2480
Channel No.:39
Test Mode: GFSK (LE)
Polarity: Horizontal
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB/m)
1	2480	86.29	52.29	N/A	N/A	8.90	25.10
2	2483.5	35.34	1.34	-38.66	74.0	8.90	25.10

Carrier frequency (MHz): 2480
Channel No.:39
Test Mode: GFSK (LE)
Polarity: Vertical
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB/m)
1	2480	77.56	43.56	N/A	N/A	8.90	25.10
2	2483.5	25.95	-8.05	-28.05	54.0	8.90	25.10

Carrier frequency (MHz): 2480
Channel No.:39
Test Mode: GFSK (LE)
Polarity: Horizontal
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB/m)
1	2480	76.50	42.50	N/A	N/A	8.90	25.10
2	2483.5	24.87	-9.13	-29.13	54.0	8.90	25.10

Sample Calculations

Determining Spurious Emissions Levels

A “reference path loss” is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{mea}} + A_{Rpl}$$

Sample calculation: $(20.39 \text{ dB}\mu\text{V/m}) = (40.09 \text{ dBuV}) + (-19.7 \text{ dB/m})$, the corresponding frequency is 34.898500MHz.

Frequency (MHz)	Result (dBuV/m)	A_{Rpl} (dB/m)	P_{mea} (dBuV)	Polarity
34.898500	20.39	-19.7	40.09	V

The worst case attitude: The EUT lay down.

For GFSK (LE)

Channel No.:0

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity
34.898500	20.39	-19.7	40.09	V
35.771500	20.33	-19.5	39.83	V
36.014000	21.07	-19.4	40.47	V
37.954000	29.22	-18.8	48.02	V
38.099500	29.30	-18.8	48.1	V
38.730000	30.59	-18.6	49.19	V
39.797000	29.48	-18.2	47.68	V
42.319000	28.97	-17.9	46.87	V
42.707000	28.31	-17.8	46.11	V
43.871000	28.18	-17.7	45.88	V

For GFSK (LE)

Channel No.:19


Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity
37.178000	29.24	-20.5	49.74	V
38.002500	30.48	-20.1	50.58	V
38.148000	29.31	-18.8	48.11	V
38.342000	30.11	-18.6	48.71	V
39.312000	29.77	-18.5	48.27	V
42.901000	28.09	-18.4	46.49	V
45.520000	27.36	-18.1	45.46	V
46.247500	27.01	-18.0	45.01	V
64.435000	20.32	-17.8	38.12	V
800.034500	23.29	-17.5	40.79	V

For GFSK (LE)

Channel No.:39


Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity
30.145500	20.83	-21.1	41.93	V
31.649000	21.70	-20.7	42.4	V
32.813000	21.71	-20.3	42.01	V
33.880000	20.36	-20.0	40.36	V
34.074000	20.23	-20.0	40.23	V
42.319000	23.37	-17.9	41.27	V
45.956500	27.22	-17.5	44.72	V
63.853000	18.69	-19.7	38.39	V
901.011500	22.79	-1.5	24.29	V
928.802000	22.82	-1.1	23.92	V

Full Spectrum




Frequency Range: 30MHz-1000 MHz
Detector: QP mode
Modulation type: GFSK (LE)
Channel No.:0

Full Spectrum




Frequency Range: 1GHz-3GHz
Detector: Av mode and PK mode
Modulation type: GFSK (LE)
Channel No.:0

Full Spectrum




Frequency Range: 3GHz-18GHz
Detector: Av mode and PK mode
Modulation type: GFSK (LE)
Channel No.:0

Full Spectrum



Frequency Range: 18GHz-26.5GHz
Detector: Av mode and PK mode
Modulation type: GFSK (LE)
Channel No.:0

Full Spectrum




Frequency Range: 30MHz-1000 MHz

Detector: QP mode

Modulation type: GFSK (LE)

Channel No.:19

Full Spectrum




Frequency Range: 1GHz-3GHz

Detector: Av mode and PK mode

Modulation type: GFSK (LE)


Channel No.:19

Full Spectrum




Frequency Range: 3GHz-18GHz
Detector: Av mode and PK mode
Modulation type: GFSK (LE)
Channel No.:19

Full Spectrum




Frequency Range: 18GHz-26.5GHz
Detector: Av mode and PK mode
Modulation type: GFSK (LE)
Channel No.:19

Full Spectrum




Frequency Range: 30MHz-1000 MHz
 Detector: QP mode
 Modulation type: GFSK (LE)
 Channel No.:39

Full Spectrum




Frequency Range: 1GHz-3GHz
 Detector: Av mode and PK mode
 Modulation type: GFSK (LE)
 Channel No.:39

Full Spectrum



Frequency Range: 3GHz-18GHz
Detector: Av mode and PK mode
Modulation type: GFSK (LE)
Channel No.:39

Full Spectrum



Frequency Range: 18GHz-26.5GHz
Detector: Av mode and PK mode
Modulation type: GFSK (LE)
Channel No.:39

AC Power line Conducted Emission


A "reference path loss" Corr.(dB) is established and the $L_{cable}+ATT+VDF$ is the attenuation of "reference path loss", and including the cable loss, the attenuation of the attenuator, the voltage division factor of AMN.

The measurement results are obtained as described below:

$$P_{result} = P_{mea} + Corr.(dB)$$

Sample calculation: $(43.87 \text{ dB}\mu\text{V}) = (14.17 \text{ dB}\mu\text{V}) + (29.7 \text{ dB})$, the corresponding frequency is 0.308295MHz.

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)	Pmea MaxPeak (dBμV)	Pmea Average (dBμV)
0.308295	43.87	---	60.02	16.14	L1	29.7	14.1	---



MEASUREMENT RESULT:

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)	Pme a Max Peak (dBμV)	Pme a Average (dBμV)
0.308295	43.87	---	60.02	16.14	L1	29.7	14.1	---
0.308295	---	37.26	50.02	12.75	L1	29.7	---	7.56
0.466591	48.36	---	56.57	8.21	L1	29.7	18.6	---
0.466591	---	41.93	46.57	4.64	L1	29.7	---	12.2
1.258068	46.06	---	56.00	9.94	L1	29.7	16.3	---
1.262591	---	39.91	46.00	6.09	L1	29.7	---	10.2
2.474682	43.30	---	56.00	12.70	L1	29.8	13.5	---
2.515386	---	37.65	46.00	8.35	L1	29.8	---	7.85
5.201886	38.19	---	60.00	21.81	L1	29.8	8.39	---
5.242591	---	30.53	50.00	19.47	L1	29.8	---	0.73
16.386591	37.29	---	60.00	22.72	N	29.9	7.39	---
29.936682	---	28.01	50.00	21.99	L1	29.9	---	-1.89

---End of Test Report---