

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is a RC Car operating at 2.4G Band. The EUT can be powered by DC 7.4V (1 x 7.4V Rechargeable battery). Once use the USB cable charging to the EUT, the wireless function will be disabled. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -16.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -16.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 78.7dB $\mu$ V/m at 3m in the frequency 2432MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -16.53dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 76.7dB $\mu$ V/m at 3m in the frequency 2463MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -18.53dBm

which is within the production variation.

The maximum conducted output power specified is -13.0dBm= 0.050mW

The source- based time-averaging conducted output power =0.050mW

The SAR Exclusion Threshold Level:

=  $3.0 \cdot (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

=  $3.0 \cdot 5 / \text{sqrt}(2.463)$  mW

= 9.56 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.