

## **MPE Calculation**

Applicant:	Ningbo Fiercer Leopard Electrical Appliance Co., Ltd.
Address:	No. 1&2, Wanghai Road (Wanghai Industrial Area) Xidian Town, 315611 Ninghai, Ningbo Zhejiang, PEOPLE'S REPUBLIC OF CHINA
Product:	Camera sensor wall light
FCC ID:	2ARY8-S-18
Model No.:	S-1801, S-1801A
Reference RF report #	68.940.18.0053.01A

According to subpart 15.247(i)and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure						
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm2)	Averaging Time (minutes)		
0.3–1.34	614	1.63	*(100)	30		
1.34–30	824/f	2.19/f	*(180/f²)	30		
30–300	27.5	0.073	0.2	30		
300–1,500	/	/	f/1500	30		
1,500–100,000	/	/	1.0	30		

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

 $S = PG/4 \pi R^2 =$  power density (in appropriate units, e.g. mW/cm2);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch

Building 12&13, Zhiheng Wisdomland Business Park, Nantou Checkpoint Road 2, Nanshan District, Shenzhen City,

518052, P. R. China Tel. +86 755 8828 6998, Fax: +86 755 8828 5299



For Camera sensor wall light

Maximum Average output power at antenna input terminal (dBm):	14.9
Maximum peak output power at antenna input terminal (mW):	30.9
Prediction distance (cm):	20
Antenna Gain, typical (dBi):	5
Maximum Antenna Gain (numeric):	3.16
The worst case is power density at predication frequency at 20 cm (mW/cm2):	0.0213
MPE limit for general population exposure at prediction frequency (mW/cm2):	1.0

0.0194(mW/cm<sup>2</sup>) < 1 (mW/cm<sup>2</sup>)

Result: Compliant

TUV SUD China, Shenzhen Branch

Reviewed by:

Prepared by:

Laurent Yuan/EMC Project Manager Date: 2019-02-28

Dani. Lu

Dawi Xu/EMC Project Engineer Date:2019-02-28