

# RF Exposure evaluation

FCC ID: **2ARYF-AW-90**

According to 447498 D01 General RF Exposure Guidance v06

## 4.3. General SAR test exclusion guidance

### 4.3.1. Standalone SAR test exclusion considerations

- a) For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR,<sup>30</sup> where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>31</sup>
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

<sup>30</sup> This is equivalent to the formula written as:  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (60 / \sqrt{f(\text{GHz})} \text{ mW})] \cdot [20 \text{ mm} / (\text{min. test separation distance, mm})] \leq 1.0$  for 1-g SAR; also see Appendix A for approximate exclusion threshold numerical values at selected frequencies and distances.

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{EXd})^2 / 30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, ---  $10((\text{dBuV/m})/20)/10^6$

d = measurement distance in meters (m)---3m

$$\text{So pt} = (\text{EXd})^2 / 30 \times \text{gt}$$

## RF Exposure evaluation

Copied from the FCC test report: clause 9.4 Maximum Peak Output Power

### Test Result:

For BLE:

Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
GFSK(BLE)	2402	0.10	1.0233	1000
	2442	0.06	1.0139	1000
	2480	-3.54	0.4426	1000

*Note: the antenna gain of 0dB less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.*

For EDR:

Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
GFSK(BLE)	2402	-2.32	0.5861	1000
	2442	-1.37	0.7295	1000
	2480	-1.06	0.7834	1000

EIRP/ dBm= Conducted Max Output Power/ dBm+ Antenna gain /dBi.

General RF Exposure:

$(1.0233\text{mW})/5.0\text{mm} \times \sqrt{2.402\text{ GHz}} = 0.32$

$(1.0139\text{mW})/5.0\text{mm} \times \sqrt{2.442\text{ GHz}} = 0.32$

$(0.4426\text{mW})/5.0\text{mm} \times \sqrt{2.480\text{ GHz}} = 0.14$

$(0.5861\text{mW})/5.0\text{mm} \times \sqrt{2.402\text{ GHz}} = 0.18$

$(0.7295\text{mW})/5.0\text{mm} \times \sqrt{2.442\text{ GHz}} = 0.23$

$(0.7834\text{mW})/5.0\text{mm} \times \sqrt{2.480\text{ GHz}} = 0.24$

SAR requirement: S=3.0

General RF Exposure<3

Then SAR evaluation is not required