

RF EXPOSURE REPORT

FOR

Applicant	:	Foner Technology Co., Ltd
Address	:	4/F, Fuxing Bldg, Binlang Road, Futian Free Trade Zone, SHENZHEN
Equipment under Test	:	Bluetooth Audio Adapter
Model No.	:	HOMI
Trade Mark	:	Palovue
FCC ID	:	2ARYG-HOMI
Manufacturer	:	Foner Electronics Co., Ltd.
Address	:	201, Floor 2, No.2 Building, Foxda Industrial Zone, Northern Lanzhu Road, Pingshan, Shenzhen, Guangdong, China

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,

Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

	Test report declares.....	3
1.	General Information	5
1.1.	Description of equipment	5
1.2.	Assess laboratory.....	5
2.	RF Exposure evaluation for FCC	5
2.1.	Tune-up	6

Test Report Declare

Applicant	:	Foner Technology Co., Ltd
Address	:	4/F, Fuxing Bldg, Binlang Road, Futian Free Trade Zone, SHENZHEN
Equipment under Test	:	Bluetooth Audio Adapter
Model No.	:	HOMi
Trade mark	:	Palovue
Manufacturer	:	Foner Electronics Co., Ltd.
Address	:	201, Floor 2, No.2 Building, Foxda Industrial Zone, Northern Lanzhu Road, Pingshan, Shenzhen, Guangdong, China

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-R20090914-2E7		
Date of Receipt:	Sep. 25, 2020	Date of Test:	Sep. 25, 2020 ~ Nov. 25, 2020

Prepared By:

Talent Zhang

Talent Zhang/Engineer



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Nov. 25, 2020	

1. General Information

1.1. Description of equipment

Eut* Name	: Bluetooth Audio Adapter
Model Number	: HOMi
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 5V by Type C USB port
Radio Specification	: Bluetooth V5.0
Operation Frequency	: 2402MHz-2480MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Data Rate	: 1 Mbps, 2 Mbps, 3 Mbps
Antenna Type	: PCB antenna, maximum PK gain: 4 dBi
Sample Type	: Series production

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,
Guangdong Province, China, 523808

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com

CNAS Registration No. CNAS L6451; A2LA Certificate Number: 3870.01;

FCC Designation Number: CN1182; FCC Test Firm Registration Number: 540522

Industry Canada Site Registration Number: 10288A-1

2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

2.1. Tune-up

Mode	Antenna	Freq. (MHz)	Result (dBm)	Tune-up power
GFSK	ANT1	2402	6.56	7.00
	ANT1	2441	7.01	7.50
	ANT1	2480	5.99	6.00
$\pi/4$ -DQPSK	ANT1	2402	4.48	5.00
	ANT1	2441	5.21	6.00
	ANT1	2480	4.30	5.00
8DPSK	ANT1	2402	4.89	5.00
	ANT1	2441	5.66	6.00
	ANT1	2480	4.68	5.00

Worse case is as below: [2441MHz,7.50dBm 5.62mW) output power]

$(5.62/5) \cdot [\sqrt{2.441(\text{GHz})}] = 1.756 < 3.0$ for 1-g SAR

Then SAR evaluation is not required

END OF REPORT