

■ Report No.: DDT-R20072703-1E3

■Issued Date: Aug. 30, 2020

# RF EXPOSURE REPORT

### **FOR**

Applicant	:	Foneric Technology Co., Ltd
Address	:-	4/F, Fuxing Bldg, Binlang Road, Futian Free Trade Zone, SHENZHEN
Equipment under Test	:	Bluetooth 5.0 Hi-Fi Audio Adapter
Model No. ONG D		Liveflow ESTING
Trade Mark	••	Palovue
FCC ID	:	2ARYG-LIVEFLOW
Manufacturer		Foneric Electronics Co., Ltd.
Address	:	201, Floor 2, No.2 Building, Foxda Industrial Zone, Northern Lanzhu Road, Pingshan, Shenzhen, Guangdong, China

# Issued By: Dongguan Dongdian Testing Service Co., Ltd.

**Add.:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, E-mail: ddt@dgddt.com, http://www.dgddt.com



# **Table of Contents**

	Test report declares	3
1.	General Information	5
1.1.	Description of equipment	5
1.2.	Assess laboratory	5
2.	RF Exposure evaluation for FCC	5

## **Test Report Declare**

Applicant	:	Foneric Technology Co., Ltd
Address	:	4/F, Fuxing Bldg, Binlang Road, Futian Free Trade Zone, SHENZHEN
Equipment under Test	:	Bluetooth 5.0 Hi-Fi Audio Adapter
Model No.	:	Liveflow
Trade mark	:	Palovue
Manufacturer	:	Foneric Electronics Co., Ltd.
Address	:	201, Floor 2, No.2 Building, Foxda Industrial Zone, Northern Lanzhu Road, Pingshan, Shenzhen, Guangdong, China

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

#### We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-R20072703-1E3		
Date of Receipt:	Aug. 11, 2020	Date of Test:	Aug. 11, 2020 ~ Aug. 30, 2020

Prepared By:

Talent Zhang/Engineer

Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

# **Revision History**

Rev.	Revisions	Issue Date	Revised By
	Initial issue	Aug. 30, 2020	

### 1. General Information

### 1.1. Description of equipment

Eut* Name	:	Bluetooth 5.0 Hi-Fi Audio Adapter
Model Number	:	Liveflow
<b>EUT Function Description</b>	••	Please reference user manual of this device
Power Supply	••	DC 5V by USB
Radio Specification	::	Bluetooth V5.0
Operation Frequency	••	2402MHz-2480MHz
Modulation	••	GFSK, π/4-DQPSK, 8DPSK
Data Rate	••	1 Mbps, 2 Mbps, 3 Mbps
Antenna Type	:	Ceramic antenna, maximum PK gain: 2.57 dBi
Sample Type	:	Series production

### 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,

Guangdong Province, China, 523808

Tel.: +86-0769-38826678, http://www.dgddt.com, Email: ddt@dgddt.com

CNAS Registration No. CNAS L6451; A2LA Certificate Number: 3870.01;

FCC Designation Number: CN1182; FCC Test Firm Registration Number: 540522

Industry Canada Site Registration Number: 10288A-1

## 2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where:

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Worse case is as below: [2441MHz,5.24dBm 3.34mW) output power]

 $(3.34/5) \cdot [\sqrt{2.441}(GHz)] = 1.044 < 3.0 \text{ for } 1-g \text{ SAR}$ 

Then SAR evaluation is not required

#### **END OF REPORT**