

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2ARYH -SAYA-SA0100

### EUT Specification

|                                   |   |   |  |
|-----------------------------------|---|---|--|
| <b>EUT</b>                        | <b>BLUEBOX UHF 1CH Mid Range Controller</b> |   |  |
| <b>Frequency band (Operating)</b> | <input type="checkbox"/>                    | WLAN: 2.412GHz ~ 2.462GHz   |  |
|                                   | <input type="checkbox"/>                    | WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz                       |  |
|                                   | <input type="checkbox"/>                    | WLAN: 5.745GHz ~ 5.825GHz   |  |
|                                   | <input checked="" type="checkbox"/>         | Others 910-920MHz   |  |
| <b>Device category</b>            | <input type="checkbox"/>                    | Portable (<20cm separation)                                       |  |
|                                   | <input checked="" type="checkbox"/>         | Mobile (>20cm separation)   |  |
|                                   | <input type="checkbox"/>                    | Others ____   |  |
| <b>Exposure classification</b>    | <input type="checkbox"/>                    | Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> )       |  |
|                                   | <input checked="" type="checkbox"/>         | General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> ) |  |
| <b>Antenna diversity</b>          | <input checked="" type="checkbox"/>         | Single antenna  |  |
|                                   | <input type="checkbox"/>                    | Multiple antennas   |  |
|                                   | <input type="checkbox"/>                    | Tx diversity  |  |
|                                   | <input type="checkbox"/>                    | Rx diversity  |  |
|                                   | <input type="checkbox"/>                    | Tx/Rx diversity   |  |
| <b>Max. output power</b>          | 13.670dBm (0.0233W)                         |   |  |
| <b>Antenna gain (Max)</b>         | 1.5 dBi                                     |   |  |
| <b>Evaluation applied</b>         | <input checked="" type="checkbox"/>         | MPE Evaluation  |  |
|                                   | <input type="checkbox"/>                    | SAR Evaluation  |  |

Limits for Maximum Permissible Exposure(MPE)

| Frequency Range(MHz)   | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm <sup>2</sup> ) | Average Time |
|--|------------------------------|------------------------------|------------------------------------|--------------|
| <b>(A) Limits for Occupational/Control Exposures</b>         |                              |                              |                                    |              |
| 300-1500   | --                           | --                           | F/300                              | 6            |
| 1500-100000  | --                           | --                           | 5                                  | 6            |
| <b>(B) Limits for General Population/Uncontrol Exposures</b> |                              |                              |                                    |              |
| 300-1500   | --                           | --                           | F/1500                             | 6            |
| 1500-100000  | --                           | --                           | 1                                  | 30           |

## Friis transmission formula: $P_d = \frac{P_{out} * G}{4 * \pi * R^2}$

Where

$P_d$  = Power density in  $mW/cm^2$

$P_{out}$  = output power to antenna in Mw

$G$  = gain of antenna in linear scale

$\pi = 3.1416$

$R$  = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE,  $1mW/cm^2$ . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

| Channel Frequency (MHz) | Measured Power (dBm) | Tune up tolerance (dBm) | Max. Tune up Power (dBm) | Antenna Gain (dBi) | Power density at 20cm ( $mW/cm^2$ ) | Power density Limits ( $mW/cm^2$ ) |
|-------------------------|----------------------|-------------------------|--------------------------|--------------------|-------------------------------------|------------------------------------|
| 910                     | 13.256               | $13.256 \pm 1$          | 14.26                    | 1.5                | 0.0075                              | 0.6067                             |
| 915                     | 13.297               | $13.297 \pm 1$          | 14.30                    | 1.5                | 0.0076                              | 0.6100                             |
| 920                     | 13.670               | $13.670 \pm 1$          | 14.67                    | 1.5                | 0.0082                              | 0.6133                             |