



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V04
Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No. : CQASZ20191001048E-02
Applicant: Dongguan OSM Technologies Co., Ltd
Address of Applicant: 1 to 6 / F, Building A, Longdi Industrial Park, No. 6 Tiansha Road, Keyuan City, Tangxia Town, Dong guan City
Equipment Under Test (EUT):
EUT Name: Beautiful Picture Tripod Selfie Stick
Mode No.: Oth-AB202PRO, Oth-AB202YT, Oth-AB202DY, Oth-AB202, ATSS024, hocoK13, SS101, SNAP-X10, M801, JH402
Test Mode No.: Oth-AB202
Brand Name: SEAJIC
FCC ID: 2ARZU-AB202
Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2019-10-21
Date of Test: 2019-10-21 to 2019-10-25
Date of Issue: 2019-10-25
Test Result : **PASS***

* In the configuration tested, the EUT complied with the standards specified above.

Tested By:

Tom Chen

(Tom chen)

Reviewed By:

Sheek Luo

(Sheek Luo)

Approved By:

Jack Ai

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20191001048E-02	Rev.01	Initial report	2019-10-25

2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i>	5
4.1.2 <i>Limits</i>	5
4.1.3 <i>EUT RF Exposure</i>	6

3 General Information

3.1 Client Information

Applicant:	Dongguan OSM Technologies Co., Ltd
Address of Applicant:	1 to 6 / F, Building A, Longdi Industrial Park, No. 6 Tiansha Road, Keyuan City, Tangxia Town, Dong guan City
Manufacturer:	Dongguan OSM Technologies Co., Ltd
Address of Manufacturer:	1 to 6 / F, Building A, Longdi Industrial Park, No. 6 Tiansha Road, Keyuan City, Tangxia Town, Dong guan City

3.2 General Description of EUT

Product Name:	Beautiful Picture Tripod Selfie Stick
Model No.:	Oth-AB202PRO, Oth-AB202YT, Oth-AB202DY, Oth-AB202, ATSS024, hocoK13, SS101, SNAP-X10, M801, JH402
Test Model No.:	Oth-AB202
Trade Mark:	SEAJIC
Hardware Version:	V2.0
Software Version:	V2.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.2
Modulation Type:	GFSK
Transfer Rate:	1Mbps
Number of Channel:	40
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	Maxscend Bluetooth MP Tool(MXD2660x) (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	0dBi
EUT Power Supply:	lithium battery:DC3.7V, Charge by DC5.0V

Note:

Model No.: Oth-AB202PRO, Oth-AB202YT, Oth-AB202DY, Oth-AB202, ATSS024, hocoK13, SS101, SNAP-X10, M801, JH402

Only the model Oth-AB202 was tested, There are identical on circuitry design, PCB layout, electrical components used, internal wiring and functions with the model/item No.Oth-AB202, only different on the shape and technology of plastic shell, There are same from the electronic part,function; and schematic diagram.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

For BLE

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-4.96	-5.5±1	-4.5	0.355
Middle(2440MHz)	-4.49	-5.0±1	-4.0	0.398
Highest(2480MHz)	-3.88	-4.5±1	-3.5	0.447

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-4.96	-5.5±1	-4.5	0.355	0.110	3.0
Middle (2440MHz)	-4.49	-5.0±1	-4.0	0.398	0.124	
Highest (2480MHz)	-3.88	-4.5±1	-3.5	0.447	0.141	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20191001048E-01.