


Voltage 120/277VAC, 50/60Hz per UL
Current 0.89A Max per UL

Voltage 120/277VAC, 50/60Hz per UL
Current 0.89A Max per UL

35-51VDC
0.6-1.5A Max Output
80W

35-51VDC
0.6-1.5A Max Output
80W



Connect power before servicing or installing.
Brancher l'alimentation avant le dépannage

Risk of electrical shock. Disconnect power before servicing or installing product.
 Risque de choc électrique. Couper l'alimentation avant le dépannage ou avant l'installation du produit.
 Risk of fire or electric shock. Do not interconnect output terminations.
 Risque d'incendie ou de choc électrique. Ne pas interconnecter les bornes de sortie.

120-277V

LED Class 2
10% dimmable at programmed output
High power factor (PF>0.9)
Min start temp 0C
Tc = 80C Max
For connections, use wire rated for at least 90C (194F)
Install and ground per national electric code
Use only within an enclosure
For dry or damp locations
FCC Part 15 Class
CAN ICES-005 (A) / NMB-005 (A)
FCC ID: 2A53F-80MCCZ2P15
IEC: 25008-80MCCZ2P15, VHIN: A-1002271-01 REV3

Current Lighting Solutions, LLC
www.gecurrent.com

For assistance call 1-866-855-8629

Made in China

Date:
Firmware:

GE current
a Daintree company

