



UltraMax® Connected  
LED Driver

GED80MCC/Z2P1500

95040689



95040689

INPUT

Voltage 120/277VAC, 50/60Hz per UL  
Current 0.89A Max per UL

LED OUTPUT

35-51VDC  
0.6-1.5A Max Output  
80W

Input:

Hot (black)  
Neutral (white)  
Ground (green)

Tc location: 13mm down side,  
110mm from end



Class 2 Output:

Antenna  
LED + (red)  
LED - (blue)

⚠ WARNING/AVERTISSEMENT

Risk of electrical shock. Disconnect power before servicing or installing product.  
Risque de choc électrique. Couper l'alimentation avant le dépannage ou avant l'installation du produit.  
Risk of fire or electric shock. Do not interconnect output terminations.  
Risque d'incendie ou de choc électrique. Ne pas interconnecter les bornes de sortie.

120-277V

LED Class 2  
10% dimmable at programmed output  
High power factor (PF>0.9)  
Min start temp 0C  
Tc = 80C Max  
For connections, use wire rated for at least 90C (194F)  
Install and ground per national electric code  
Use only within an enclosure  
For dry or damp locations  
FCC Part 15 Class A  
CAN ICES-005 (A) / NMB-005 (A)  
Contains FCC ID: 2AS3F-80MCCZ2P15  
IC: 25008-80MCCZ2P15, HVIN: A-1002271-01 REV3

Current Lighting Solutions, LLC  
www.gecurrent.com

For assistance call 1-866-855-8629

Made in China

Date:  
Firmware:



a Dainippon company



LISTED  
Class P  
E340135