


EMF TEST REPORT

Test Report No. : OT-215-RWD-110
Reception No. : 2103001143
Applicant : 3i Inc
Address : 3-321 523, Dongdaegu-ro, Dong-gu, Daegu, Korea
Manufacturer : 3i Inc
Address : 3-321 523, Dongdaegu-ro, Dong-gu, Daegu, Korea
Type of Equipment : Pivo Pod
FCC ID. : 2AS3Q-PIVOR1
Model Name : PIVO-R1
Serial number : N/A
Total page of Report : 7 pages (including this page)
Date of Incoming : April 22, 2021
Date of issue : May 31, 2021

SUMMARY

The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247*
 This test report only contains the result of a single test of the sample supplied for the examination.
 It is not a generally valid assessment of the features of the respective products of the mass-production.





Tested by / Youngyong Kim/ Assistant Manager ONETECH Corp.	Reviewed by / Ha-Ram Lee / Manager ONETECH Corp.	Approved by / Ki-Hong, Nam / General Manager ONETECH Corp.
--	--	--

CONTENTS**PAGE**

1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	5
3. EUT MODIFICATIONS.....	5
4. MAXIMUM PERMISSIBLE EXPOSURE.....	6
4.1 RF EXPOSURE CALCULATION	6
4.2 EUT DESCRIPTION.....	6
4.3 CALCULATED MPE SAFE DISTANCE FOR BLUETOOTH LE	7

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-215-RWD-110	May 31, 2021	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : 3i Inc
 Address : 3-321 523, Dongdaegu-ro, Dong-gu, Daegu, Korea
 Contact Person : Hyekang Park / Manager
 Telephone No. : +82-10-7540-8593
 FCC ID : 2AS3Q-PIVOR1
 Model Name : PIVO-R1
 Brand Name : N/A
 Serial Number : N/A
 Date : May 31, 2021

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	Pivo Pod
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The 3i Inc, Model PIVO-R1 (referred to as the EUT in this report) is a Pivo Pod. The product specification described herein was obtained from product data sheet or user’s manual.

Device Type	Pivo Pod
Operating Frequency	2 402 MHz ~ 2 480 MHz
RF Output Power	-10.64 dBm
Number of Channel	40 Channels
Modulation Type	GFSK
Antenna Type	PCB Antenna
Antenna Gain	1.98 dBi
Rated Supply Voltage	DC 5.0 V
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	16 MHz, 32 MHz

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are $f/1500 \text{ mW/cm}^2$ for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm^2 for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm^2 exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm^2 , Z = Impedance of free space, 377Ω

E = Electric field strength in V/m, G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using $P (\text{mW}) = P (\text{W}) / 1 000$, $d (\text{cm}) = 0.01 * d (\text{m})$

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm, P = Power in mW, G = Numeric antenna gain, and S = Power density in mW/cm^2

4.2 EUT Description

Kind of EUT	Pivo Pod
Device Category	<input type="checkbox"/> Portable (< 20 cm separation)
	<input checked="" type="checkbox"/> Mobile (> 20 cm separation)
	<input type="checkbox"/> Others
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE
	<input type="checkbox"/> SAR
	<input type="checkbox"/> N/A

4.3 Calculated MPE Safe Distance for Bluetooth LE

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)	Log	Linear			
2 402 ~ 2 480	Bluetooth LE	-10.64 ± 1.0	-9.64	0.11	1.98	1.58	0.12	0.000 03	1.00

According to above table, for 2 402 ~ 2480 MHz Band(LE), safe distance,

$$D = 0.282 * \sqrt{(0.11 * 1.58)/1.00} = 0.12 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 0.11 * 1.58 / (4 * \pi * 20^2) = 0.000 03$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna