

FCC Part 15C Measurement and Test Report

For

Qualitrol Corporation

1385 Fairport Rd, Fairport, NY 14450 USA

FCC ID: 2AS43-GTWRF100

FCC Rule(s): FCC Part 15.249

Product Description: QGateway MODEL 100

Tested Model: QGateway MODEL 100

Report No.: WTX19X04020300W

Sample Receipt Date: 2019-04-04

Tested Date: 2019-04-04 to 2019-04-10

Issued Date: 2019-04-11

Tested By: Mike Shi / Engineer

Reviewed By: Silin Chen / EMC Manager

Approved & Authorized By: Jandy So / PSQ Manager

Prepared By:

Mike Shi

Silin Chen

Jandy So

Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.



TABLE OF CONTENTS

1. GENERAL INFORMATION.....3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....3
1.2 TEST STANDARDS.....4
1.3 TEST METHODOLOGY4
1.4 TEST FACILITY4
1.5 EUT SETUP AND TEST MODE.....5
1.6 MEASUREMENT UNCERTAINTY5
1.7 TEST EQUIPMENT LIST AND DETAILS6

2. SUMMARY OF TEST RESULTS7

3. ANTENNA REQUIREMENTS.....8
3.1 STANDARD APPLICABLE.....8
3.2 TEST RESULT.....8

4. RADIATED EMISSIONS.....9
4.1 STANDARD APPLICABLE.....9
4.2 TEST PROCEDURE.....9
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....11
4.4 SUMMARY OF TEST RESULTS/PLOTS11

5. OUT OF BAND EMISSIONS.....16
5.1 STANDARD APPLICABLE.....16
5.2 TEST PROCEDURE.....16
5.3 SUMMARY OF TEST RESULTS/PLOTS16

6. EMISSION BANDWIDTH.....19
6.1 STANDARD APPLICABLE.....19
6.2 TEST PROCEDURE.....19
6.3 SUMMARY OF TEST RESULTS/PLOTS19



1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Qualitrol Corporation
Address of applicant: 1385 Fairport Rd, Fairport, NY 14450 USA

Manufacturer: Qualitrol Corporation
Address of manufacturer: 1385 Fairport Rd, Fairport, NY 14450 USA

General Description of EUT	
Product Name:	QGateway MODEL 100
Brand Name:	Qualitro
Model No.:	QGateway MODEL 100
Adding Model:	/
Rated Voltage:	DC1.2V*3
Battery capacity:	/
Power Adaptor:	/
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	915MHz
Max. Field Strength:	91.70dBuV/m
Modulation:	LoRa
Antenna Type:	Integral Antenna
Antenna Gain:	2.0dBi
Lowest Internal Frequency of EUT:	32MHz

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.249: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5875 MHz, and 24.0-24.25 GHz.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Transmitting	915MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~56 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	±0.42dB
Occupied Bandwidth	Conducted	± 1.5%
Conducted Spurious Emission	Conducted	± 2.17dB
Conducted Emissions	Conducted	9-150kHz ± 3.74dB
		0.15-30MHz ± 3.34dB
Transmitter Spurious Emissions	Radiated	30-200MHz ± 4.52dB
		0.2-1GHz ± 5.56dB
		1-6GHz ± 3.84dB
		6-18GHz ± 3.92dB

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2018-05-22	2019-05-21
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2018-05-22	2019-05-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2018-05-22	2019-05-21
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2018-05-22	2019-05-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2018-05-22	2019-05-21
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-08	2020-06-07
SEMT-1042	Horn Antenna	ETS	3117	00086197	2017-06-08	2020-06-07
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-08	2020-06-07
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-08	2020-06-07
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2018-05-22	2019-05-21
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2018-05-22	2019-05-21
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2018-05-22	2019-05-21
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2018-05-22	2019-05-21
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2018-05-22	2019-05-21
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2018-05-22	2019-05-21
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2018-03-19	2021-03-18
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2018-05-22	2019-05-21
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2018-05-22	2019-05-21
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2018-05-22	2019-05-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2019-03-18	2020-03-17
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2019-03-18	2020-03-17
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2019-03-18	2020-03-17
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2019-03-18	2020-03-17
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17



2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	N/A
§15.209(a)(f)	Radiated Spurious Emissions	Compliant
§15.249(a)	Field Strength of Emissions	Compliant
§15.249(d)	Out of Band Emission	Compliant
§15.215 (c)	Emission Bandwidth	Compliant

N/A: not applicable

3. Antenna Requirements

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an integral antenna, fulfill the requirement of this section.

4. Radiated Emissions

4.1 Standard Applicable

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field Strength of Fundamental (milli-volts/meter)	Field Strength of Harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.



The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

4.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.249(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=300KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of $-6\text{dB}\mu\text{V}$ means the emission is $6\text{dB}\mu\text{V}$ below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15C Limit}$$

4.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


➤ Spurious Emissions Below 1GHz

Test Channel	/	Polarity:	Horizontal
--------------	---	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	43.8119	35.55	-8.01	27.54	40.00	-12.46	208	100	peak
2	143.8295	48.11	-17.73	30.38	43.50	-13.12	90	100	peak
3	223.7334	38.88	-12.40	26.48	46.00	-19.52	60	100	peak
4	272.2776	45.75	-10.36	35.39	46.00	-10.61	106	100	peak
5	304.6099	42.73	-9.25	33.48	46.00	-12.52	344	100	peak
6	916.0687	89.90	1.80	91.70	114.00	-22.30	219	100	Fundamental

Test Channel	/	Polarity:	Vertical
--------------	---	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	44.4307	36.83	-8.02	28.81	40.00	-11.19	236	100	peak
2	68.6310	39.07	-13.87	25.20	40.00	-14.80	117	100	peak
3	79.8002	41.33	-17.01	24.32	40.00	-15.68	105	100	peak
4	143.8294	42.08	-17.73	24.35	43.50	-19.15	99	100	peak
5	272.2776	37.43	-10.36	27.07	46.00	-18.93	82	100	peak
6	916.0687	87.03	1.80	88.83	114.00	-25.17	260	100	Fundamental



➤ Spurious Emissions 1GHz to 18GHz

Test Channel	/	Polarity:	Horizontal
--------------	---	-----------	------------

No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	2442.751	52.86	-7.01	45.85	74.00	-28.15	132	150	peak
2	2452.091	42.58	-6.96	35.62	54.00	-18.38	153	150	AVG
3	7046.452	39.45	1.60	41.05	54.00	-12.95	153	150	AVG
4	7056.092	46.47	1.58	48.05	74.00	-25.95	12	150	peak
5	17896.247	39.64	14.13	53.77	74.00	-20.23	172	150	peak
6	17905.867	33.85	14.14	47.99	54.00	-6.01	153	150	AVG

Test Channel	/	Polarity:	Vertical
--------------	---	-----------	----------

No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	2339.107	50.13	-7.61	42.52	74.00	-31.48	156	150	peak
2	2349.107	41.58	-7.55	34.03	54.00	-19.97	153	150	AVG
3	7695.244	46.30	1.37	47.67	74.00	-26.33	145	150	peak
4	7699.544	38.49	1.38	39.87	54.00	-14.13	153	150	AVG
5	17996.220	32.45	14.35	46.80	54.00	-7.20	153	150	AVG
6	18000.000	41.02	14.36	55.38	74.00	-18.62	142	150	peak

➤ Spurious Emissions 18GHz to 30GHz

Test Channel	/	Polarity:	Horizontal
--------------	---	-----------	------------

No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	19245.743	46.99	0.00	46.99	74.00	-27.01	137	150	peak
2	19253.903	38.45	0.00	38.45	54.00	-15.55	153	150	AVG
3	24383.750	42.45	0.00	42.45	54.00	-11.55	153	150	AVG
4	24393.410	49.39	0.00	49.39	74.00	-24.61	169	150	peak
5	28149.742	46.78	0.00	46.78	54.00	-7.22	153	150	AVG
6	28158.662	51.53	0.00	51.53	74.00	-22.47	143	150	peak

Test Channel	/	Polarity:	Vertical
--------------	---	-----------	----------

No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	20275.112	50.80	0.00	50.80	74.00	-23.20	178	150	peak
2	20283.292	42.15	0.00	42.15	54.00	-11.85	153	150	AVG
3	23178.623	52.20	0.00	52.20	74.00	-21.80	196	150	peak
4	23182.803	44.58	0.00	44.58	54.00	-9.42	153	150	AVG
5	29255.306	48.45	0.00	48.45	54.00	-5.55	153	150	AVG
6	29258.406	53.48	0.00	53.48	74.00	-20.52	136	150	peak

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
The measurements greater than 20dB below the limit from 9kHz to 30MHz.

5. Out of Band Emissions

5.1 Standard Applicable

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Procedure

As the radiation test, set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2483.5MHz, than mark the higher-level emission for comparing with the FCC rules.


5.3 Summary of Test Results/Plots

Test mode	Frequency	Limit	Result
	MHz	dBuV / dBc	
Lowest	902.00	<46 dBuV	Pass
Highest	928.00	<46 dBuV	Pass

The edge emissions are below the FCC 15.209 Limits or complies with the 15.249 requirements.


Please refer to the test plots as below.

Test Channel	Low	Polarity:	Horizontal (worst case)
--------------	-----	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	902.0000	30.89	0.95	31.84	46.00	-14.16	Peak Detector
2	914.8480	86.71	1.37	88.08	/	/	Fundamental

Test Channel	High	Polarity:	Horizontal (worst case)
--------------	------	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	914.7680	86.54	1.37	87.91	/	/	Fundamental
2	928.0000	30.85	1.32	32.17	46.00	-13.83	Peak Detector

6. Emission Bandwidth

6.1 Standard Applicable

According to §15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

6.2 Test Procedure

According to the ANSI 63.10-2013, the emission bandwidth test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = 1MHz, centered on a transmitting channel

RBW \geq 1% 20dB Bandwidth, VBW \geq RBW

Sweep = auto

Detector function = peak


Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.

6.3 Summary of Test Results/Plots

Channel	Frequency MHz	20dB Bandwidth kHz
Channel	915	690.788

Please refer to the following test plots



***** END OF REPORT *****