



INCX

睿生光電股份有限公司

Document No.: APS-22-8-055

Approval Sheet Rev.: A

Spec. Rev. : A

APPROVAL SHEET

Product Model No. / 產品品名 : PC143.54.0470A

Customer No. / 客戶料號 : _____

Issue Date / 發行日期 : 2022 / 02 / 11

Approved Date / 承認日期 : _____

Approved by customer: (signing or stamping here)



TAOGLAS®

Datasheet

[InnoCare™ PCB Dual-band 2.4/5.8 GHz Antenna]

Part No:
[PC143.54.0470A]

Description


[2.4/5.8GHz PCB Antenna 470mm 1.13 black cable IPEX MHF4L]

Features:

Customized antenna
2.4/ 5.8GHz Dual Bands for WiFi Antenna.
IP65 Waterproof Enclosure
Dims: 70.0mm * 9.6mm * 1.0mm
470mm O.D 1.13mm coaxial cable with I-PEX MHF4L(M) connectors
Custom Cables and Connectors Available
RoHS & Reach Compliant

1. Specification	2
2. Test Setup	3
3. Antenna Characteristics	6
4. Radiation Patterns	9
5. Mechanical Drawing	11
6. Packaging.....	12
7. Electrical Specification Standard	13

Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly prohibited.



Specification

WIFI		
Frequency (MHz)	2.4GHz	5.8GHz
	2400-2500	5150-5825
Efficiency (%)		
PC143.54.0470A	19.8	6.5
Average Gain (dB)		
PC143.54.0470A	-7.04	-11.85
Peak Gain (dBi)		
PC143.54.0470A	-0.68	-0.89
Impedance	50 Ω	
Polarization	Linear	
Radiation Pattern	Omni	
Input power	5 W	

Mechanical	
Dimensions (mm)	70.0 x 9.6 x 1.0
Weight (g)	2.8
Material	FR-4
Connector	IPEX MHF4L(M)
Cable	Black_470mm_ ϕ 1.13 (mm) coaxial cable
Environmental	
Temperature Range	-40°C to 85°C
Humidity	Non-condensing 65°C 95% RH


Test Setup

S11 / VSWR / Return Loss

AUT





Vector Network Analyzer





PC143.54.0470A

S12 / Isolation




Radiation Performance




Antenna Characteristics


VSWR




Return Loss




Isolation




Efficiency



Average Gain




Peak Gain



Radiation Patterns

WIFI PC143.54.0470A 3D and 2D Radiation Patterns




Gain total, 2450MHz




XY Plane

XZ Plane




YZ Plane



Gain total, 5490MHz



XY Plane XZ Plane YZ Plane





Mechanical Drawing

ISO NO.: EDW-21-8-1325


STATE: Release

- NOTES:
1. No dregs or insufficient soldering. Solder thickness 0.3 ~1.7mm.
 2. The solder must be smooth and full to the edges of the pad.
 3. The connector position has special orientation to the PCB as per drawing.
 4. All material must be RoHS compliant.
 5. Open/short OC, VSWR required.
 6. Soldered area.
 7. Keep out area.

REV.	DESCRIPTION	ENG.	APPROVED	DATE
001	Initial Design	Ruby	Aaron	2021/11/03



IPEX MHF4L



Detail A
Scale: 4:1

	Name	Material	Finish	QTY
1	PC143 PCB	Composite 1.0t	Black	1
2	1.13 Coaxial Cable	FEP	Black	1
3	IPEX MHF4L	Copper Alloy	Au/Ni Plated	1


APPROVED BY: Aaron	TW Design Centre This drawing and its inherent design concepts are property of Taoglas. Not to be copied or given to third parties without the written consent of Taoglas.
CHECK BY: Aaron	
DRAWN BY: Ruby	
DATE: 2021/11/03	TITLE : 2.4/5GHz PCB Antenna 470mm 1.13 black cable IPEX MHF4L
UNLESS OTHERWISE SPECIFIED TOLERANCES ON:	PART NO. : PC143.54.0470A
THIRD ANGLE PROJECTION	UNIT: mm SCALE: 1:25:1 PAGES: 1/1 REV: D01

Packaging



- 100 PCS/ Vacuum PE bag
- 100 PCS / Bubble cloth
- tape
- 1 PCS / 3g Desiccant
- SPQ Label

(Based on the number of finished products)



- 2000 PCS / Carton
- Carton(mm): 320x250x230
- Carton Label

電性規範辦法

Electrical Specification Standard

PC143.54.0470A

Patch Antenna


Revised History

Date	Version	Author	Revised Record
2021/11/30	D01	Amos	Released <Reference>


1 電器規格【Electrical Characteristics Limited】

1.1 生產時依照量產治具作為測試依據，請依下列電性作為測試標準

【Measure the electrical characteristics with calibrated network analyzer. The electrical properties listed below should be followed.】




1.2 Measure Environment



1.3 Limit Values - Test setup:

- Free Space
- Sweep Points: 801 points
- Start Frequency: 2,000 MHz
- Stop Frequency: 6,000 MHz
- Antenna Parameter (VSWR)



- PC143.54.0470A (2400-2500MHz/ 5150-5825MHz)

Test Freq.(MHz)	2,100	2,450	5,150	5,500	5,825
VSWR(USL)	6.0	5.3	2.2	3.1	3.1
VSWR(LSL)	4.0	1	1	1	1

- Golden Sample Data

Test Freq.(MHz)	2,100	2,450	5,150	5,500	5,825
Sample 1	5.05	4.80	1.66	2.54	2.49
Sample 2	4.94	4.65	1.67	2.45	2.52
Sample 3	5.00	4.72	1.69	2.47	2.53
Sample 4	4.97	4.69	1.68	2.47	2.52
Sample 5	4.94	4.70	1.67	2.56	2.50



www.taoglas.com

