

# RF Exposure Evaluation

## FCC ID: 2AS5D-TM001G

### 1. Client Information

**Applicant** : SHENZHEN SUPER TIME INDUSTRIAL CO.,LTD.(CHINA)  
**Address** : Room 505-508 BAOYUNDA Building, QIANJIN Road 2, XIXIANG Street, BAOAN, SHENZHEN, China  
**Manufacturer** : SHENZHEN SUPER TIME INDUSTRIAL CO.,LTD.(CHINA)  
**Address** : Room 505-508 BAOYUNDA Building, QIANJIN Road 2, XIXIANG Street, BAOAN, SHENZHEN, China

### 2. General Description of EUT

<b>EUT Name</b>	:	Dazzle Series	
<b>Models No.</b>	:	TM001G	
<b>Model Different</b>	:	N/A	
<b>Product Description</b>	:	Operation Frequency:	Bluetooth V4.0: 2402MHz~2480MHz
	:	RF Output Power:	BLE:4.36dBm (Max)
	:	Antenna Gain:	-0.51dBi Integral Antenna
<b>Power Supply</b>	:	DC Voltage Supply from USB Changer Base. DC Supply by the Li-ion Battery.	
<b>Power Rating</b>	:	DC 5.0 V from the USB Changer Base. DC 3.7V by 100mAh Li-ion Battery.	
<b>Software Version</b>	:	N/A	
<b>Hardware Version</b>	:	V1.0.0	
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual	

**Note:** More test information about the EUT please refer the RF Test Report.

## SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

(1) Clause 4.3: General SAR test reduction and exclusion guidance

Sub clause 4.31: Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance  $\leq 5$  mm are determined by:

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}]}{\leq 3.0 \text{ for 1-g SAR}}$$

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}]}{\leq 7.5.0 \text{ for 10-g SAR}}$$

**2. Calculation:**

Test separation: 5mm						
BLE Mode (GFSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	4.360	4±1	5	3.162	0.980	3.0
2.442	4.205	4±1	5	3.162	0.988	3.0
2.480	3.792	4±1	5	3.162	0.996	3.0

**So standalone SAR measurements are not required.**

-----END OF REPORT-----