

MPE REPORT

FCC ID:2AS5O-19578

Date of issue: July 16, 2020

Report number:	MTi20060908-13E2
Sample description:	Bluetooth speaker
Model(s):	E-BS-19578
Applicant:	China Etech Groups Ltd
Address:	16/F, Block C, 2nd Phase of Central Avenue, Haihong Industrial Area, Xixiang Road, Baoan District, Shenzhen, China
Date of test:	June 17, 2020 to July 16, 2020

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>



RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*300/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm (20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

BT:

Operation Frequency: BT GFSK, $\pi/4$ -DQPSK: 2402-2480MHz,

Power density limited: 1mW/ cm²

Antenna Type: BT Antenna: PCB Antenna;

WIFI antenna gain: -0.68dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(-0.68/10)}=0.86$

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	3.515	4±1	5	3.162	-0.68	0.86	0.0005	1
2441		4.465	4±1	5	3.162	-0.68	0.86	0.0005	1
2480		4.122	4±1	5	3.162	-0.68	0.86	0.0005	1
2402	$\pi/4$ -DQPSK	4.324	5±1	6	3.981	-0.68	0.86	0.0007	1
2441		5.162	5±1	6	3.981	-0.68	0.86	0.0007	1
2480		5.785	5±1	6	3.981	-0.68	0.86	0.0007	1

Conclusion:

For the max result: 0.0007 ≤ 1.0 for 1g SAR, No SAR is required.

----END OF REPORT----