



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



RF EXPOSURE EVALUATION REPORT

Applicant: Fujian Senhaix Electronic Technology Co., Ltd

Address: No.7, Zi Hua Road, Jiangnan High-tech Industrial Zone, Licheng,
Quanzhou, Fujian, China

FCC ID: 2AS7F-SPTT-100

Product Name: MOBILE RADIO

Standard(s): 47 CFR §1.1307, 47 CFR §2.1091

**KDB 447498 D04 Interim General RF Exposure
Guidance v01**

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR22050036-00C

Date Of Issue: 2022-08-15

Reviewed By: Sun Zhong

Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

1.1 Applicable Standard

According to §1.1307(b)(3)(i)

(C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2R^2$.

1.2 EUT Information ▲:

Operation Modes	Operation Frequency (MHz)	Conducted output power including Tune-up Tolerance (dBm)	Maximum Antenna Gain (dBi)
WCDMA B2	1850-1910	23	3.66
WCDMA B4	1710-1755	23	3.87
WCDMA B5	824-849	24	0.88
LTE B2	1850-1910	23	3.66
LTE B4	1710-1755	23	3.87
LTE B5	824-849	23	0.88
LTE B12	699-716	24	-0.70
LTE B13	777-787	24	0.31
LTE B14	788-798	24	-0.29
LTE B66	1710-1780	23	3.87
LTE B71	663-698	24	-1.38

Note:

1. The Above Parameters were provided by the manufacturer.

1.3 Measurement Result

Operation Modes	Frequency (MHz)	$\lambda/2\pi$ (mm)	Distance (mm)	Exemption ERP		Maximum Conducted Power including Tune-up Tolerance (dBm)	Antenna Gain (dBi)	ERP (dBm)	MPE-Based Exemption
				(mW)	(dBm)				
WCDMA B2	1850-1910	25.82	200	768	28.85	23	3.66	24.51	Compliant
WCDMA B4	1710-1755	27.94	200	768	28.85	23	3.87	24.72	Compliant
WCDMA B5	824-849	57.97	200	422	26.25	24	0.88	22.73	Compliant
LTE B2	1850-1910	25.82	200	768	28.85	23	3.66	24.51	Compliant
LTE B4	1710-1755	27.94	200	768	28.85	23	3.87	24.72	Compliant
LTE B5	824-849	57.97	200	422	26.25	23	0.88	21.73	Compliant
LTE B12	699-716	68.34	200	358	25.54	24	-0.70	21.15	Compliant
LTE B13	777-787	61.48	200	398	26.00	24	0.31	22.16	Compliant
LTE B14	788-798	60.62	200	403	26.06	24	-0.29	21.56	Compliant
LTE B66	1710-1780	27.94	200	768	28.85	23	3.87	24.72	Compliant
LTE B71	663-698	72.05	200	339	25.31	24	-1.38	20.47	Compliant

Result: The device compliant the Exemption at 20cm distances.

===== END OF REPORT =====