



CTK Co., Ltd.
The First Leader of Global Regulatory Compliance

CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea

Tel: +82-31-339-9970 Fax: +82-31-624-9501

www.e-ctk.com

RF EXPOSURE EVALUATION

Applicant : SEONG JI INDUSTRIAL CO., LTD

Applicant Address : 54-33, Dongtanhana 1-gil, Hwaseong-si,
Gyeonggi-do, South Korea

Kind of Product : AUDIO TRANSCEIVER

**Equipment
model name** : ATM510, ATM511

FCC ID : 2AS8LATM510

Certification Number IC : 25119-ATM510

Antenna type : PCB Antenna(ANT1, ANT2)

Antenna Gain : ANT1 Gain : 1.2 dBi
ANT2 Gain : 1.7 dBi



Standard Requirement

The following RF exposure procedures are applicable :

- FCC Rules
Part 1.1310 Radiofrequency radiation exposure limits

Table 1 below sets forth limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

Table 1—Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposure | | | | |
| 0.3-3.0 | 614 | 1.63 | *100 | 6 |
| 3.0-30 | 1842/f | 4.89/f | *900/f ² | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1,500 | | | f/300 | 6 |
| 1,500-100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | *100 | 30 |
| 1.34-30 | 824/f | 2.19/f | *180/f ² | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1,500 | | | f/1500 | 30 |
| 1,500-100,000 | | | 1.0 | 30 |

f = frequency in MHz

* = Plane-wave equivalent power density

- ISED Rules
RSS-102 Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

Table 4 : RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

| Frequency Range (MHz) | Electric Field (V/m rms) | Magnetic Field (A/m rms) | Power Density (W/m ²) | Reference Period (minutes) |
|-----------------------|----------------------------------|---|--|---------------------------------|
| 0.003-10 | 83 | 90 | - | Instantaneous* |
| 0.1-10 | - | 0.73/ <i>f</i> | - | 6** |
| 1.1-10 | 87/ <i>f</i> ^{0.5} | - | - | 6** |
| 10-20 | 27.46 | 0.0728 | -2 | 6 |
| 20-48 | 58.07/ <i>f</i> ^{0.25} | 0.1540/ <i>f</i> ^{0.25} | 8.944/ <i>f</i> ^{0.5} | 6 |
| 48-300 | 22.06 | 0.05852 | 1.291 | 6 |
| 300-6000 | 3.142 <i>f</i> ^{0.3417} | 0.008335 <i>f</i> ^{0.3417} | 0.02619 <i>f</i>^{0.6834} | 6 |
| 6000-15000 | 61.4 | 0.163 | 10 | 6 |
| 15000-150000 | 61.4 | 0.163 | 10 | 616000/ <i>f</i> ^{1.2} |
| 150000-300000 | 0.158 <i>f</i> ^{0.5} | 4.21 x 10 ⁻⁴ <i>f</i> ^{0.5} | 6.67 x 10 ⁻⁵ <i>f</i> | 616000/ <i>f</i> ^{1.2} |

Note: *f* is frequency in MHz.

* Based on nerve stimulation (NS).

** Based on specific absorption rate (SAR).



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea

Tel: +82-31-339-9970 Fax: +82-31-624-9501

www.e-ctk.com

MPE Calculations

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user. The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

| | |
|----------------|--|
| $EIRP = P + G$ | Where, P = Power input to the antenna (mW) G = Power gain of the antenna (dBi) |
|----------------|--|

The numeric gain(G) of the antenna with a gain specified in dB is determined by:

$$G = \text{Log}^{-1} (\text{dB antenna gain} / 10)$$

Power density at the specific separation:

| | |
|----------------------|---|
| $S = PG / (4R^2\pi)$ | Where, S = Maximum power density (mW/cm ²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20cm = limit for MPE) |
|----------------------|---|

Estimated safe separation:

| | |
|--------------------------|--|
| $R = \sqrt{(PG / 4\pi)}$ | Where, P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20cm = limit for MPE) |
|--------------------------|--|



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea

Tel: +82-31-339-9970 Fax: +82-31-624-9501

www.e-ctk.com

RF Exposure Results

| Mode | P (dBm) | G (dBi) | EIRP (dBm) | Power Density | | R (cm) |
|-------------------------------|------------|------------|---------------|------------------------------|-----------------------------|--------|
| | | | | FCC (mW/cm ²) | ISED (W/m ²) | |
| Digital Modulation_2MHz_BW | 8.11 | 1.7 | 9.81 | 0.0019 | 0.019 | 20 |
| Digital Modulation_4MHz_BW | 7.32 | | 9.02 | 0.0016 | 0.016 | |