

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is an Nano Rock CrushR™ operating at 2.4G Band. The EUT can be powered by DC 6.0V (4 x 1.5V AA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

Modulation Type: GFSK.

The normal radiated output power (e.i.r.p) is: -8.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -8.0dBm (tolerance: +/- 3dB).

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 88.5dBμV/m at 3m in the frequency 2475MHz

The EIRP = $[(FS * D)^2 / 30]$ mW = -6.73dBm
which is within the production variation.

The Minimum peak radiated emission for the EUT is 85.7dBμV/m at 3m in the frequency 2410MHz

The EIRP = $[(FS * D)^2 / 30]$ mW = -9.53dBm
which is within the production variation.

The maximum conducted output power specified is -5.0dBm = 0.316mW

The source- based time-averaging conducted output power = 0.316mW

The SAR Exclusion Threshold Level:

= $3.0 * (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

= $3.0 * 5 / \text{sqrt}(2.475)$ mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

FCC ID: 2AS9M10310NIK-TX