

FCC RF Exposure

EUT Description: **Fitness Tracker**

Model No.: **S90**

FCC ID: **2ASAU-S90**

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,

Where:

Result = $P/D \cdot \sqrt{F}$

F = the RF channel transmit frequency in GHz

P = Maximum turn-up power in mW

D = Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

| | Output power (dBm) | Tune Up Power (dBm) | Max Tune Up power mW | Min test separation distance mm | Result | Limit | SAR Test Exclusion |
|--|--------------------|---------------------|----------------------|---------------------------------|--------|-------|--------------------|
| BLE | -0.43 | -1±1(0) | 1 | 5 | 0.310 | 3.0 | Pass |
| Note: PK Output power = conducted power. Conducted power see the test report HK2107192437-E antenna gain = 0.08dBi | | | | | | | |

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.310 which is ≤ 3 , SAR testing is not required.

Note: Exclusion Thresholds Results = $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Distance = 5mm