



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0488
Page (1) of (27)

EMC TEST REPORT

Test Report No. : KES-EM-22T0488
Date of Issue : Jun. 20, 2022
Product name : SlowJec plus
Model/Type No. : DSD-PLA-0100
Variant Mode : -
Applicant : OSSTEM IMPLANT CO., LTD. Chair Business
Applicant Address : 192, Haebong-ro, Danwon-gu, Ansan-si, Gyeonggi-do, 15428, Republic of Korea
Manufacturer : OSSTEM IMPLANT CO., LTD. Chair Business
Manufacturer Address : 192, Haebong-ro, Danwon-gu, Ansan-si, Gyeonggi-do, 15428, Republic of Korea
FCC ID : 2ASB7PLA-0100C
Date of Receipt : Jan. 20, 2022
Test date : Apr. 20, 2022 ~ Apr. 21, 2022
Test Results : **In Compliance** **Not in Compliance**

Tested by

Min Seong, Kim
EMC Test Engineer

Reviewed by

Dong Hun, Jang
EMC Technical Manager

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0488
Page (2) of (27)

REPORT REVISION HISTORY

Date	Test Report No.	Revision History
Jun. 20, 2022	KES-EM-22T0488	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0488
Page (3) of (27)

TABLE OF CONTENTS

1.0	General Product Description.....	4
1.1	Test Voltage & Frequency	5
1.2	Variant Model Differences	5
1.3	Device Modifications	5
1.4	Equipment Under Test.....	5
1.5	Support Equipments	5
1.6	External I/O Cabling	6
1.7	EUT Operating Mode(s)	6
1.8	Configuration.....	7
1.9	Remarks when standards applied	8
1.10	Calibration Details of Equipment Used for Measurement	8
1.11	Test Facility	8
1.12	Measurement Procedure.....	8
1.13	Laboratory Accreditations and Listings	9
2.0	Test Regulations.....	10
2.1	Conducted Emissions at Mains Power Ports	11
2.2	Radiated Electric Field Emissions(Below 1 GHz)	13
2.3	Radiated Electric Field Emissions(Above 1 GHz)	15
APPENDIX A – TEST DATA.....		17
Conducted Emissions at Mains Power Ports.....		17
Radiated Electric Field Emissions(Below 1 GHz)		19
Radiated Electric Field Emissions(Above 1 GHz).....		21
APPENDIX B - Test Setup Photos and Configuration.....		23
Radiated Electric Field Emissions(Below 1 GHz)		24
Radiated Electric Field Emissions(Above 1 GHz).....		26

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



1.0 General Product Description

Main Specifications of EUT are:

- Voltage : AC 100 V ~ 240 V
- Frequency : 50/60 Hz
- AC adapter : 5 V / 2 A
- Battery : 3.7 V, 500 mAh, Li-polymer
- Classification : Class II B type

- EUT Internal Operating Frequencies:

Frequency (MHz)	Description
8 MHz	MCU Clock(ATmega 168PB)
21 kHz	Timer Clock(Inner MCU)
400 Hz	PWM Timer Clock(Inner MCU)
8 kHz	Single-Chip Voice Record/Playback Devices (ISD2130)
400 kHz	9-Segment LED Display Drivers(MAX6958)

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

AC 120 V, 60 Hz

1.2 Variant Model Differences

Not applicable

1.3 Device Modifications

Not applicable

1.4 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
SlowJec plus (Main Body)	DSD-PLA-0100	-	OSSTEM IMPLANT CO., LTD. Chair Business	EUT
SlowJec plus (Cradle)	DSD-PLA-0100C	-	OSSTEM IMPLANT CO., LTD. Chair Business	
AC / DC MEDICAL ADAPTOR	GEM12I05	-	MEAN WELL	
Battery	-	-	-	

1.5 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
-	-	-	-	-



1.6 External I/O Cabling

■ AC 230 V, 50 Hz_Charging

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
SlowJec plus (Main Body) (EUT)	Power	Battery (EUT)	Power	-	-
	Wireless Charging	SlowJec plus (Cradle) (EUT)	Wireless Charging	-	-
SlowJec plus (Cradle) (EUT)	DC Jack	AC / DC MEDICAL ADAPTOR (EUT)	Line-Out (DC Jack)	0.5	U

* Unshielded = U, Shielded = S

■ Battery_Operating

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
SlowJec plus (Main Body) (EUT)	Power	Battery (EUT)	Power	-	-

* Unshielded = U, Shielded = S

1.7 EUT Operating Mode(s)

Test mode	Normal operating	Test Voltages
Charging	Check the normal operation by looking at the charging LED of SlowJec plus(Cradle)(EUT).	AC 120 V 60 Hz
Operating	After continuous operation of SlowJec plus(Main Body)(EUT), check whether it operates normally.	Battery


EUT Test operating S/W		
Name	Version	Manufacture Company
-	-	-

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr


1.8 Configuration

- AC Main
- DC Main

■ AC 120 V, 60 Hz_Charging



■ Battery_Operating



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr

1.9 Remarks when standards applied

N/A

1.10 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

1.11 Test Facility

The measurement facility is located at 473-21 Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Korea. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019

1.12 Measurement Procedure

- Conducted Emissions







The conducted emission levels were measured on each current-carrying line with the spectrum analyzer operating in the CISPR quasi-peak mode (or peak mode if applicable). The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. If the conducted emission exceed the average limit with the instrument set to the quasi-peak mode, the measurements are made in the average mode. The emission spectrum was scanned from 150 kHz to 30 MHz. The highest emission amplitudes relative to the appropriate limits were measured and have been recorded. Quasi-peak readings are distinguished with a "QP".

- Radiated Electric Field Emissions

The test was done at a SEMI ANECHOIC CHAMBER with quasi-peak detector. The final test data was measured using a Quasi-Peak detector below 1GHz at 10 m or 3 m distance and a Peak and Average detector above 1 GHz at 3 m distance. Test was proceeded worst case test mode and cable configuration. Measurements were made with the antenna positioned in both the horizontal and vertical planes of polarization. The antenna height was varied from 1 m to 4 m and the EUT was rotated 360° to find the maximum emitting point for each frequency.

Measurement procedures was In accordance with ANSI C63.4-2014 7.3.3, 7.3.4, 8.3.1.1, 8.3.1.2, 8.3.2.1, 8.3.2.2

1.13 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	RRA	EMI (3 m & 10 m Semi-Aechoic Chamber ,10 m Open Area and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KR0100
International	KOLAS	EMI (3 m & 10 m Semi-Aechoic Chamber , and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KT489
USA	FCC	3 m & 10 m Semi-Aechoic Chamber, 10 m Open Area and Conducted test site to perform FCC Part 15/18 measurements.	 KR0100
Canada	ISED	3 m & 10 m Semi-Aechoic Chamber and Conducted test site	 23298-1
JAPAN	VCCI	Mains Ports Conducted Interference Measurement, Telecommunication Ports Conducted Disturbance Measurement and Radiation 10 meter site, Facility for measuring radiated disturbance above 1 GHz	 R-20056, C-20036 T-20040, G-20057
Europe	TÜV SÜD	EMI (3 m & 10 m Semi-Aechoic Chamber , 10 m Open Area and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 CARAT 001633 0004

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



2.0 Test Regulations

The emissions tests were performed according to following regulations:

47 CFR Part 15, Subpart B

CISPR 22:2009 +A1:2010

Class A

Class B

ANSI C63.4-2014

Class A

Class B

2.1 Conducted Emissions at Mains Power Ports


Test Date
 Apr. 20, 2022

Test Location
 Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due	calibration interval
<input checked="" type="checkbox"/>	EMI Test S/W	EMC32	R & S	9.12.00	-	-
<input checked="" type="checkbox"/>	EMI TEST RECEIVER	ESR3	R & S	101783	12, 28, 2022	1 Year
<input checked="" type="checkbox"/>	LISN	ENV216	R & S	101787	12, 27, 2022	1 Year
<input type="checkbox"/>	LISN	ESH2-Z5	R & S	100450	12, 27, 2022	1 Year
<input checked="" type="checkbox"/>	PULSE LIMITER	ESH3-Z2	R & S	101915	12, 27, 2022	1 Year

Diagram of test setup



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0488
Page (12) of (27)

Test Conditions

Temperature: (22,5 ± 0,2) °C
Relative Humidity: (43,0 ± 0,3) % R.H.

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Results

The requirements are:

- PASS
- NOT PASS
- NOT APPLICABLE

Remarks

See Appendix A for test data.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

2.2 Radiated Electric Field Emissions(Below 1 GHz)

Test Date

Apr. 20, 2022

Test Location


OPEN AREA TEST SITE #2

SEMI ANECHOIC CHAMBER #4(10 m)

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due	calibration interval
<input checked="" type="checkbox"/>	EMI Test S/W	EP5/RE	TOYO Corporation	6.0.0	-	-
<input checked="" type="checkbox"/>	EMI TEST RECEIVER	ESU26	R & S	100551	03, 31, 2023	1 Year
<input checked="" type="checkbox"/>	AMPLIFIER	SCU 01	R & S	100603	11, 24, 2022	1 Year
<input checked="" type="checkbox"/>	TRILOG-BROADBAND ANTENNA	VULB9163	Schwarzbeck	715	12, 08, 2022	2 Year
<input checked="" type="checkbox"/>	ATTENUATOR	8491A	HP	32173	03, 08, 2023	1 Year

Diagram of test setup



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0488
Page (14) of (27)

Test Conditions

Temperature: (23,2 ± 0,2) °C
Relative Humidity: (42,9 ± 0,4) % R.H.

Frequency Range of Measurement

30 MHz to 1 GHz

Instrument Settings

IF Band Width: 120 kHz

Test Results

The requirements are:

- PASS
- NOT PASS
- NOT APPLICABLE

Remarks

See Appendix A for test data.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

2.3 Radiated Electric Field Emissions(Above 1 GHz)

Test Date

Apr. 21, 2022


Test Location

SEMI ANECHOIC CHAMBER #5

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due	calibration interval
☒	EMI Test S/W	EP5/RE	TOYO Corporation	6.0.120	-	-
☒	EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100552	03, 31, 2023	1 Year
☒	HORN ANTENNA	BBHA 9120D	SCHWARZBECK	9120D-1802	12, 16, 2022	1 Year
☒	PREAMPLIFIER	8449B	HP	3008A00538	06, 21, 2022	1 Year

Diagram of test setup



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0488
Page (16) of (27)

Test Conditions

Temperature: (23,8 ± 0,1) °C
Relative Humidity: (44,0 ± 0,2) % R.H.

Frequency Range of Measurement

1 GHz to 12,5 GHz

Instrument Settings

IF Band Width: 1 MHz

Test Results

The requirements are:

- PASS
- NOT PASS
- NOT APPLICABLE

Remarks

See Appendix A for test data.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

APPENDIX A – TEST DATA


Conducted Emissions at Mains Power Ports

■ AC 120 V, 60 Hz_Charging

HOT LINE

Common Information

Test Description:	Conducted Emission
Model No.:	DSD-PLA-0100
Phase:	L1
Mode:	AC 120 V, 60 Hz_Charging
Operator Name:	KES



Final Result


Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.474000	---	29.12	46.44	17.32	1000.0	9.000	L1	19.9
0.474000	38.54	---	56.44	17.90	1000.0	9.000	L1	19.9
1.494000	---	20.20	46.00	25.80	1000.0	9.000	L1	20.4
1.494000	29.18	---	56.00	26.82	1000.0	9.000	L1	20.4
1.874000	---	19.06	46.00	26.94	1000.0	9.000	L1	20.5
1.874000	28.17	---	56.00	27.83	1000.0	9.000	L1	20.5
9.026000	---	17.70	50.00	32.30	1000.0	9.000	L1	20.1
9.026000	22.81	---	60.00	37.19	1000.0	9.000	L1	20.1
29.518000	---	15.77	50.00	34.23	1000.0	9.000	L1	21.2
29.518000	24.83	---	60.00	35.17	1000.0	9.000	L1	21.2

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

NEUTRAL LINE

Common Information

Test Description:	Conducted Emission
Model No.:	DSD-PLA-0100
Phase:	N
Mode:	AC 120 V, 60 Hz_Charging
Operator Name:	KES



Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.238000	---	32.95	52.17	19.22	1000.0	9.000	N	19.6
0.238000	37.54	---	62.17	24.63	1000.0	9.000	N	19.6
0.478000	---	23.44	46.37	22.93	1000.0	9.000	N	19.8
0.478000	32.89	---	56.37	23.48	1000.0	9.000	N	19.8
1.862000	---	14.72	46.00	31.28	1000.0	9.000	N	20.4
1.862000	23.48	---	56.00	32.52	1000.0	9.000	N	20.4
2.922000	---	19.23	46.00	26.77	1000.0	9.000	N	20.4
2.922000	24.49	---	56.00	31.51	1000.0	9.000	N	20.4
24.290000	---	10.93	50.00	39.07	1000.0	9.000	N	20.9
24.290000	23.29	---	60.00	36.71	1000.0	9.000	N	20.9
29.262000	---	17.06	50.00	32.94	1000.0	9.000	N	21.2
29.262000	26.97	---	60.00	33.03	1000.0	9.000	N	21.2

◆ Calculation

QuasiPeak [dBuV] / CAverage [dBuV] = Reading Value [dBuV] + Corr. [dB]

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.


Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Radiated Electric Field Emissions(Below 1 GHz)

■ AC 120 V, 60 Hz_Charging




Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	52.310	V	58.6	-21.5	37.1	40.0	2.9	100.0	189.0	
2	54.856	V	57.8	-21.8	36.0	40.0	4.0	100.0	144.0	
3	57.403	V	57.8	-22.0	35.8	40.0	4.2	103.0	133.0	
4	58.130	V	59.1	-22.1	37.0	40.0	3.0	100.0	267.0	
5	59.464	V	59.8	-22.3	37.5	40.0	2.5	100.0	31.0	
6	59.828	H	44.4	-22.3	22.1	40.0	17.9	301.0	98.0	
7	62.010	V	60.2	-22.8	37.4	40.0	2.6	100.0	20.0	
8	62.859	V	60.5	-23.0	37.5	40.0	2.5	105.0	99.0	
9	86.988	H	47.6	-25.7	21.9	40.0	18.1	400.0	200.0	
10	175.985	H	47.2	-24.6	22.6	43.5	20.9	274.0	173.0	
11	260.496	H	48.8	-19.9	28.9	46.0	17.1	312.0	16.0	
12	360.406	H	51.2	-16.2	35.0	46.0	11.0	236.0	158.0	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Battery_Operating



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	61.525	V	40.3	-22.7	17.6	40.0	22.4	136.0	27.0	
2	65.041	V	42.7	-23.7	19.0	40.0	21.0	192.0	27.0	
3	96.324	H	41.4	-23.7	17.7	43.5	25.8	310.0	128.0	
4	124.939	V	42.9	-25.5	17.4	43.5	26.1	178.0	80.0	
5	242.794	H	37.5	-20.4	17.1	46.0	28.9	296.0	150.0	
6	296.750	H	37.5	-19.1	18.4	46.0	27.6	331.0	25.0	
7	328.033	V	36.2	-17.2	19.0	46.0	27.0	100.0	315.0	
8	335.065	H	40.6	-16.9	23.7	46.0	22.3	386.0	33.0	
9	465.045	H	42.9	-13.7	29.2	46.0	16.8	317.0	112.0	
10	503.845	V	36.5	-12.6	23.9	46.0	22.1	134.0	105.0	
11	562.651	H	36.9	-11.1	25.8	46.0	20.2	400.0	33.0	
12	611.758	V	36.6	-9.8	26.8	46.0	19.2	132.0	113.0	

◆ Calculation – SAC #4(10 m)

Result(QP) [dB(μV/m)] = (Reading(QP)[dB(μV)] + c.f[dB(1/m)])

Margin(QP)[dB] = Limit[dB(μV/m)] - Result(QP) [dB(μV/m)]

Reading(QP) : Reading value, Result(QP) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr




KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
 Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
 Tel: +82-31-425-6200 / Fax: +82-31-424-0450
 www.kes.co.kr

Report No.:
 KES-EM-22T0488
 Page (21) of (27)

Radiated Electric Field Emissions(Above 1 GHz)

■ AC 120 V, 60 Hz_Charging
 - (1 ~ 5) GHz




Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]	Remark
1	1293.763	V	37.3	26.6	-6.0	31.3	20.6	74.0	54.0	42.7	33.4	162.0	285.0	
2	1561.265	H	34.4	23.8	-4.7	29.7	19.1	74.0	54.0	44.3	34.9	389.0	79.3	
3	1788.801	V	37.3	26.7	-3.7	33.6	23.0	74.0	54.0	40.4	31.0	100.0	244.3	
4	2438.817	H	34.3	23.6	-1.4	32.9	22.2	74.0	54.0	41.1	31.8	276.0	270.9	
5	2789.357	V	32.8	22.9	0.4	33.2	23.3	74.0	54.0	40.8	30.7	194.0	49.8	
6	3241.232	H	32.9	21.9	1.6	34.5	23.5	74.0	54.0	39.5	30.5	332.0	254.5	
7	3438.737	V	33.7	23.0	1.7	35.4	24.7	74.0	54.0	38.6	29.3	108.0	75.0	
8	3776.256	H	31.7	21.1	2.4	34.1	23.5	74.0	54.0	39.9	30.5	400.0	47.7	
9	3919.347	V	34.8	23.9	2.9	37.7	26.8	74.0	54.0	36.3	27.2	100.0	145.9	
10	4302.617	H	32.5	22.0	4.4	36.9	26.4	74.0	54.0	37.1	27.6	331.0	219.3	
11	4749.369	V	35.5	24.8	6.4	41.9	31.2	74.0	54.0	32.1	22.8	117.0	272.2	
12	4820.000	H	32.6	21.9	6.6	39.2	28.5	74.0	54.0	34.8	25.5	285.0	146.9	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr



■ Battery_Operating
- (1 ~ 5) GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]	Remark
1	1319.332	H	42.4	31.8	-5.8	36.6	26.0	74.0	54.0	37.4	28.0	324.0	269.1	
2	1363.698	V	49.6	38.1	-5.5	44.1	32.6	74.0	54.0	29.9	21.4	100.0	16.1	
3	1481.312	H	42.9	31.5	-4.9	38.0	26.6	74.0	54.0	36.0	27.4	287.0	277.8	
4	1587.418	H	42.7	30.9	-4.6	38.1	26.3	74.0	54.0	35.9	27.7	330.0	277.8	
5	2431.894	V	42.9	30.7	-1.4	41.5	29.3	74.0	54.0	32.5	24.7	194.0	357.5	
6	2547.542	H	40.1	30.0	-0.9	39.2	29.1	74.0	54.0	34.8	24.9	280.0	282.2	
7	2608.139	V	41.7	30.8	-0.6	41.1	30.2	74.0	54.0	32.9	23.8	132.0	357.1	
8	2746.881	H	40.3	28.8	0.2	40.5	29.0	74.0	54.0	33.5	25.0	309.0	255.6	
9	3563.769	V	42.5	31.9	1.8	44.3	33.7	74.0	54.0	29.7	20.3	181.0	357.1	
10	4335.624	V	42.7	31.0	4.6	47.3	35.6	74.0	54.0	26.7	18.4	210.0	357.1	
11	4578.123	H	33.9	21.8	5.5	39.4	27.3	74.0	54.0	34.6	26.7	299.0	46.1	
12	4671.882	V	38.2	26.9	6.0	44.2	32.9	74.0	54.0	29.8	21.1	100.0	358.8	

* No spurious emission were detected above 6 GHz.

◆ Calculation

$$\text{Result(PK/CAV)} [dB(\mu V/m)] = (\text{Reading(PK/CAV)} [dB(\mu V)] + c.f [dB(1/m)])$$

$$\text{Margin(PK/CAV)} [dB] = \text{Limit} [dB(\mu V/m)] - \text{Result(PK/CAV)} [dB(\mu V/m)]$$

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Marjin value

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr