

## RF Exposure Evaluation Report

**Report Reference No.**.....: **MTWG22040245-H**

**FCC ID**..... : **2ASBG-YH-9700L**

Compiled by

( position+printed name+signature)..: File administrators **Alisa Luo**



*Alisa Luo*

Supervised by

( position+printed name+signature)..: Test Engineer **Sunny Deng\***

*Sunny Deng*

Approved by

( position+printed name+signature)..: Manager **Yvette Zhou**

*Yvette Zhou*

Date of issue.....: **May 19,2022**

**Representative Laboratory Name .:** **Shenzhen Most Technology Service Co., Ltd.**

Address .....: No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park,  
Nanshan, Shenzhen, Guangdong, China.

**Applicant's name**.....: **FUJIAN YIHE ELECTRONICS CO., LTD**

Address .....: JI'AN ROAD, QINXIYANG INDUSTRIAL PARK, FUAN, FUJIAN,  
355000 CHINA .

**Test specification/ Standard** .....: **47 CFR Part 1.1307**

**47 CFR Part 2.1093**

TRF Originator.....: Shenzhen Most Technology Service Co., Ltd.

**Shenzhen Most Technology Service Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description** .....: Massage Chair

Trade Mark .....: RockerTech, INFINITY

Manufacturer .....: **FUJIAN YIHE ELECTRONICS CO., LTD**

Model/Type reference.....: YH-9700L

Listed Models .....: Sensation 4D, Riage 4D, YH-9700, YH-9700INF, YH-9701  
(SKU No.: 197001111,197004511,197002111,197004611)

Modulation Type .....: GFSK, Π/4DQPSK,8DPSK

Operation Frequency.....: From 2402MHz to 2480MHz

Hardware Version..... V1.1

Software Version ..... V1.0

Rating .....: 85-132V~, 60Hz

**TEST REPORT**

Equipment under Test : Massage Chair

Model /Type : YH-9700L

Listed Models : Sensation 4D, Riage 4D, YH-9700, YH-9700INF, YH-9701  
(SKU No.: 1970011111,197004511,197002111,197004611)

Remark : Only the model name is different.

Applicant : **FUJIAN YIHE ELECTRONICS CO., LTD**

Address : JI'AN ROAD, QINXIYANG INDUSTRIAL PARK, FUAN, FUJIAN,  
355000 CHINA

Manufacturer : **FUJIAN YIHE ELECTRONICS CO., LTD**

Address : JI'AN ROAD, QINXIYANG INDUSTRIAL PARK, FUAN, FUJIAN,  
355000 CHINA

<b>Test Result:</b>	<b>PASS</b>
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## 1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2022-05-19	Initial Issue	Alisa Luo

## 2. SAR Evaluation

### 2.1 RF Exposure Compliance Requirement

#### 2.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

#### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 2.1.2 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$  Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 2.1.3 EUT RF Exposure

## Measurement Data

## BT classic

GFSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	-0.504	$-0.504 \pm 1$	0.496
Middle(2440MHz)	0.191	$0.191 \pm 1$	1.191
Highest(2480MHz)	-0.840	$-0.840 \pm 1$	0.16

$\pi/4$ DQPSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	-0.664	$-0.664 \pm 1$	0.336
Middle(2440MHz)	-0.141	$-0.141 \pm 1$	0.859
Highest(2480MHz)	-0.799	$-0.799 \pm 1$	0.201

8DPSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	-0.772	$-0.772 \pm 1$	0.228
Middle(2440MHz)	-0.059	$-0.059 \pm 1$	0.941
Highest(2480MHz)	-0.892	$-0.892 \pm 1$	0.108

## EDR

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Maximum Peak Conducted Output Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
Highest(2440 MHz)	1.191	1.32	0.2	0.0003	1.0	Pass

Note: 1) Refer to report **MTWG22020077-R1** for EUT test Max Conducted average Output Power value.

Note: 2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (1.32 * 0.95) / (4 * 3.1416 * 20^2) = 0.0003$

V

BLE

GFSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	-0.273	0.296 ± 1	0.727
Middle(2441MHz)	1.337	3.289 ± 1	2.337
Highest(2480MHz)	-1.005	4.054 ± 1	-0.005

BLE

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Maximum Peak Conducted Output Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
Highest(2441 MHz)	2.337	1.71	0.2	0.0003	1.0	Pass

Note: 1) Refer to report MTWG22020077-R1 for EUT test Max Conducted average Output Power value.

Note: 2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (1.71 * 0.95) / (4 * 3.1416 * 20^2) = 0.0003$

.....**THE END OF REPORT**.....