

APPLICATION CERTIFICATION FCC Part 15C
On Behalf of
FUJIAN YIHE ELECTRONICS CO., LTD.

Massage Chair

Model No.: Titan Pro-Commander, YH-9210F, YH-9200, YH-9220, YH-9230

FCC ID: 2ASBG-YH9210F

Prepared for : FUJIAN YIHE ELECTRONICS CO., LTD.
Address : JIAN ROAD, QINXIYANG INDUSTRIAL PARK, FUAN,
FUJIAN 355000 CHINA

Prepared by : Shenzhen Accurate Technology Co., Ltd.
Address : 1/F., Building A, Changyuan New Material Port, Science & Industry
Park, Nanshan District, Shenzhen, Guangdong, P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report No. : ATE20190041
Date of Test : January 15-January 17, 2019
Date of Report : January 21, 2019

TABLE OF CONTENTS

Description	Page
Test Report Certification	
TABLE OF CONTENTS	2
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT)	5
1.2. Accessory and Auxiliary Equipment	5
1.3. Description of Test Facility	6
1.4. Measurement Uncertainty	6
2. MEASURING DEVICE AND TEST EQUIPMENT	7
3. OPERATION OF EUT DURING TESTING	8
3.1. Operating Mode	8
3.2. Configuration and peripherals	8
4. TEST PROCEDURES AND RESULTS	9
5. 20DB BANDWIDTH TEST	10
5.1. Block Diagram of Test Setup	10
5.2. The Requirement For Section 15.247(a)(1)	10
5.3. EUT Configuration on Test	10
5.4. Operating Condition of EUT	10
5.5. Test Procedure	10
5.6. Test Result	11
6. CARRIER FREQUENCY SEPARATION TEST	16
6.1. Block Diagram of Test Setup	16
6.2. The Requirement For Section 15.247(a)(1)	16
6.3. EUT Configuration on Test	16
6.4. Operating Condition of EUT	16
6.5. Test Procedure	17
6.6. Test Result	17
7. NUMBER OF HOPPING FREQUENCY TEST	23
7.1. Block Diagram of Test Setup	23
7.2. The Requirement For Section 15.247(a)(1)(iii)	23
7.3. EUT Configuration on Test	23
7.4. Operating Condition of EUT	23
7.5. Test Procedure	23
7.6. Test Result	24
8. DWELL TIME TEST	26
8.1. Block Diagram of Test Setup	26
8.2. The Requirement For Section 15.247(a)(1)(iii)	26
8.3. EUT Configuration on Test	26
8.4. Operating Condition of EUT	26
8.5. Test Procedure	26
8.6. Test Result	27
9. MAXIMUM PEAK OUTPUT POWER TEST	33
9.1. Block Diagram of Test Setup	33

9.2.	The Requirement For Section 15.247(b)(1)	33
9.3.	EUT Configuration on Test	33
9.4.	Operating Condition of EUT	33
9.5.	Test Procedure	33
9.6.	Test Result	34
10.	RADIATED EMISSION TEST	40
10.1.	Block Diagram of Test Setup	40
10.2.	The Limit For Section 15.247(d)	41
10.3.	Restricted bands of operation	42
10.4.	Configuration of EUT on Test.....	42
10.5.	Operating Condition of EUT	43
10.6.	Test Procedure	43
10.7.	Data Sample.....	44
10.8.	Test Results	44
11.	BAND EDGE COMPLIANCE TEST	57
11.1.	Block Diagram of Test Setup	57
11.2.	The Requirement For Section 15.247(d)	57
11.3.	EUT Configuration on Test	57
11.4.	Operating Condition of EUT	57
11.5.	Test Procedure	58
11.6.	Test Result	58
12.	AC POWER LINE CONDUCTED EMISSION TEST	69
12.1.	Block Diagram of Test Setup	69
12.2.	Power Line Conducted Emission Test Limits	70
12.3.	Configuration of EUT on Test.....	70
12.4.	Operating Condition of EUT	70
12.5.	Test Procedure	70
12.6.	Data Sample.....	71
12.7.	Test Results	71
13.	ANTENNA REQUIREMENT	74
13.1.	The Requirement	74
13.2.	Antenna Construction.....	74

Test Report Certification

Applicant : FUJIAN YIHE ELECTRONICS CO., LTD.
Manufacturer : FUJIAN YIHE ELECTRONICS CO., LTD.
Product : Massage Chair
Model No. : Titan Pro-Commander, YH-9210F, YH-9200, YH-9220, YH-9230

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247 ANSI C63.10: 2013

The device described above is tested by Shenzhen Accurate Technology Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and Shenzhen Accurate Technology Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Shenzhen Accurate Technology Co., Ltd.

Date of Test : January 15-January 17, 2019
Date of Report : January 21, 2019

Prepared by : _____
(Star Yang, Engineer)

Approved & Authorized Signer : _____
(Sean Liu, Manager)



1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Model Number	:	Titan Pro-Commander, YH-9210F, YH-9200, YH-9220, YH-9230 (Note: We hereby state that these models are identical in interior structure, electrical circuits and components, Just appearance is different in color and shape. Therefore only model Titan Pro-Commander is for tests.)
Bluetooth version	:	V4.0 classic mode for single mode
Frequency Range	:	2402MHz-2480MHz
Number of Channels	:	79
Antenna Gain(Max)	:	2dBi
Antenna type	:	PCB Antenna
Modulation mode	:	GFSK, $\pi/4$ DQPSK, 8DPSK
Trade Mark	:	N/A
Power supply	:	AC 120V~60Hz
Applicant Address	:	FUJIAN YIHE ELECTRONICS CO., LTD. JIAN ROAD, QINXIYANG INDUSTRIAL PARK, FUAN, FUJIAN 355000 CHINA
Manufacturer Address	:	FUJIAN YIHE ELECTRONICS CO., LTD. JIAN ROAD, QINXIYANG INDUSTRIAL PARK, FUAN, FUJIAN 355000 CHINA

1.2. Accessory and Auxiliary Equipment

N/A

1.3. Description of Test Facility

EMC Lab	:	Recognition of accreditation by Federal Communications Commission (FCC) The Designation Number is CN1189 The Registration Number is 708358
		Listed by Innovation, Science and Economic Development Canada (ISED) The Registration Number is 5077A-2
		Accredited by China National Accreditation Service for Conformity Assessment (CNAS) The Registration Number is CNAS L3193
		Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 4297.01
Name of Firm	:	Shenzhen Accurate Technology Co., Ltd.
Site Location	:	1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

1.4. Measurement Uncertainty

Conducted Emission Expanded Uncertainty	=	2.23dB, k=2
Radiated emission expanded uncertainty (9kHz-30MHz)	=	3.08dB, k=2
Radiated emission expanded uncertainty (30MHz-1000MHz)	=	4.42dB, k=2
Radiated emission expanded uncertainty (Above 1GHz)	=	4.06dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment


Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Cal. Interval
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 05, 2019	One Year
EMI Test Receiver	Rohde&Schwarz	ESR	101817	Jan. 05, 2019	One Year
Spectrum Analyzer	Rohde&Schwarz	FSV-40	101495	Jan. 05, 2019	One Year
Pre-Amplifier (Radiated Emission)	Compliance Direction	RSU-M2	38322	Jan. 05, 2019	One Year
Pre-Amplifier (Radiated Emission)	Agilent	8447D	294A10619	Jan. 05, 2019	One Year
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 05, 2019	One Year
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 05, 2019	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 05, 2019	One Year
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 05, 2019	One Year
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 05, 2019	One Year
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 05, 2019	One Year
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 05, 2019	One Year
RF Coaxial Cable (Conducted Emission)	SUHNER	N-2m	No.2	Jan. 05, 2019	One Year
RF Coaxial Cable (Radiated Emission)	SUHNER	N-5m	NO.3	Jan. 05, 2019	One Year
RF Coaxial Cable (Radiated Emission)	SUHNER	N-5m	NO.4	Jan. 05, 2019	One Year
RF Coaxial Cable (Radiated Emission)	SUHNER	N-1m	NO.5	Jan. 05, 2019	One Year
RF Coaxial Cable (Radiated Emission)	SUHNER	N-1m	NO.6	Jan. 05, 2019	One Year
Conducted Emission Measurement Software: ES-K1 V1.71					
Radiated Emission Measurement Software: EZ_EMV V1.1.4.2					

3. OPERATION OF EUT DURING TESTING

3.1. Operating Mode

The mode is used: Transmitting mode
Low Channel: 2402MHz
Middle Channel: 2441MHz
High Channel: 2480MHz
Hopping

3.2. Configuration and peripherals



Note: The power was switched from 85% to 115%, and the worse case data was recorded.

4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.247(a)(1)	20dB Bandwidth Test	Compliant
Section 15.247(a)(1)	Carrier Frequency Separation Test	Compliant
Section 15.247(a)(1)(iii)	Number Of Hopping Frequency Test	Compliant
Section 15.247(a)(1)(iii)	Dwell Time Test	Compliant
Section 15.247(b)(1)	Maximum Peak Output Power Test	Compliant
Section 15.247(d) Section 15.209	Radiated Emission Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.207	AC Power Line Conducted Emissions Limits Test	Compliant
Section 15.203	Antenna Requirement	Compliant

5. 20DB BANDWIDTH TEST

5.1. Block Diagram of Test Setup



5.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

5.3. EUT Configuration on Test

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.4. Operating Condition of EUT

5.4.1. Setup the EUT and simulator as shown as Section 5.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

5.5. Test Procedure

5.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

5.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz.


5.5.3. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

5.6. Test Result

Channel	Frequency (MHz)	GFSK 20dB Bandwidth (MHz)	Π/4-DQPSK 20dB Bandwidth (MHz)	8DPSK 20dB Bandwidth (MHz)	Result
Low	2402	1.212	1.374	1.410	Pass
Middle	2441	1.194	1.356	1.386	Pass
High	2480	1.182	1.350	1.386	Pass


The spectrum analyzer plots are attached as below.

GFSK Mode




Date: 17.JAN.2019 16:34:02

Middle channel



Date: 17.JAN.2019 16:35:54


High channel



Date: 17.JAN.2019 16:36:40


Π/4-DQPSK Mode

Low channel




Date: 17.JAN.2019 16:40:09

Middle channel



Date: 17.JAN.2019 16:39:03


High channel



Date: 17.JAN.2019 16:37:55


8DPSK Mode

Low channel




Date: 17.JAN.2019 16:41:15

Middle channel



Date: 17.JAN.2019 16:42:33

High channel



Date: 17.JAN.2019 16:43:34

6. CARRIER FREQUENCY SEPARATION TEST

6.1. Block Diagram of Test Setup



6.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

6.3. EUT Configuration on Test

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

6.5. Test Procedure

6.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

6.5.2. Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz. Adjust Span to 3MHz.

6.5.3. Set the adjacent channel of the EUT Maxhold another trace.

6.5.4. Measurement the channel separation

6.6. Test Result

GFSK Mode

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.002	25KHz or 2/3*20dB bandwidth	Pass
	2403			
Middle	2440	1.002	25KHz or 2/3*20dB bandwidth	Pass
	2441			
High	2479	0.996	25KHz or 2/3*20dB bandwidth	Pass
	2480			

Π/4-DQPSK Mode


Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.008	25KHz or 2/3*20dB bandwidth	Pass
	2403			
Middle	2440	1.002	25KHz or 2/3*20dB bandwidth	Pass
	2441			
High	2479	0.996	25KHz or 2/3*20dB bandwidth	Pass
	2480			

8DPSK Mode


Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	0.978	25KHz or 2/3*20dB bandwidth	Pass
	2403			
Middle	2440	1.002	25KHz or 2/3*20dB bandwidth	Pass
	2441			
High	2479	0.978	25KHz or 2/3*20dB bandwidth	Pass
	2480			

The spectrum analyzer plots are attached as below.

GFSK Mode




Date: 18.JAN.2019 14:15:38



Date: 18.JAN.2019 14:17:11


High channel



Date: 18.JAN.2019 14:18:43


$\Pi/4$ -DQPSK Mode

Low channel




Date: 18.JAN.2019 14:22:56

Middle channel



Date: 18.JAN.2019 14:21:38


High channel



Date: 18.JAN.2019 14:20:10


8DPSK Mode

Low channel




Date: 18.JAN.2019 14:24:20

Middle channel



Date: 18.JAN.2019 14:29:57

High channel



Date: 18.JAN.2019 14:31:40

7. NUMBER OF HOPPING FREQUENCY TEST

7.1. Block Diagram of Test Setup



7.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

7.3. EUT Configuration on Test

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX (Hopping on) modes measure it.

7.5. Test Procedure

7.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.


7.5.2. Set the spectrum analyzer as RBW=100 kHz, VBW=300 kHz.

7.5.3. Max hold, view and count how many channel in the band.

7.6. Test Result


Total number of hopping channel	Measurement result(CH)	Limit(CH)	Result
		79	≥ 15

The spectrum analyzer plots are attached as below.




Date: 17.JAN.2019 17:02:53

Number of hopping channels ($\Pi/4$ -DQPSK Mode)



Date: 17.JAN.2019 17:18:15


Number of hopping channels (8DPSK Mode)



Date: 17.JAN.2019 17:21:00

8. DWELL TIME TEST

8.1. Block Diagram of Test Setup



8.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.3. EUT Configuration on Test

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 8.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

8.5. Test Procedure

8.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

8.5.2. Set center frequency of spectrum analyzer = operating frequency.

8.5.3. Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span=0Hz, Adjust Sweep=5ms, 10ms, 15ms. Get the pulse time.

8.5.4. Repeat above procedures until all frequency measured were complete.

8.6. Test Result

Pass.

GFSK Mode (Worst case)

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2441	0.420	134.4	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2*79)) \times 31.6$				
DH3	2441	1.660	265.6	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4*79)) \times 31.6$				
DH5	2441	2.820	300.8	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6*79)) \times 31.6$				

$\Pi/4$ -DQPSK Mode (Worst case)

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2441	0.440	140.8	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2*79)) \times 31.6$				
DH3	2441	1.620	259.2	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4*79)) \times 31.6$				
DH5	2441	2.800	298.7	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6*79)) \times 31.6$				

8DPSK Mode (Worst case)


Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2441	0.410	131.2	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2*79)) \times 31.6$				
DH3	2441	1.810	289.6	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4*79)) \times 31.6$				
DH5	2441	2.830	301.9	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6*79)) \times 31.6$				

Note: We tested GFSK mode and $\Pi/4$ -DQPSK & 8DPSK mode the low, middle and high channel and recorded the worst case data for all test mode.

The spectrum analyzer plots are attached as below.


GFSK Mode

DH1 Middle channel




Date: 18.JAN.2019 14:57:07

DH3 Middle channel



Date: 18.JAN.2019 14:58:18


DH5 Middle channel



Date: 18.JAN.2019 14:59:33


$\Pi/4$ -DQPSK Mode

2-DH1 Middle channel




Date: 18.JAN.2019 15:03:03

2-DH3 Middle channel



Date: 18.JAN.2019 15:04:14


2-DH5 Middle channel



Date: 18.JAN.2019 15:05:56


8DPSK Mode

3-DH1 Middle channel




Date: 18.JAN.2019 15:09:21

3-DH3 Middle channel



Date: 18.JAN.2019 15:08:24


3-DH5 Middle channel



Date: 18.JAN.2019 15:07:18

9. MAXIMUM PEAK OUTPUT POWER TEST

9.1. Block Diagram of Test Setup



9.2. The Requirement For Section 15.247(b)(1)

Section 15.247(b)(1): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

9.3. EUT Configuration on Test

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.4. Operating Condition of EUT

9.4.1. Setup the EUT and simulator as shown as Section 9.1.

9.4.2. Turn on the power of all equipment.

9.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

9.5. Test Procedure

9.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

9.5.2. Set RBW of spectrum analyzer to 3MHz and VBW to 10MHz.

9.5.3. Measurement the maximum peak output power.

9.6. Test Result

GFSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W	Result
Low	2402	-0.66/0.0009	21 / 0.125	Pass
Middle	2441	-1.08/0.0008	21 / 0.125	Pass
High	2480	-1.51/0.0007	21 / 0.125	Pass

Π/4-DQPSK Mode


Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W	Result
Low	2402	-0.67/0.0009	21 / 0.125	Pass
Middle	2441	-1.17/0.0008	21 / 0.125	Pass
High	2480	-1.63/0.0007	21 / 0.125	Pass

8DPSK Mode


Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W	Result
Low	2402	-0.66/0.0009	21 / 0.125	Pass
Middle	2441	-1.08/0.0008	21 / 0.125	Pass
High	2480	-1.54/0.0007	21 / 0.125	Pass

The spectrum analyzer plots are attached as below.

GFSK Mode




Date: 17.JAN.2019 17:24:05



Date: 17.JAN.2019 17:24:47


High channel



Date: 17.JAN.2019 17:25:23


$\Pi/4$ -DQPSK Mode

Low channel




Date: 17.JAN.2019 16:03:50

Middle channel




Date: 17.JAN.2019 17:27:28

High channel




Date: 17.JAN.2019 17:26:12

8DPSK Mode




Date: 17.JAN.2019 17:31:13



Date: 17.JAN.2019 17:33:24

High channel




Date: 17.JAN.2019 17:35:28

10.RADIATED EMISSION TEST


10.1.Block Diagram of Test Setup

10.1.1.Block diagram of connection between the EUT and peripherals




10.1.2.Semi-Anechoic Chamber Test Setup Diagram


(A) Radiated Emission Test Set-Up, Frequency below 30MHz



(B) Radiated Emission Test Set-Up, Frequency 30MHz-1GHz



(C) Radiated Emission Test Set-Up. Frequency above 1GHz



10.2. The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

10.3.Restricted bands of operation

10.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

10.4.Configuration of EUT on Test

The equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.5. Operating Condition of EUT

10.5.1. Setup the EUT and simulator as shown as Section 10.1.

10.5.2. Turn on the power of all equipment.

10.5.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

10.6. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.1 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. This EUT was tested in 3 orthogonal positions and the worst case position data was reported.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

10.7.Data Sample

Frequency (MHz)	Reading (dB μ v)	Factor (dB/m)	Result (dB μ v/m)	Limit (dB μ v/m)	Margin (dB)	Remark
X.XX	48.69	-13.35	35.34	46	-10.66	QP

Frequency(MHz) = Emission frequency in MHz

Reading(dB μ v) = Uncorrected Analyzer/Receiver reading

Factor (dB/m) = Antenna factor + Cable Loss – Amplifier gain

Result(dB μ v/m) = Reading(dB μ v) + Factor(dB/m)

Limit (dB μ v/m) = Limit stated in standard

Margin (dB) = Result(dB μ v/m) - Limit (dB μ v/m)

QP = Quasi-peak Reading

Calculation Formula:

Margin(dB) = Result (dB μ V/m)–Limit(dB μ V/m)

Result(dB μ V/m)= Reading(dB μ V)+ Factor(dB/m)

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit.

10.8.Test Results

Pass.

Note: 1.We tested GFSK mode, $\Pi/4$ -DQPSK & 8DPSK Mode and recorded the worst case data (GFSK mode) for all test mode.

2. Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from 9kHz to 30MHz and 18 to 26.5GHz.

The spectrum analyzer plots are attached as below.

Below 1GHz


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 1# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: FRANK2019 #73	Polarization: Horizontal
Standard: FCC Part 15C 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2019/01/15
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 14:52:09
EUT: Massage Chair	Engineer Signature:
Mode: TX2402MHz	Distance: 3m
Model: Titan Pro-Commander	
Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.	

Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	44.3098	40.97	-24.31	16.66	40.00	-23.34	QP	200	302	
2	85.1770	52.35	-27.46	24.89	40.00	-15.11	QP	200	116	
3	109.3110	50.12	-27.39	22.73	43.50	-20.77	QP	200	92	
4	139.7908	55.31	-27.94	27.37	43.50	-16.13	QP	200	119	
5	231.8531	52.31	-23.85	28.46	46.00	-17.54	QP	200	310	
6	348.5144	46.02	-19.37	26.65	46.00	-19.35	QP	200	211	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019 #74
Standard: FCC Part 15C 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Massage Chair
Mode: TX2402MHz
Model: Titan Pro-Commander
Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2019/01/15
Time: 14:53:19
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	30.0000	48.65	-20.20	28.45	40.00	-11.55	QP	100	302	
2	44.3098	53.12	-24.31	28.81	40.00	-11.19	QP	100	116	
3	84.8782	55.32	-27.45	27.87	40.00	-12.13	QP	100	92	
4	142.7692	60.13	-28.01	32.12	43.50	-11.38	QP	100	169	
5	168.9970	57.65	-26.11	31.54	43.50	-11.96	QP	100	354	
6	231.8531	55.32	-23.85	31.47	46.00	-14.53	QP	100	206	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: FRANK2019 #76	Polarization: Horizontal
Standard: FCC Part 15C 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2019/01/15
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 14:54:22
EUT: Massage Chair	Engineer Signature:
Mode: TX2441MHz	Distance: 3m
Model: Titan Pro-Commander	
Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.	

Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	44.1544	40.32	-24.29	16.03	40.00	-23.97	QP	200	116	
2	84.8782	53.78	-27.45	26.33	40.00	-13.67	QP	200	302	
3	139.7908	54.54	-27.94	26.60	43.50	-16.90	QP	200	159	
4	214.6063	52.32	-24.06	28.26	43.50	-15.24	QP	200	95	
5	231.8531	52.01	-23.85	28.16	46.00	-17.84	QP	200	156	
6	371.2679	45.30	-18.75	26.55	46.00	-19.45	QP	200	302	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019 #75	Polarization: Vertical
Standard: FCC Part 15C 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2019/01/15
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 14:53:30
EUT: Massage Chair	Engineer Signature:
Mode: TX2441MHz	Distance: 3m
Model: Titan Pro-Commander	
Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.	

Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	30.0000	48.12	-20.20	27.92	40.00	-12.08	QP	100	201	
2	44.3098	53.32	-24.31	29.01	40.00	-10.99	QP	100	146	
3	87.2980	54.52	-27.44	27.08	40.00	-12.92	QP	100	99	
4	132.6142	56.26	-27.79	28.47	43.50	-15.03	QP	100	61	
5	168.9970	57.65	-26.11	31.54	43.50	-11.96	QP	100	115	
6	231.8531	55.32	-23.85	31.47	46.00	-14.53	QP	100	211	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019 #77	Polarization: Horizontal
Standard: FCC Part 15C 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 2019/01/15
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 14:54:37
EUT: Massage Chair	Engineer Signature:
Mode: TX2480MHz	Distance: 3m
Model: Titan Pro-Commander	
Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.	

Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	84.8782	53.15	-27.45	25.70	40.00	-14.30	QP	200	321	
2	108.9275	51.20	-27.46	23.74	43.50	-19.76	QP	200	166	
3	139.7908	54.95	-27.94	27.01	43.50	-16.49	QP	200	61	
4	168.4043	51.36	-26.17	25.19	43.50	-18.31	QP	200	95	
5	214.6063	52.67	-24.06	28.61	43.50	-14.89	QP	200	116	
6	231.8531	51.35	-23.85	27.50	46.00	-18.50	QP	200	302	



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019 #78
Standard: FCC Part 15C 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Massage Chair
Mode: TX2480MHz
Model: Titan Pro-Commander
Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 2019/01/15
Time: 14:55:26
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	30.0000	47.32	-20.20	27.12	40.00	-12.88	QP	100	103	
2	44.3098	53.45	-24.31	29.14	40.00	-10.86	QP	100	302	
3	84.8782	54.95	-27.45	27.50	40.00	-12.50	QP	100	291	
4	134.9643	57.31	-27.85	29.46	43.50	-14.04	QP	100	201	
5	167.8136	57.15	-26.23	30.92	43.50	-12.58	QP	100	92	
6	220.7240	53.15	-24.02	29.13	46.00	-16.87	QP	100	221	

Above 1GHz




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019 #162	Polarization: Horizontal
Standard: FCC Part 15C 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 19/01/17/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 16/56/43
EUT: Massage Chair	Engineer Signature:
Mode: TX2402MHz(GFSK)	Distance: 3m
Model: Titan Pro-Commander	
Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.	

Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.019	95.37	-6.37	89.00	/	/	peak	200	116	
2	4804.057	50.47	0.70	51.17	74.00	-22.83	peak	200	62	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019 #163	Polarization: Vertical
Standard: FCC Part 15C 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 19/01/17/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 17/02/34
EUT: Massage Chair	Engineer Signature:
Mode: TX2402MHz(GFSK)	Distance: 3m
Model: Titan Pro-Commander	
Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.	

Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.019	91.43	-6.37	85.06	/	/	peak	150	159	
2	4804.057	48.65	0.70	49.35	74.00	-24.65	peak	150	92	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019 #165	Polarization: Horizontal
Standard: FCC Part 15C 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 19/01/17/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 17/10/17
EUT: Massage Chair	Engineer Signature:
Mode: TX2441MHz(GFSK)	Distance: 3m
Model: Titan Pro-Commander	
Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.	

Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.107	93.73	-6.10	87.63	/	/	peak	200	52	
2	4882.117	48.53	1.32	49.85	74.00	-24.15	peak	200	164	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019 #164	Polarization: Vertical
Standard: FCC Part 15C 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 19/01/17/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 17/06/31
EUT: Massage Chair	Engineer Signature:
Mode: TX2441MHz(GFSK)	Distance: 3m
Model: Titan Pro-Commander	
Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.	

Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.124	95.64	-6.14	89.50	/	/	peak	150	41	
2	4882.017	46.53	1.32	47.85	74.00	-26.15	peak	150	321	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019 #166	Polarization: Horizontal
Standard: FCC Part 15C 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 19/01/17/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 17/15/43
EUT: Massage Chair	Engineer Signature:
Mode: TX2480MHz(GFSK)	Distance: 3m
Model: Titan Pro-Commander	
Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.	

Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.034	94.15	-6.04	88.11	/	/	peak	200	219	
2	4960.144	45.07	1.50	46.57	74.00	-27.43	peak	250	130	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019 #167	Polarization: Vertical
Standard: FCC Part 15C 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 19/01/17/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 17/20/12
EUT: Massage Chair	Engineer Signature:
Mode: TX2480MHz(GFSK)	Distance: 3m
Model: Titan Pro-Commander	
Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.	


Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.034	94.15	-6.04	88.11	/	/	peak	150	219	
2	4960.044	49.57	1.50	51.07	74.00	-22.93	peak	150	321	

11. BAND EDGE COMPLIANCE TEST

11.1. Block Diagram of Test Setup



11.2. The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

11.3. EUT Configuration on Test

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

11.4. Operating Condition of EUT

11.4.1. Setup the EUT and simulator as shown as Section 11.1.

11.4.2. Turn on the power of all equipment.

11.4.3. Let the EUT work in TX (Hopping off, Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2480MHz TX frequency to transmit.

11.5. Test Procedure

11.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

11.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz with convenient frequency span including 100 kHz bandwidth from band edge.

11.5.3. The band edges was measured and recorded.

11.6. Test Result

Note: Both hopping-on mode and hopping-off mode had been pre-tested, and only the worst case was recorded in the test report.


Conducted Band Edge Result

Non-hopping mode


Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)	Result
GFSK Mode			
2400.00	34.34	> 20dBc	Pass
2483.50	38.62	> 20dBc	Pass
Π/4-DQPSK Mode			
2400.00	31.59	> 20dBc	Pass
2483.50	34.30	> 20dBc	Pass
8DPSK Mode			
2400.00	27.44	> 20dBc	Pass
2483.50	31.83	> 20dBc	Pass

The spectrum analyzer plots are attached as below.

GFSK Mode




Date: 18.JAN.2019 13:38:23




Date: 18.JAN.2019 13:42:16

Π/4-DQPSK Mode




Date: 18.JAN.2019 13:46:54




Date: 18.JAN.2019 13:44:48

8DPSK Mode



Date: 18.JAN.2019 13:55:10



Date: 18.JAN.2019 14:13:13

Radiated Band Edge Result

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

3. Display the measurement of peak values.

Test Procedure:

The EUT and its simulators are placed on a turntable, which is 0.1 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. This EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Let the EUT work in TX (Hopping off, Hopping on) modes measure it.
We select 2402MHz, 2480MHz TX frequency to transmit(Hopping off mode).
We select 2402-2480MHz TX frequency to transmit(Hopping on mode).

During the radiated emission test, the spectrum analyzer was set with the following configurations:

- 1.The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz.
- 2.The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
- 3.All modes of operation were investigated and the worst case (GFSK mode) emissions are reported.

The spectrum analyzer plots are attached as below.

Non-hopping mode


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 1# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: FRANK2019 #145

Polarization: Horizontal

Standard: FCC Part 15C 3M Radiated

Power Source: AC 120V/60Hz

Test item: Radiation Test

Date: 19/01/17/

Temp.(C)/Hum.(%) 25 C / 55 %

Time: 15/05/12

EUT: Massage Chair

Engineer Signature:


Mode: TX2402MHz(GSFK)

Distance: 3m

Model: Titan Pro-Commander

Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.

Note: Report NO.:ATE20190041




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	48.32	-6.32	42.00	74.00	-32.00	peak	200	300	
2	2390.000	39.54	-6.32	33.22	54.00	-20.78	AVG	200	92	
3	2400.000	58.70	-6.27	52.43	74.00	-21.57	peak	200	210	
4	2400.000	49.96	-6.27	43.69	54.00	-10.31	AVG	200	301	

Note: Average measurement with peak detection at No.2&4

Job No.: FRANK2019 #144	Polarization: Vertical
Standard: FCC Part 15C 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 19/01/17/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15/02/13
EUT: Massage Chair	Engineer Signature:
Mode: TX2402MHz(GSFK)	Distance: 3m
Model: Titan Pro-Commander	
Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.	

Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	47.31	-6.32	40.99	74.00	-33.01	peak	150	201	
2	2390.000	38.48	-6.32	32.16	54.00	-21.84	AVG	150	92	
3	2400.000	55.47	-6.27	49.20	74.00	-24.80	peak	150	113	
4	2400.000	46.77	-6.27	40.50	54.00	-13.50	AVG	150	201	

Note: Average measurement with peak detection at No.2&4



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd.
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: FRANK2019 #154

Standard: FCC Part 15C 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Massage Chair

Mode: TX2480MHz(GFSK)

Model: Titan Pro-Commander

Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 19/01/17/

Time: 15/37/20

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	52.76	-5.89	46.87	74.00	-27.13	peak	200	44	
2	2500.000	49.29	-5.81	43.48	74.00	-30.52	peak	200	211	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019 #155	Polarization: Vertical
Standard: FCC Part 15C 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 19/01/17/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15/41/17
EUT: Massage Chair	Engineer Signature:
Mode: TX2480MHz(GFSK)	Distance: 3m
Model: Titan Pro-Commander	
Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.	

Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	51.34	-5.89	45.45	74.00	-28.55	peak	150	302	
2	2483.500	42.37	-5.89	36.48	54.00	-17.52	AVG	150	119	
3	2500.000	43.14	-5.81	37.33	74.00	-36.67	peak	150	91	
4	2500.000	34.54	-5.81	28.73	54.00	-25.27	AVG	150	62	

Note: Average measurement with peak detection at No.2&4

Hopping mode


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 1# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: FRANK2019 #157

Polarization: Horizontal

Standard: FCC Part 15C 3M Radiated

Power Source: AC 120V/60Hz

Test item: Radiation Test

Date: 19/01/17/

Temp.(C)/Hum.(%) 25 C / 55 %

Time: 16/01/45

EUT: Massage Chair

Engineer Signature:


Mode: HOPPING(GFSK)

Distance: 3m

Model: Titan Pro-Commander

Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.

Note: Report NO.:ATE20190041



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	47.30	-6.32	40.98	74.00	-33.02	peak	250	302	
2	2390.000	39.45	-6.32	33.13	54.00	-20.87	AVG	200	119	
3	2400.000	51.06	-6.27	44.79	74.00	-29.21	peak	250	22	
4	2400.000	42.31	-6.27	36.04	54.00	-17.96	AVG	200	69	
5	2483.500	50.69	-5.89	44.80	74.00	-29.20	peak	250	101	
6	2483.500	41.45	-5.89	35.56	54.00	-18.44	AVG	200	221	
7	2500.000	45.90	-5.81	40.09	74.00	-33.91	peak	200	68	
8	2500.000	36.45	-5.81	30.64	54.00	-23.36	AVG	200	113	

Note: Average measurement with peak detection at No.2&4&6&8




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019 #156	Polarization: Vertical
Standard: FCC Part 15C 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 19/01/17/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15/50/31
EUT: Massage Chair	Engineer Signature:
Mode: HOPPING(GFSK)	Distance: 3m
Model: Titan Pro-Commander	
Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.	

Note: Report NO.:ATE20190041




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	41.92	-6.32	35.60	74.00	-38.40	peak	150	302	
2	2390.000	32.45	-6.32	26.13	54.00	-27.87	AVG	150	100	
3	2400.000	46.98	-6.27	40.71	74.00	-33.29	peak	150	301	
4	2400.000	37.54	-6.27	31.27	54.00	-22.73	AVG	150	96	
5	2483.500	45.56	-5.89	39.67	74.00	-34.33	peak	150	149	
6	2483.500	36.45	-5.89	30.56	54.00	-23.44	AVG	150	95	
7	2500.000	42.12	-5.81	36.31	74.00	-37.69	peak	150	116	
8	2500.000	33.45	-5.81	27.64	54.00	-26.36	AVG	150	302	

Note: Average measurement with peak detection at No.2&4&6&8


12.AC POWER LINE CONDUCTED EMISSION TEST

12.1.Block Diagram of Test Setup

12.1.1.Block diagram of connection between the EUT and simulators



12.1.2.Test System Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 0.1m from other units and other metal planes support units.

12.2.Power Line Conducted Emission Test Limits

Frequency (MHz)	Conducted Limit dB(μV)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0

NOTE1: The lower limit shall apply at the transition frequencies.
 NOTE2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

12.3.Configuration of EUT on Test

The equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

12.4.Operating Condition of EUT

12.4.1.Setup the EUT and simulator as shown as Section 12.1.

12.4.2.Turn on the power of all equipment.

12.4.3.Let the EUT work in test mode and measure it.

12.5.Test Procedure

The EUT is put on the plane 0.1m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Measurement. The bandwidth of test receiver (R & S ESCS30) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

12.6.Data Sample

Frequency (MHz)	Transducer value (dB)	QuasiPeak Level (dBμV)	Average Level (dBμV)	QuasiPeak Limit (dBμV)	Average Limit (dBμV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
X.XX	10.5	51.1	34.2	56.0	46.0	4.9	11.8	Pass

Frequency(MHz) = Emission frequency in MHz

Transducer value(dB) = Insertion loss of LISN + Cable Loss

Level(dBμV) = Quasi-peak Reading/Average Reading + Transducer value

Limit (dBμV) = Limit stated in standard

Margin = Limit (dBμV) - Level (dBμV)

Calculation Formula:

Margin = Limit (dBμV) - Level (dBμV)

12.7.Test Results

Pass.

The frequency range from 150kHz to 30MHz is checked.

Maximizing procedure was performed on the six (6) highest emissions of the EUT. Emissions attenuated more than 20 dB below the permissible value are not reported.

All data was recorded in the Quasi-peak and average detection mode.

The spectral diagrams are attached as below.


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15C

EUT: Massage Chair M/N:Titan Pro-Commander
 Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.
 Operating Condition: BT Communication
 Test Site: 1#Shielding Room
 Operator: Frank
 Test Specification: L 120V/60Hz
 Comment: Report NO.:ATE20190041
 Start of Test: 2019-1-15 / 9:27:22

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "F-0041-1_fin"

2019-1-15 9:29

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.150000	48.00	10.8	66	18.0	QP	L1	GND
0.519000	32.60	11.0	56	23.4	QP	L1	GND
1.099500	25.30	11.1	56	30.7	QP	L1	GND
4.924500	22.70	11.4	56	33.3	QP	L1	GND
8.128500	42.60	11.5	60	17.4	QP	L1	GND
19.734000	16.80	11.7	60	43.2	QP	L1	GND

MEASUREMENT RESULT: "F-0041-1_fin2"

2019-1-15 9:29

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.150000	37.10	10.8	56	18.9	AV	L1	GND
0.519000	22.20	11.0	46	23.8	AV	L1	GND
1.108500	18.30	11.2	46	27.7	AV	L1	GND
4.924500	14.70	11.4	46	31.3	AV	L1	GND
8.133000	20.20	11.5	50	29.8	AV	L1	GND
19.734000	7.60	11.7	50	42.4	AV	L1	GND


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15C

EUT: Massage Chair M/N:Titan Pro-Commander
 Manufacturer: FUJIAN YIHE ELECTRONICS CO., LTD.
 Operating Condition: BT Communication
 Test Site: 1#Shielding Room
 Operator: Frank
 Test Specification: N 120V/60Hz
 Comment: Report NO.:ATE20190041
 Start of Test: 2019-1-15 / 9:30:23

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "F-0041-2_fin"

2019-1-15 9:32

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.150000	49.60	10.8	66	16.4	QP	N	GND
0.442500	32.20	11.0	57	24.8	QP	N	GND
0.964500	30.10	11.1	56	25.9	QP	N	GND
2.931000	27.20	11.3	56	28.8	QP	N	GND
8.146500	37.40	11.5	60	22.6	QP	N	GND
13.816500	31.30	11.6	60	28.7	QP	N	GND

MEASUREMENT RESULT: "F-0041-2_fin2"

2019-1-15 9:32

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.258000	31.50	10.9	52	20.0	AV	N	GND
0.519000	23.70	11.0	46	22.3	AV	N	GND
1.846500	23.10	11.2	46	22.9	AV	N	GND
2.179500	22.20	11.3	46	23.8	AV	N	GND
8.146500	29.10	11.5	50	20.9	AV	N	GND
19.770000	5.60	11.7	50	44.4	AV	N	GND


13.ANTENNA REQUIREMENT

13.1.The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

13.2.Antenna Construction

Device is equipped with permanent attached antenna, which isn't displaced by other antenna. The Max Antenna gain of EUT is 2dBi. Therefore, the equipment complies with the antenna requirement of Section 15.203.



Antenna

***** End of Test Report *****