

RADIO FREQUENCY EXPOSURE

Limit

According to section B.3 MPE-based Exemption of 447498 D04 Interim General RF Exposure Guidance v01

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source Frequency			Minimum Distance		Threshold ERP
f_L MHz		f_H MHz	$\lambda_L / 2\pi$	$\lambda_H / 2\pi$	W
0.3	—	1.34	159 m	—	35.6 m 1.920 R^2
1.34	—	30	35.6 m	—	1.6 m $3,450 \text{ R}^2/f^2$
30	—	300	1.6 m	—	159 mm 3.83 R^2
300	—	1,500	159 mm	—	31.8 mm $0.0128 \text{ R}^2/f$
1,500	—	100,000	31.8 mm	—	0.5 mm 19.2 R^2

Subscripts L and H are low and high; λ is wavelength.
From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than $ERP_{20\text{cm}}$ in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole).

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

Results

Channel Frequency (MHz)	Level [dB μ V/m]	Max. ERP (dBm, Peak)	Max. ERP (W, Peak)	Exemption Limit (W)
13.56	53.43	-41.8	0.0000001	0.7505

Note:

1. Max. ERP(dBm, Peak) = 95.23 - Level[dB μ V/m]
2. Exemption Limit(mW) = $3,450 \cdot R^2/f^2 = 3450 * 0.2^2/(13.56)^2 = 0.7505(W)$
3. The distance is 20cm from user manual provide by manufacturer

the Maximum Eirp is used for MPE-based Exemption according to B.3 of 447498 D04 Interim General RF Exposure Guidance v01.

So, the SAR evaluation is not required.