Cover Letter-Modular Approval

FCC ID: 2ASC3CM358

Date: 2023-04-12

Gentlemen:

There's WIFI+BT Module that would like to have your authorization as a modular approval. The specific product as below, radar Module with its designed features and specified description, meets special requirements for Full modular approval on FCC KDB996369 by cross-reference list below.

Company	Positec Technology (China) Co.,Ltd.
Model Name	WIFI+BT Module
Model Number	AW-CM358
FCC ID	2ASC3CM358

Requirement of FCC KDB996369	Comply (Y/N)
1. The modular transmitter must have its own RF shielding.	Y The EUT has its own RF shielding. Please refer to EUT Photos.
2. The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with Part 15 requirements under conditions of excessive data rates or over-modulation.	Y The EUT uses the chip: (88W8987) as an embedded processor to buffer the data. Please refer to Schematics.
3. The modular transmitter must have its own power supply regulation.	Y The EUT uses the chip 88W8987 with built-in power management components, The module rated power is 3.3V. Please refer to Schematics.
4. The modular transmitter must comply with the antenna and transmission system requirements of Sections 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of Section 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.	Y The EUT meets the PCB antenna requirements; unique antenna connector and photo of antenna are shown in the test report.
5. The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing.	Y The EUT was tested with a test cable, see test report and setup photo
6. The modular transmitter must be labeled with its own FCC ID number, and, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: 2ASC3CM358" or "Contains FCC ID: 2ASC3CM358" Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide	Y Please see exhibition label sample for the FCC ID of this module. And also in the exhibition User's manual, there are instructions to the OEM on how to label the end product.

Thank you.

Sincerely,

Print Name: Allen Ding Title: Deputy Chief Engineer

Hais

Signature:

On behalf of Company: Positec Technology (China) Co., Ltd. Telephone: 86 512 65152888-2571