

FCC §15.247 (i), §2.1091 – RF Exposure

# FCC ID: 2ASCB-DL032NLB

#### **Applied procedures / limit**

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)	
0.3-3.0	614	1.63	(100)*	6	
3.0-30	1842 / f	4.89 / f	(900 / f)*	6	
30-300	61.4	0.163	1.0	6	
300-1500			F/300	6	
1500-100,000			5	6	

# Limits for Occupational / Controlled Exposure

Note: *f* is frequency in MHz

\* = Power density limit is applicable at frequencies greater than 100 MHz

#### Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

\* = Plane-wave equivalent power density



### MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01  $S=PG/4\pi R^2$ 

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=0.2m

## **TEST RESULTS**

Mode	Tune up Produce power	Maximum peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Limit (mW/ cm2)	Result
2.4G WIFI	14±1	15	31.623	2.03 (3.07dBi)	0.012771	1	Pass
5.1G WIFI	13±1	14	25.119	2.04 (3.1dBi)	0.010194	1	Pass
5.8G WIFI	11±1	12	15.849	2.03 (3.08dBi)	0.006401	1	Pass
BLE	8±1	9	7.943	2.03 (3.07dBi)	0.003208	1	Pass
ВТ	2±1	3	1.995	2.03 (3.07dBi)	0.000806	1	Pass

Conclusion:

For the all Power Density≤ 1.0, compliance with FCC's RF Exposure

The Product unsupported at the same time to Transmitting.