FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2ASCB-DW060VB

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)	
0.3-3.0	614	1.63	(100)*	6	
3.0-30	1842 / f	4.89 / f	(900 / f)*	6	
30-300	61.4	0.163	1.0	6	
300-1500			F/300	6	
1500-100,000			5	6	

Note: *f* is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)	
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f)*	30	
30-300	27.5	0.073	0.2	30	
300-1500			F/1500	30	
1500-100,000			1.0	30	

Note: f = frequency in MHz

* = Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

	Modes& Channel Freq. (MHz)	Tune up Produce power	Maximu m peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Limit (mW / cm2)	Result
2.4G WIFI ANT1	802.11b&2 437	14±1	15	31.6228	1.6032 (2.05dBi)	0.0101	1	Pass
2.4G WIFI ANT2	802.11b&2 412	14±1	15	31.6228	1.6032 (2.05dBi)	0.0101	1	Pass
EDR	8DPSK &HCH	0±1	1	1.2589	1.6032 (2.05dBi)	0.0004	1	Pass

Tech nolo gy	Proc	e up duce (dBm) ANT 2	Tun	mum e-up 3m) ANT 2	Antenna Gain(ANT 1/ANT 2) (numeric)	(\$	Density S) cm2) ANT 2	MPE Limit (mW/ cm2)	∑ MPE Ratio	∑ MPE Ratio Limit	Result
2.4G WIFI MIM O	14 土1	14 土1	15	15	1.6032 (2.05dBi)	0.0101	0.0101	1	0.0202	1	Pass