

## RF EXPOSURE EVALUATION

#### 1. PRODUCT INFORMATION

_	11 1 KOBOOT IN CHAIR CHA		
	Product Description	Air conduction wireless sports headset	
	Test Model	Q5	
	Series Model	Q2, Q6, Q7, HBM306	
	FCC ID	2ASCI-HBM306Q5	

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR.

Where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

#### 3. CALCULATION

**BR&EDR**:

P<sub>t</sub>=4.223dBm=2.64mW

The value of the Maximum output power P<sub>t</sub> is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation SAR= $(2.64\text{mW} / 5\text{mm}).[\sqrt{2.402\text{GHz}}]=0.818<3.0$  for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR.

# 4. CONCLUSION

The SAR evaluation is not required.