



FCC PART 15.247

TEST REPORT

For

New Hantat Technology Ltd.

Building 18-19,Zone2,Huaide Cuigang Industrial Park,Fuyong Town, Bao'an District, Shenzhen, China

FCC ID: 2ASCIHB163

Report Type: Original Report	Product Name: Bluetooth Speaker
Report Number:	<u>RDG190111004-00</u>
Report Date:	<u>2019-01-21</u>
Reviewed By:	<u>Allen Qiao RF Supervisor</u> <i>Allen Qiao</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE.....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY.....	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION.....	6
EUT EXERCISE SOFTWARE.....	6
EQUIPMENT MODIFICATIONS.....	6
SUPPORT EQUIPMENT LIST AND DETAILS.....	7
SUPPORT CABLE LIST AND DETAILS.....	7
BLOCK DIAGRAM OF TEST SETUP.....	7
SUMMARY OF TEST RESULTS.....	8
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE.....	9
APPLICABLE STANDARD.....	9
FCC §15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD.....	10
ANTENNA CONNECTOR CONSTRUCTION.....	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS.....	11
APPLICABLE STANDARD.....	11
EUT SETUP.....	11
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE.....	11
CORRECTED AMPLITUDE & MARGIN CALCULATION.....	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST DATA.....	12
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	15
APPLICABLE STANDARD.....	15
EUT SETUP.....	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP.....	16
TEST PROCEDURE.....	16
CORRECTED AMPLITUDE & MARGIN CALCULATION.....	16
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST DATA.....	17
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST.....	25
APPLICABLE STANDARD.....	25
TEST EQUIPMENT LIST AND DETAILS.....	25
TEST PROCEDURE.....	25
TEST DATA.....	25
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING.....	31
APPLICABLE STANDARD.....	31
TEST PROCEDURE.....	31

TEST EQUIPMENT LIST AND DETAILS.....31
 TEST DATA31

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST37
 APPLICABLE STANDARD37
 TEST PROCEDURE37
 TEST EQUIPMENT LIST AND DETAILS.....37
 TEST DATA37

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....41
 APPLICABLE STANDARD41
 TEST PROCEDURE41
 TEST EQUIPMENT LIST AND DETAILS.....41
 TEST DATA41

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT48
 APPLICABLE STANDARD48
 TEST PROCEDURE48
 TEST EQUIPMENT LIST AND DETAILS.....48
 TEST DATA48

FCC §15.247(d) - BAND EDGES TESTING54
 APPLICABLE STANDARD54
 TEST PROCEDURE54
 TEST EQUIPMENT LIST AND DETAILS.....54
 TEST DATA55

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:	Bluetooth Speaker
EUT Model:	HB163
Rated Input Voltage:	3.7Vdc from battery or 5Vdc from USB port
External Dimension:	85mm(L)* 75mm(W)* 75 mm(H)
Serial Number:	190111004
EUT Received Date:	2019.01.11

Objective

This report is prepared on behalf of *New Hantat Technology Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

N/A

Test Methodology

All measurements detailed in this test report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices" and 558074 D01 15.247 Meas Guidance v05.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB,200M~1GHz: 5.92 dB,1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode. For 2.4GHz BT, 79 channels are provided to testing.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	41	2443
2	2404
...	...	77	2479
38	2440	78	2480
39	2441	/	/

EUT was tested with channel 0, 39 and 78.

EUT Exercise Software

Test software: 'BK32xx RF Test_V1.5.exe' was used in test; the system configured maximum power level as below setting:

Mode	Channel	Frequency (MHz)	Power Level
GFSK	Low	2402	3
	Middle	2441	3
	High	2480	3
$\pi/4$ -DQPSK	Low	2402	3
	Middle	2441	3
	High	2480	3
8DPSK	Low	2402	3
	Middle	2441	3
	High	2480	3

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
HUAWEI	Adapter	HW-050200C01	/
APPLE	Phone	MGAA2CG/A	FK1R95UYG5QT

Support Cable List and Details

Cable Description	Shielding Cable	Ferrite Core	Length (m)	From Port	To
USB Cable	yes	No	1.2	EUT	Adapter

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The max conducted power including tune-up tolerance is 5.0 dBm (3.16 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 3.16/5 \cdot (\sqrt{2.480}) = 1.0 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement for BT, and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main LISN with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2018-12-10	2019-12-10
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2018-09-05	2019-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
R&S	Two-line V-network	ENV 216	101614	2018-12-10	2019-12-10

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	25.8 °C
Relative Humidity:	54 %
ATM Pressure:	100.8 kPa

The testing was performed by Ade Xiao on 2019-01-15.

Test Result: Pass

Test Mode: Charging & Transmitting


AC120V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.175915	39.8	9.000	L1	10.8	24.9	64.7
0.181612	38.9	9.000	L1	10.8	25.5	64.4
0.195114	43.3	9.000	L1	10.7	20.5	63.8
0.234359	37.5	9.000	L1	10.4	24.8	62.3
0.295282	38.3	9.000	L1	10.2	22.1	60.4
0.319773	32.4	9.000	L1	10.1	27.3	59.7

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.937592	17.7	9.000	L1	9.8	28.3	46.0
1.890344	26.3	9.000	L1	9.7	19.7	46.0
2.815577	21.9	9.000	L1	9.8	24.1	46.0
3.781003	20.8	9.000	L1	9.8	25.2	46.0
4.726090	20.7	9.000	L1	9.8	25.3	46.0
23.633576	19.4	9.000	L1	10.1	30.6	50.0

AC120V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.159873	53.5	9.000	N	11.0	12.0	65.5
0.166371	51.6	9.000	N	10.9	13.5	65.1
0.183065	49.4	9.000	N	10.8	14.9	64.3
0.225205	45.1	9.000	N	10.5	17.5	62.6
0.230654	45.7	9.000	N	10.4	16.7	62.4
0.247802	45.2	9.000	N	10.3	16.6	61.8

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.407671	22.3	9.000	N	9.8	23.7	46.0
1.890344	24.2	9.000	N	9.8	21.8	46.0
2.815577	22.4	9.000	N	9.8	23.6	46.0
3.302007	19.8	9.000	N	9.8	26.2	46.0
4.726090	26.1	9.000	N	9.8	19.9	46.0
5.631624	22.7	9.000	N	9.8	27.3	50.0


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission Below 1GHz tests were performed in the 3 meters chamber A, above 1GHz tests were performed in the 3 meters chamber B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

According to FCC public notice: DA-00-705, during the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2018-12-10	2019-12-10
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2018-05-06	2019-05-06
HP	Amplifier	8447D	2727A05902	2018-09-05	2019-09-05
Agilent	Spectrum Analyzer	E4440A	SG43360054	2019-01-04	2020-01-04
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-11
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2016-11-18	2019-11-18
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2016-11-18	2019-11-18
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-2.4J2.4J-50	C-0700-02	2018-06-27	2019-06-27
MITEQ	Amplifier	AFS42-00101800- 25-S-42	2001271	2018-09-05	2019-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2018-06-27	2019-06-27
E-Microwave	Band-stop Filters	OBSF-2400-2483.5- S	OE01601525	2018-06-16	2019-06-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	23.4~24.3 °C
Relative Humidity:	43~51 %
ATM Pressure:	100.3~100.8kPa

The testing was performed by Vern Shen, Kami Zhou on 2019-01-15~2019-01-16.

Test Mode: Transmitting


1) 30MHz-1GHz (8DPSK low channel was the worst)

Horizontal:



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
30.9700	27.68	peak	0.91	28.59	40.00	11.41
86.2600	40.10	peak	-11.42	28.68	40.00	11.32
122.1500	39.03	peak	-4.57	34.46	43.50	9.04
187.1400	39.76	peak	-7.29	32.47	43.50	11.03
240.4900	39.21	peak	-5.99	33.22	46.00	12.78
288.9900	40.58	peak	-3.98	36.60	46.00	9.40

Vertical:



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
30.9700	30.99	QP	0.91	31.90	40.00	8.10
85.2900	40.55	peak	-11.41	29.14	40.00	10.86
121.1800	39.88	QP	-4.68	35.20	43.50	8.30
172.5900	39.10	peak	-6.79	32.31	43.50	11.19
289.9600	38.05	peak	-3.94	34.11	46.00	11.89
964.1100	11.74	peak	22.90	34.64	54.00	19.36

2)1GHz-25GHz**BDR Mode (GFSK):**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Measurement	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	59.41	PK	H	28.10	1.80	0.00	89.31	N/A	N/A
2402.00	49.63	AV	H	28.10	1.80	0.00	79.53	N/A	N/A
2402.00	64.66	PK	V	28.10	1.80	0.00	94.56	N/A	N/A
2402.00	55.38	AV	V	28.10	1.80	0.00	85.28	N/A	N/A
2390.00	24.90	PK	V	28.08	1.80	0.00	54.78	74.00	19.22
2390.00	13.26	AV	V	28.08	1.80	0.00	43.14	54.00	10.86
4804.00	56.50	PK	V	32.91	3.17	37.20	55.38	74.00	18.62
4804.00	45.53	AV	V	32.91	3.17	37.20	44.41	54.00	9.59
7206.00	53.89	PK	V	35.74	4.82	37.23	57.22	74.00	16.78
7206.00	41.56	AV	V	35.74	4.82	37.23	44.89	54.00	9.11
Middle Channel: 2441 MHz									
2441.00	58.58	PK	H	28.18	1.82	0.00	88.58	N/A	N/A
2441.00	49.26	AV	H	28.18	1.82	0.00	79.26	N/A	N/A
2441.00	63.21	PK	V	28.18	1.82	0.00	93.21	N/A	N/A
2441.00	53.94	AV	V	28.18	1.82	0.00	83.94	N/A	N/A
4882.00	58.21	PK	V	33.06	3.27	37.21	57.33	74.00	16.67
4882.00	47.41	AV	V	33.06	3.27	37.21	46.53	54.00	7.47
7323.00	53.92	PK	V	36.04	4.62	37.38	57.20	74.00	16.80
7323.00	41.38	AV	V	36.04	4.62	37.38	44.66	54.00	9.34
High Channel: 2480 MHz									
2480.00	60.24	PK	H	28.26	1.84	0.00	90.34	N/A	N/A
2480.00	51.14	AV	H	28.26	1.84	0.00	81.24	N/A	N/A
2480.00	65.42	PK	V	28.26	1.84	0.00	95.52	N/A	N/A
2480.00	56.25	AV	V	28.26	1.84	0.00	86.35	N/A	N/A
2483.50	35.50	PK	V	28.27	1.84	0.00	65.61	74.00	8.39
2483.50	13.96	AV	V	28.27	1.84	0.00	44.07	54.00	9.93
4960.00	58.20	PK	V	33.22	3.23	37.25	57.40	74.00	16.60
4960.00	48.17	AV	V	33.22	3.23	37.25	47.37	54.00	6.63
7440.00	53.99	PK	V	36.34	4.41	37.52	57.22	74.00	16.78
7440.00	41.87	AV	V	36.34	4.41	37.52	45.10	54.00	8.90

EDR Mode ($\pi/4$ -DQPSK):




Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Measurement	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	61.25	PK	H	28.10	1.80	0.00	91.15	N/A	N/A
2402.00	49.67	AV	H	28.10	1.80	0.00	79.57	N/A	N/A
2402.00	66.51	PK	V	28.10	1.80	0.00	96.41	N/A	N/A
2402.00	54.95	AV	V	28.10	1.80	0.00	84.85	N/A	N/A
2390.00	24.88	PK	V	28.08	1.80	0.00	54.76	74.00	19.24
2390.00	13.26	AV	V	28.08	1.80	0.00	43.14	54.00	10.86
4804.00	58.41	PK	V	32.91	3.17	37.20	57.29	74.00	16.71
4804.00	45.39	AV	V	32.91	3.17	37.20	44.27	54.00	9.73
7206.00	55.86	PK	V	35.74	4.82	37.23	59.19	74.00	14.81
7206.00	41.69	AV	V	35.74	4.82	37.23	45.02	54.00	8.98
Middle Channel: 2441 MHz									
2441.00	60.24	PK	H	28.18	1.82	0.00	90.24	N/A	N/A
2441.00	48.67	AV	H	28.18	1.82	0.00	78.67	N/A	N/A
2441.00	65.12	PK	V	28.18	1.82	0.00	95.12	N/A	N/A
2441.00	53.26	AV	V	28.18	1.82	0.00	83.26	N/A	N/A
4882.00	59.70	PK	V	33.06	3.27	37.21	58.82	74.00	15.18
4882.00	46.52	AV	V	33.06	3.27	37.21	45.64	54.00	8.36
7323.00	54.20	PK	V	36.04	4.62	37.38	57.48	74.00	16.52
7323.00	40.19	AV	V	36.04	4.62	37.38	43.47	54.00	10.53
High Channel: 2480 MHz									
2480.00	62.75	PK	H	28.26	1.84	0.00	92.85	N/A	N/A
2480.00	50.84	AV	H	28.26	1.84	0.00	80.94	N/A	N/A
2480.00	67.50	PK	V	28.26	1.84	0.00	97.60	N/A	N/A
2480.00	55.80	AV	V	28.26	1.84	0.00	85.90	N/A	N/A
2483.50	29.77	PK	V	28.27	1.84	0.00	59.88	74.00	14.12
2483.50	14.01	AV	V	28.27	1.84	0.00	44.12	54.00	9.88
4960.00	60.57	PK	V	33.22	3.23	37.25	59.77	74.00	14.23
4960.00	47.46	AV	V	33.22	3.23	37.25	46.66	54.00	7.34
7440.00	53.49	PK	V	36.34	4.41	37.52	56.72	74.00	17.28
7440.00	39.71	AV	V	36.34	4.41	37.52	42.94	54.00	11.06

EDR Mode (8DPSK):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Measurement	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	58.41	PK	H	28.10	1.80	0.00	88.31	N/A	N/A
2402.00	46.26	AV	H	28.10	1.80	0.00	76.16	N/A	N/A
2402.00	64.88	PK	V	28.10	1.80	0.00	94.78	N/A	N/A
2402.00	52.75	AV	V	28.10	1.80	0.00	82.65	N/A	N/A
2390.00	24.47	PK	V	28.08	1.80	0.00	54.35	74.00	19.65
2390.00	13.26	AV	V	28.08	1.80	0.00	43.14	54.00	10.86
4804.00	58.96	PK	V	32.91	3.17	37.20	57.84	74.00	16.16
4804.00	45.16	AV	V	32.91	3.17	37.20	44.04	54.00	9.96
7206.00	55.97	PK	V	35.74	4.82	37.23	59.30	74.00	14.70
7206.00	40.25	AV	V	35.74	4.82	37.23	43.58	54.00	10.42
Middle Channel: 2441 MHz									
2441.00	59.75	PK	H	28.18	1.82	0.00	89.75	N/A	N/A
2441.00	47.64	AV	H	28.18	1.82	0.00	77.64	N/A	N/A
2441.00	65.36	PK	V	28.18	1.82	0.00	95.36	N/A	N/A
2441.00	53.67	AV	V	28.18	1.82	0.00	83.67	N/A	N/A
4882.00	60.02	PK	V	33.06	3.27	37.21	59.14	74.00	14.86
4882.00	46.21	AV	V	33.06	3.27	37.21	45.33	54.00	8.67
7323.00	54.64	PK	V	36.04	4.62	37.38	57.92	74.00	16.08
7323.00	40.52	AV	V	36.04	4.62	37.38	43.80	54.00	10.20
High Channel: 2480 MHz									
2480.00	62.88	PK	H	28.26	1.84	0.00	92.98	N/A	N/A
2480.00	50.67	AV	H	28.26	1.84	0.00	80.77	N/A	N/A
2480.00	68.13	PK	V	28.26	1.84	0.00	98.23	N/A	N/A
2480.00	56.35	AV	V	28.26	1.84	0.00	86.45	N/A	N/A
2483.50	30.26	PK	V	28.27	1.84	0.00	60.37	74.00	13.63
2483.50	15.24	AV	V	28.27	1.84	0.00	45.35	54.00	8.65
4960.00	60.79	PK	V	33.22	3.23	37.25	59.99	74.00	14.01
4960.00	46.97	AV	V	33.22	3.23	37.25	46.17	54.00	7.83
7440.00	52.85	PK	V	36.34	4.41	37.52	56.08	74.00	17.92
7440.00	38.41	AV	V	36.34	4.41	37.52	41.64	54.00	12.36




Worst plots (GFSK high channel)
Horizontal

Fundamental
Test with Band
Rejection Filter



Vertical

Fundamental Test with Band Rejection Filter



FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2018-12-10	2019-12-10
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	25.5 °C
Relative Humidity:	46 %
ATM Pressure:	100.8 kPa

* *The testing was performed by Carrie He on 2019-01-15.*

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
BDR (GFSK)	Low	2402	1.000	0.68
	Middle	2441	1.000	0.69
	High	2480	1.000	0.68
EDR ($\pi/4$ -DQPSK)	Low	2402	1.004	0.90
	Middle	2441	1.000	0.91
	High	2480	1.000	0.91
EDR (8DPSK)	Low	2402	1.000	0.90
	Middle	2441	1.000	0.90
	High	2480	1.004	0.90


Note: Limit= (2/3) × 20dB bandwidth

BDR Mode (GFSK):




Date: 15.JAN.2019 09:09:12

Middle Channel



Date: 15.JAN.2019 09:11:20


High Channel



Date: 15.JAN.2019 09:14:01


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 15.JAN.2019 09:17:27

Middle Channel



Date: 15.JAN.2019 09:19:47


High Channel



Date: 15.JAN.2019 09:22:27


EDR Mode (8DPSK):

Low Channel




Date: 15.JAN.2019 09:27:47

Middle Channel



Date: 15.JAN.2019 09:30:16

High Channel



Date: 15.JAN.2019 09:33:26

FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2018-12-10	2019-12-10
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.5 °C
Relative Humidity:	46 %
ATM Pressure:	100.8 kPa

* The testing was performed by Carrie He on 2019-01-15.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	1.024
	Middle	2441	1.028
	High	2480	1.024
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	1.356
	Middle	2441	1.360
	High	2480	1.360
EDR Mode (8DPSK)	Low	2402	1.352
	Middle	2441	1.348
	High	2480	1.348


BDR Mode (GFSK):

Low Channel




Date: 15.JAN.2019 09:07:27

Middle Channel



Date: 15.JAN.2019 10:37:45


High Channel



Date: 15.JAN.2019 09:11:55


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 15.JAN.2019 09:14:31

Middle Channel



Date: 15.JAN.2019 09:18:07


High Channel



Date: 15.JAN.2019 09:20:20


EDR Mode (8DPSK):

Low Channel




Date: 15.JAN.2019 09:24:49

Middle Channel



Date: 15.JAN.2019 09:28:21

High Channel



Date: 15.JAN.2019 09:30:49

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2018-12-10	2019-12-10
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.5 °C
Relative Humidity:	46 %
ATM Pressure:	100.8 kPa

* *The testing was performed by Carrie He on 2019-01-15.*

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Number of Hopping Channels




Date: 15.JAN.2019 10:05:07

EDR Mode ($\pi/4$ -DQPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15

Number of Hopping Channels




Date: 15.JAN.2019 10:11:39

EDR Mode (8DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Number of Hopping Channels



Date: 15.JAN.2019 10:22:05

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; the time of single pulses was tested.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2018-12-10	2019-12-10
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.5 °C
Relative Humidity:	46 %
ATM Pressure:	100.8 kPa

* *The testing was performed by Carrie He on 2019-01-15.*

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Middle	0.410	0.131	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s				
DH3	Middle	1.692	0.271	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s				
DH5	Middle	2.970	0.317	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s				

DH1: Middle Channel




Date: 15.JAN.2019 09:47:56

DH3: Middle Channel



Date: 15.JAN.2019 09:48:22

DH5: Middle Channel




Date: 15.JAN.2019 09:48:44

EDR Mode ($\pi/4$ -DQPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
2DH1	Middle	0.410	0.131	0.4	Compliance
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s				
2DH3	Middle	1.668	0.267	0.4	Compliance
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s				
2DH5	Middle	2.970	0.317	0.4	Compliance
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s				

2DH1: Middle Channel




Date: 15.JAN.2019 09:49:43

2DH3: Middle Channel



Date: 15.JAN.2019 09:50:08

2DH5: Middle Channel




Date: 15.JAN.2019 09:50:46

EDR Mode (8DPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
3DH1	Middle	0.392	0.125	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s				
3DH3	Middle	1.692	0.271	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s				
3DH5	Middle	2.960	0.316	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s				

3DH1: Middle Channel




Date: 15.JAN.2019 09:51:24

3DH3: Middle Channel



Date: 15.JAN.2019 09:52:10

3DH5: Middle Channel



Date: 15.JAN.2019 10:23:26

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2018-12-10	2019-12-10
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.5 °C
Relative Humidity:	46 %
ATM Pressure:	100.8 kPa

* *The testing was performed by Carrie He on 2019-01-15.*

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

Mode	Frequency (MHz)	Peak Conducted Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	2402	1.82	21
	2441	1.58	21
	2480	0.97	21
EDR Mode ($\pi/4$ -DQPSK)	2402	3.95	21
	2441	3.74	21
	2480	3.40	21
EDR Mode (8DPSK)	2402	4.17	21
	2441	3.95	21
	2480	3.59	21


Note: The data above was tested in conducted mode.

BDR Mode (GFSK):




Date: 15.JAN.2019 09:08:06

Middle Channel



Date: 15.JAN.2019 09:10:24


High Channel



Date: 15.JAN.2019 09:12:31


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 15.JAN.2019 09:16:19

Middle Channel



Date: 15.JAN.2019 09:19:08


High Channel



Date: 15.JAN.2019 09:24:09


EDR Mode (8DPSK):

Low Channel




Date: 15.JAN.2019 09:26:10

Middle Channel



Date: 15.JAN.2019 09:29:22

High Channel



Date: 15.JAN.2019 09:31:56

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW/ VBW of spectrum analyzer to 100/300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2018-12-10	2019-12-10
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	25.5 °C
Relative Humidity:	46 %
ATM Pressure:	100.8 kPa

* The testing was performed by Carrie He on 2019-01-15.

Test Result: Compliance


Single Channel Mode,
BDR Mode (GFSK):

Band Edge, Left Side



Date: 15.JAN.2019 09:08:29


Band Edge, Right Side



Date: 15.JAN.2019 09:13:00


EDR Mode ($\pi/4$ -DQPSK):

Band Edge, Left Side



Date: 15.JAN.2019 09:16:52


Band Edge, Right Side



Date: 15.JAN.2019 09:21:29


EDR Mode (8DPSK):

Band Edge, Left Side



Date: 15.JAN.2019 09:26:56


Band Edge, Right Side



Date: 15.JAN.2019 09:32:32


*Hopping Mode,
BDR Mode (GFSK):*

Band Edge, Left Side



Date: 15.JAN.2019 09:37:27


Band Edge, Right Side



Date: 15.JAN.2019 09:37:56

EDR Mode ($\pi/4$ -DQPSK):


Band Edge, Left Side



Date: 15.JAN.2019 09:38:51


EDR Mode (8DPSK):

Band Edge, Left Side




Date: 15.JAN.2019 09:39:36

Band Edge, Right Side



Date: 15.JAN.2019 09:40:33

Band Edge, Right Side



Date: 15.JAN.2019 09:41:34

***** END OF REPORT *****