



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15.247

TEST REPORT

For

New Hantat Technology Ltd.

Building 18-19,Zone2,Huaide Cuigang Industrial Park, Fuyong Town, Bao'an District, Shenzhen, China

FCC ID: 2ASCITWS006

Report Type: Original Report	Product Name: Bluetooth Earphone
Report Number:	<u>RDG190730003-00A</u>
Report Date:	<u>2019-09-02</u>
Reviewed By:	Jerry Zhang EMC Manager
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE.....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY.....	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION.....	6
EQUIPMENT MODIFICATIONS.....	6
EUT EXERCISE SOFTWARE.....	6
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS.....	8
SUPPORT CABLE LIST AND DETAILS.....	8
BLOCK DIAGRAM OF TEST SETUP.....	8
SUMMARY OF TEST RESULTS.....	10
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE.....	11
APPLICABLE STANDARD.....	11
FCC §15.203 - ANTENNA REQUIREMENT.....	12
APPLICABLE STANDARD.....	12
ANTENNA INFORMATION AND CONNECTOR CONSTRUCTION.....	12
FCC §15.207 (a)– AC LINE CONDUCTED EMISSIONS.....	13
APPLICABLE STANDARD.....	13
EUT SETUP.....	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE.....	13
CORRECTED AMPLITUDE & MARGIN CALCULATION.....	14
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST DATA.....	14
FCC §15.209, §15.205, §15.247(d) - SPURIOUS EMISSIONS.....	17
APPLICABLE STANDARD.....	17
EUT SETUP.....	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP.....	18
TEST PROCEDURE.....	18
CORRECTED AMPLITUDE & MARGIN CALCULATION.....	18
TEST EQUIPMENT LIST AND DETAILS.....	19
TEST DATA.....	19
FCC §15.247(a) (2) –6 dB EMISSION BANDWIDTH.....	26
APPLICABLE STANDARD.....	26
TEST PROCEDURE.....	26
TEST EQUIPMENT LIST AND DETAILS.....	26
TEST DATA.....	26
FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	31
APPLICABLE STANDARD.....	31
TEST PROCEDURE.....	31

TEST EQUIPMENT LIST AND DETAILS.....31
TEST DATA31

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....33

APPLICABLE STANDARD33
TEST PROCEDURE33
TEST EQUIPMENT LIST AND DETAILS.....33
TEST DATA33

FCC §15.247(e) - POWER SPECTRAL DENSITY36

APPLICABLE STANDARD36
TEST PROCEDURE36
TEST EQUIPMENT LIST AND DETAILS.....36
TEST DATA36

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:	Bluetooth Earphone
EUT Model:	TWS006
Operation Frequency:	2402-2480MHz
Maximum Output Power (Conducted):	-10.63 dBm
Modulation Type:	GFSK
Rated Input Voltage:	DC 3.7V from battery or charging from DC 5V from charger box
Serial Number:	190730004-1(Left Earbud) 190730004-2(Right Earbud) 190730004-3(Charger Box)
EUT Received Date:	2019-08-02

Note: the left Earbud and Right Earbud is identical, RF test only performed at Left Earbud.

Objective

This report is prepared on behalf of *New Hantat Technology Ltd.* in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209, 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15C DSS submittal with FCC ID: 2ASCITWS006

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and KDB 558074 D01 DTS Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404
...
...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software


The software: 'RF_Tool_5.2.1.8' was used during test, which was provided by manufacturer. The maximum power level was configured by the software as below table:

Mode	Channel	Frequency (MHz)	Power level
LE 1Mbps	Low	2402	2
	Middle	2440	2
	High	2480	2
LE 2Mbps	Low	2402	2
	Middle	2440	2
	High	2480	2

The duty cycle as below:


Model	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
1Mbps	2.184	2.524	86.53
2Mbps	1.104	1.884	58.60

1Mbps



Date: 5.AUG.2019 18:06:56

2Mbps



Date: 5.AUG.2019 18:05:27

Local Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
HOFFMANN	Adapter	X-ULTRA	7376088

Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From	To
USB Cable	yes	No	0.4	Adapter	EUT Charger Box

Block Diagram of Test Setup

AC Line Conducted Test:



Radiated Emissions:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
FCC §15.203	Antenna requirement	Compliance
FCC §15.207(a)	AC line conducted emissions	Compliance
FCC §15.205, §15.209, §15.247(d)	Spurious emissions	Compliance
FCC §15.247(a)(2)	6 dB emission bandwidth	Compliance
FCC §15.247(b)(3)	Maximum conducted output power	Compliance
FCC §15.247(d)	100 kHz Bandwidth of frequency band edge	Compliance
FCC §15.247(e)	Power spectral density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The max conducted power including tune-up tolerance is -10 dBm (0.1 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 0.1/5 \cdot (\sqrt{2.480}) = 0.03 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Information And Connector Construction

The EUT has one internal antenna arrangement, fulfill the requirement of this section. Please refer to below information and the EUT photos:

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
Chip	50	0 dBi/2.4~2.5GHz


Result: Compliance.

FCC §15.207 (a)– AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main lisn with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2018-09-05	2019-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
R&S	Two-line V-network	ENV 216	101614	2018-12-10	2019-12-10
R&S	EMI Test Receiver	ESPI	100120	2019-05-09	2020-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	27.1°C
Relative Humidity:	63%
ATM Pressure:	99.5 kPa
Tester:	Sky Lu
Test Date:	2019-08-07

Test Result: Compliance

Test Mode: Charging


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.150000	39.0	9.000	L1	11.2	27.0	66.0
0.259279	21.5	9.000	L1	10.3	40.0	61.5
0.422196	23.7	9.000	L1	9.9	33.7	57.4
0.552321	19.6	9.000	L1	9.8	36.4	56.0
0.847248	18.8	9.000	L1	9.8	37.2	56.0
1.896889	18.4	9.000	L1	9.7	37.6	56.0

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.405722	16.1	9.000	L1	10.0	31.6	47.7
0.563423	16.1	9.000	L1	9.8	29.9	46.0
1.212216	15.6	9.000	L1	9.8	30.4	46.0
1.915858	15.5	9.000	L1	9.7	30.5	46.0
2.268959	14.3	9.000	L1	9.8	31.7	46.0
3.768918	14.8	9.000	L1	9.8	31.2	46.0

AC120 V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.153015	37.0	9.000	N	11.1	28.8	65.8
0.264490	20.1	9.000	N	10.3	41.2	61.3
0.654116	18.4	9.000	N	9.8	37.6	56.0
1.054583	18.8	9.000	N	9.8	37.2	56.0
1.274051	18.5	9.000	N	9.8	37.5	56.0
3.088796	19.1	9.000	N	9.8	36.9	56.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.426418	15.9	9.000	N	9.9	31.4	47.3
0.641227	15.7	9.000	N	9.8	30.3	46.0
1.130656	16.4	9.000	N	9.8	29.6	46.0
1.248947	16.0	9.000	N	9.8	30.0	46.0
3.119684	14.9	9.000	N	9.8	31.1	46.0
3.658074	14.6	9.000	N	9.8	31.4	46.0


FCC §15.209, §15.205, §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission below 1GHz tests were performed in the 10 meters chamber, above 1GHz tests were performed in the 3 meters chamber B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	101121	2019-05-09	2020-05-09
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sunol Sciences	Antenna	JB3	A060611-3	2017-07-21	2020-07-21
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-02	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2018-09-24	2019-09-24
HP	Amplifier	8447F	2443A01912	2018-09-05	2019-09-05
Agilent	Spectrum Analyzer	E4440A	SG43360054	2019-05-09	2020-05-09
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2018-09-05	2019-09-05
MITEQ	Amplifier	AFS42-00101800-25-S-42	2001271	2018-09-05	2019-09-05
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2016-11-18	2019-11-18
Unknown	Coaxial Cable	C-2.4J2.4J-50	C-0700-02	2019-06-16	2020-06-16
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2019-06-16	2020-06-16
E-Microwave	Band-stop Filters	OBSF-2400-2483.5-S	OE01601525	2019-06-16	2020-06-16
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2019-06-16	2020-06-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Test Items	Radiation Below 1GHz	Radiation Above 1GHz
Temperature:	25.5 °C	25.3 °C
Relative Humidity:	59%	52%
ATM Pressure:	100.3 kPa	100.1 kPa
Tester:	Sunny Cen	Lucy Lu
Test Date:	2019-08-07	2019-08-06

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table and plots.


1) 30MHz-1GHz (1Mbps High Channel was the worst):

Horizontal:



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
30.9700	28.22	peak	-8.40	19.82	40.00	20.18
82.3800	30.70	peak	-19.34	11.36	40.00	28.64
162.8900	31.71	peak	-12.88	18.83	43.50	24.67
201.6900	27.78	peak	-13.08	14.70	43.50	28.80
407.3300	33.10	peak	-8.05	25.05	46.00	20.95
421.8800	34.39	peak	-7.94	26.45	46.00	19.55

Vertical:



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
30.9700	28.05	peak	-8.40	19.65	40.00	20.35
133.7900	28.54	peak	-13.13	15.41	43.50	28.09
200.7200	28.17	peak	-12.90	15.27	43.50	28.23
328.7600	27.63	peak	-10.06	17.57	46.00	28.43
520.8200	26.20	peak	-5.36	20.84	46.00	25.16
744.8900	25.46	peak	-1.29	24.17	46.00	21.83

2) 1-25GHz:

1 Mbps:




Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	55.42	PK	H	28.10	1.80	0.00	85.32	N/A	N/A
2402.00	54.82	AV	H	28.10	1.80	0.00	84.72	N/A	N/A
2402.00	49.55	PK	V	28.10	1.80	0.00	79.45	N/A	N/A
2402.00	48.97	AV	V	28.10	1.80	0.00	78.87	N/A	N/A
2390.00	25.31	PK	H	28.08	1.80	0.00	55.19	74.00	18.81
2390.00	14.23	AV	H	28.08	1.80	0.00	44.11	54.00	9.89
4804.00	54.13	PK	H	32.91	3.17	37.20	53.01	74.00	20.99
4804.00	48.49	AV	H	32.91	3.17	37.20	47.37	54.00	6.63
7206.00	48.05	PK	H	35.74	4.82	37.23	51.38	74.00	22.62
7206.00	39.93	AV	H	35.74	4.82	37.23	43.26	54.00	10.74
Middle Channel: 2440 MHz									
2440.00	57.39	PK	H	28.18	1.82	0.00	87.39	N/A	N/A
2440.00	56.73	AV	H	28.18	1.82	0.00	86.73	N/A	N/A
2440.00	51.54	PK	V	28.18	1.82	0.00	81.54	N/A	N/A
2440.00	50.94	AV	V	28.18	1.82	0.00	80.94	N/A	N/A
4880.00	56.01	PK	H	33.06	3.27	37.21	55.13	74.00	18.87
4880.00	51.25	AV	H	33.06	3.27	37.21	50.37	54.00	3.63
7320.00	47.57	PK	H	36.03	4.62	37.37	50.85	74.00	23.15
7320.00	36.54	AV	H	36.03	4.62	37.37	39.82	54.00	14.18
High Channel: 2480 MHz									
2480.00	59.33	PK	H	28.26	1.84	0.00	89.43	N/A	N/A
2480.00	58.46	AV	H	28.26	1.84	0.00	88.56	N/A	N/A
2480.00	54.49	PK	V	28.26	1.84	0.00	84.59	N/A	N/A
2480.00	53.68	AV	V	28.26	1.84	0.00	83.78	N/A	N/A
2483.50	24.88	PK	H	28.27	1.84	0.00	54.99	74.00	19.01
2483.50	13.81	AV	H	28.27	1.84	0.00	43.92	54.00	10.08
4960.00	57.93	PK	H	33.22	3.23	37.25	57.13	74.00	16.87
4960.00	53.70	AV	H	33.22	3.23	37.25	52.90	54.00	1.10
7440.00	46.54	PK	H	36.34	4.41	37.52	49.77	74.00	24.23
7440.00	34.11	AV	H	36.34	4.41	37.52	37.34	54.00	16.66

2Mbps:




Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	55.63	PK	H	28.10	1.80	0.00	85.53	N/A	N/A
2402.00	53.86	AV	H	28.10	1.80	0.00	83.76	N/A	N/A
2402.00	49.56	PK	V	28.10	1.80	0.00	79.46	N/A	N/A
2402.00	47.79	AV	V	28.10	1.80	0.00	77.69	N/A	N/A
2390.00	24.56	PK	H	28.08	1.80	0.00	54.44	74.00	19.56
2390.00	13.58	AV	H	28.08	1.80	0.00	43.46	54.00	10.54
4804.00	54.55	PK	H	32.91	3.17	37.20	53.43	74.00	20.57
4804.00	47.43	AV	H	32.91	3.17	37.20	46.31	54.00	7.69
7206.00	49.55	PK	H	35.74	4.82	37.23	52.88	74.00	21.12
7206.00	37.34	AV	H	35.74	4.82	37.23	40.67	54.00	13.33
Middle Channel: 2440 MHz									
2440.00	57.35	PK	H	28.18	1.82	0.00	87.35	N/A	N/A
2440.00	55.64	AV	H	28.18	1.82	0.00	85.64	N/A	N/A
2440.00	50.47	PK	V	28.18	1.82	0.00	80.47	N/A	N/A
2440.00	48.94	AV	V	28.18	1.82	0.00	78.94	N/A	N/A
4880.00	56.12	PK	H	33.06	3.27	37.21	55.24	74.00	18.76
4880.00	50.07	AV	H	33.06	3.27	37.21	49.19	54.00	4.81
7320.00	48.51	PK	H	36.03	4.62	37.37	51.79	74.00	22.21
7320.00	36.54	AV	H	36.03	4.62	37.37	39.82	54.00	14.18
High Channel: 2480 MHz									
2480.00	59.44	PK	H	28.26	1.84	0.00	89.54	N/A	N/A
2480.00	57.74	AV	H	28.26	1.84	0.00	87.84	N/A	N/A
2480.00	52.12	PK	V	28.26	1.84	0.00	82.22	N/A	N/A
2480.00	50.34	AV	V	28.26	1.84	0.00	80.44	N/A	N/A
2483.50	25.88	PK	H	28.27	1.84	0.00	55.99	74.00	18.01
2483.50	13.45	AV	H	28.27	1.84	0.00	43.56	54.00	10.44
4960.00	57.67	PK	H	33.22	3.23	37.25	56.87	74.00	17.13
4960.00	51.96	AV	H	33.22	3.23	37.25	51.16	54.00	2.84
7440.00	46.78	PK	H	36.34	4.41	37.52	50.01	74.00	23.99
7440.00	35.79	AV	H	36.34	4.41	37.52	39.02	54.00	14.98

Worst plots (1Mbps High Channel) Horizontal

Fundamental
Test with Band
Rejection Filter



Vertical



FCC §15.247(a) (2) –6 dB EMISSION BANDWIDTH


Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0013	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	29.9°C
Relative Humidity:	57%
ATM Pressure:	100.4 kPa
Tester:	Lily Xie
Test Date:	2019-08-05


Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table and plots.

Mode	Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
LE 1Mbps	Low	2402	0.660	≥0.5
	Middle	2440	0.664	≥0.5
	High	2480	0.660	≥0.5
LE 2Mbps	Low	2402	1.120	≥0.5
	Middle	2440	1.112	≥0.5
	High	2480	1.120	≥0.5


1 Mbps

Low Channel




Date: 5.AUG.2019 17:47:03

Middle Channel




High Channel




2Mbps:

Low Channel




Date: 5.AUG.2019 17:57:38

Middle Channel



Date: 5.AUG.2019 17:53:24

High Channel



Date: 5.AUG.2019 17:59:01

FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-SJ00-0013	C0010/01	Each time	N/A
Agilent	USB Wideband Power Sensor	U2022XA	MY5417006	2018-12-10	2019-12-10

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	29.9 °C
Relative Humidity:	57 %
ATM Pressure:	99.5 kPa
Tester:	Chris Mo
Test Date:	2019-08-07

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table.

Mode	Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)	Limit (dBm)
LE 1Mbps	Low	2402	-10.63	30
	Middle	2440	-12.32	30
	High	2480	-14.26	30
LE 2Mbps	Low	2402	-10.65	30
	Middle	2440	-12.43	30
	High	2480	-14.28	30

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

According to FCC§15.247(d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0013	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	27.5°C
Relative Humidity:	58%
ATM Pressure:	100.5 kPa
Tester:	Lily Xie
Test Date:	2019-09-02

Test mode: Transmitting


Test Result: Compliance. Please refer to following plots.

1Mbps:

Band Edge, Left Side



Band Edge, Right Side



2Mbps:

Band Edge, Left Side



Band Edge, Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

According to FCC§15.247(e):For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0013	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	29.9°C
Relative Humidity:	57%
ATM Pressure:	100.4 kPa
Tester:	Lily Xie
Test Date:	2019-08-05


Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table and plots

Mode	Channel	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
LE 1Mbps	Low	2402	-26.59	≤8
	Middle	2440	-29.13	≤8
	High	2480	-27.17	≤8
LE 2Mbps	Low	2402	-28.30	≤8
	Middle	2440	-25.10	≤8
	High	2480	-25.41	≤8


1Mbps:

Power Spectral Density, Low Channel




Date: 5.AUG.2019 17:47:32

Power Spectral Density, Middle Channel




Power Spectral Density, High Channel




2Mbps:


Power Spectral Density, Low Channel



Power Spectral Density, Middle Channel



Power Spectral Density, High Channel



Date: 5.AUG.2019 18:00:26

***** END OF REPORT *****