



HAC TEST REPORT

Applicant TAKUMI JAPAN Corp.

FCC ID 2ASCR-KAZUNA

Product 4G basic phone

Brand KAZUNA

Model KAZ-F119, KAZ-F019

Report No. R1901A0035-H2

Issue Date March 28, 2019

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **ANSI C63.19-2011**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Songyan Fan *Guangchang Fan*

Approved by: Songyan Fan

Approved by: Guangchang Fan

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



Table of Contents

| | | |
|-------|---|----|
| 1 | Test Laboratory..... | 3 |
| 1.1 | Notes of the Test Report | 3 |
| 1.2 | Test facility | 3 |
| 1.3 | Testing Location..... | 4 |
| 1.4 | Laboratory Environment..... | 4 |
| 2 | Statement of Compliance | 5 |
| 3 | Description of Equipment under Test..... | 6 |
| 4 | Test Specification and Operational Conditions | 8 |
| 4.1 | Test Specification..... | 8 |
| 5 | Test Information..... | 9 |
| 5.1 | Operational Conditions during Test..... | 9 |
| 5.1.1 | General Description of Test Procedures | 9 |
| 5.2 | T-Coil Measurements System Configuration..... | 9 |
| 5.2.1 | T-coil Measurement Set-up | 9 |
| 5.2.2 | AM1D Probe..... | 12 |
| 5.2.3 | Audio Magnetic Measurement Instrument (AMMI)..... | 13 |
| 5.2.4 | Helmholtz Calibration Coil (AMCC) | 14 |
| 5.2.5 | Test Arch Phantom & Phone Positioner..... | 14 |
| 5.3 | T-Coil measurement points and reference plane | 15 |
| 5.4 | T-Coil Test Procedueres | 16 |
| 6 | T-Coil Performance Requirements | 18 |
| 6.1 | T-Coil coupling field intensity..... | 18 |
| 6.2 | Frequency response | 18 |
| 6.3 | Signal quality..... | 19 |
| 7 | T-Coil testing for GSM | 20 |
| 8 | T-Coil testing for WCDMA | 20 |
| 9 | T-Coil testing for VoLTE..... | 21 |
| 10 | T-Coil testing for VoWIFI | 23 |
| 11 | Summary Test Results..... | 25 |
| 12 | Measurement Uncertainty | 27 |
| 13 | Main Test Instruments | 28 |
| | ANNEX A: Test Layout..... | 29 |
| | ANNEX B: Graph Results | 30 |
| | ANNEX C: Probe Calibration Certificate..... | 57 |
| | ANNEX D: DAE4 Calibration Certificate | 60 |
| | ANNEX E: The EUT Appearances and Test Configuration | 65 |



1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd**. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test facility

CNAS (accreditation number: L2264)

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

IC (recognition number is 8510A)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.



1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

1.4 Laboratory Environment

| | |
|---|--------------------------|
| Temperature | Min. = 18°C, Max. = 28°C |
| Relative humidity | Min. = 0%, Max. = 80% |
| Ground system resistance | < 0.5 Ω |
| Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards. | |

2 Statement of Compliance

Table 2.1: T-Coil signal quality categories of each tested Mode

| Band | Category |
|------------------------------------|----------|
| GSM 850 | T4 |
| GSM 1900 | T4 |
| WCDMA Band II | T4 |
| WCDMA Band V | T4 |
| LTE Band 2 | T4 |
| LTE Band 4 | T4 |
| LTE Band 5 | T4 |
| LTE Band 13 | T4 |
| WIFI2.4G | T4 |
| Date of Testing: February 13, 2019 | |



3 Description of Equipment under Test

Client Information

| | |
|-----------------------------|--|
| Applicant | TAKUMI JAPAN Corp. |
| Applicant address | 3-9-3 Uchiyama building 7F Nishishinbashi, Minato-ku Tokyo JAPAN 105-0003 |
| Manufacturer | TAKUMI JAPAN Corp. |
| Manufacturer address | 3-9-3 Uchiyama building 7F Nishishinbashi, Minato-ku Tokyo JAPAN 105-0003 |

General Technologies

| | | |
|--------------------------------------|--|-----------------|
| Device Type: | Portable Device | |
| EUT Stage | Production Unit | |
| Model | KAZ-F119,KAZ-F019 | |
| IMEI: | IMEI 1:354834100002819 IMEI 2: 354834100002157 | |
| Hardware Version | F1_MB_1V2 | |
| Software Version | R013 | |
| Antenna Type | Internal Antenna | |
| Power Class: | GSM 850: 4 GSM 1900: 1 WCDMA Band II /V: 3 LTE FDD 2/4/5/13:3 | |
| Power Level | GSM 850: level 5 GSM 1900: level 0 WCDMA Band II /V: All up bits LTE FDD 2/4/5/13:max power | |
| Test Modulation: | (GSM)GMSK; (WCDMA) QPSK; (LTE)QPSK, 16QAM; | |
| Operating Frequency Range(s): | Mode | Tx (MHz) |
| | GSM 850 | 824 ~ 849 |
| | GSM 1900 | 1850 ~ 1910 |
| | WCDMA Band II | 1850 ~ 1910 |
| | WCDMA Band V | 824 ~ 849 |
| | LTE Band 2 | 1850 ~ 1910 |
| | LTE Band 4 | 1710 ~ 1755 |
| | LTE Band 5 | 824 ~ 849 |
| | LTE Band 13 | 777~787 |
| | Wi-Fi 2.4G | 2412 ~ 2462 |
| | BT | 2402 ~2480 |
| Accessory Equipment | | |
| Adapter | Manufacturer: Dongguan Aohai Technology Co., Ltd. Model: A8-501000 | |



Battery

Manufacturer: ZHONGSHAN TIANMAO BATTERY CO.,LTD
Model: BP1578

| Air-Interface | Band (MHz) | Type | ANSI C63.19 tested | Simultaneous Transmissions | Voice over Digital Transport OTT Capability | Name of Voice Service | Power Reduction |
|----------------|------------|------|--------------------|----------------------------|---|-----------------------|-----------------|
| GSM | 850 | VO | Yes | Yes BT or Wi-Fi | N/A | # | No |
| | 1900 | | | | | | |
| | GPRS/EGPRS | DT | No | | No | | |
| WCDMA | Band II | VO | Yes | Yes BT or Wi-Fi | N/A | # | No |
| | Band V | | | | | | |
| | HSPA | DT | No | | No | | |
| LTE | Band 2 | VD | Yes | Yes BT or Wi-Fi | No | Yes## | No |
| | Band 4 | | | | | | |
| | Band 5 | | | | | | |
| | Band 13 | | | | | | |
| Wi-Fi | 2450 | VD | Yes | Yes GSM, WCDMA, LTE | No | Wi-Fi Calling | No |
| Bluetooth (BT) | 2450 | DT | No | Yes GSM, WCDMA, LTE | N/A | NA | No |

VO= legacy Cellular Voice Service from Table 7.1 in 7.4.2.1 of ANSI C63.19-2011

VD= IP voice service over digital transport.

DT= Digital Transport only (no voice)

Ref Lev in accordance with 7.4.2.1 of ANSI C63.19-2011

Ref Lev in accordance with the July 2012 VoLTE interpretation.



4 Test Specification and Operational Conditions

4.1 Test Specification

The tests documented in this report were performed in accordance with the following:

FCC CFR47 Part 20.19

ANSI C63.19-2011

285076 D01 HAC Guidance v05

285076 D02 T-Coil Testing v03

5 Test Information

5.1 Operational Conditions during Test

5.1.1 General Description of Test Procedures

The phone was tested in all normal configurations for the ear use. The EUT is mounted in the device holder equivalent as for classic dosimeter measurements. The acoustic output of the EUT shall coincide with the center point of the area formed by the dielectric wire and the middle bar of the arch's top frame. The EUT shall be moved vertically upwards until it touches the frame. The fine adjustment is possible by sliding the complete EUT holder on the yellow base plate of the Test Arch phantom. During the test, the EUT is selected on T-Coil mode, the LCD backlight is turn off and volume is adjusted to maximum level.

A communication link is set up with a System Simulator (SS) by RF cable, and a call is established. The Absolute Radio Frequency Channel Number (ARFCN) is allocated to Ch Middle respectively in the case of Band. T-Coil configurations is measured using System Simulator (SS) of CMU200/ CMW 500, at the same time the EUT shall be operated at its maximum RF output power setting.

5.2 T-Coil Measurements System Configuration

5.2.1 T-coil Measurement Set-up

These measurements are performed using the DASY5 automated dosimetric assessment system. It is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland. It consists of high precision robotics system (Stäubli), robot controller, Intel Core computer, near-field probe, probe alignment sensor. The robot is a six-axis industrial robot performing precise movements. Cell controller systems contain the power supply, robot controller, teach pendant (Joystick) and remote control, and are used to drive the robot motors. The Stäubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification; signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.




Figure 1T-Coil Test Measurement Set-up

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.




Figure 2T-Coil Test Measurement Set-up

5.2.2 AM1D Probe

The AM1D probe is an active probe with a single sensor. It is fully RF-shielded and has a rounded tip 6mm in diameter incorporating a pickup coil with its center offset 3mm from the tip and the sides. The symmetric signal preamplifier in the probe is fed via the shielded symmetric output cable from the AMMI with a 48V "phantom" voltage supply. The 7-pin connector on the back in the axis of the probe does not carry any signals. It is mounted to the DAE for the correct orientation of the sensor. If the probe axis is tilted 54.7 degree from the vertical, the sensor is approximately vertical when the signal connector is at the underside of the probe (cable hanging downwards).

Specification

| | |
|-----------------|--|
| frequency range | 0.1 - 20 kHz (RF sensitivity <-100 dB, fully RF shielded) |
| sensitivity | <-50 dB A/m @ 1 kHz |
| pre-amplifier | 40 dB, symmetric |
| dimensions | tip diameter / length: 6 / 290 mm, sensor according to ANSI-C63.19 |



Figure 3AM1D Probe

5.2.3 Audio Magnetic Measurement Instrument (AMMI)

The Audio Magnetic Measuring Instrument (AMMI) is a desktop 19-inch unit containing a sampling unit, a waveform generator for test and calibration signals, and a USB interface.



Figure 4AMMI front panel

Port description:

| | |
|------------------|--|
| Audio Out | BNC, audio signal to the base station simulator, for >500Ohm load |
| Coil Out | BNC, test and calibration signal to the AMCC (top connector), for 50Ohm load |
| Coil In | XLR, monitor signal from the AMCC BNO connector, 600 Ohm |
| Probe In | XLR, probe signal and phantom supply to the probe Lemo connector |



Figure 5AMMI rear side

| | |
|-------------------------------|---|
| Sampling rate | 48 kHz / 24 bit |
| Dynamic range | 85 dB |
| Test signal generation | User selectable and predefined (vis PC) |
| Calibration | Auto-calibration / full system calibration using AMCC with monitor output |
| Dimensions | 482 x 65 x 270 mm |

5.2.4 Helmholtz Calibration Coil (AMCC)

The Audio Magnetic Calibration coil is a Helmholtz Coil designed for calibration of the AM1D probe. The two horizontal coils generate a homogeneous magnetic field in the z direction. The DC input resistance is adjusted by a series resistor to approximately 50Ohm, and a shunt resistor of 10Ohm permits monitoring the current with a scale of 1:10




Figure 6 AMCC

Port description:

| Signal | Connector | Resistance |
|--------------|-----------|--|
| Coil In | BNC | Typically 50Ohm |
| Coil Monitor | BNO | 10Ohm $\pm 1\%$ (100mV corresponding to 1 A/m) |

Specification:

| | |
|------------|--|
| Dimensions | 370 x 370 x 196 mm, according to ANSI-C63.19 |
|------------|--|

5.2.5 Test Arch Phantom & Phone Positioner

The Test Arch phantom should be positioned horizontally on a stable surface. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. It enables easy and well defined positioning of the phone and validation dipoles as well as simple teaching of the robot (Dimensions: 370 x 370 x 370 mm). The Device reference point is set for the EUT at 6.3 mm, the Grid reference point is on the upper surface at the origin of the coordinates, and the “user point \Height Check 0.5 mm” is 0.5mm above the center, allowing verification of the gap of 0.5mm while the probe is positioned there.

The Phone Positioner supports accurate and reliable positioning of any phone with effect on near field $<\pm 0.5$ dB.



Figure 7T-coil Phantom & Device Holder

5.3 T-Coil measurement points and reference plane

The following figure illustrates the standard probe orientations. Position 1 is the perpendicular orientation of the probe coil; orientation 2 is the transverse orientation. The space between the measurement positions is not fixed. It is recommended that a scan of the WD be performed for each probe coil orientation and that the maximum level recorded be used as the reading for that orientation of the probe coil.

- 1) The reference plane is the planar area that contains the highest point in the area of the phone that normally rests against the user's ear. It is parallel to the centerline of the receiver area of the phone and is defined by the points of the receiver-end of the EUT handset, which, in normal handset use, rest against the ear.
- 2) The measurement plane is parallel to, and 10 mm in front of, the reference plane.
- 3) The reference axis is normal to the reference plane and passes through the center of the receiver speaker section (or the center of the hole array); or may be centered on a secondary inductive source. The actual location of the measurement point shall be noted in the test report as the measurement reference point.
- 4) The measurement points may be located where the axial and radial field intensity measurements are optimum with regard to the requirements. However, the measurement points should be near the acoustic output of the EUT and shall be located in the same half of the phone as the EUT receiver. In a EUT handset with a centered receiver and a circularly symmetrical magnetic field, the measurement axis and the reference axis would coincide.

- 5) The relative spacing of each measurement orientation is not fixed. The axial and two radial orientations should be chosen to select the optimal position.
- 6) The measurement point for the axial position is located 10 mm from the reference plane on the measurement axis.
- 7) The actual location of the measurement point shall be noted in test reports and designated as the measurement reference point.




Figure 8Axis and planes for EUT audio frequency magnetic field measurements

5.4 T-Coil Test Procedures

The following illustrate a typical test scan over a wireless communications device:

- 1) Geometry and signal check: system probe alignment, proper operation of the field probe, probe measurement system, other instrumentation, and the positioning system was confirmed. A surface calibration was performed before each setup change to ensure repeatable spacing and proper maintenance of the measurement plane using the test Arch.
- 2) Set the reference drive level of signal voice defined in C63.19 per 7.4.2.1.
- 3) The ambient and test system background noise (dB A/m) was measured as well as ABM2 over the full measurement. The maximum noise level must be at least 10dB below the limit of C63.19 per 8.3.2.
- 4) The EUT was positioned in its intended test position, acoustic output point of the device perpendicular to the field probe.
- 5) The EUT operation for maximum rated RF output power was configured and connected by using of coaxial cable connection to the base station simulator at the test channel and other normal operating parameters as intended for the test. The battery was ensured to be fully charged before each test. The center sub-grid was centered over the center of the acoustic output (also audio band magnetic output, if applicable). The EUT audio output was positioned tangent (as physically possible) to the measurement plane.
- 6) The EUT's RF emission field was eliminated from T-coil results by using a well RF-shielding of the probe, AM1D, and by using of coaxial cable connection to a Base Station Simulator. One test channel was pre-measurement to avoid this possibility.
- 7) Determined the optimal measurement locations for the EUT by following the three steps, coarse



resolution scan, fine resolution scans, and point measurement, as described in C63.19 per 7.4.4.2. At each measurement locations, samples in the measurement window duration were evaluated to get ABM1 and the signal spectrum. The noise measurement was performed after the scan with the signal, the same happened, just with the voice signal switched off. The ABM2 was calculated from this second scan.

- 8) All results resulting from a measurement point in a T-Coil job were calculated from the signal samples during this window interval. ABM values were averaged over the sequence of these samples.
- 9) At an optimal point measurement, the SNR (ABM1/ABM2) was calculated for axial,radial transverse and radial longitudinal orientation, and the frequency response was measured in axial axis.
- 10) Corrected for the frequency response after the EUT measurement since the DASY5 system had known the spectrum of the input signal by using a reference job.
- 11) In SEMCAD postprocessing, the spectral points are in addition scaled with the high-pass (half-band) and the A-weighting, bandwidth compensated factor (BWC) and those results are final as shown in this report.

6 T-Coil Performance Requirements


In order to be rated for T-Coil use, a EUT shall meet the requirements for signal level and signal quality contained in this part.

6.1 T-Coil coupling field intensity

When measured as specified in ANSI C63.19, the T-Coil signal shall be ≥ -18 dB (A/m) at 1 kHz, in a 1/3 octave band filter for all orientations.


6.2 Frequency response

The frequency response of the axial component of the magnetic field, measured in 1/3 octave bands, shall follow the response curve specified in this sub-clause, over the frequency range 300 Hz to 3000 Hz. The following figures provide the boundaries for the specified frequency. These response curves are for true field strength measurements of the T-Coil signal. Thus the 6 dB/octave probe response has been corrected from the raw readings.



NOTE—Frequency response is between 300 Hz and 3000 Hz.

Figure 9 Magnetic field frequency response for EUTs with a field ≤ -15 dB (A/m) at 1 kHz



NOTE—Frequency response is between 300 Hz and 3000 Hz.

Figure 10Magnetic field frequency response for EUTs with a field that exceeds -15 dB(A/m) at 1 kHz

6.3 Signal quality

This part provides the signal quality requirement for the intended T-Coil signal from a EUT. Only the RF immunity of the hearing aid is measured in T-Coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. So, the only criteria that can be measured is the RF immunity in T-Coil mode. This is measured using the same procedure as for the audio coupling mode and at the same levels.

The worst signal quality of the two T-Coil signal measurements shall be used to determine the T-Coil mode category per Table 1

Table 1:T-Coil signal quality categories

| Category | Telephone parameters WD signal quality [(signal + noise) – to – noise ratio in decibels] |
|-------------|--|
| Category T1 | 0 dB to 10 dB |
| Category T2 | 10 dB to 20 dB |
| Category T3 | 20 dB to 30 dB |
| Category T4 | > 30 dB |

7 T-Coil testing for GSM

1. Codec investigation

An investigation was performed to determine the audio codec to be used for testing by SNR comparison. The FR V1 setting was used for the testing as the worst-case codec.

| Codec Investigation - GSM | | | | | |
|---------------------------|---------------|--------|-------------|---------|---------|
| Codec Setting | FR V1 | HR V1 | Orientation | Band | Channel |
| ABM1 (dBA/m) | -4.71 | -3.69 | z (Axial): | GSM 850 | 190 |
| ABM2 (dBA/m) | -47.12 | -46.11 | | | |
| Frequency Response | Pass | Pass | | | |
| Signal Quality (dB) | 42.41 | 42.42 | | | |

2. Air Interface Investigation

Using the worst case codec to test low/middle/high channels in each band.

8 T-Coil testing for WCDMA

1. Codec investigation

An investigation was performed to determine the audio codec to be used for testing by SNR comparison. The AMR 12.2kbps setting was used for the testing as the worst-case codec.

| Codec Investigation - WCDMA | | | | | | |
|-----------------------------|---------------|--------------|--------------|-------------|---------|---------|
| Codec Setting | AMR 12.2kbps | AMR 7.95kbps | AMR 4.75kbps | Orientation | Band | Channel |
| ABM1 (dBA/m) | -4.11 | -3.56 | -3.21 | z (Axial): | Band II | 9400 |
| ABM2 (dBA/m) | -52.21 | -52.64 | -52.21 | | | |
| Frequency Response | Pass | Pass | Pass | | | |
| Signal Quality (dB) | 48.1 | 49.08 | 49 | | | |

2. Air Interface Investigation


Using the worst case codec to test low/middle/high channels in each band.

9 T-Coil testing for VoLTE

I. Test setup for VoLTE over IMS T-coil Testing

1. Test setup

The general test setup used for VoLTE over IMS is shown below. The call box used when performing VoLTE over IMS T-coil measurement is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.



2. Audio level setting

According to the July 2012 interpretations by the C63 Committee regarding the appropriate audio levels to be used for VoLTE over IMS T-coil testing, -16dBm0 shall be used for the nomal speech input level. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -16dBm0 speech input level to the DUT for the VoLTE over IMS connection.

II. DUT configuration for VoLTE over IMS T-coil Testing

1. Radio configuration investigation

An investigation was performed to determine the modulation and RB configuration to be used for testing. QPSK, 1RB, 0RB offset was used for the testing as the worst-case configuration.

Radio Configuration Investigation

| VOLTE over IMS SNNR by Radio Configuration | | | | | | | | |
|--|---------|-----------------|------------|---------|-----------|----------------|----------------|---------------------|
| Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | ABM1 [dB(A/m)] | ABM2 [dB(A/m)] | Signal Quality [dB] |
| 1880 | 18900 | 20 | QPSK | 1 | 0 | -3.1 | -49.91 | 46.81 |
| 1880 | 18900 | 20 | QPSK | 1 | 50 | -1.79 | -49.57 | 47.78 |
| 1880 | 18900 | 20 | QPSK | 1 | 99 | -1.85 | -49.06 | 47.21 |
| 1880 | 18900 | 20 | QPSK | 50 | 0 | -1.31 | -49.64 | 48.33 |



| | | | | | | | | |
|------|-------|----|-------|-----|----|-------|--------|-------|
| 1880 | 18900 | 20 | QPSK | 50 | 25 | -1.54 | -49.18 | 47.64 |
| 1880 | 18900 | 20 | QPSK | 50 | 50 | -2.81 | -50.68 | 47.87 |
| 1880 | 18900 | 20 | QPSK | 100 | 0 | -1.64 | -49.33 | 47.69 |
| 1880 | 18900 | 20 | 16QAM | 1 | 0 | -1.87 | -49.34 | 47.47 |
| 1880 | 18900 | 20 | 16QAM | 1 | 50 | -1.35 | -49.86 | 48.51 |
| 1880 | 18900 | 20 | 16QAM | 1 | 99 | -2.47 | -50.92 | 48.45 |
| 1880 | 18900 | 20 | 16QAM | 50 | 0 | -1.67 | -48.79 | 47.12 |
| 1880 | 18900 | 20 | 16QAM | 50 | 25 | -2.54 | -49.81 | 47.27 |
| 1880 | 18900 | 20 | 16QAM | 50 | 50 | -2.61 | -50.74 | 48.13 |
| 1880 | 18900 | 20 | 16QAM | 100 | 0 | -1.98 | -50.43 | 48.45 |

2. Codec investigation

An investigation was performed to determine the audio codec to be used for testing. The WB AMR 6.60kbps setting was used for the audio codec on the CMW500 for VoLTE over IMS T-coil testing.

| AMR Codec Investigation - VoLTE over IMS | | | | | | | |
|--|---------------------|---------------------|---------------------|---------------------|-------------|-----------------|---------|
| Codec Setting | WB AMR 23.85kbps | WB AMR 6.60 kbps | NB AMR 12.2 kbps | NB AMR 4.75 kbps | Orientation | Band /BW | Channel |
| ABM1 (dB/m) | -3.16 | -4.76 | -4.35 | -2.57 | z (Axial): | Band2/ 20MHz | 18900 |
| ABM2 (dB/m) | -49.94 | -50 | -50.02 | -47.99 | | | |
| Frequency Response | Pass | Pass | Pass | Pass | | | |
| Signal Quality (dB) | 46.78 | 45.24 | 45.67 | 45.42 | | | |

| EVS Codec Investigation - VoLTE over IMS | | | | | | | |
|--|---------------------|---------------------|---------------------|---------------------|-------------|-----------------|---------|
| Codec Setting | WB AMR 23.85kbps | WB AMR 6.60 kbps | NB AMR 12.2 kbps | NB AMR 4.75 kbps | Orientation | Band /BW | Channel |
| ABM1 (dB/m) | -3.38 | -3.91 | -2.67 | -4.15 | z (Axial): | Band2/ 20MHz | 18900 |
| ABM2 (dB/m) | -50.02 | -51.38 | -49.48 | -51.62 | | | |
| Frequency Response | Pass | Pass | Pass | Pass | | | |
| Signal Quality (dB) | 46.64 | 47.47 | 46.81 | 47.47 | | | |

3. Air Interface Investigation

The worst case band for each probe orientation is additionally tested on all bandwidth combination. LTE B2 at 20MHz is the worst case for the Axial and Radial probe orientation.

10 T-Coil testing for VoWIFI

I. Test setup for VoWIFI over IMS T-coil Testing

1. Test setup

The general test setup used for VoWIFI over IMS, or CMRS WIFI calling, is shown below. The call box used when performing VoWIFI over IMS T-coil measurement is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.

2. Audio level setting

According to the KDB285076 D02, regarding the appropriate audio levels to be used for WIFI over IMS T-coil testing, -20dBm0 shall be used for the normal speech input level. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the VoWIFI over IMS connection.

II. DUT configuration for VoWIFI over IMS T-coil Testing

1. Radio configuration investigation

Investigate the lowest and highest data rates and modulation to determine worst radio configuration to be used for testing by SNR comparison.

| 802.11b Radio configuration investigation | | | | | |
|--|---------|------------------|----------------|----------------|---------------------|
| Mode | Channel | Data Rate [Mbps] | ABM1 [dB(A/m)] | ABM2 [dB(A/m)] | Signal Quality [dB] |
| 802.11b | 6 | 1 | -6.67 | -51 | 44.33 |
| 802.11b | 6 | 11 | -6.74 | -52.59 | 45.85 |
| 802.11g Radio configuration investigation | | | | | |
| Mode | Channel | Data Rate [Mbps] | ABM1 [dB(A/m)] | ABM2 [dB(A/m)] | Signal Quality [dB] |
| 802.11g | 6 | 6 | -5.23 | -52.87 | 47.64 |
| 802.11g | 6 | 54 | -6.58 | -52.74 | 46.16 |
| 802.11n HT20 Radio configuration investigation | | | | | |
| Mode | Channel | Data Rate [Mbps] | ABM1 [dB(A/m)] | ABM2 [dB(A/m)] | Signal Quality [dB] |
| 802.11n HT20 | 6 | MCS0 | -6.62 | -52.74 | 46.12 |
| 802.11n HT20 | 6 | MCS7 | -6.37 | -52.08 | 45.71 |
| 802.11n HT40 Radio configuration investigation | | | | | |
| Mode | Channel | Data Rate [Mbps] | ABM1 [dB(A/m)] | ABM2 [dB(A/m)] | Signal Quality [dB] |
| 802.11n HT40 | 6 | MCS0 | -6.94 | -51.51 | 44.57 |
| 802.11n HT40 | 6 | MCS7 | -6.62 | -52.74 | 46.12 |



2. Codec investigation

Determine the worst-case codec by SNR comparison.

The WB AMR 6.60kbps setting was used for the audio codec on the CMW500 for VoWIFI over IMS T-coil testing.

| AMR Codec Investigation - VoWIFI over IMS | | | | | | | | |
|---|---------------------|---------------------|---------------------|---------------------|-------------|--------|----------|---------|
| Codec Setting | WB AMR 23.85kbps | WB AMR 6.60 kbps | NB AMR 12.2 kbps | NB AMR 4.75 kbps | Orientation | Band | Standard | Channel |
| ABM1 (dBA/m) | -5.87 | -6.07 | -5.09 | -5.64 | z (Axial): | 2.4GHz | 802.11b | 6 |
| ABM2 (dBA/m) | -51.2 | -50.11 | -50.71 | -51.25 | | | | |
| Frequency Response | Pass | Pass | Pass | Pass | | | | |
| Signal Quality (dB) | 45.33 | 44.04 | 45.62 | 45.61 | | | | |

| EVS Codec Investigation - VoWIFI over IMS | | | | | | | | |
|---|---------------------|---------------------|---------------------|---------------------|-------------|--------|----------|---------|
| Codec Setting | WB AMR 23.85kbps | WB AMR 6.60 kbps | NB AMR 12.2 kbps | NB AMR 4.75 kbps | Orientation | Band | Standard | Channel |
| ABM1 (dBA/m) | -5.99 | -6.41 | -5.67 | -5.79 | z (Axial): | 2.4GHz | 802.11b | 6 |
| ABM2 (dBA/m) | -51.11 | -50.52 | -50.69 | -50.71 | | | | |
| Frequency Response | Pass | Pass | Pass | Pass | | | | |
| Signal Quality (dB) | 45.12 | 44.11 | 45.02 | 44.92 | | | | |

3. Air Interface Investigation

Using the worst case codec to proceed T-coil test of worst case mode for axial and radial orientations.
(802.11b is the worst case mode)



11 Summary Test Results

| Band | Channel /Frequency (MHz) | Probe Orientation | ABM1 [dB (A/m)] | ABM2 [dB (A/m)] | ABM SNR (dB) | Freq. Resp. Diff(dB) | Frequency Response | T-Rating | Plot No. |
|------------------------------|--------------------------|-------------------|-----------------|-----------------|--------------|----------------------|--------------------|----------|----------|
| GSM 850 Voice Coder | 190/836.6 | y (Radial): | -12.11 | -53.42 | 41.31 | / | / | T4 | 1 |
| | | z (Axial): | -4.46 | -47.01 | 42.55 | 1.41 | Pass | T4 | 2 |
| GSM 1900 Voice Coder | 661/1880 | y (Radial): | -12.39 | -53.40 | 41.01 | / | / | T4 | 3 |
| | | z (Axial): | -4.46 | -50.04 | 45.58 | 1.29 | Pass | T4 | 4 |
| WCDMA Band II Voice Coder | 9400/1880 | y (Radial): | -10.47 | -47.56 | 37.09 | / | / | T4 | 5 |
| | | z (Axial): | -4.21 | -48.14 | 43.93 | 1.56 | Pass | T4 | 6 |
| WCDMA Band V Voice Coder | 4183/836.6 | y (Radial): | -12.33 | -53.62 | 41.29 | / | / | T4 | 7 |
| | | z (Axial): | -4.33 | -53.01 | 48.68 | 0.32 | Pass | T4 | 8 |

Note:

1. The LCD backlight is turn off and volume is adjusted to maximum level during T-Coil testing.
2. Signal strength measurement scan plots are presented in Annex B.



| Air interface investigation for LTE B2 | | | | | | | | | | |
|--|-------------|-----------------|---------|-----------------|-----------------|--------------------------|-----------------------------------|---------------------|---------------------|----------|
| Mode | Orientation | Bandwidth (MHz) | Channel | ABM1 [dB (A/m)] | ABM2 [dB (A/m)] | Ambient Noise [dB (A/m)] | Frequency Response Variation (dB) | Signal Quality (dB) | C63.19-201 1 Rating | Plot No. |
| LTE Band 2 | z (Axial): | 20 | 18900 | -4.95 | -52.9 | -58.53 | 0.49 | 47.95 | T4 | 11 |
| | | 15 | 18900 | -2.49 | -50.52 | -58.53 | 0.49 | 48.03 | T4 | - |
| | | 10 | 18900 | -2.31 | -50.32 | -58.53 | 0.49 | 48.01 | T4 | - |
| | | 5 | 18900 | -1.34 | -49.47 | -58.53 | 0.49 | 48.13 | T4 | - |
| | | 3 | 18900 | -2.81 | -51.29 | -58.53 | 0.49 | 48.48 | T4 | - |
| | | 1.4 | 18900 | -1.98 | -49.96 | -58.53 | 0.49 | 47.98 | T4 | - |
| | y (Radial): | 20 | 18900 | -13.17 | -54.05 | -58.87 | / | 40.88 | T4 | 12 |
| | | 15 | 18900 | -13.74 | -54.84 | -58.87 | / | 41.1 | T4 | - |
| | | 10 | 18900 | -13.34 | -54.36 | -58.87 | / | 41.02 | T4 | - |
| | | 5 | 18900 | -13.71 | -55.27 | -58.87 | / | 41.56 | T4 | - |
| | | 3 | 18900 | -14.71 | -55.99 | -58.87 | / | 41.28 | T4 | - |
| | | 1.4 | 18900 | -14.79 | -56.38 | -58.87 | / | 41.59 | T4 | - |

| Band | Channel /Frequency (MHz) | Probe Orientation | ABM1 [dB (A/m)] | ABM2 [dB (A/m)] | ABM SNR (dB) | Freq. Resp. Diff(dB) | Frequency Response | T-Rating | Plot No. |
|--|--|-------------------|-----------------|-----------------|--------------|----------------------|--------------------|----------|----------|
| LTE FDD B2 Voice WB AMR Codec: 6.60kbit/s | 18900/1880 (QPSK_20M_1RB_0offset) | y (Radial): | -13.17 | -54.05 | 40.88 | / | / | T4 | 9 |
| | | z (Axial): | -4.95 | -52.90 | 47.95 | 0.49 | Pass | T4 | 10 |
| LTE FDD B4 Voice WB AMR Codec: 6.60kbit/s | 20175/1732.5 (QPSK_20M_1RB_0offset) | y (Radial): | -12.88 | -54.11 | 41.23 | / | / | T4 | 11 |
| | | z (Axial): | -4.90 | -52.71 | 47.81 | 0.58 | Pass | T4 | 12 |
| LTE FDD B5 Voice WB AMR Codec: 6.60kbit/s | 20525/836.5 (QPSK_10M_1RB_0offset) | y (Radial): | -12.51 | -52.47 | 39.96 | / | / | T4 | 13 |
| | | z (Axial): | -4.84 | -49.61 | 44.77 | 0.38 | Pass | T4 | 14 |
| LTE FDD B13 Voice WB AMR Codec: 6.60kbit/s | 23230/782 (QPSK_10M_1RB_0offset) | y (Radial): | -12.48 | -52.07 | 39.59 | / | / | T4 | 15 |
| | | z (Axial): | -4.86 | -49.80 | 44.94 | 0.36 | Pass | T4 | 16 |
| WIFI2.4G: 802.11b Voice WB AMR Codec: 6.60kbit/s | 6/2437 (BW:20M_Rate:1M) | y (Radial): | -14.42 | -54.48 | 40.06 | / | / | T4 | 17 |
| | | z (Axial): | -6.74 | -52.59 | 45.85 | 0.32 | Pass | T4 | 18 |

Note:

1. The LCD backlight is turn off and volume is adjusted to maximum level during T-Coil testing.
2. Signal strength measurement scan plots are presented in Annex B.



12 Measurement Uncertainty

Measurement uncertainty evaluation template for DUT HAC T-Coil test

| Error source | Type | Uncertainty Value a_i (%) | Prob. Dist. | k | ABM1 c_i | ABM2 c_i | Std. Unc. ABM1 ($\pm \%$) | Std. Unc. ABM2 ($\pm \%$) | Degree of freedom $V_{eff} \text{ or } V_i$ |
|---------------------------------------|------|-----------------------------|-------------|-------|------------|------------|-----------------------------|-----------------------------|---|
| Probe Sensitivity | | | | | | | | | |
| Reference Level | B | 3.0 | N | 1 | 1 | 1 | 3.0 | 3.0 | ∞ |
| AMCC Geometry | B | 0.4 | R | 1.732 | 1 | 1 | 0.2 | 0.2 | ∞ |
| AMCC Current | B | 0.6 | R | 1.732 | 1 | 1 | 0.3 | 0.3 | ∞ |
| Probe Positioning during Calibration | B | 0.1 | R | 1.732 | 1 | 1 | 0.1 | 0.1 | ∞ |
| Noise Contribution | B | 0.7 | R | 1.732 | 0.0143 | 1 | 0.0 | 0.4 | ∞ |
| Frequency Slope | B | 5.9 | R | 1.732 | 0.1 | 1 | 0.3 | 3.4 | ∞ |
| Probe System | | | | | | | | | |
| Repeatability / Drift | B | 1.0 | R | 1.732 | 1 | 1 | 0.6 | 0.6 | ∞ |
| Linearity / Dynamic Range | B | 0.6 | R | 1.732 | 1 | 1 | 0.3 | 0.3 | ∞ |
| Acoustic Noise | B | 1.0 | R | 1.732 | 0.1 | 1 | 0.1 | 0.6 | ∞ |
| Probe Angle | B | 2.3 | R | 1.732 | 1 | 1 | 1.3 | 1.3 | ∞ |
| Spectral Processing | B | 0.9 | R | 1.732 | 1 | 1 | 0.5 | 0.5 | ∞ |
| Integration Time | B | 0.6 | N | 1 | 1 | 5 | 0.6 | 3.0 | ∞ |
| Field Distribution | B | 0.2 | R | 1.732 | 1 | 1 | 0.1 | 0.1 | ∞ |
| Test Signal | | | | | | | | | |
| Ref.Signal Spectral Response | B | 0.6 | R | 1.732 | 0 | 1 | 0.0 | 0.3 | ∞ |
| Positioning | | | | | | | | | |
| Probe Positioning | B | 1.9 | R | 1.732 | 1 | 1 | 1.1 | 1.1 | ∞ |
| Phantom Thickness | B | 0.9 | R | 1.732 | 1 | 1 | 0.5 | 0.5 | ∞ |
| EUT Positioning | B | 1.9 | R | 1.732 | 1 | 1 | 1.1 | 1.1 | ∞ |
| External Contributions | | | | | | | | | |
| RF Interference | B | 0.0 | R | 1.732 | 1 | 0.3 | 0.0 | 0.0 | ∞ |
| Test Signal Variation | B | 2.0 | R | 1.732 | 1 | 1 | 1.2 | 1.2 | ∞ |
| Combined Std. Uncertainty (ABM Field) | | | | | | | 4.0 | 6.1 | |
| Expanded Std. Uncertainty | | | | | | | 8.0 | 12.2 | |



13 Main Test Instruments

| Name | Manufacturer | Type | Serial Number | Last Cal. | Cal. Due Date |
|--------------------------------------|--------------|---------------|---------------|------------|---------------|
| Audio Magnetic 1D Field Probe | SPEAG | AM1DV3 | 3082 | 2018-03-26 | 2021-03-25 |
| DAE | SPEAG | DAE4 | 1317 | 2018-03-23 | 2019-03-22 |
| Universal Radio Communication Tester | R&S | CMU 200 | 118133 | 2018-05-20 | 2019-05-19 |
| Universal Radio Communication Tester | R&S | CMW 500 | 146734 | 2018-05-20 | 2019-05-19 |
| Audio Magnetic Calibration Coil | SPEAG | AMCC | 1101 | 2017-11-22 | 2020-11-21 |
| Audio Measuring Instrument | SPEAG | AMMI | 1112 | 2017-11-22 | 2020-11-21 |
| TMFS | SPEAG | SE UMS 021 AA | 1018 | 2017-11-22 | 2020-11-21 |
| Hygrothermograph | Anymetr | NT-311 | 20150731 | 2018-05-15 | 2019-05-16 |
| HAC Phantom | SPEAG | SD HAC P01 BB | 1117 | 2017-11-22 | 2020-11-21 |
| Software for Test | Speag | DASY5 | 52.8.8.1222 | / | / |
| Software for Tissue | Agilent | 85070 | E06.01.36 | / | / |

*****END OF REPORT *****

ANNEX A: Test Layout



Picture 1:HAC T-Coil System Layout

ANNEX B: Graph Results

Plot 1 T-Coil GSM 850 Y transversal

Date: 2/13/2019

Communication System: UID 0, GSM (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2017/11/21

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

KAZ-F119 GSM850 HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.17 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 41.31 dB

ABM1 comp = -12.11 dBA/m

BWC Factor = 0.17 dB

Location: 0, 4.2, 3.7 mm





Plot 2 T-Coil GSM 850 Z Axial

Date: 2/13/2019

Communication System: UID 0, GSM (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2017/11/21

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

KAZ-F119 GSM850 HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM

SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.17 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 42.55 dB

ABM1 comp = -4.46 dBA/m

BWC Factor = 0.17 dB

Location: 0, -4.2, 3.7 mm

KAZ-F119 GSM850 HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 66.12

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.81 dB


Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 1.41 dB


BWC Factor = 10.81 dB

Location: 0, -4.2, 3.7 mm



General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)

Loc: 0, -4.2, 3.7 mm Diff: 1.41dB



Plot 3 T-Coil GSM 1900 Y transversal

Date: 2/13/2019

Communication System: UID 0, GSM (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2017/11/21

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

KAZ-F119 GSM1900 HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 41.01 dB

ABM1 comp = -12.39 dBA/m

BWC Factor = 0.16 dB

Location: 0, 4.2, 3.7 mm



0 dB = 112.3 = 41.01 dB

Plot 4 T-Coil GSM 1900 Z Axial

Date: 2/13/2019

Communication System: UID 0, GSM (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2017/11/21

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

KAZ-F119 GSM1900 HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM

SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 45.58 dB

ABM1 comp = -4.46 dBA/m

BWC Factor = 0.16 dB

Location: 0, -4.2, 3.7 mm

KAZ-F119 GSM1900 HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 66.12

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.81 dB


Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 1.29 dB


BWC Factor = 10.81 dB

Location: 0, -4.2, 3.7 mm



General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)

Loc: 0, -4.2, 3.7 mm Diff: 1.29dB



Plot 5 T-Coil WCDMA Band II Y transversal

Date: 2/13/2019

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2017/11/21

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

A6L-G WCDMA B2 HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 37.09 dB

ABM1 comp = -10.47 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 4.2, 3.7 mm



$$0 \text{ dB} = 71.54 = 37.09 \text{ dB}$$

Plot 6 T-Coil WCDMA Band II Z Axial

Date: 2/13/2019

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2017/11/21

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

A6L-G WCDMA B2 HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM

SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 43.93 dB

ABM1 comp = -4.21 dBA/m

BWC Factor = 0.16 dB

Location: 0, -4.2, 3.7 mm

A6L-G WCDMA B2 HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 66.12

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.81 dB


Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 1.56 dB


BWC Factor = 10.81 dB

Location: 0, -4.2, 3.7 mm



General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)

Loc: -4.2, 0, 3.7 mm Diff: 1.56dB



Plot 7 T-Coil WCDMA Band V Y transversal

Date: 2/13/2019

Communication System: UID 0, WCDMA V (0); Frequency: 836.6 MHz; Duty Cycle: 1:1

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2017/11/21

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

KAZ-F119 WCDMA B5 HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x

50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 41.29 dB

ABM1 comp = -12.33 dBA/m

BWC Factor = 0.16 dB

Location: 0, 4.2, 3.7 mm



**Plot 8 T-Coil WCDMA Band V Z Axial**

Date: 2/13/2019

Communication System: UID 0, WCDMA V (0); Frequency: 836.6 MHz; Duty Cycle: 1:1

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2017/11/21

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

KAZ-F119 WCDMA B5 HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM

SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 48.68 dB

ABM1 comp = -4.33 dBA/m

BWC Factor = 0.16 dB

Location: 0, -4.2, 3.7 mm

KAZ-F119 WCDMA B5 HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 66.12

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.81 dB


Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 0.32 dB

BWC Factor = 10.81 dB


Location: 0, -4.2, 3.7 mm



0 dB = 271.6 = 48.68 dB

General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)

Loc: 0, -4.2, 3.7 mm Diff: 0.32dB



Plot 9 T-Coil LTE Band 2 Y transversal

Date: 2/13/2019

Communication System: UID 0, LTE (0); Frequency: 2595 MHz; Duty Cycle: 1:1

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

KAZ-F119 LTE B2 1RB HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x

50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.17 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 40.88 dB

ABM1 comp = -13.17 dBA/m

BWC Factor = 0.17 dB

Location: 0, 4.2, 3.7 mm



0 dB = 110.7 = 40.88 dB



Plot 10 T-Coil LTE Band 2 Z Axial

Date: 2/13/2019

Communication System: UID 0, LTE (0); Frequency: 2595 MHz; Duty Cycle: 1:1

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

KAZ-F119 LTE B2 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM

SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.17 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 47.95 dB

ABM1 comp = -4.95 dBA/m

BWC Factor = 0.17 dB

Location: 0, 0, 3.7 mm

KAZ-F119 LTE B2 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 66.12

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.81 dB


Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 0.49 dB


BWC Factor = 10.81 dB

Location: 0, 0, 3.7 mm



General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)

Loc: 0, 0, 3.7 mm Diff: 0.49dB



Plot 11 T-Coil LTE Band 4 Y transversal

Date: 2/13/2019

Communication System: UID 0, LTE (0); Frequency: 2595 MHz; Duty Cycle: 1:1

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

KAZ-F119 LTE B4 1RB HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x

50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.17 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 41.23 dB

ABM1 comp = -12.88 dBA/m

BWC Factor = 0.17 dB

Location: 0, -8.3, 3.7 mm



0 dB = 115.2 = 41.23 dB



Plot 12 T-Coil LTE Band 4 Z Axial

Date: 2/13/2019

Communication System: UID 0, LTE (0); Frequency: 2595 MHz; Duty Cycle: 1:1

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

KAZ-F119 LTE B4 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM

SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.17 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 47.81 dB

ABM1 comp = -4.90 dBA/m

BWC Factor = 0.17 dB

Location: 0, 0, 3.7 mm

KAZ-F119 LTE B4 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 66.12

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.81 dB


Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 0.58 dB


BWC Factor = 10.81 dB

Location: 0, 0, 3.7 mm



General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)

Loc: 0, 0, 3.7 mm Diff: 0.58dB



Plot 13 T-Coil LTE Band 5 Y transversal

Date: 2/13/2019

Communication System: UID 0, LTE (0); Frequency: 836.5 MHz; Duty Cycle: 1:1

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

KAZ-F119 LTE B5 1RB HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x

50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.17 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 39.96 dB

ABM1 comp = -12.51 dBA/m

BWC Factor = 0.17 dB

Location: 0, 4.2, 3.7 mm





Plot 14 T-Coil LTE Band 5 Z Axial

Date: 2/13/2019

Communication System: UID 0, LTE (0); Frequency: 836.5 MHz; Duty Cycle: 1:1

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

KAZ-F119 LTE B5 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM

SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.17 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 44.77 dB

ABM1 comp = -4.84 dBA/m

BWC Factor = 0.17 dB

Location: 0, -4.2, 3.7 mm

KAZ-F119 LTE B5 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 66.12

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.81 dB


Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 0.38 dB


BWC Factor = 10.81 dB

Location: 0, -4.2, 3.7 mm



General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)

Loc: 0, -4.2, 3.7 mm Diff: 0.38dB



Plot 15 T-Coil LTE Band 13 Y transversal

Date: 2/13/2019

Communication System: UID 0, LTE (0); Frequency: 782 MHz; Duty Cycle: 1:1

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

KAZ-F119 LTE B13 1RB HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x

50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.17 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 39.59 dB

ABM1 comp = -12.48 dBA/m

BWC Factor = 0.17 dB

Location: 0, -8.3, 3.7 mm



0 dB = 95.44 = 39.59 dB



Plot 16 T-Coil LTE Band 13 Z Axial

Date: 2/13/2019

Communication System: UID 0, LTE (0); Frequency: 782 MHz; Duty Cycle: 1:1

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

KAZ-F119 LTE B13 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM

SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.17 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 44.94 dB

ABM1 comp = -4.86 dBA/m

BWC Factor = 0.17 dB

Location: 0, 0, 3.7 mm

KAZ-F119 LTE B13 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 66.12

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.81 dB


Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 0.36 dB

BWC Factor = 10.81 dB


Location: 0, 0, 3.7 mm



$$0 \text{ dB} = 176.7 = 44.94 \text{ dB}$$

General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)

Loc: 0, 0, 3.7 mm Diff: 0.36dB



Plot 17 T-Coil802.11b Y transversal

Date: 2/13/2019

Communication System: UID 0, 802.11b (0); Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0 \text{ S/m}$, $\epsilon_r = 1$; $\rho = 1 \text{ kg/m}^3$

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

A6L-G 802.11b HAC_TCoil_WD_Emission NB/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.17 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 40.06 dB

ABM1 comp = -14.42 dBA/m

BWC Factor = 0.17 dB

Location: 4.2, -8.3, 3.7 mm



**Plot 18 T-Coil 802.11b Z Axial**

Date: 2/13/2019

Communication System: UID 0, 802.11b (0); Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0 \text{ S/m}$, $\epsilon_r = 1$; $\rho = 1 \text{ kg/m}^3$

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: TCoil Section

DASY5 Configuration:

Sensor-Surface: 0mm (Mechanical Surface Detection)

Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26

Electronics: DAE4 Sn1291; Calibrated: 2018/12/4

Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

KAZ-F119 802.11b HAC_TCoil_WD_Emission NB/General Scans/z (axial) 4.2mm 50 x 50/ABM

SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 33.76

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.17 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 45.85 dB

ABM1 comp = -6.74 dBA/m

BWC Factor = 0.17 dB

Location: 0, -4.2, 3.7 mm

KAZ-F119 802.11b HAC_TCoil_WD_Emission NB/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 66.12

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.81 dB


Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 0.32 dB

BWC Factor = 10.81 dB


Location: 0, -4.2, 3.7 mm



$$0 \text{ dB} = 196.1 = 45.85 \text{ dB}$$

General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)

Loc: 0, -4.2, 3.7 mm Diff: 0.32dB





ANNEX C: Probe Calibration Certificate

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **TA-SH (Auden)**Certificate No: **AM1DV3-3082_Mar18**

CALIBRATION CERTIFICATE

| Object | AM1DV3 - SN: 3082 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|-----------------------------------|-----------------------|-------------------|------|----------------------------|-----------------------|-------------------------------|-------------|-----------------------|--------|------------------------|----------|-----------------------------------|--------|------|---------|--------------------------------|--------|---------------------|------|-----------------------|-----------------|------|----------|-----------------------------------|--------|---------------------------------|----------|-----------------------------------|--------|----------------|-------------------------|-----------------------------------|---------------|--------------|---------------|-------------------|--|
| Calibration procedure(s) | QA CAL-24.v4 Calibration procedure for AM1D magnetic field probes and TMFS in the audio range | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Calibration date: | March 26, 2018 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.</p> <p>All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.</p> <p>Calibration Equipment used (M&TE critical for calibration)</p> <table border="1"> <tr> <th>Primary Standards</th> <th>ID #</th> <th>Cal Date (Certificate No.)</th> <th>Scheduled Calibration</th> </tr> <tr> <td>Keithley Multimeter Type 2001</td> <td>SN: 0810278</td> <td>31-Aug-17 (No. 21092)</td> <td>Aug-18</td> </tr> <tr> <td>Reference Probe AM1DV3</td> <td>SN: 3000</td> <td>24-Aug-17 (No. AM1DV3-3000_Aug17)</td> <td>Aug-18</td> </tr> <tr> <td>DAE4</td> <td>SN: 781</td> <td>17-Jan-18 (No. DAE4-781_Jan18)</td> <td>Jan-19</td> </tr> </table> <table border="1"> <tr> <th>Secondary Standards</th> <th>ID #</th> <th>Check Date (in house)</th> <th>Scheduled Check</th> </tr> <tr> <td>AMCC</td> <td>SN: 1050</td> <td>01-Oct-13 (in house check Oct-17)</td> <td>Oct-19</td> </tr> <tr> <td>AMMI Audio Measuring Instrument</td> <td>SN: 1062</td> <td>26-Sep-12 (in house check Oct-17)</td> <td>Oct-19</td> </tr> </table> <table border="1"> <tr> <td>Calibrated by:</td> <td>Name Jelton Kastrati</td> <td>Function Laboratory Technician</td> <td>Signature </td> </tr> <tr> <td>Approved by:</td> <td>Katja Pokovic</td> <td>Technical Manager</td> <td></td> </tr> </table> <p>Issued: March 26, 2018</p> <p>This calibration certificate shall not be reproduced except in full without written approval of the laboratory.</p> | | | | Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration | Keithley Multimeter Type 2001 | SN: 0810278 | 31-Aug-17 (No. 21092) | Aug-18 | Reference Probe AM1DV3 | SN: 3000 | 24-Aug-17 (No. AM1DV3-3000_Aug17) | Aug-18 | DAE4 | SN: 781 | 17-Jan-18 (No. DAE4-781_Jan18) | Jan-19 | Secondary Standards | ID # | Check Date (in house) | Scheduled Check | AMCC | SN: 1050 | 01-Oct-13 (in house check Oct-17) | Oct-19 | AMMI Audio Measuring Instrument | SN: 1062 | 26-Sep-12 (in house check Oct-17) | Oct-19 | Calibrated by: | Name Jelton Kastrati | Function Laboratory Technician | Signature | Approved by: | Katja Pokovic | Technical Manager | |
| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Keithley Multimeter Type 2001 | SN: 0810278 | 31-Aug-17 (No. 21092) | Aug-18 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Reference Probe AM1DV3 | SN: 3000 | 24-Aug-17 (No. AM1DV3-3000_Aug17) | Aug-18 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| DAE4 | SN: 781 | 17-Jan-18 (No. DAE4-781_Jan18) | Jan-19 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Secondary Standards | ID # | Check Date (in house) | Scheduled Check | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| AMCC | SN: 1050 | 01-Oct-13 (in house check Oct-17) | Oct-19 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| AMMI Audio Measuring Instrument | SN: 1062 | 26-Sep-12 (in house check Oct-17) | Oct-19 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Calibrated by: | Name Jelton Kastrati | Function Laboratory Technician | Signature | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Approved by: | Katja Pokovic | Technical Manager | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Certificate No: AM1DV3-3082_Mar18

Page 1 of 3



[References]

- [1] ANSI-C63.19-2007 American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
- [2] ANSI-C63.19-2011 American National Standard, Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
- [3] DASY5 manual, Chapter: Hearing Aid Compatibility (HAC) T-Coil Extension

Description of the AM1D probe

The AM1D Audio Magnetic Field Probe is a fully shielded magnetic field probe for the frequency range from 100 Hz to 20 kHz. The pickup coil is compliant with the dimensional requirements of [1+2]. The probe includes a symmetric low noise amplifier for the signal available at the shielded 3 pin connector at the side. Power is supplied via the same connector (phantom power supply) and monitored via the LED near the connector. The 7 pin connector at the end of the probe does not carry any signals, but determines the angle of the sensor when mounted on the DAE. The probe supports mechanical detection of the surface.

The single sensor in the probe is arranged in a tilt angle allowing measurement of 3 orthogonal field components when rotating the probe by 120° around its axis. It is aligned with the perpendicular component of the field, if the probe axis is tilted nominally 35.3° above the measurement plane, using the connector rotation and sensor angle stated below.

The probe is fully RF shielded when operated with the matching signal cable (shielded) and allows measurement of audio magnetic fields in the close vicinity of RF emitting wireless devices according to [1+2] without additional shielding.

Handling of the item

The probe is manufactured from stainless steel. In order to maintain the performance and calibration of the probe, it must not be opened. The probe is designed for operation in air and shall not be exposed to humidity or liquids. For proper operation of the surface detection and emergency stop functions in a DASY system, the probe must be operated with the special probe cup provided (larger diameter).

Methods Applied and Interpretation of Parameters

- **Coordinate System:** The AM1D probe is mounted in the DASY system for operation with a HAC Test Arch phantom with AMCC Helmholtz calibration coil according to [3], with the tip pointing to "southwest" orientation.
- **Functional Test:** The functional test preceding calibration includes test of Noise level RF immunity (1kHz AM modulated signal). The shield of the probe cable must be well connected. Frequency response verification from 100 Hz to 10 kHz.
- **Connector Rotation:** The connector at the end of the probe does not carry any signals and is used for fixation to the DAE only. The probe is operated in the center of the AMCC Helmholtz coil using a 1 kHz magnetic field signal. Its angle is determined from the two minima at nominally +120° and -120° rotation, so the sensor in the tip of the probe is aligned to the vertical plane in z-direction, corresponding to the field maximum in the AMCC Helmholtz calibration coil.
- **Sensor Angle:** The sensor tilting in the vertical plane from the ideal vertical direction is determined from the two minima at nominally +120° and -120°. DASY system uses this angle to align the sensor for radial measurements to the x and y axis in the horizontal plane.

Sensitivity: With the probe sensor aligned to the z-field in the AMCC, the output of the probe is compared to the magnetic field in the AMCC at 1 kHz. The field in the AMCC Helmholtz coil is given by the geometry and the current through the coil, which is monitored on the precision shunt resistor of the coil.

**AM1D probe identification and configuration data**

| | |
|-----------|--------------------------------------|
| Item | AM1DV3 Audio Magnetic 1D Field Probe |
| Type No | SP AM1 001 BA |
| Serial No | 3082 |

| | |
|--------------------|------------------------------------|
| Overall length | 296 mm |
| Tip diameter | 6.0 mm (at the tip) |
| Sensor offset | 3.0 mm (centre of sensor from tip) |
| Internal Amplifier | 20 dB |

| | |
|-----------------------|--|
| Manufacturer / Origin | Schmid & Partner Engineering AG, Zurich, Switzerland |
| Manufacturing date | May 28, 2010 |

Calibration data

| | | | |
|--------------------------|------------------|-------------------|-----------------|
| Connector rotation angle | (in DASY system) | 7.6 ° | +/- 3.6 ° (k=2) |
| Sensor angle | (in DASY system) | 0.24 ° | +/- 0.5 ° (k=2) |
| Sensitivity at 1 kHz | (in DASY system) | 0.00739 V / (A/m) | +/- 2.2 % (k=2) |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.



ANNEX D: DAE4 Calibration Certificate

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client TA-SH (Auden)

Certificate No: DAE4-1317_Mar18

CALIBRATION CERTIFICATE

Object DAE4 - SD 000 D04 BM - SN: 1317

Calibration procedure(s) QA CAL-06.v29
Calibration procedure for the data acquisition electronics (DAE)

Calibration date: March 23, 2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
|-------------------------------|--------------------|----------------------------|------------------------|
| Keithley Multimeter Type 2001 | SN: 0810278 | 31-Aug-17 (No:21092) | Aug-18 |
| Secondary Standards | ID # | Check Date (in house) | Scheduled Check |
| Auto DAE Calibration Unit | SE UWS 053 AA 1001 | 04-Jan-18 (in house check) | In house check: Jan-19 |
| Calibrator Box V2.1 | SE UMS 006 AA 1002 | 04-Jan-18 (in house check) | In house check: Jan-19 |

| | | | |
|----------------|---------------------------|-----------------------------------|---------------|
| Calibrated by: | Name Dominique Steffen | Function Laboratory Technician | Signature |
| Approved by: | Sven Kühn | Deputy Manager | |

Issued: March 23, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Glossary

| | |
|-----------------|---|
| DAE | data acquisition electronics |
| Connector angle | information used in DASY system to align probe sensor X to the robot coordinate system. |

Methods Applied and Interpretation of Parameters

- *DC Voltage Measurement*: Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle*: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
 - *DC Voltage Measurement Linearity*: Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
 - *Common mode sensitivity*: Influence of a positive or negative common mode voltage on the differential measurement.
 - *Channel separation*: Influence of a voltage on the neighbor channels not subject to an input voltage.
 - *AD Converter Values with inputs shorted*: Values on the internal AD converter corresponding to zero input voltage
 - *Input Offset Measurement*: Output voltage and statistical results over a large number of zero voltage measurements.
 - *Input Offset Current*: Typical value for information; Maximum channel input offset current, not considering the input resistance.
 - *Input resistance*: Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
 - *Low Battery Alarm Voltage*: Typical value for information. Below this voltage, a battery alarm signal is generated.
 - *Power consumption*: Typical value for information. Supply currents in various operating modes.

**DC Voltage Measurement**

A/D - Converter Resolution nominal

High Range: 1LSB = 6.1 μ V, full range = -100...+300 mV

Low Range: 1LSB = 61nV, full range = -1.....+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| Calibration Factors | X | Y | Z |
|---------------------|------------------------------------|------------------------------------|------------------------------------|
| High Range | $403.713 \pm 0.02\% \text{ (k=2)}$ | $404.474 \pm 0.02\% \text{ (k=2)}$ | $403.834 \pm 0.02\% \text{ (k=2)}$ |
| Low Range | $3.97916 \pm 1.50\% \text{ (k=2)}$ | $3.99031 \pm 1.50\% \text{ (k=2)}$ | $3.96832 \pm 1.50\% \text{ (k=2)}$ |

Connector Angle

| | |
|---|---------------------------|
| Connector Angle to be used in DASY system | $332.0^\circ \pm 1^\circ$ |
|---|---------------------------|

Appendix (Additional assessments outside the scope of SCS0108)**1. DC Voltage Linearity**

| High Range | Reading (µV) | Difference (µV) | Error (%) |
|-------------------|--------------|-----------------|-----------|
| Channel X + Input | 200033.59 | -2.39 | -0.00 |
| Channel X + Input | 20006.23 | 0.60 | 0.00 |
| Channel X - Input | -20003.30 | 2.01 | -0.01 |
| Channel Y + Input | 200032.59 | -3.60 | -0.00 |
| Channel Y + Input | 20003.70 | -1.89 | -0.01 |
| Channel Y - Input | -20004.09 | 1.35 | -0.01 |
| Channel Z + Input | 200035.04 | -0.93 | -0.00 |
| Channel Z + Input | 20005.33 | -0.22 | -0.00 |
| Channel Z - Input | -20006.76 | -1.25 | 0.01 |

| Low Range | Reading (µV) | Difference (µV) | Error (%) |
|-------------------|--------------|-----------------|-----------|
| Channel X + Input | 2001.75 | 0.20 | 0.01 |
| Channel X + Input | 200.99 | -0.43 | -0.21 |
| Channel X - Input | -197.13 | 1.49 | -0.75 |
| Channel Y + Input | 2001.26 | -0.25 | -0.01 |
| Channel Y + Input | 200.67 | -0.56 | -0.28 |
| Channel Y - Input | -199.10 | -0.34 | 0.17 |
| Channel Z + Input | 2000.98 | -0.47 | -0.02 |
| Channel Z + Input | 200.06 | -1.17 | -0.58 |
| Channel Z - Input | -199.95 | -1.19 | 0.60 |

2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| | Common mode Input Voltage (mV) | High Range Average Reading (µV) | Low Range Average Reading (µV) |
|-----------|-----------------------------------|------------------------------------|-----------------------------------|
| Channel X | 200 | 11.88 | 10.25 |
| | -200 | -8.69 | -10.35 |
| Channel Y | 200 | 11.35 | 11.40 |
| | -200 | -13.19 | -12.90 |
| Channel Z | 200 | 1.73 | 1.34 |
| | -200 | -2.98 | -3.58 |

3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| | Input Voltage (mV) | Channel X (µV) | Channel Y (µV) | Channel Z (µV) |
|-----------|--------------------|----------------|----------------|----------------|
| Channel X | 200 | - | 2.22 | -4.63 |
| Channel Y | 200 | 8.79 | - | 3.02 |
| Channel Z | 200 | 10.60 | 6.05 | - |

**4. AD-Converter Values with inputs shorted**

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| | High Range (LSB) | Low Range (LSB) |
|-----------|------------------|-----------------|
| Channel X | 15758 | 16030 |
| Channel Y | 16498 | 16052 |
| Channel Z | 16107 | 15724 |

5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Input $10M\Omega$

| | Average (μ V) | min. Offset (μ V) | max. Offset (μ V) | Std. Deviation (μ V) |
|-----------|--------------------|------------------------|------------------------|---------------------------|
| Channel X | 1.03 | -0.09 | 2.36 | 0.48 |
| Channel Y | -0.33 | -1.77 | 1.22 | 0.54 |
| Channel Z | -1.81 | -3.67 | -0.40 | 0.67 |

6. Input Offset Current

Nominal Input circuitry offset current on all channels: <25fA

7. Input Resistance (Typical values for information)

| | Zeroing (kOhm) | Measuring (MOhm) |
|-----------|----------------|------------------|
| Channel X | 200 | 200 |
| Channel Y | 200 | 200 |
| Channel Z | 200 | 200 |

8. Low Battery Alarm Voltage (Typical values for information)

| Typical values | Alarm Level (VDC) |
|----------------|-------------------|
| Supply (+ Vcc) | +7.9 |
| Supply (- Vcc) | -7.6 |

9. Power Consumption (Typical values for information)

| Typical values | Switched off (mA) | Stand by (mA) | Transmitting (mA) |
|----------------|-------------------|---------------|-------------------|
| Supply (+ Vcc) | +0.01 | +6 | +14 |
| Supply (- Vcc) | -0.01 | -8 | -9 |

ANNEX E: The EUT Appearances and Test Configuration



Picture 2: Constituents of EUT



Picture 3: Test Setup