

## Maximum Permissible Exposure Report

### Product Information

FCC ID:	2ASCW-NLPRO
Product name	Table Bluetooth Speaker and Oil Lamp
Model number	Nordic Light PRO
Power supply	DC 7.4V by Rechargeable Li-ion Battery(3000mAh) Maximum Charging Voltage: DC 5V/2A
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Antenna Type	Internal Antenna
Antenna Gain	2.88dBi(Max.)
Hardware version	V1.0
Software version	V1.0
BT FCC Operation frequency	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Extreme temp. Tolerance	-20°C to +40°C
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Device

### 2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

### 3. Limit

#### 3.1 Refer evaluation method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

### 3.2 Limit

#### Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

#### Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

### 4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

### 5. Antenna Information

Nordic Light PRO can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 0	Internal Antenna	2000 MHz – 2500 MHz	2.88dBi

### 6. Conducted Power

Test Mode	Channel	Frequency (MHz)	Measured Peak Output Power (dBm)
GFSK	0	2402	1.603
	39	2441	1.563
	78	2480	1.763
$\pi/4$ -DQPSK	0	2402	3.609
	39	2441	3.609
	78	2480	3.791
8-DPSK	0	2402	4.187
	39	2441	4.218
	78	2480	4.355

**E.I.R.P Power Results**

Mode		Channel	Frequency (MHz)	Field Strength (dB $\mu$ V /m)	d (m)	E.I.R.P Power (dBm)
5.8G SRD	GFSK	2	5731	88.11	3.0	-7.119
		9	5767	88.39	3.0	-6.839
		14	5793	88.05	3.0	-7.179

Note:

$$e.i.r.p = pt * gt = (E*d)^2/30$$

where:

pt = transmitter output power in watts

gt = numeric gain of the transmitting antenna (numeric)

E = electric field strength in V/m

d = measurement distance in meters (m)

**7. Manufacturing Tolerance****2.4GBT**

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1.0	1.0	1.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ -DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	3.0	3.0	3.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8-DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	4.0	4.0	4.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

**5.8SRD (Peak)**

Channel	Channel 2	Channel 9	Channel 14
Target (dBm)	-7.0	-6.5	-7.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

**8. Measurement Results****8.1 Standalone MPE**

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r=20\text{cm}$ , as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

**Antenna BT**

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
GFSK	2.0	1.5849	2.88	1.94	100%	0.0006	1.0000
$\pi/4$ -DQPSK	4.0	2.5119	2.88	1.94	100%	0.0010	1.0000
8-DPSK	5.0	3.1623	2.88	1.94	100%	0.0012	1.0000

**Antenna 5.8SRD**

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
GFSK	-5.5	0.2818	2.88	1.94	100%	0.0001	1.0000

**Remark:**

1. Output power (Peak) including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

**8.2 Simultaneous Transmission MPE**

The sample supports 2 antennas for BT&5.8SRD. The BT and 5.8G SRD can transmit simultaneous. According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$\Sigma$  of MPE ratios  $\leq$  1.0

**8.2.1 Summary simultaneous transmission information**

Work Frequency Band	Transmit Antenna		Antenna 0 Antenna 1 Synchronization transmit
	Antenna 0	Antenna 1	
BT&5.8DRD	Yes	Yes	Yes

**8.2.2 Summary simultaneous transmission results**

Work Frequency Band	MPE Antenna0 (mW/c m <sup>2</sup> )	MPE Antenna1 (mW/c m <sup>2</sup> )	$\Sigma$ MPE ratios	Limit	Results
BT&5.8DRD	0.0012	0.0001	0.0013	1.0	PASS

**9. Conclusion**

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----