



H.B. Compliance Solutions

Maximum Permissible Exposure Statement

For the

Hiber Inc.

LPGAN Modem Model CN1

March 7, 2019

Prepared for:

Hiber, Inc.

8400 Baltimore Ave., Suite 320,

College Park, MD 20704

Prepared By:

H.B. Compliance Solutions

5005 S. Ash Avenue, Suite # A-10

Tempe, Arizona 85282

Reviewed By:

A handwritten signature in black ink, appearing to read 'Hoosamuddin Bandukwala'.

Hoosamuddin Bandukwala



Cert # ATL-0062-E

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where,

S = power density (mW/cm²)

P = output power at the antenna terminal (mW)

G = gain of transmit antenna (numeric)

R = distance from transmitting antenna (cm)

Maximum peak output power at antenna input terminal = 30.23 (dBm) *

Maximum peak output power at antenna input terminal = 1054.3 (mW)

Antenna gain (typical) = 0 (dBi)

Maximum antenna gain = 1.0 (numeric)

Prediction distance = 30 (cm)

Prediction frequency = 399.9 (MHz)

MPE limit for uncontrolled exposure at prediction frequency = 0.267 (mW/cm²)

Power density at prediction frequency = 0.09322 (mW/cm²)

*Includes 1dB of manufacturer output power tolerance.

To solve for the minimum mounting distance required;

$$R = \sqrt{PG/4\pi S}$$

$$R = \sqrt{346 \times 1.4 / 4\pi \times 0.09322} = \underline{30 \text{ cm}} \text{ (Based on continuous transmission)}$$

END OF TEST REPORT