

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2ASEO-HPYKE24

EUT Specification

EUT	2.4G&5G Dual Band WIFI Module
Model Number	HPYKE24
Input Rating	DC 3.3V
Frequency band (Operating)	<input type="checkbox"/> BT: 2.402GHz ~ 2.480GHz <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz <input checked="" type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation)
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power (peak power)	IEEE 802.11b: 16.39 dBm IEEE 802.11g: 15.26 dBm IEEE 802.11n-HT20: 14.95 dBm IEEE 802.11n-HT40: 14.99 dBm 5180 MHz to 5240 MHz: 14.92 dBm 5745 MHz to 5825 MHz: 14.70 dBm
Antenna gain (Max)	2.4GHz WIFI: 1 dBi 5.8G WIFI: 4 dBi
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $Pd=(Pout \cdot G)/(4 \cdot \pi \cdot R^2)$

Where

Pd = Power density in mW/cm², $Pout$ =output power to antenna in Mw

G = gain of antenna in linear scale, $\pi=3.1416$

R = distance between observation point and center of the radiator in cm=20cm

Pd the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation

$$\sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

$Evaluated_k$: the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure Limit_k$: either the general population/uncontrolled maximum permissible exposure (MPE) or specific Absorption rate (SAR) limit for each fixed, mobile, or portable RF source k .

Measurement Result

Operation Mode	Channel Frequency (MHz)	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power (dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
2.4GHz WIFI (802.11b)	2462	16.39	16±1	17	50.119	1	1.259	0.012552	1
5180 MHz to 5240MHz (802.11n 40)	5180	14.92	15±1	16	39.811	4	2.512	0.019894	1
5745 MHz to 5825MHz (802.11n 20)	5745	14.70	15±1	16	39.811	4	2.512	0.019894	1

Maximum Simultaneous transmission MPE Ratio for 2.4G WIFI & 5.8G WIFI

Maximum MPE ratio (2.4G WIFI)	Maximum MPE ratio (5.8G WIFI)	∑ MPE ratios	Limit	Results
0.012552	0.019894	0.032446	1.000	Pass

The Product unsupported at the same time to Transmitting. According to KDB 447498, and no simultaneous SAR measurement is required.

Signature:

