

# RF EXPOSURE REPORT

## FOR

<b>Applicant</b>	:	Shenzhen HOPE Microelectronics Co., Ltd
<b>Address</b>	:	30th floor of 8th Building, C Zone, Vanke Cloud City, Xili Sub-district, Nanshan, Shenzhen, GD, P.R. China
<b>Equipment under Test</b>	:	LoRa Module
<b>Model No.</b>	:	RFM6601
<b>Trade Mark</b>	:	<b>HOPERF</b> <sup>®</sup>
<b>FCC ID</b>	:	2ASEO-RFM6601
<b>Manufacturer</b>	:	Shenzhen HOPE Microelectronics Co., Ltd
<b>Address</b>	:	30th floor of 8th Building, C Zone, Vanke Cloud City, Xili Sub-district, Nanshan, Shenzhen, GD, P.R. China

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

**Tel:** +86-0769-38826678, **E-Mail:** ddt@dgddt.com, <http://www.dgddt.com>

# REPORT

## Table of Contents

- Test report declares.....3
- 1. General information..... 5
  - 1.1. Description of Equipment ..... 5
  - 1.2. Assess laboratory ..... 5
- 2. RF Exposure evaluation ..... 5
  - 2.1. Requirement..... 5
  - 2.2. Refer Evaluation Method..... 6
  - 2.3. Limits ..... 6
  - 2.4. Calculation Method ..... 6
  - 2.5. Antenna Information ..... 6
  - 2.6. Estimation Result ..... 7
  - 2.7. Conclusion..... 7

## Test Report Declare

<b>Applicant</b>	:	Shenzhen HOPE Microelectronics Co., Ltd
<b>Address</b>	:	30th floor of 8th Building, C Zone, Vanke Cloud City, Xili Sub-district, Nanshan, Shenzhen, GD, P.R. China
<b>Equipment under Test</b>	:	LoRa Module
<b>Model No.</b>	:	RFM6601
<b>Trade mark</b>	:	<b>HOPERF</b> <sup>®</sup>
<b>Manufacturer</b>	:	Shenzhen HOPE Microelectronics Co., Ltd
<b>Address</b>	:	30th floor of 8th Building, C Zone, Vanke Cloud City, Xili Sub-district, Nanshan, Shenzhen, GD, P.R. China

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No:</b>	DDT-R22051717-2E05		
<b>Date of Receipt:</b>	Jul. 08, 2022	<b>Date of Test:</b>	Jul. 08, 2022 ~ Aug. 06, 2022

**Prepared By:**

*Ella Gong*

**Ella Gong/Engineer**

**Approved By:**



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

### Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Aug. 06, 2022	

## 1. General information

### 1.1. Description of Equipment

EUT* Name	: LoRa Module
Model Number	: RFM6601
EUT function description	: Please reference user manual of this device
Power supply	: 3.3V
Operation frequency	: 902-928 MHz
Modulation	: CSS
Antenna Type	: RP-SMA antenna, Peak Gain: 2.15 dBi.
Sample Number	: S22051717-01

### 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com).

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

## 2. RF Exposure evaluation

### 2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required

by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

## 2.2. Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

## 2.3. Limits

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

## 2.4. Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

## 2.5. Antenna Information

RFM6601 can only use antenna certificated as follows provided by manufacturer;

Internal Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Note
-------------------------	---------------------------------	------------------------	----------------------	------

Antenna 1	RP-SMA antenna	902-928 MHz	2.15 dBi	915MHz Antenna
-----------	----------------	-------------	----------	----------------

## 2.6. Estimation Result

### 2.6.1 Manufacturing Tolerance

Mode	Maximum Peak power declared by Manufacturer (dBm)
FHSS	$\leq 22$
DTS (Uplink)	$\leq 21$
DTS (Downlink)	$\leq 21$

### 2.6.2 Evaluation Results

Mode	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	(dBm)	(mW)					
FHSS	22	158.49	2.15	1.64	100%	0.052	1.00
DTS (Uplink)	21	125.89	2.15	1.64	100%	0.041	1.00
DTS (Downlink)	21	125.89	2.15	1.64	100%	0.041	1.00

Remark:

1. Maximum power including tune-up tolerance;
2. MPE use distance is 20cm from manufacturer declaration of user manual.

## 2.7. Conclusion

The measurement results comply with the FCC part §2.1091 for the uncontrolled RF Exposure of mobile device.

**END OF REPORT**