FCC ID: 2ASEORFM95C

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)				
(A) Limits for Occupational/Controlled Exposure								
0.3-3.0	614	1.63	*100	6				
3.0-30	1842/1	4.89/1	*900/f ²	6				
30-300	61.4	0.163	1.0	6				
300-1,500			f/300	6				
1,500-100,000			5	6				
	(B) Limits for Gener	ral Population/Uncontrolled	Exposure					
0.3-1.34	614	1.63	*100	30				
1.34-30	824/1	2.19/1	*180/f ²	30				
30-300	27.5	0.073	0.2	30				
300-1,500			f/1500	30				
1,500-100,000			1.0	30				

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E (V/m) = \frac{\sqrt{30*P*G}}{d}$$
 Power Density: $Pd (W/m^2) = \frac{E^2}{377}$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

MAX OUTPUT POWER

Test Channel	Frequency (MHz) Power Setting		Average Output Power (dBm)	LIMIT (dBm)	Verdict
0	915	Default	11.601	30	PASS

Measurement Result

Operation Frequency: LORA: 915 MHz Power density limited: 0.61mW/ cm²

Antenna Type: Reverse SMA Adapter whip antenna

Antenna gain: 2.15 dBi, R=20cm

LORA:

Channel Freq. (MHz)	modulation	conducted power	Tune-up	Max		Antenna		Evaluation result	Power density
		nodulation	power (dBm)	tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric	(IIIVV/CIIIZ)	(IIIVV/CIIIZ)
915	LORA	11.601	11±1	12	15.849	2.15	1.64	0.0052	0.61

Conclusion:

For the max result : 0.0052≤ 0.61 for Max Power Density, compliance RF exposure..

Signature:

NAME AND TITLE (Please print or type): Jason Chen/Manager

Jason chen

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.

Date: 2019/2/14