

## RF EXPOSURE EVALUATION

### EUT Specification

<b>EUT</b>	Shenzhen Linklite Smart Lighting Co., Ltd
<b>Model Number</b>	KT-CS11-16.4, EH-S02MB, EN-S02MB, KT-CS11-12.5, MGmiline138A, MGmiline150A
<b>FCC ID</b>	2ASF2KT-CS11
<b>Antenna gain (Max)</b>	2.21dBi
<b>Operation Frequency</b>	BT: 2402-2480MHz WLAN:2412MHz-2462MHz
<b>Input Rating</b>	DC 12V from AC/DC ADAPTER
<b>Max. output power</b>	BT:6.47dBm WLAN: 802.11b:14.29dBm 802.11g:13.33dBm 802.11n(HT20):14.92dBm 802.11n(HT40):13.49dBm

### Test Requirement:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

11.1 Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$ =output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

$P_i=3.1416$

R= distance between observation point and center of the radiator in cm=20cm

$P_d$  the limit of MPE,  $1\text{mW}/\text{cm}^2$ . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

### 11.2 Measurement Result

Antenna gain: 2.21 dBi

BT :

Mode	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain (Numeric)	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
GFSK	2402	6.47	6±1	7	1.663	0.001659	1
GFSK	2440	0.25	0±1	1	1.663	0.000417	1
GFSK	2480	-2.46	-2±1	-1	1.663	0.000263	1

WiFi:

Mode	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain (Numeric)	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
802.11b	1	14.29	14±1	15	1.663	0.010470	1
	6	13.91	14±1	15	1.663	0.010470	1
	11	13.29	13±1	14	1.663	0.008317	1
802.11g	1	13.33	13±1	14	1.663	0.008317	1
	6	12.91	13±1	14	1.663	0.008317	1
	11	11.62	12±1	13	1.663	0.006606	1
802.11n(HT20)	1	14.92	15±1	16	1.663	0.013181	1
	6	12.13	12±1	13	1.663	0.006606	1
	11	11.73	12±1	13	1.663	0.006606	1
802.11n(HT40)	3	13.25	13±1	14	1.663	0.008317	1
	6	13.49	13±1	14	1.663	0.008317	1
	9	12.2	12±1	13	1.663	0.006606	1

Signature:

*Tiger Xu*

Tiger Xu

Date: 2022-11-10