ONE WORLD • OUR APPROVAL



Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

•••••••••••••••••••••••••••••••••••••••	
Maximum peak output power at device output terminal:	
Cable and Jumper loss:	<u>0.0</u> dB
Maximum peak output power at antenna input terminal:	26.00 dBm
· · · · ·	398.1071706 mW
	3 dBi
Number of Antennae:	1
=	
Total Antenna gain (typical): _	<mark>3</mark> dBi
	1.995262315 (numeric)
Prediction distance:	20 cm
Prediction frequency:	903.24 MHz
MPE limit for uncontrolled exposure at prediction frequency:	0.60216 mW/cm ²
Power density at prediction frequency:	0.158027 mW/cm ²
	1.580266 W/m ²
Tx On time:	1.000000 ms
Tx period time:	1.000000 ms
Average Factor:	
Average Power density at prediction frequency:	1.580266 W/m ²
Maximum allowable antenna gain:	8.809817584 dBi
Margin of Compliance:	5.809817584 dB