

TEST REPORT

Client Information:

Applicant: Iasus Concepts Limited

Applicant add.: Flat 907A, 9/FI., Shiu Fat Industrial Building, 139-141 Wai Yip St.,Kwun Tong, Kowloon, Hong Kong

Manufacturer: Dongguan chang 'an yaosu electronic business department

Manufacturer add.: Room 808, fuyuan business center, no. 5, lane 13, xin 'an maiyuan road, chang 'an town, dongguan city

Product Information:

Product Name: RFID reader/writer

Model No.(HVIN): RFCP-2

Brand Name: N/A

FCC ID: 2ASIJ-RFCP2

IC: 25018-RFCP2

Applicable standards: FCC CFR 47 PART 15 C(15.225)
RSS-210 Issue 10 / RSS-Gen Issue 5

Prepared By:

Dongguan Yaxu (AiT) Technology Limited

No.22, Jinqianling 3rd Street, Jitigang, Huangjiang,Dongguan,
Guangdong, China

Tel.: +86-769-8202 0499 Fax.: +86-769-8202 0495

Date of Receipt: Dec. 01, 2022 Date of Test: Dec. 01, 2022~Dec. 08, 2022

Date of Issue: Dec. 09, 2022 Test Result: Pass

This device described above has been tested by Dongguan Yaxu (AiT) Technology Limited and the test results show that the equipment under test (EUT) is in compliance with the FCC/ISED requirements. And it is applicable only to the tested sample identified in the report.

Note: This report shall not be reproduced except in full, without the written approval of Dongguan Yaxu (AiT) Technology Limited, this document may be altered or revised by Dongguan Yaxu (AiT) Technology Limited, personal only, and shall be noted in the revision of the document. This test report must not be used by the client to claim product endorsement.

Reviewed by: _____

Simba Huang

Approved by: _____

Seal.chen

1 Contents

	Page
COVER PAGE	
1 CONTENTS	2
2 TEST SUMMARY	4
2.1 Statement of the Measurement Uncertainty	4
2.2 Measurement Uncertainty	4
3 TEST FACILITY	5
3.1 Deviation from standard	5
3.2 Abnormalities from standard conditions	5
3.3 Test Location	5
4 GENERAL INFORMATION	6
4.1 Test frequencies	7
4.2 EUT Peripheral List	7
4.3 Test Peripheral List	7
4.4 TEST METHODOLOGY	8
4.5 Description of Test Modes	9
5 EQUIPMENT USED DURING TEST	10
6 TEST RESULTS AND MEASUREMENT DATA	11
6.1 Antenna requirement	11
6.2 Bandwidth of Operating Frequency Measurement	12
6.3 Radiated Emissions Measurement	14
6.9 Field Strength of Fundamental Emissions and Mask Measurement	22
6.4 Frequency Stability Measurement	24
6.5 Conducted Emissions	25
7 TEST SETUP PHOTO	28
8 EUT CONSTRUCTIONAL DETAILS	28

Revision History

Revision	Issue Date	Revisions	Revised By
000	Dec. 09, 2022	Initial Issue	Seal Chen

2 Test Summary

Test Item	Section in CFR 47	Result
Line Conducted Emissions	§15.207(a) RSS-Gen§8.8	Pass
Field Strength of Fundamental Emissions	§15.225(a)(b)(c) RSS-210 §B.6	Pass
Radiated Emissions	§15.225(d) & §15.209 RSS-Gen§6.13 RSS-Gen§8.9 RSS-Gen§8.10	Pass
20dB Bandwidth Occupied Bandwidth	§ 2.1049 RSS-Gen§6.7	Pass
Frequency Stability	§15.225(e) RSS-210 §B.6	Pass
Antenna Requirement	§15.203 RSS-Gen§6.8 RSP-100	Pass

Note

1. Test according to ANSI C63.10:2013, RSS-Gen.
2. The measurement uncertainty is not included in the test result.

2.1 Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the AiT quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

2.2 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	0.009MHz-30MHz	3.10dB	(1)
Radiated Emission	30MHz-1GHz	3.75dB	(1)
Radiated Emission	1GHz-18GHz	3.88dB	(1)
Radiated Emission	18GHz-40GHz	3.88dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	1.20dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

3 Test Facility

The test facility is recognized, certified or accredited by the following organizations:

.CNAS- Registration No: L6177

Dongguan Yaxu (AiT) technology Limited is accredited to ISO/IEC 17025:2017 general Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the competence of testing and calibration laboratories) on April 18, 2022

FCC-Registration No.: 703111 Designation Number: CN1313

Dongguan Yaxu (AiT) technology Limited has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC —Registration No.: 6819A CAB identifier: CN0122

The 3m Semi-anechoic chamber of Dongguan Yaxu (AiT) technology Limited has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 6819A

A2LA-Lab Cert. No.: 6317.01

Dongguan Yaxu (AiT) technology Limited has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

3.1 Deviation from standard

None

3.2 Abnormalities from standard conditions

None

3.3 Test Location

Dongguan Yaxu (AiT) Technology Limited

Address: No.22, Jinqianling 3rd Street, Jitigang, Huangjiang, Dongguan, Guangdong, China

Tel.: +86-769-8202 0499

Fax.: +86-769-8202 0495

4 General Information

EUT Name:	RFID reader/writer
Model No:	RFCP-2
Serial Model:	N/A
Test sample(s) ID:	22120104-1
Sample(s) Status:	Engineer sample
Serial No.:	N/A
Operation frequency:	13.56MHz;
Channel Number:	1 channels
Modulation Technology:	ASK
Antenna Type:	Loop Antenna
Antenna gain:	0dBi (max.)
Hardware version.:	N/A
Software version.:	N/A
Power supply:	DC5V ± 10%150mA
Model different:	N/A
Note:	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

4.1 Test frequencies

EUT channels and frequencies list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	13.56	/	/	/	/

4.2 EUT Peripheral List

No.	Equipment	Manufacturer	EMC Compliance	Model No.	Serial No.	Power cord	Signal cord
1	Notebook	Unowhy	S4200	N/A	N/A	N/A	N/A
2	Watch	Huawei	5X Pro	N/A	N/A	N/A	N/A

4.3 Test Peripheral List

No.	Equipment	Manufacturer	EMC Compliance	Model No.	Serial No.	Power cord	Signal cord
1	N/A	N/A	N/A	N/A	N/A	N/A	N/A

4.4 TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Dongguan Yaxu (AiT) Technology Limit.

EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT Exercise

The EUT was operated in the RFID tag provided by client to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.225 under the FCC Rules Part 15 Subpart C.

General Test Procedures

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013.

4.5 Description of Test Modes

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in Y position.

AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/50Hz modes, recorded worst case.

AC conducted emission pre-test at both at power adapter and power from PC modes, recorded worst case.

Worst-case mode and channel used for 150 KHz-30 MHz power line conducted emissions was the mode and channel with the highest output power.

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power.

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Transmitting mode	Keep the EUT in continuously transmitting mode.		
Test software:	/		
Frequency	13.56 MHz	/	/
Parameters	Default	/	/

5 Equipment Used during Test

No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date
1	Spectrum Analyzer	R&S	FSV40	101470	2022.09.02	2023.09.01
2	EMI Measuring Receiver	R&S	ESR	101660	2022.09.02	2023.09.01
3	Low Noise Pre Amplifier	HP	HP8447E	1937A01855	2022.09.02	2023.09.01
4	Low Noise Pre Amplifier	Tsj	MLA-0120-A02-34	2648A04738	2022.09.02	2023.09.01
5	Passive Loop	ETS	6512	00165355	2022.09.04	2024.09.03
6	TRILOG Super Broadband test Antenna	SCHWARZBECK	VULB9160	9160-3206	2021.08.29	2024.08.28
7	Broadband Horn Antenna	SCHWARZBECK	BBHA9120D	452	2021.08.29	2024.08.28
8	SHF-EHF Horn Antenna 15-40GHz	SCHWARZBECK	BBHA9170	BBHA917036 7d	2020.11.24	2023.11.23
9	EMI Test Receiver	R&S	ESCI	100124	2022.09.02	2023.09.01
10	LISN	Kyoritsu	KNW-242	8-837-4	2022.09.02	2023.09.01
11	LISN	R&S	ESH3-Z2	0357.8810.54-101161-S2	2022.09.02	2023.09.01
12	Pro.Temp&Humi.chamber	MENTEK	MHP-150-1C	MAA0811250 1	2022.09.02	2023.09.01
13	RF Automatic Test system	MW	MW100-RFCB	21033016	2022.09.02	2023.09.01
14	Signal Generator	Agilent	N5182A	MY50143009	2022.09.02	2023.09.01
15	Wideband Radio communication tester	R&S	CMW500	1201.0002K5 0	2022.09.02	2023.09.01
16	RF Automatic Test system	MW	MW100-RFCB	21033016	2022.09.02	2023.09.01
17	DC power supply	ZHAOXIN	RXN-305D-2	2807000255 9	N/A	N/A
18	RE Software	EZ	EZ-EMC_RE	Ver.AIT-03A	N/A	N/A
19	CE Software	EZ	EZ-EMC_CE	Ver.AIT-03A	N/A	N/A
20	RF Software	MW	MTS 8310	2.0.0.0	N/A	N/A
21	temporary antenna connector(Note)	NTS	R001	N/A	N/A	N/A

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

6 Test results and Measurement Data

6.1 Antenna requirement

6.1.1 Standard requirement:

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

According to RSS-Gen,

The applicant for equipment certification, as per RSP-100, must provide a list of all antenna types that may be used with the licence-exempt transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna.

Licence-exempt transmitters that have received equipment certification may operate with different types of antennas. However, it is not permissible to exceed the maximum equivalent isotropically radiated power (e.i.r.p.) limits specified in the applicable standard (RSS) for the licence-exempt apparatus.

Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level.⁹ When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.

6.1.2 EUT Antenna:

The gains of antenna used for transmitting is 0dBi, and the antenna is a Loop antenna connect to PCB board and no consideration of replacement. Please see EUT photo for details.

6.2 Bandwidth of Operating Frequency Measurement

6.4.1 Standard requirement:

Intentional radiators must be designed to ensure that the 20 dB bandwidth of the emissions in the specific band (13.553 ~ 13.567MHz).


6.4.2 Measuring Instruments:

Please refer to equipment's list in this report.

6.4.3 Test Procedures

1. Set resolution bandwidth (RBW) = 100 Hz.
2. Set the video bandwidth (VBW) = 100 Hz.
3. Span = 500Hz.
4. Sweep = auto couple.


6.4.4 Test Setup Layout



6.4.5 Test result

PASS

Frequency (MHz)	-20 dB Bandwidth (Hz)	OCW (Hz)	Limit Bandwidth (MHz)	Verdict
13.56	479.50	472.53	/	Pass



6.3 Radiated Emissions Measurement

6.8.1 Standard requirement:

According to §15.209/ §15.205 or RSS-210 §B.6/RSS-Gen

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\1\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293.	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	\2\)
13.36-13.41			

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

6.8.2 Measuring Instruments and Setting:

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10 th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB/VB 120kHz/1MHz for QP

6.8.3 Test Procedures

1) Sequence of testing 9 kHz to 30 MHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions.

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna height is 1.0 meter.

--- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

--- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).

--- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 3 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.

--- The final measurement will be done with QP detector with an EMI receiver.

--- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height scan range is 1 meter to 2.5 meter.

--- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.

--- The final measurement will be done in the position (turntable, EUT-table and antenna

polarization) causing the highest emissions with Peak and Average detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 1 meter.

--- The EUT was set into operation.

Premereasurement:


--- The antenna is moved spherical over the EUT in different polarisations of the antenna.


Final measurement:

--- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.


--- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

6.8.4 Test Setup Layout





Below 1GHz



Above 1GHz

Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

6.8.5 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

6.8.6 Test result

Temperature	17.0 °C	Humidity	52.1%
Test Engineer	Simba Huang	Configurations	TX

Remarks:

1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which is worse case.

6.3.1 Field Strength of the Fundamental Signal

■ Results of Radiated Emissions (9 KHz~30MHz)

Note: Only recorded the worst test result.

Freq. MHz	Reading dBuV	Factor dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark
0.0785	7.38	43.29	50.67	109.62	-58.95	QP
0.2404	10.16	38.5	48.66	99.95	-51.29	QP
0.7923	18.85	28.07	46.92	69.64	-22.72	QP
1.4322	21.89	24.35	46.24	64.51	-18.27	QP
1.7542	26.46	23.08	49.54	69.5	-19.96	QP
3.9163	30.64	16.68	47.32	69.5	-22.18	QP
13.5600	57.21	13.58	70.79	124.0	-53.21	QP

*Note: Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

Margin = Emission Limit – Emission Values


-- means noise floor.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

6.3.2 Spurious emissions

■ Results of Radiated Emissions (30MHz~1GHz)



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dB	Detector
1	!	54.2610	42.90	-6.59	36.31	40.00	-3.69 QP
2		81.2116	38.05	-11.18	26.87	40.00	-13.13 QP
3	!	108.2667	47.10	-7.78	39.32	43.50	-4.18 QP
4	*	210.7860	44.24	-4.16	40.08	43.50	-3.42 QP
5		431.0316	33.23	-1.17	32.06	46.00	-13.94 QP
6		804.6028	26.49	6.76	33.25	46.00	-12.75 QP

Model name:	RFCP-2	Test Date :	2022-12-02
Polarization :	Horizontal	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	54.2610	40.10	-4.24	35.86	40.00	-4.14	QP
2		81.2117	35.23	-11.13	24.10	40.00	-15.90	QP
3		108.2667	43.58	-7.18	36.40	43.50	-7.10	QP
4	!	213.7632	45.71	-7.17	38.54	43.50	-4.96	QP
5		423.5403	33.44	1.19	34.63	46.00	-11.37	QP
6		731.9203	27.83	6.43	34.26	46.00	-11.74	QP

Note:


Pre-scan all modes and recorded the worst case results in this report.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level = Level.

6.9 Field Strength of Fundamental Emissions and Mask Measurement

6.3.35.2.1. Block Diagram of Test Setup



6.3.45.2.2. Field strength of fundamental emissions limit and Mask limit

The field strength of fundamental emissions shall not exceed 15848 microvolts/meter at 30 meters. The emissions limit in this paragraph is based on measurement instrumentation employing a QP detector.

Frequencies (MHz)	Field Strength (microvolts/meter)	Field Strength (dB μ V/m) at 10m	Field Strength (dB μ V/m) at 3m
13.553 ~ 13.567MHz	15848 at 30m	103.08 (QP)	124 (QP)

Mask Limit:


Frequency (MHz)	Limit (dB μ V/m)	Distance (m)
1.705-13.110	69.5	3
13.110-13.410	80.5	3
13.410-13.553	90.5	3
13.553-13.567	124.0	3
13.567-13.710	90.5	3
13.710-14.010	80.5	3
14.010-30.000	69.5	3

6.3.55.2.3. Test Results

PASS.

The test data please refer to following page:

Note: Only recorded the worst test result.



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	13.5618	57.25	13.58	70.83	124.00	-53.17	peak

Remark:

Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

Emission level (dB μ V/m) = 20 \log Emission level (\mu V/m).

Measured distance is 3m.

All emissions emit from non-NFC function of digital unintentional emissions. All NFC's spurious emissions are below 20dB of limits.

6.4 Frequency Stability Measurement

6.4.1 Standard Applicable

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a full charged battery.

6.4.2 Test Result

Voltage vs. Frequency Stability

Voltage(V)	Measurement Frequency (MHz)	Deviation (KHz)	Deviation (ppm)
DC 5.00V	13.56032	0.32	23.60
DC 4.25V	13.56033	0.33	24.34
DC 5.75V	13.56028	0.28	20.65

Temperature vs. Frequency Stability

Temperature (°C)	Measurement Frequency (MHz)	Deviation (KHz)	Deviation (ppm)
-20	13.56031	0.31	22.86
-10	13.56025	0.25	18.44
0	13.56028	0.28	20.65
10	13.56019	0.19	14.01
20	13.56027	0.27	19.91
30	13.56031	0.31	22.86
40	13.56036	0.36	26.55
50	13.56030	0.3	22.12

6.5 Conducted Emissions

6.9.1 Standard requirement:

According to §15.207 (a) or RSS-Gen: For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

* Decreasing linearly with the logarithm of the frequency

6.9.2 Measuring Instruments and Setting:

Please refer to equipment list in this report. The following table is the setting of the spectrum analyzer.


Spectrum Parameter	Setting
Detector	Peak
Attenuation	Auto
RB / VB (Emission in restricted band)	100KHz/300KHz
RB / VB (Emission in non-restricted band)	100KHz/300KHz

6.9.3 Test Procedures

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz

The spectrum from 9 kHz to 26.5GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


6.9.4 Test Setup Layout




6.9.5 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

6.9.6 Test result

Model name:	RFCP-2	Test Date :	2022-12-02																																																																																																																													
Temperature:	18.9° C	Relative Humidity:	52.0%																																																																																																																													
ATM Pressure:	101 kPa	Test by:	Simba Huang																																																																																																																													
Phase :	Line	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail																																																																																																																													
																																																																																																																																
<p>Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Measurement Result=Reading Level +Correct Factor; Over Limit= Measurement Result- Limit;</p>																																																																																																																																
<table border="1"> <thead> <tr> <th>No.</th> <th>Mk.</th> <th>Freq.</th> <th>Reading Level</th> <th>Correct Factor</th> <th>Measure-ment</th> <th>Limit</th> <th>Over</th> </tr> <tr> <th></th> <th></th> <th>MHz</th> <th>dBuV</th> <th>dB</th> <th>dBuV</th> <th>dBuV</th> <th>dB</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td></td> <td>0.1539</td> <td>39.06</td> <td>11.84</td> <td>50.90</td> <td>65.78</td> <td>-14.88</td> <td>QP</td> </tr> <tr> <td>2</td> <td></td> <td>0.1539</td> <td>11.35</td> <td>11.84</td> <td>23.19</td> <td>55.78</td> <td>-32.59</td> <td>AVG</td> </tr> <tr> <td>3</td> <td></td> <td>0.1980</td> <td>38.34</td> <td>11.16</td> <td>49.50</td> <td>63.69</td> <td>-14.19</td> <td>QP</td> </tr> <tr> <td>4</td> <td></td> <td>0.1980</td> <td>26.68</td> <td>11.16</td> <td>37.84</td> <td>53.69</td> <td>-15.85</td> <td>AVG</td> </tr> <tr> <td>5</td> <td></td> <td>0.2700</td> <td>30.15</td> <td>10.83</td> <td>40.98</td> <td>61.12</td> <td>-20.14</td> <td>QP</td> </tr> <tr> <td>6</td> <td></td> <td>0.2700</td> <td>16.40</td> <td>10.83</td> <td>27.23</td> <td>51.12</td> <td>-23.89</td> <td>AVG</td> </tr> <tr> <td>7</td> <td></td> <td>0.3460</td> <td>26.32</td> <td>10.13</td> <td>36.45</td> <td>59.06</td> <td>-22.61</td> <td>QP</td> </tr> <tr> <td>8</td> <td></td> <td>0.3460</td> <td>12.31</td> <td>10.13</td> <td>22.44</td> <td>49.06</td> <td>-26.62</td> <td>AVG</td> </tr> <tr> <td>9</td> <td></td> <td>13.5620</td> <td>36.99</td> <td>10.25</td> <td>47.24</td> <td>60.00</td> <td>-12.76</td> <td>QP</td> </tr> <tr> <td>10</td> <td>*</td> <td>13.5620</td> <td>35.22</td> <td>10.25</td> <td>45.47</td> <td>50.00</td> <td>-4.53</td> <td>AVG</td> </tr> <tr> <td>11</td> <td></td> <td>20.5980</td> <td>40.23</td> <td>10.80</td> <td>51.03</td> <td>60.00</td> <td>-8.97</td> <td>QP</td> </tr> <tr> <td>12</td> <td></td> <td>20.5980</td> <td>30.47</td> <td>10.80</td> <td>41.27</td> <td>50.00</td> <td>-8.73</td> <td>AVG</td> </tr> </tbody> </table>				No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB	dBuV	dBuV	dB	Detector	1		0.1539	39.06	11.84	50.90	65.78	-14.88	QP	2		0.1539	11.35	11.84	23.19	55.78	-32.59	AVG	3		0.1980	38.34	11.16	49.50	63.69	-14.19	QP	4		0.1980	26.68	11.16	37.84	53.69	-15.85	AVG	5		0.2700	30.15	10.83	40.98	61.12	-20.14	QP	6		0.2700	16.40	10.83	27.23	51.12	-23.89	AVG	7		0.3460	26.32	10.13	36.45	59.06	-22.61	QP	8		0.3460	12.31	10.13	22.44	49.06	-26.62	AVG	9		13.5620	36.99	10.25	47.24	60.00	-12.76	QP	10	*	13.5620	35.22	10.25	45.47	50.00	-4.53	AVG	11		20.5980	40.23	10.80	51.03	60.00	-8.97	QP	12		20.5980	30.47	10.80	41.27	50.00	-8.73	AVG
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																																																																																																									
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector																																																																																																																								
1		0.1539	39.06	11.84	50.90	65.78	-14.88	QP																																																																																																																								
2		0.1539	11.35	11.84	23.19	55.78	-32.59	AVG																																																																																																																								
3		0.1980	38.34	11.16	49.50	63.69	-14.19	QP																																																																																																																								
4		0.1980	26.68	11.16	37.84	53.69	-15.85	AVG																																																																																																																								
5		0.2700	30.15	10.83	40.98	61.12	-20.14	QP																																																																																																																								
6		0.2700	16.40	10.83	27.23	51.12	-23.89	AVG																																																																																																																								
7		0.3460	26.32	10.13	36.45	59.06	-22.61	QP																																																																																																																								
8		0.3460	12.31	10.13	22.44	49.06	-26.62	AVG																																																																																																																								
9		13.5620	36.99	10.25	47.24	60.00	-12.76	QP																																																																																																																								
10	*	13.5620	35.22	10.25	45.47	50.00	-4.53	AVG																																																																																																																								
11		20.5980	40.23	10.80	51.03	60.00	-8.97	QP																																																																																																																								
12		20.5980	30.47	10.80	41.27	50.00	-8.73	AVG																																																																																																																								

Model name:	RFCP-2	Test Date :	2022-12-02
Temperature:	18.9° C	Relative Humidity:	52.0%
ATM Pressure:	101 kPa	Test by:	Simba Huang
Phase :	Neutral	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq. MHz	Reading	Correct	Measure-	Limit	Over
			Level dBuV	Factor dB	ment dBuV		
1		0.1500	38.91	11.94	50.85	65.99	-15.14 QP
2		0.1500	21.04	11.94	32.98	55.99	-23.01 AVG
3		0.2020	37.28	11.12	48.40	63.52	-15.12 QP
4		0.2020	23.02	11.12	34.14	53.52	-19.38 AVG
5		0.2660	34.12	10.84	44.96	61.24	-16.28 QP
6		0.2660	21.83	10.84	32.67	51.24	-18.57 AVG
7		0.3420	30.39	10.13	40.52	59.15	-18.63 QP
8		0.3420	15.55	10.13	25.68	49.15	-23.47 AVG
9		1.9860	22.74	9.96	32.70	56.00	-23.30 QP
10		1.9860	14.87	9.96	24.83	46.00	-21.17 AVG
11	*	20.2939	40.80	10.76	51.56	60.00	-8.44 QP
12		20.2939	29.78	10.76	40.54	50.00	-9.46 AVG

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7 Test Setup Photo

Reference to the **appendix Setup photo** for details.

8 EUT Constructional Details

Reference to the appendix **External EUT photo & Internal EUT photo** for details.

-----End-----