

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant: PIN GENIE, INC. DBA LOCKLY
Address of applicant: 676 Transfer Rd., St. Paul, MN 55114

Manufacturer: Smart Electronic Industrial (Dong Guan) Co., Ltd.
Address of manufacturer: Qing Long Road, Long Jian Tian Village, Huang Jiang Town,
Dong Guan, Guang Dong, China

General Description of EUT:

Product Name: Electronic Deadbolt lock with FP/BLE/Z-WAVE
Brand Name: LOCKLY
Model No.: PGD728FZP
Adding Model(s): PGD728WP ZU, PGD728WP ZU1
FCC ID: 2ASIVPGD768FNP
Rated Voltage: Input:DC 6V,1.5V*4(*2)
Power Adapter: /

Technical Characteristics of EUT:

BLE

Bluetooth Version: V5.0 (BLE mode)
Frequency Range: 2402-2480MHz
RF Output Power: -2.46dBm (Conducted)
Data Rate: 1Mbps
Modulation: GFSK
Quantity of Channels: 40
Channel Separation: 2MHz
Type of Antenna: FPC Antenna
Antenna Gain: -0.4dBi

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalent power density

1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

Maximum Tune-Up output power: -2(dBm)

Maximum peak output power at antenna input terminal: 0.63 (mW)

Prediction distance: >20(cm)

Prediction frequency: 2402 (MHz)

Antenna gain: -0.4(dBi)

Directional gain (numeric gain): 0.91

The worst case is power density at prediction frequency at 20cm: 0.0001(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Result: Pass