



FCC/IC - TEST REPORT

Report Number : **68.950.22.0462.01** Date of Issue: **June 6, 2022**

Model / HVIN : **AP6398S2**

Product Type : Wi-Fi and Bluetooth functionalities module

Applicant : Roboteam Home Technology (Shenzhen) Co., Ltd

Address : 22F, CHANGFU JINMAO BUILDING NO.5 SHIHUA ROAD,
FUTIAN DISTRICT, 518000 SHENZHEN, PEOPLE'S REPUBLIC
OF CHINA

Manufacturer : Roboteam Home Technology (Shenzhen) Co., Ltd

Address : 22F, CHANGFU JINMAO BUILDING NO.5 SHIHUA ROAD,
FUTIAN DISTRICT, 518000 SHENZHEN, PEOPLE'S REPUBLIC
OF CHINA

Test Result : **Positive** **Negative**

Total pages including Appendices : **62**

Any use for advertising purposes must be granted in writing. This technical report may only be quoted in full. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production. For further details, please see testing and certification regulation, chapter A-3.4.



1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory	3
3	Description of the Equipment Under Test	4
4	Summary of Test Standards	5
5	Summary of Test Results	6
6	General Remarks	7
7	Test Setups	8
8	Systems test configuration	9
9	Technical Requirement	10
9.1	Conducted Emission	10
9.2	Conducted peak output power & EIRP	13
9.3	20 dB bandwidth and 99% Occupied Bandwidth	15
9.4	Carrier Frequency Separation	25
9.5	Number of hopping frequencies	28
9.6	Dwell Time.....	31
9.7	Spurious RF conducted emissions.....	39
9.8	Band edge testing	50
9.9	Spurious radiated emissions for transmitter	56
10	Test Equipment List.....	60
11	System Measurement Uncertainty	62



2 Details about the Test Laboratory

Details about the Test Laboratory

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12 & 13, Zhiheng Wisdomland Business Park, Nantou Checkpoint Road
2, Nanshan District
Shenzhen 518052
P.R. China

Telephone: 86 755 8828 6998
Fax: 86 755 828 5299

FCC Registration No.: 514049

FCC Designation Number: CA5009

IC Registration No.: 10320A

3 Description of the Equipment Under Test

Product:	Wi-Fi and Bluetooth functionalities module
Model no.:	AP6398S2
Hardware Version Identification No. (HVIN)	AP6398S2
Brand name:	t e m i
FCC ID:	2ASJLAP6398S2
IC:	24774-AP6398S2
Options and accessories:	N/A
Rating:	Supplied by 3.3VDC
RF Transmission Frequency:	2402MHz-2480MHz
No. of Operated Channel:	79
Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Type:	Integrated antenna
Antenna 1	Gain: -0.5dBi
Antenna 2	Gain: -2.5dBi
Description of the EUT:	The Equipment Under Test (EUT) is a Wi-Fi and Bluetooth functionalities module which support Bluetooth function and Wi-Fi operated at 5GHz and 2.4GHz. Only Bluetooth (BR+EDR) included in this report.

NOTE 1: The above EUT's information is declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

NOTE 2: This report contains two kinds of antenna, they are identical only except antenna gain, testing only performed at the antenna support higher gain.

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2020 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-Gen Issue 5 April 2018 + A1 + A2	General Requirements for Compliance of Radio Apparatus
RSS-247 Issue 2 February 2017	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSS) and License-Exempt Local Area Network (LE- LAN) Devices

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 Measurement Guidance and ANSI C63.10 (2013).

5 Summary of Test Results

Technical Requirements			
FCC Part 15 Subpart C/ RSS-247 Issue 2/RSS-Gen Issue 5			
Test Condition		Pages	Test Result
§15.207& RSS-Gen 8.8	Conducted emission AC power port	10	Pass
§15.247(b)(1) & RSS-247 5.4(b)	Conducted peak output power	13	Pass
RSS-247 5.4(b)	Equivalent Isotropic Radiated Power	13	Pass
§15.247(e) & RSS-247 5.2(b)	Power spectral density	--	N/A
§15.247(a)(2) & RSS-247 5.2(a) & RSS-Gen 6.7	6dB bandwidth and 99% Occupied Bandwidth	--	N/A
§15.247(a)(1) & RSS-247 5.1(a) & RSS-Gen 6.7	20dB bandwidth and 99% Occupied Bandwidth	15	Pass
§15.247(a)(1) & RSS-247 5.1(b)	Min. of Hopping Channel Carrier Frequency Separation	25	Pass
§15.247(a)(1)(iii) & RSS-247 5.1(d)	Min number of hopping frequencies	28	Pass
§15.247(a)(1)(iii) & RSS-247 5.1(d)	Dwell Time - Average Time of Occupancy	31	Pass
§15.247(d) & RSS-247 5.5	Spurious RF conducted emissions	34	Pass
§15.247(d) & RSS-247 5.5	Band edge	45	Pass
§15.247(d) & §15.209 & RSS-247 5.5 & RSS-Gen 6.13	Spurious radiated emissions for transmitter	51	Pass
§15.203 & RSS-Gen 6.8	Antenna requirement	See note 2	Pass

Note 1: N/A=Not Applicable.

Note 2: The EUT uses an external antenna and manufacturer will stick it down with glue, which gain is - 0.5dBi. In accordance to §15.203 & RSS-Gen 6.8, it is considered sufficiently to comply with the provisions of this section.

6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2ASJLAP6398S2, IC: 24774-AP6398S2, complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C rules and RSS-247, RSS-GEN.

SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment Under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.


Sample Received Date: April 25, 2022

Testing Start Date: April 27, 2022

Testing End Date: June 6, 2022


- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch -

Reviewed by:



Laurent Yuan
Section Manager

Prepared by:



Alan Xiong
Project Engineer

Tested by:




Carry Cai
Test Engineer




7 Test Setups


7.1 AC Power Line Conducted Emission test setups




7.2 Radiated test setups Below 1GHz



Above 1GHz



7.3 Conducted RF test setups



8 Systems Test Configuration

Auxiliary Equipment Used during Test:

Description	Manufacturer	Model NO.	S/N
Laptop	Thinkpad	X230	0A72162
Adapter	HOLOTO	ADS-25FSG-12	12VDC, 2.0A

Cables Used During Test:

Cable	Length	Shielded/unshielded	With / without ferrite
USB Cable	1.0m	Shielded	Without ferrite

The system was configured to hopping mode and non-hopping mode.

Hopping mode: typical working mode (normal hopping status)

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power

9 Technical Requirement

9.1 Conducted Emission

Test Method

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both sides of AC line were checked for maximum conducted interference.
6. The frequency range from 150 kHz to 30 MHz was searched.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


Limit

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Conducted Emission

Product Type : Wi-Fi and Bluetooth functionalities module
 M/N : AP6398S2
 Operating Condition : Normal Working
 Test Specification : Line
 Comment : AC 120V/60Hz




Frequency (MHz)	Max Peak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.162000	40.21	---	65.36	25.15	L1	9.73
0.254000	41.98	---	61.63	19.64	L1	9.67
0.298000	---	41.03	50.30	9.26	L1	9.66
0.298000	44.24	---	60.30	16.06	L1	9.66
0.442000	32.38	---	57.02	24.65	L1	9.65
0.846000	31.39	---	56.00	24.61	L1	9.66
1.246000	31.43	---	56.00	24.57	L1	9.66

Remark:
 Max Peak= Read level + Corrector factor
 Correct factor=cable loss + LISN factor

Conducted Emission

Product Type : Wi-Fi and Bluetooth functionalities module
 M/N : AP6398S2
 Operating Condition : Normal Working
 Test Specification : Neutral
 Comment : AC 120V/60Hz



Frequency (MHz)	Max Peak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.162000	36.81	---	65.36	28.55	N	9.77
0.254000	38.08	---	61.63	23.55	N	9.70
0.298000	---	36.65	50.30	13.65	N	9.70
0.298000	43.57	---	60.30	16.73	N	9.70
0.702000	28.03	---	56.00	27.97	N	9.68
5.026000	33.75	---	60.00	26.25	N	9.87
15.730000	40.31	---	60.00	19.69	N	10.35

Remark:
 Max Peak= Read level + Corrector factor
 Correct factor=cable loss + LISN factor

9.2 Conducted Peak Output Power & EIRP

Test Method

1. The RF output of EUT was connected to the test receiver by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following test receiver settings:
Span = approximately 5 times the 20dB bandwidth, centered on a hopping channel
RBW > the 20dB bandwidth of the emission being measured, VBW ≥ RBW,
Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power and record the results in the test report.
5. Repeat above procedures until all frequencies measured were complete.

Limits

According to §15.247 (b) (1) & RSS-247 5.4(b), conducted peak output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

According to & RSS-247 5.4(b), EIRP limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤4	≤36

Conducted Peak Output Power & EIRP

Bluetooth Mode GFSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Antenna Gain dBi	EIRP dBm	Result
Low channel 2402MHz	5.92	-0.5	5.42	Pass
Middle channel 2441MHz	5.85	-0.5	5.35	Pass
High channel 2480MHz	5.83	-0.5	5.33	Pass

Bluetooth Mode $\pi/4$ -DQPSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Antenna Gain dBi	EIRP dBm	Result
Low channel 2402MHz	7.13	-0.5	6.63	Pass
Middle channel 2441MHz	6.65	-0.5	6.15	Pass
High channel 2480MHz	7.10	-0.5	6.60	Pass

Bluetooth Mode 8DPSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Antenna Gain dBi	EIRP dBm	Result
Low channel 2402MHz	7.66	-0.5	7.16	Pass
Middle channel 2441MHz	7.13	-0.5	6.63	Pass
High channel 2480MHz	7.60	-0.5	7.10	Pass

9.3 20 dB Bandwidth and 99% Occupied Bandwidth

Test Method

1. The RF output of EUT was connected to the test receiver by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Use the following test receiver settings:
Span = approximately 5 times the 20dB bandwidth, centered on a hopping channel
RBW > the 20dB bandwidth of the emission being measured, VBW \geq RBW,
Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth. Record the results.
5. Repeat above procedures until all frequencies measured were complete.

Limit

Limit [kHz]


N/A

20 dB bandwidth and 99% Occupied Bandwidth


Bluetooth Mode GFSK Modulation test result

Frequency MHz	20 dB Bandwidth MHz	99% Bandwidth MHz	Limit MHz	Result
2402	1.131	0.923	--	Pass
2441	1.128	0.905	--	Pass
2480	1.134	0.902	--	Pass

Low channel 2402MHz




Date: 9 MAY.2022 10:39:53




Date: 9 MAY.2022 10:39:42

20 dB bandwidth and 99% Occupied Bandwidth

Middle channel 2441MHz



Date: 9 MAY.2022 10:42:10




Date: 9 MAY.2022 10:42:00

20 dB bandwidth and 99% Occupied Bandwidth

High channel 2480MHz



Date: 9 MAY 2022 10:43:51




Date: 9 MAY 2022 10:43:40

20 dB bandwidth and 99% Occupied Bandwidth


Bluetooth Mode $\pi/4$ -DQPSK Modulation test result

Frequency MHz	20 dB Bandwidth MHz	99% Bandwidth MHz	Limit MHz	Result
2402	1.410	1.199	--	Pass
2441	1.410	1.193	--	Pass
2480	1.407	1.193	--	Pass

Low channel 2402MHz



Date: 9.MAY.2022 10:45:43




Date: 9.MAY.2022 10:45:32

20 dB bandwidth and 99% Occupied Bandwidth

Middle channel 2441MHz



Date: 9 MAY.2022 10:47:34




Date: 9 MAY.2022 10:47:23

20 dB bandwidth and 99% Occupied Bandwidth

High channel 2480MHz



Date: 9 MAY.2022 10:49:16



Date: 9 MAY.2022 10:49:06

20 dB bandwidth and 99% Occupied Bandwidth


Bluetooth Mode 8DPSK Modulation test result

Frequency MHz	20 dB Bandwidth MHz	99% Bandwidth MHz	Limit MHz	Result
2402	1.404	1.202	--	Pass
2441	1.404	1.199	--	Pass
2480	1.407	1.199	--	Pass

Low channel 2402MHz



Date: 9 MAY 2022 10:51:05




Date: 9 MAY 2022 10:50:54

20 dB bandwidth and 99% Occupied Bandwidth

Middle channel 2441MHz



Date: 9 MAY.2022 10:52:48




Date: 9 MAY.2022 10:52:37

20 dB bandwidth and 99% Occupied Bandwidth

High channel 2480MHz



Date: 9 MAY.2022 10:54:33



Date: 9 MAY.2022 10:54:23

9.4 Carrier Frequency Separation

Test Method

1. The RF output of EUT was connected to the test receiver by RF cable The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit to hopping mode.
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels, RBW \geq 1% of the span, VBW) \geq RBW, Sweep = auto, Detector function = peak
4. By using the Max-Hold function record the separation of two adjacent channels.
5. Measure the frequency difference of these two adjacent channels by spectrum analyzer marker function. Record the results.
6. Repeat above procedures until all frequencies measured were complete.

Limit

Limit kHz
\geq 25KHz or 2/3 of the 20 dB bandwidth which is greater

Limit


Frequency MHz	2/3 of 20 dB Bandwidth kHz
2402	887
2441	940
2480	940

Carrier Frequency Separation

Test result: The measurement was performed with the typical configuration (normal hopping status).

GFSK Modulation test result


Modulation	Frequency MHz	Carrier Frequency Separation MHz	Result
GFSK	2441	1.000	Pass
$\pi/4$ -DQPSK	2441	1.009	Pass
8DPSK	2441	0.997	Pass



Date: 9 MAY.2022 11:01:19


Carrier Frequency Separation

$\pi/4$ -DQPSK Mode: 2441MHz



Date: 9 MAY.2022 11:13:49

8DPSK Mode: 2480MHz



Date: 9 MAY.2022 11:20:21

9.5 Number of Hopping Frequencies

Test Method

1. The RF output of EUT was connected to the test receiver by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit to hopping mode.
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels, $RBW \geq 1\%$ of the span, $VBW \geq RBW$, Sweep = auto, Detector function = peak
4. Set the spectrum analyzer on Max-Hold Mode,
5. Record all the signals from each channel until each one has been recorded.
6. Repeat above procedures until all frequencies measured were complete.

Limit


Limit
number
—————
 ≥ 15

Number of Hopping Frequencies

Test result: The measurement was performed with the typical configuration (normal hopping status), and the total hopping channels is constant for the all modulation mode according with the Bluetooth Core Specification.


Number of hopping frequencies	Result
79	Pass

GFSK Mode



Date: 9 MAY 2022 11:01:36


$\pi/4$ -DQPSK Mode



Date: 9 MAY 2022 11:14:11

Number of Hopping Frequencies

8DPSK Mode



Date: 9.MAY.2022 11:20:39

9.6 Dwell Time

Test Method

1. The RF output of EUT was connected to the test receiver by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit to hopping mode.
3. Use the following spectrum analyzer settings:
RBW: 1MHz; VBW: 1MHz; SPAN: Zero Span
Set the spectrum analyzer on Max-Hold Mode,
4. Adjust the center frequency of spectrum analyzer on any frequency be measured.
5. Measure the Dwell Time by spectrum analyzer Marker function. Record the results.
Dwell Time = Burst Width * Total Hops
6. Repeat above procedures until all frequencies measured were complete.

Limit

The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Dwell Time

Dwell time


The maximum dwell time shall be 0.4 s.


According to the Bluetooth Core Specification, the worse result (DH5 mode) was reported to show compliance.

The Dwell Time = Burst Width * Total Hops. The detailed calculations are showed as follows:
 The duration for dwell time calculation: 0.4 [s] * hopping number = 0.4 [s] * 79 [ch] = 31.6 [s*ch];
 The burst width, which is directly measured, refers to the duration on one channel hop.


Test Result

Test Mode	Antenna	Channel	Burst Width (ms)	Total Hops	Result (s)	Limit (s)	Verdict
DH1	Ant0	Hop	0.38	330	0.125	<=0.4	PASS
DH3	Ant0	Hop	1.63	160	0.26	<=0.4	PASS
DH5	Ant0	Hop	2.87	110	0.315	<=0.4	PASS
2DH1	Ant0	Hop	0.38	320	0.123	<=0.4	PASS
2DH3	Ant0	Hop	1.63	150	0.244	<=0.4	PASS
2DH5	Ant0	Hop	2.87	90	0.258	<=0.4	PASS
3DH1	Ant0	Hop	0.38	320	0.123	<=0.4	PASS
3DH3	Ant0	Hop	1.63	180	0.293	<=0.4	PASS
3DH5	Ant0	Hop	2.87	100	0.287	<=0.4	PASS








DH3_Ant0_Hop





DH5_Ant0_Hop






2DH1_Ant0_Hop








2DH3_Ant0_Hop





2DH5_Ant0_Hop






3DH1_Ant0_Hop








3DH3_Ant0_Hop



3DH5_Ant0_Hop





9.7 Spurious RF Conducted Emissions

Test Method


1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
4. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency


Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20

Spurious RF Conducted Emissions


Test Mode	Antenna	Channel (MHz)	Frequency Range (MHz)	Reference Level	Result (dBm)	Limit (dBm)	Verdict
DH5	Ant0	2402	Reference	5.41	5.41	---	PASS
			30~1000	30~1000	-68.22	<=-14.59	PASS
			1000~26500	1000~26500	-45.71	<=-14.59	PASS
		2441	Reference	5.16	5.16	---	PASS
			30~1000	30~1000	-67.6	<=-14.84	PASS
			1000~26500	1000~26500	-49.27	<=-14.84	PASS
		2480	Reference	5.83	5.83	---	PASS
			30~1000	30~1000	-67.77	<=-14.17	PASS
			1000~26500	1000~26500	-50.31	<=-14.17	PASS
2DH5	Ant0	2402	Reference	4.29	4.29	---	PASS
			30~1000	30~1000	-67.82	<=-15.71	PASS
			1000~26500	1000~26500	-44.55	<=-15.71	PASS
		2441	Reference	3.93	3.93	---	PASS
			30~1000	30~1000	-67.74	<=-16.07	PASS
			1000~26500	1000~26500	-49.03	<=-16.07	PASS
		2480	Reference	4.56	4.56	---	PASS
			30~1000	30~1000	-68.06	<=-15.44	PASS
			1000~26500	1000~26500	-48.88	<=-15.44	PASS
3DH5	Ant0	2402	Reference	4.24	4.24	---	PASS
			30~1000	30~1000	-68.38	<=-15.76	PASS
			1000~26500	1000~26500	-45.26	<=-15.76	PASS
		2441	Reference	3.86	3.86	---	PASS
			30~1000	30~1000	-68.28	<=-16.14	PASS
			1000~26500	1000~26500	-48.24	<=-16.14	PASS
		2480	Reference	4.50	4.50	---	PASS
			30~1000	30~1000	-67.86	<=-15.5	PASS
			1000~26500	1000~26500	-48.73	<=-15.5	PASS






Date: 9 MAY 2022 10:40:15

DH5_Ant0_2402_1000~26500




Date: 9 MAY 2022 10:40:22

DH5_Ant0_2441_0~Reference




Date: 9 MAY 2022 10:42:16

DH5_Ant0_2441_30~1000




Date: 9 MAY 2022 10:42:22

DH5_Ant0_2441_1000~26500




Date: 9 MAY 2022 10:42:30

DH5_Ant0_2480_0~Reference




Date: 9 MAY 2022 10:44:06

DH5_Ant0_2480_30~1000




Date: 9 MAY 2022 10:44:12

DH5_Ant0_2480_1000~26500




Date: 9 MAY 2022 10:44:20

2DH5_Ant0_2402_0~Reference




Date: 9 MAY 2022 10:45:57

2DH5_Ant0_2402_30~1000




Date: 9 MAY 2022 10:46:03

2DH5_Ant0_2402_1000~26500




Date: 9 MAY 2022 10:46:11

2DH5_Ant0_2441_0~Reference




Date: 9 MAY 2022 10:47:39

2DH5_Ant0_2441_30~1000




Date: 9 MAY 2022 10:47:46

2DH5_Ant0_2441_1000~26500




Date: 9 MAY 2022 10:47:53

2DH5_Ant0_2480_0~Reference




Date: 9 MAY 2022 10:49:31

2DH5_Ant0_2480_30~1000




Date: 9 MAY 2022 10:49:37

2DH5_Ant0_2480_1000~26500




Date: 9 MAY 2022 10:49:45

3DH5_Ant0_2402_0~Reference




Date: 9 MAY 2022 10:51:19

3DH5_Ant0_2402_30~1000




Date: 9 MAY 2022 10:51:26

3DH5_Ant0_2402_1000~26500




Date: 9 MAY 2022 10:51:33

3DH5_Ant0_2441_0~Reference




Date: 9 MAY 2022 10:52:53

3DH5_Ant0_2441_30~1000




Date: 9 MAY 2022 10:52:59

3DH5_Ant0_2441_1000~26500




Date: 9 MAY 2022 10:53:07

3DH5_Ant0_2480_0~Reference




Date: 9 MAY 2022 10:54:48

3DH5_Ant0_2480_30~1000



Date: 9 MAY.2022 10:54:54

3DH5_Ant0_2480_1000~26500



Date: 9 MAY.2022 10:55:02

9.8 Band Edge Testing

Test Method



1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
4. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency
6. Set to the maximum power setting and enable the EUT hopping mode, repeat the test.


Limit:

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.

Band Edge


Test Mode	Antenna	Channel	Channel (MHz)	Reference Level (dBm)	Result (dBm)	Limit (dBm)	Verdict
DH5	Ant0	Low	2402	4.78	-55.64	<=-15.22	PASS
		High	2480	5.73	-57.36	<=-14.27	PASS
		Low	Hop_2402	5.01	-58.63	-14.99	PASS
		High	Hop_2480	5.63	-56.56	-14.37	PASS
2DH5	Ant0	Low	2402	4.32	-54.44	<=-15.68	PASS
		High	2480	4.35	-57.27	<=-15.65	PASS
		Low	Hop_2402	1.28	-58.37	-18.72	PASS
		High	Hop_2480	4.16	-57.94	-15.84	PASS
3DH5	Ant0	Low	2402	4.18	-54.34	<=-15.82	PASS
		High	2480	4.41	-57.39	<=-15.59	PASS
		Low	Hop_2402	2.86	-58.58	-17.14	PASS
		High	Hop_2480	4.33	-57.72	-15.67	PASS






Date: 9 MAY 2022 10:56:48

DH5_Ant0_High_Hop_2480




Date: 9 MAY 2022 11:07:40

2DH5_Ant0_Low_2402




Date: 9 MAY 2022 10:45:52

2DH5_Ant0_High_2480




Date: 9 MAY 2022 10:49:25

2DH5_Ant0_Low_Hop_2402




Date: 9 MAY 2022 11:12:59

2DH5_Ant0_High_Hop_2480




Date: 9 MAY 2022 11:16:31

3DH5_Ant0_Low_2402




Date: 9 MAY 2022 10:51:14

3DH5_Ant0_High_2480




Date: 9 MAY 2022 10:54:42

3DH5_Ant0_Low_Hop_2402



Date: 9 MAY 2022 11:19:42

3DH5_Ant0_High_Hop_2480



Date: 9 MAY 2022 11:22:59

9.9 Spurious Radiated Emissions for Transmitter

Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meters chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
4. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
5. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
6. Use the following spectrum analyzer settings According to C63.10:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.For average measurement:
VBW = 10 Hz, when duty cycle is no less than 98 percent.
VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
7. Repeat above procedures until all frequencies measured were complete.

Note:

- 1: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for peak detection (PK) at frequency above 1GHz.
- 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average ((duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($20\log(1/\text{duty cycle})$).
- 4: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.

Spurious Radiated Emissions for Transmitter

Limit

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205 & RSS-GEN 8.10, must comply with the radiated emission limits specified in section 15.209 & RSS-Gen 6.13.

Frequency MHz	Field Strength uV/m	Field Strength dBµV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

The only worse case (which is subject to the maximum EIRP, GFSK mode, 2402MHz) test result is listed in the report.

Transmitting spurious emission test result as below:

GFSK Modulation 2402MHz Test Result

Frequency Band	Frequency MHz	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Margin dBuV/m	Correct factor (dB/m)	Result
30-1000MHz	45.142778	21.29	H	40.00	QP	18.71	20.41	Pass
	49.723333	21.33	H	40.00	QP	18.67	20.70	Pass
	72.733889	20.60	H	40.00	QP	19.40	15.98	Pass
	111.426111	20.45	H	43.50	QP	23.05	18.26	Pass
	346.220000	28.87	H	46.00	QP	17.13	22.76	Pass
	836.285556	35.12	H	46.00	QP	10.88	29.96	Pass
	Other Frequencies	--	H	--	QP	--	--	Pass
	30.000000	32.21	V	40.00	QP	7.79	17.38	Pass
	36.897778	24.74	V	40.00	QP	15.26	18.18	Pass
	67.345000	28.09	V	40.00	QP	11.91	17.90	Pass
	77.098889	29.90		40.00		10.10	14.37	Pass
	84.805000	27.93		40.00		12.07	14.77	Pass
	123.497222	28.08	V	43.50	QP	15.42	16.20	Pass
Other Frequencies	--	V	--	QP	--	--	Pass	
1000-2500MHz	*2340.00	41.35	H	74	PK	32.65	-5.67	Pass
	*4771.50	46.88	H	74	PK	27.12	3.67	Pass
	*7405.50	42.54	H	74	PK	31.46	9.15	Pass
	8949.00	45.12	H	74	PK	28.88	12.78	Pass
	*12588.0	48.73	H	74	PK	25.27	14.90	Pass
	14968.50	51.45	H	74	PK	22.55	18.83	Pass
	Other frequency	---	H	74	PK	---	---	Pass
	*1596.50	44.83	V	74	PK	29.17	-9.49	Pass
	*2353.50	42.20	V	74	PK	31.80	-5.76	Pass
	*4821.00	47.64	V	74	PK	26.36	3.93	Pass
	*7568.00	41.53	V	74	PK	32.47	10.03	Pass
	10568.50	45.03	V	74	PK	28.97	12.08	Pass
	16821.50	50.99	V	74	PK	23.01	22.01	Pass
Other frequency	---	V	74	PK	---	---	Pass	

Remark:

- (1) "*" means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205 & RSS-GEN 8.10.
- (2) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (3) Corrected Amplitude = Read level + Corrector factor

Above 1GHz: Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain
Below 1GHz: Corrector factor = Antenna Factor + Cable Loss

10 Test Equipment List

List of Test Instruments

Radiated Emission Test

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	68-4-74-14-002	101269	1	2022-6-4
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9162	68-4-80-19-003	284	1	2023-1-17
Wave Guide Antenna	ETS	3117	68-4-80-19-001	00218954	1	2022-5-24
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-001	100745	1	2022-10-10
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-002	100746	1	2022-10-10
Sideband Horn Antenna	Q-PAR	QWH-SL-18-40-K-SG	68-4-80-14-008	12827	1	2022-7-21
Pre-amplifier	Rohde & Schwarz	SCU 40A	68-4-29-14-002	100432	1	2022-7-27
Attenuator	Mini-circuits	UNAT-6+	68-4-81-21-002	15542	1	2022-8-23
3m Semi-anechoic chamber	TDK	SAC-3 #2	68-4-90-19-006	----	2	2023-5-28
Test software	Rohde & Schwarz	EMC32	68-4-90-19-006-A01	Version10.35.0 2	N/A	N/A

Conducted Emission Test

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 3	68-4-74-14-001	101782	1	2022-6-4
LISN	Rohde & Schwarz	ENV4200	68-4-87-14-001	100249	1	2022-6-5
LISN	Rohde & Schwarz	ENV432	68-4-87-16-001	101318	1	2022-6-5
LISN	Rohde & Schwarz	ENV216	68-4-87-14-002	100326	1	2022-6-5
ISN	Rohde & Schwarz	ENY81	68-4-87-14-003	100177	1	2022-6-5
ISN	Rohde & Schwarz	ENY81-CA6	68-4-87-14-004	101664	1	2022-6-5
High Voltage Probe	Schwarzbeck	TK9420(VT9420)	68-4-27-14-001	9420-584	1	2022-6-5
RF Current Probe	Rohde & Schwarz	EZ-17	68-4-27-14-002	100816	1	2022-6-5
Attenuator	Shanghai Huaxiang	TS2-26-3	68-4-81-16-003	080928189	1	2022-6-3
Test software	Rohde & Schwarz	EMC32	68-4-90-14-003-A10	Version9.15.0 0	N/A	N/A
Shielding	TDK	CSR #1	68-4-90-19-	----	3	2022-11-07

Room			004			
------	--	--	-----	--	--	--

Conducted RF Test System

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
Signal Analyzer	Rohde & Schwarz	FSV40	68-4-74-14-004	101030	1	2022-6-3
RF Switch Module	Rohde & Schwarz	OSP120/OSP-B157	68-4-93-14-003	101226/100851	1	2022-6-3
Power Splitter	Weinschel	1580	68-4-85-14-001	SC319	1	2022-6-3
Test software	Tonscend	System for BT/WIFI	68-4-74-14-006-A13	Version 2.6.77.0518	N/A	N/A
Shielding Room	TDK	TS8997	68-4-90-19-003	----	3	2022-11-07

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Conducted Emission 150kHz-30MHz (for test using AMN ENV432 or ENV4200)	3.31dB
Uncertainty for Radiated Emission in new 3m chamber (68-4-90-19-006) 30MHz-1000MHz	Horizontal: 4.67dB; Vertical: 4.65dB;
Uncertainty for Radiated Emission in new 3m chamber (68-4-90-19-006) 1000MHz-18000MHz	Horizontal: 4.76dB; Vertical: 4.75dB;
Uncertainty for Radiated Emission 18000MHz-40000MHz	Horizontal: 4.51dB; Vertical: 4.50dB;
Uncertainty for Conducted RF test	RF Power Conducted: 1.27dB Frequency test involved: 0.6×10^{-7} or 1%

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2007, clause 4.4.3 and 4.5.1.

THE END