



Radio Frequency Exposure Evaluation Report

FOR:
Globe Tracker ApS

Model:
LYNXFLEET-22L

Product Description:
Asset Tracking Device / Data Modem

FCC ID: 2ASJR-LYNXFLEET-22L
IC: 25752-LYNXFLEET22

Per:
CFR Part Part1 (1.1307 & 1.1310), Part 2 (2.1091),
FCC KDB 447498 D01 General RF Exposure Guidance v06
ISED RSS-102 Issue 5

Report number: EMC_GLOBE-005-22001_FCC_ISED_MPE_Rev3

DATE: 2022-11-28



CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: Contact@cetecom.com • <http://www.cetecom.com>
CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

1 Assessment

This RF Exposure evaluation report provides evidence for compliance of the below identified device with the RF Exposure limits for mobile devices as defined in FCC CFR Part 1 (1.1307 & 1.1310), Part 2 (2.1091) and IC standard RSS-102 issue 5 under worst case conditions (measured or rated RF output power, antenna gain, distance towards human body, multiple transmitter information as presented by the applicant).

In addition, maximum antenna gain or minimum distance towards the human body is calculated respectively, where relevant.

The device meets the limits as stipulated by the above given FCC and IC rule parts based on available specifications for worst case conditions at 20cm distance to the body.

Company	Description	Model #
Globe Tracker ApS	Asset Tracking Device / Data Modem	LYNXFLEET-22L

Report reviewed by: TCB Evaluator

2022-11-28 Compliance Arndt Stoecker
 (Director of Regulatory Services)

Date	Section	Name	Signature
------	---------	------	-----------

Responsible for the Report:

2022-11-28 Compliance Cheng Song
 (EMC Engineer)

Date	Section	Name	Signature
------	---------	------	-----------

2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
Lab Manager:	Arndt Stoecker
Responsible Project Leader:	Akanksha Baskaran

2.2 Identification of the Client / Manufacturer

Client's Name:	Globe Tracker ApS
Street Address:	Strandgade 91, 4th floor
City/Zip Code	DK-1401 Copenhagen K
Country	USA

Identification of the Manufacturer

Manufacturer's Name:	Same as Client
Manufacturers Address:	
City/Zip Code	
Country	

3 Equipment under Assessment

Model No:	LYNXFLEET-22L
HW Version :	Rev 5
SW Version :	10.10
FCC-ID :	2ASJR-LYNXFLEET-22L
IC:	25752-LYNXFLEET22
PMN:	ML5 Asset Tracker
Product Description:	Asset Tracking Device / Data Modem
Radio Information:	<u>LoRa:</u> <ul style="list-style-type: none"> • Module: Semtech SX1279 • Frequency of Operation: 433 MHz, 863-870 MHz (EU), 902-928 MHz (NA)
Antenna Information as declared:	<u>900 ISM</u> <ul style="list-style-type: none"> • Peak Gain: -0.5 dBi
Power Supply/ Rated Operating Voltage Range:	AC Input: Voltage Range: 12-36 VAC, Frequency: 50/60 Hz DC Input: Voltage Range: 9-18 VDC Lithium Ion Battery
Operating Temperature Range	-25 °C to 70 °C
Sample Revision	<input type="checkbox"/> Prototype Unit; <input type="checkbox"/> Production Unit; <input checked="" type="checkbox"/> Pre-Production

4 RF Exposure Limits and FCC and IC Basic Rules

For the specific described radio apparatus the following basic limits and rules apply for both, FCC and IC where not indicated differently.

4.1 Power Density Limits acc. to FCC 1.1310(e) / RSS-102 i5, cl. 4:

FCC

Frequency Range (MHz)	Power density (mW/cm ²)	Averaging time (minutes)
300 – 1500	f (MHz) /1500	30
1500 – 100000	1.0	30

IC

Frequency Range (MHz)	Power density (W/m ²)	Averaging time (minutes)
300 – 6000	0.02619 x f (MHz) ^{0.6834}	6

4.2 Routine Environmental Evaluation Categorical Exclusion Limits acc. to FCC 2.1091(c) / RSS-102, cl. 2.5 (rounded to 1 decimal point):

FCC

operating frequency < 1.5GHz: excluded if ERP < 1.5W / 31.8dBm (EIRP: 33.9 dBm);
 operating frequency > 1.5GHz: excluded if ERP < 3.0W / 34.8dBm (EIRP: 36.9 dBm);

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

IC

300MHz <= operating frequency < 6 GHz: excluded if EIRP < 0.0131 x f (MHz)^{0.6834} W

4.3 RF Exposure Estimation (MPE Estimation)

Having available the source based average output power and peak antenna gain or the ERP/EIRP of the specified device and for a known minimum distance of its radiating structures from the body of persons according to its use cases (at least 20cm) the power density at that distance can be estimated by the following formula for plane-wave equivalent conditions (far-field conditions), when ground reflection is neglected.

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (mW/cm² or W/m²)
 P = power input to the antenna (mW or W)
 G = power gain of the antenna in the direction of interest relative to an isotropic radiator
 R = distance to the center of radiation of the antenna (cm or m)

5 Evaluations

5.1 Analysis of RF Exposure

- Evaluations are based on worst case power density limits for US and Canada.
- Calculations are made for 20cm.
- Evaluations are based on ERP/EIRP measured or calculated from known gain and conducted output power.

FCC:

LoRa

Operating frequency < 1.5GHz, ERP20cm Limit = $2040 \times 0.907 = 1850.28\text{mW} = 1.85\text{W}$

Actual ERP = $0.0015\text{W} < 1.85\text{W}$; Excluded.

IC:

LoRa

EIRP Limit = $0.0131 \times f \text{ (MHz)}^{0.6834} = 1.38\text{W}$

Actual EIRP = $0.0024\text{W} < 1.38\text{W}$; Excluded.

5.2 Conclusion:

The equipment is passing RF exposure requirements for 20cm distance.

6 Revision History

Date	Report Name	Changes to report	Prepared by
2022-10-18	EMC_GLOBE-005-22001_FCC_ISED_MPE	Initial Release	Cheng Song
2022-11-02	EMC_GLOBE-005-22001_FCC_ISED_MPE_Rev1	Updated RF Exposure Calculation	Cheng Song
2022-11-11	EMC_GLOBE-005-22001_FCC_ISED_MPE_Rev2	Changed 900M ISM antenna gain to -0.5 dBi	Cheng Song
2022-11-28	EMC_GLOBE-005-22001_FCC_ISED_MPE_Rev3	Updated section 5, removed measurement for cellular	Cheng Song

<<< The End >>>